
Weblate Documentation

Release 2.8

Michal Čihař

August 31, 2016

1	About Weblate	3
1.1	Project goals	3
1.2	Project name	3
1.3	Project website	3
1.4	Authors	3
2	Translators guide	5
2.1	Weblate basics	5
2.2	Registration and user profile	5
2.3	Translating using Weblate	10
2.4	Downloading and uploading translations	16
2.5	Checks and fixups	19
3	Application developer guide	25
3.1	Starting with internationalization	25
3.2	Managing translations	29
3.3	Reviewing source strings	29
3.4	Promoting the translation	33
3.5	Translation progress reporting	34
4	Administrators guide	37
4.1	Quick setup guide	37
4.2	Installation instructions	38
4.3	Weblate deployments	53
4.4	Upgrading Weblate	57
4.5	Authentication	63
4.6	Access control	66
4.7	Translation projects	72
4.8	Language definitions	82
4.9	Continuous translation	82
4.10	Translation process	89
4.11	Checks and fixups	90
4.12	Machine translation	94
4.13	Configuration	97
4.14	Sample configuration	106
4.15	Management commands	117
4.16	Whiteboard messages	124
4.17	Advertisement	126

4.18	Component Lists	127
5	Frequently Asked Questions	129
5.1	Configuration	129
5.2	Usage	131
5.3	Troubleshooting	133
5.4	Features	134
6	Supported formats	137
6.1	Automatic detection	137
6.2	GNU Gettext	137
6.3	XLIFF	138
6.4	Java properties	139
6.5	Qt Linguist .ts	139
6.6	Android string resources	139
6.7	Apple OS X strings	140
6.8	PHP strings	140
6.9	JSON files	141
6.10	.Net Resource files	141
6.11	CSV files	141
6.12	Others	142
7	Version control integration	143
7.1	Accessing repositories	143
7.2	Git	144
7.3	GitHub	145
7.4	Mercurial	145
7.5	Subversion	146
8	Weblate's Web API	147
8.1	REST API	147
8.2	Notification hooks	161
8.3	Exports	162
8.4	RSS feeds	164
9	Weblate Client	165
9.1	Instalation	165
9.2	Synopsis	165
9.3	Description	165
9.4	Files	167
9.5	Examples	167
10	Weblate's Python API	169
10.1	Instalation	169
10.2	wlc	169
10.3	wlc.config	170
10.4	wlc.main	170
11	Changes	171
11.1	weblate 2.8	171
11.2	weblate 2.7	171
11.3	weblate 2.6	172
11.4	weblate 2.5	172
11.5	weblate 2.4	173
11.6	weblate 2.3	174

11.7	weblate 2.2	175
11.8	weblate 2.1	175
11.9	weblate 2.0	176
11.10	weblate 1.9	176
11.11	weblate 1.8	177
11.12	weblate 1.7	177
11.13	weblate 1.6	177
11.14	weblate 1.5	178
11.15	weblate 1.4	179
11.16	weblate 1.3	179
11.17	weblate 1.2	180
11.18	weblate 1.1	181
11.19	weblate 1.0	181
11.20	weblate 0.9	181
11.21	weblate 0.8	182
11.22	weblate 0.7	182
11.23	weblate 0.6	182
11.24	weblate 0.5	183
11.25	weblate 0.4	183
11.26	weblate 0.3	183
11.27	weblate 0.2	183
11.28	weblate 0.1	184
12	Contributing	185
12.1	Code and development	185
12.2	Starting with our codebase	185
12.3	Earning money by coding	185
12.4	Translating	185
12.5	Funding Weblate development	186
13	License	187
14	Indices and tables	189
	HTTP Routing Table	191
	Python Module Index	193

Contents:

About Weblate

1.1 Project goals

Web based translation with tight git integration supporting wide range of file formats and makes it easy for translators to contribute.

The translations should be kept within same repository as source code and translation process should closely follow development.

There is no plan in heavy conflict resolution as these should be primarily handled on git side.

1.2 Project name

The project is named as mixture of words web and translate.

1.3 Project website

You can find project website at <https://weblate.org/>, there is also demonstration server at <https://demo.weblate.org/>. This documentation can be browsed on <http://docs.weblate.org/>.

1.4 Authors

This tool was written by Michal Čihar michal@cihar.com.

Translators guide

2.1 Weblate basics

2.1.1 Projects structure

Each project can contain various components. The reason for this structure is that all components in a project are expected to have a lot in common. Whenever translation is made in single component, it is automatically propagated to others within same project (this is especially useful when translating more version of same project, but can be disabled, see *Component configuration*).

2.2 Registration and user profile

2.2.1 Registration

While everybody can browse projects, view translations or suggest them, only registered users are allowed to actually save changes and are credited for every translation made.

You can register following two simple steps:

1. Fill out the registration form with your credentials
2. Activate registration by following in email you receive
3. Possibly adjust your profile to choose which languages you know

2.2.2 Dashboard

When you log in to Weblate, you will see an overview of projects and components and their translation progress.

New in version 2.5.

By default, this will show the components of projects you are subscribed to, cross-referenced with your preferred languages. You can switch to different views using the drop-down menu on the highlighted button.

Weblate
Dashboard
Your subscriptions
Projects
Documentation
Weblate Admin

Dashboard

Your subscriptions
Search
History
Activity
Tools

All projects
Your languages
Your subscriptions

	Translated	Words	Review	Checks	Suggestions
glogloglo/master (Czech)	<div></div>	100.0%	100.0%	0.0%	0
libgettextdemo/master (Czech)	<div></div>	100.0%	100.0%	0.0%	1

Good translations

Translations with failing checks

Fuzzy translations

Manage your languages
Manage your subscriptions

The drop-down will have several options:

- *All projects* will show translation status of all projects on the Weblate instance.
- *Your languages* will show translation status of all projects, filtered by your primary languages.
- *Your subscriptions* will show translation status of only those projects you are subscribed to, filtered by your primary languages.

In addition, the drop-down can also show any number of *component lists*, sets of project components preconfigured by the Weblate administrator.

You can configure your preferred view in the *Preferences* section of your user profile settings.

2.2.3 User profile

User profile contains your preferences, name and email. Name and email are being used in VCS commits, so keep this information accurate.

Note: All language selections offers only languages which are currently being translated. If you want to translate to other language, please request it first on the project you want to translate.

Translated languages

Choose here which languages you prefer to translate. These will be offered to you on main page to have easier access to translations.

Hosted Weblate
Dashboard
Your translations
Projects
Documentation
Michal Čihař

Dashboard

Your translations
Projects
Search
History
Activity
Statistics
Tools

Your translations

Project	Translated	Words	Fuzzy	Checks	Suggestions
CopyQ/master (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Gammu/gammu (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Gammu/lbgammu (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Gammu/wammu (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Gammu/wammu-doc (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Gammu/website (Czech)	<div></div>	83.4%	52.9%	0.0%	0
phpMyAdmin/4.2 (Czech)	<div></div>	100.0%	100.0%	0.0%	0
phpMyAdmin/master (Czech)	<div></div>	93.7%	92.2%	3.1%	1
Ukolovnik/master (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Weblate/javascript (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Weblate/master (Czech)	<div></div>	97.6%	94.7%	1.6%	1
Weblate/website (Czech)	<div></div>	100.0%	100.0%	0.0%	0
Website/master (Czech)	<div></div>	100.0%	100.0%	0.0%	0
WinCompose/master (Czech)	<div></div>	65.4%	61.4%	3.6%	0




- Good translations
 - Translations with failing checks
 - Fuzzy translations

Manage your translations





Powered by Weblate 2.0-dev
About Weblate
Contact us
Documentation
Donate to Weblate!

Secondary languages

You can define secondary languages, which will be shown you while translating together with source language. Example can be seen on following image, where Slovak language is shown as secondary:

 Hosted Weblate
 Dashboard
 Your translations ▾
 Projects ▾
 Documentation
  Michal Čihař
 

Gammu / website / Czech / translate



Untranslated strings (1 / 81)



Zen

Translate

Slovak

↵ ↶

Marcin pôvodne začal projekt ako fork Gnokii pretože nebol spokojný↵
 s niektorými časťami existujúceho kódu. prispieval väčšinou do hlavného kódu a↵
 Nokia modulu a viedol projekt do januára 2007, keď rezignoval↵
 pre nedostatok času. Už nieje aktívny na projekte.↵

Source

↵ ↶

Marcin has originally started the project as fork of Gnokii because he was not↵
 happy with some parts of the existing code. He did contribute most of core and↵
 Nokia modules and he did lead the project till January 2007, when he resigned↵
 because lack of time. He is not active in the project anymore.↵

Translation

↵ ↶

Copy

→ ↵ ...

☐ Fuzzy

Save

Suggest

Commit message:

Glossary

No related strings were found in the glossary.

Manage glossary

Source information

Source string location

html/authors.html:41

Source string age

3 weeks ago

String priority

Medium

Nearby messages

Comments

Machine translation

Search

History

History

When	User	Action	Translation
No recent activity has been recorded.			

Browse changes

Follow using RSS

Powered by Weblate 2.0-dev
 About Weblate
 Contact us
 Documentation
 Donate to Weblate!

Default dashboard view

On the *Preferences* tab, you can pick which of the available dashboard views will be displayed by default. If you pick *Component list*, you have to select which component list will be displayed from the *Default component list* drop-down.

Subscriptions

You can subscribe to various notifications on *Subscriptions* tab. You will receive notifications for selected events on chosen projects for languages you have indicated for translation (see above).

8

Chapter 2. Translators guide

If you are an owner of some project, you will always receive some important notifications, like merge failures or new language requests.

Note: You will not receive notifications for actions you've done.

Hosted Weblate Dashboard Your translations ▾ Projects ▾ Documentation Michal Čihák

Your profile

Preferences Subscriptions Account Authentication Profile Licenses

Subscribed projects

- ☐ ARandR
- ☐ Binary
- ☐ Bitcoin.cz
- ☐ BridgeClock
- ☐ CopyQ
- ☐ Debian Handbook
- ☐ django-geoip-redis
- ☐ Freeplane
- ☒ Gammu
- ☐ GePeS
- ☐ GetBack GPS
- ☐ Koha
- ☐ Monkeysphere
- ☐ MusicBottle
- ☐ OsmAnd
- ☒ phpMyAdmin
- ☐ Scarry On Lin{e}ux³
- ☐ SDAPS
- ☐ Spiel
- ☐ Summoning Wars
- ☒ Ukolovnik
- ☐ Unknown Horizons
- ☒ Weblate
- ☒ Website
- ☐ WinCompose
- ☐ WordPoints

Save

Description

You will receive chosen notifications via email for all your languages.

Documentation

Subscription settings



- ☐ Notification on any translation
- ☐ Notification on new string to translate
- ☐ Notification on new suggestion
- ☐ Notification on new contributor
- ☐ Notification on new comment
- ☐ Notification on merge failure
- ☐ Notification on new language request

Save

Powered by Weblate 2.0-dev About Weblate Contact us Documentation Donate to Weblate!

Authentication

On the *Authentication* tab you can connect various services which you can use to login into Weblate. List of services depends on Weblate configuration, but can include popular sites such as Google, Facebook, GitHub or Bitbucket.

 Hosted Weblate
 Dashboard
 Your translations ▾
 Projects ▾
 Documentation
  Michal Čihář

Your profile

Preferences
 Subscriptions
 Account
 Authentication
 Profile
 Licenses

User identities

You can manage identities which are associated to this account and which can be used to log in.

Currently associated:

Identity	User ID	Action
Password	nijel	<button>Change password</button>
GitHub	212189	<button>Disconnect</button>
Email	michal@cihar.com	<button>Disconnect</button>
Google	michal@cihar.com	<button>Disconnect</button>

Add new association:

Email

Description

You can configure how you will log in on this site.

Documentation

Removal

Removal of the account deletes all your private data.

Remove my account

Powered by Weblate 2.0-dev
 About Weblate
 Contact us
 Documentation
 Donate to Weblate!

Avatar

Weblate can be configured to show avatar for each user (depending on `ENABLE_AVATARS`). These images are obtained using libavatar protocol (see <https://www.libavatar.org/>) or using <http://gravatar.com/>.

2.3 Translating using Weblate

2.3.1 Translation links

Once you navigate to a translation, you will be shown set of links which lead to translation. These are results of various checks, like untranslated or strings needing review. Should no other checks fire, there will be still link to all translations. Alternatively you can use search field to find translation you need to fix.

The screenshot displays the Weblate web interface for the 'Koha / opac-prog / Czech' project. The top navigation bar includes links for 'Hosted Weblate', 'Dashboard', 'Your translations', 'Projects', and 'Documentation'. The user 'Michal Čihař' is logged in. The project path 'Koha / opac-prog / Czech' is shown, with a 'přeloženo 99%' badge. The main content area is divided into several sections:

- Translation status:** Shows 'Strings' (2343) and 'Words' (9274) both at 100.0% completion. A legend indicates green for 'Good translations', orange for 'Translations with failing checks', and red for 'Fuzzy translations'.
- Project Information:** Lists project website, license (GPL-2.0), Git repository, Git branch (master 3146783), and Git repository with Weblate translations.
- Strings to check:** Lists items for review, such as 'All strings' (2343), 'Strings with any failing checks' (455), and 'This message has more than one translation in this project' (25).
- Other translations:** A table showing other projects and their translation status.

Project	Translated	Words	Fuzzy	Checks	Suggestions
Koha/staff-prog	99.9%	99.8%	0.0%	1274	1
Koha/opac-ccsr	100.0%	100.0%	0.0%	5	0
Koha/pref	100.0%	100.0%	0.0%	36	0

Legend: Green - Good translations, Orange - Translations with failing checks, Red - Fuzzy translations.

Footer: Powered by Weblate 2.0-dev, About Weblate, Contact us, Documentation, Donate to Weblate!

2.3.2 Suggestions

As an anonymous user, you have no other choice than making a suggestion. However if you are logged in you can still decide to make only a suggestion instead of saving translation, for example in case you are unsure about the translation and you want somebody else to review it.

Note: Permissions might vary depending on your setup, what is described is default Weblate behaviour.

2.3.3 Translating

On translate page, you are shown source string and edit area for translating. Should the translation be plural, multiple source strings and edit areas are shown, each described with label for plural form.

Any special whitespace chars are underlined in red and indicated with grey symbols. Also more than one space is underlined in red to allow translator to keep formatting.

There are various extra information which can be shown on this page. Most of them are coming from the project source code (like context, comments or where the message is being used). When you configure secondary languages in your preferences, translation to these languages will be shown (see *Secondary languages*).

Bellow translation can be also shown suggestions from other users, which you can accept or delete.

Plurals

What are plurals? Generally spoken plurals are words which take into account numeric meanings. But as you may imagine each language has its own definition of plurals. English, for example, supports one plural. We have a singular definition, for example “car”, which means implicit one car, and we have the plural definition, “cars” which could mean more than one car but also zero cars. Other languages like Czech or Arabic have more plurals and also the rules for plurals are different.

Weblate does have support for translating these and offers you one field to translate every plural separately. The number of fields and how it is used in the translated application depends on plural equation which is different for every language. Weblate shows the basic information, but you can find more detailed description in the [Language Plural Rules](#) from the Unicode Consortium.

Hosted Weblate
Dashboard
Your translations
Projects
Documentation
Michal Čihař

phpMyAdmin / master / Czech / translate

All strings (582 / 2973)
Zen

Translate

Source

One
Total: <i>%s</i> match

Other
Total: <i>%s</i> matches

One Copy → ← ...

Celkem: <i>%s</i> odpovídající záznam

Few Copy → ← ...

Celkem: <i>%s</i> odpovídající záznamy

Other Copy → ← ...

Celkem: <i>%s</i> odpovídajících záznamů

Plural equation: (n==1) ? 0 : (n>=2 && n<=4) ? 1 : 2 [Documentation for plurals.](#)

☐ Fuzzy

Save Suggest Commit message: Additional text to include in t

Glossary

No related strings were found in the glossary.

Manage glossary

Source information

Flags
php-format

Source string location
libraries/DbSearch.class.php:300

Source string age
3 weeks ago

Translation file
po/cs.po, translation unit 582

String priority
Medium

Failing checks
Multiple failing checks

Nearby messages
Comments
Machine translation
Search
History

History

When	User	Action	Translation
No recent activity has been recorded.			

Browse changes Follow using RSS

Powered by Weblate 2.0-dev
About Weblate
Contact us
Documentation
Donate to Weblate!

Keyboard shortcuts

While translating you can use following keyboard shortcuts:

Alt+Home Navigates to first translation in current search.

Alt+End Navigates to last translation in current search.

Alt+PageUp Navigates to previous translation in current search.

Alt+PageDown Navigates to next translation in current search.

Alt+Enter or Ctrl+Enter or Command+Enter Saves current translation.

Ctrl+Shift+Enter or Command+Shift+Enter Umarks translation as fuzzy and submits it.

Alt+E Focus translation editor.

Alt+C Focus comment editor.

Alt+M Shows machine translation tab.

Alt+<NUMBER> Copies placeable of given number from source string.

Alt+M <NUMBER> Copy machine translation of given number to current translation.

Alt+I <NUMBER> Ignore failing check of given number.

Alt+N Shows nearby strings tab.

Alt+S Shows search tab.

Alt+V Copies source string

Alt+F Toggles fuzzy flag.

Translation context

Translation context part allows you to see related information about current string.

String attributes Things like message ID, context (msgctxt) or location in source code.

Nearby messages Displays messages which are located nearby in translation file. These usually are also used in similar context and you might want to check them to keep translation consistent.

Similar messages Messages which are similar to currently one, which again can help you to stay consistent within translation.

All locations In case message appears in multiple places (eg. multiple components), this tab shows all of them and for inconsistent translations (see *Inconsistent*) you can choose which one to use.

Glossary Displays words from project glossary which are used in current message.

Recent edits List of people who have changed this message recently using Weblate.

Project Project information like instructions for translators or information about VCS repository.

If translation format supports it, you can also follow links to source code which contains translated strings.

Translation history

Every change is by default (unless disabled in component settings) saved in the database and can be reverted. Of course you can still also revert anything in underlying version control system.

2.3.4 Glossary

Each project can have assigned glossary for any language. This could be used for storing terminology for given project, so that translations are consistent. You can display terms from currently translated string in bottom tabs.

Managing glossaries

On project page, on *Glossaries* tab, you can find link *Manage all glossaries*, where you can start new glossaries or edit existing ones. Once glossary is existing, it will also show up on this tab.

Hosted Weblate Dashboard Your translations Projects Documentation Michal Čihár

GePeS translated 88%

Overview History Activity Tools Share

Resources

Resource	Translated
master	88.5%

■ - Good translations
 ■ - Translations with failing checks
 ■ - Fuzzy translations

Project Information

Project website <http://cihar.com/software/gepes/>

Glossaries

Czech 1

Manage all glossaries

Powered by Weblate 2.0-dev About Weblate Contact us Documentation Donate to Weblate!

On further page, you can choose which glossary to manage (all languages used in current project are shown). Following this language link will lead you to page, which can be used to edit, import or export the glossary:

Hosted Weblate Dashboard Your translations Projects Documentation Michal Čihár

GePeS / glossaries / Czech

Browse Add new word Import glossary Export glossary History

Starting letter: Any

Source	Translation
latitude	šířka

Edit Delete

Powered by Weblate 2.0-dev About Weblate Contact us Documentation Donate to Weblate!

2.3.5 Machine translation

Based on configuration and your language, Weblate provides buttons for following machine translation tools.


All machine translations are available on single tab on translation page.

See also:

Machine translation setup

2.3.6 Automatic translation

Weblate can be used for merging or copying translations from one component to another. This tool is called *Automatic translation* and is accessible in the *Tools* menu:



You can choose which components you want to use as source and how to handle conflicts.

This feature can be useful in several situations like consolidating translation between different components (eg. website and application) or when bootstrapping translation for new component using existing translations (translation memory).

2.4 Downloading and uploading translations

Weblate supports both export and import of translation files. This allows you to work offline and then merge changes back. Your changes will be merged within existing translation (even if it has been changed meanwhile).

Note: This available options might be limited by *Access control*.

2.4.1 Downloading translations

You can download translatable file using the *Download source file* action in the *Files* menu. This will give you the file as is stored in upstream version control system.

For some formats you can also download compiled file to use withing application (for example `.mo` files for GNU Gettext) using the *Download compiled translation*.

2.4.2 Uploading translations

You can upload translated files using the *Upload translation* action in the *Files* menu.

Weblate accepts any file format it understands on upload, but it is still recommended to use same file format as is used for translation, otherwise some features might not be translated properly.

See also:

Supported formats

The uploaded file is merged to current translation, overwriting existing entries by default (this can be changed in the upload dialog).

Import methods

You can choose how imported strings will be merged out of following options:

Add as translation Imported translations are added as translation. This is most usual and default behavior.

Add as a suggestion Imported translations are added as suggestions, do this when you want to review imported strings.

Add as translation needing review Imported translations are added as translations needing review. This can be useful for review as well.

Additionally, when adding as a translation, you can choose whether to overwrite already translated strings or not or how to handle strings needing review in imported file.

Hosted Weblate

Weblate / master / Czech

přeloženo 99%

Overview

Search

History

Activity

Statistics

Files

Tools

Share

Upload

Download source file

Download compiled translation

Upload translation

Uploaded file will be merged with current translation. In case you upload a file with fuzzy strings, don't forget to enable it.

File

Procházet... Soubor nevybrán.

Merge method

Add as translation

Fuzzy strings processing

Do not import

☒ Merge file header

Merges content of file header into the translation.

☒ Merge translation comments

Merges comments into the translation.

☒ Overwrite existing translations

Whether to overwrite existing translations if the string is already translated.

Author name

Keep empty for using currently logged in user.

Author email

Keep empty for using currently logged in user.

Upload

2.5 Checks and fixups

2.5.1 Automatic fixups

In addition to *Quality checks*, Weblate can also automatically fix some common errors in translated strings. This can be quite powerful feature to prevent common mistakes in translations, however use it with caution as it can cause silent corruption as well.

See also:

AUTOFIX_LIST

2.5.2 Quality checks

Weblate does wide range of quality checks on messages. The following section describes them in more detail. The checks take account also special rules for different languages, so if you think the result is wrong, please report a bug.

See also:

CHECK_LIST, *Customizing checks*

Translation checks

These are executed on every translation change and help translators to keep good quality of translations.

Unchanged translation

The source and translated strings are the same at least in one of the plural forms. This check ignores some strings which are quite usually same in all languages and strips various markup, which can occur in the string, to reduce number of false positives.

This check can help finding strings which were mistakenly not translated .

Starting or trailing newline

Source and translated do not both start (or end) with a newline.

Newlines usually appear in source string for a good reason, so omitting or adding it can lead to formatting problems when the translated text is used in the application.

Starting spaces

Source and translation do not both start with same number of spaces.

Space in beginning is usually used for indentation in the interface and thus is important to keep.

Trailing space

Source and translated do not both end with a space.

Trailing space is usually used to give space between neighbouring elements, so removing it might break application layout.

Trailing stop

Source and translated do not both end with a full stop. Full stop is also checked in various language variants (Chinese, Japanese, Devanagari or Urdu).

Whet the original string is a sentence, the translated one should be sentence as well to be consistent within the translated content.

Trailing colon

Source and translated do not both end with a colon or the colon is not correctly spaced. This includes spacing rules for languages like French or Breton. Colon is also checked in various language variants (Chinese or Japanese).

Colon is part of a label and should be kept to provide consistent translation. Weblate also checks for various typographic conventions for colon, for example in some languages it should be preceded with space.

Trailing question

Source and translated do not both end with a question mark or it is not correctly spaced. This includes spacing rules for languages like French or Breton. Question mark is also checked in various language variants (Armenian, Arabic, Chinese, Korean, Japanese, Ethiopic, Vai or Coptic).

Question mark indicates question and this semantics should be kept in translated string as well. Weblate also checks for various typographic conventions for question mark, for example in some languages it should be preceded with space.

Trailing exclamation

Source and translated do not both end with an exclamation mark or it is not correctly spaced. This includes spacing rules for languages like French or Breton. Exclamation mark is also checked in various language variants (Chinese, Japanese, Korean, Armenian, Limbu, Myanmar or Nko).

Exclamation mark indicates some important statement and this semantics should be kept in translated string as well. Weblate also checks for various typographic conventions for exclamation mark, for example in some languages it should be preceded with space.

Trailing ellipsis

Source and translation do not both end with an ellipsis. This only checks for real ellipsis (. . .) not for three dots (. . .).

Ellipsis is usually rendered nicer than three dots, so it's good to keep it when the original string was using that as well.

See also:

[Ellipsis on wikipedia](#)

Maximum Length

Translation is too long to accept. This only checks for the length of translation characters.

Source and translation usually do not have same amount of characters, but if translation is too long, it can be affect a rendered shape. For example, in some UI widget, it should be kept in a specific length of characters in order to show complete translation within limited space.

Unlike the other checks, the flag should be set as a `key:value` pair like `max-length:100`.

Format strings

Format string does not match source. Weblate supports following formats:

- Python format
- Python brace format
- PHP format
- C format
- Javascript format
- AngularJS interpolation string

Omitting format string from translation usually cause severe problems, so you should really keep the format string matching the original one.

See also:

[Python string formatting](#), [Python brace format](#), [PHP format strings](#), [C printf format](#), [AngularJS: API: \\$interpolate](#)

Missing plurals

Some plural forms are not translated. Check plural form definition to see for which counts each plural form is being used.

Not filling in some plural forms will lead to showing no text in the application in case this plural would be displayed.

Inconsistent

More different translations of one string in a project. This can also lead to inconsistencies in displayed checks. You can find other translations of this string on *All locations* tab.

Weblate checks translations of the same string across all translation within a project to help you keep consistent translations.

Mismatched \n

Number of `\n` in translation does not match source.

Usually escaped newlines are important for formatting program output, so this should match to source.

Mismatched BBcode

BBcode in translation does not match source.

This code is used as a simple markup to highlight important parts of a message, so it is usually a good idea to keep them.

Note: The method for detecting BBcode is currently quite simple so this check might produce false positives.

Zero-width space

Translation contains extra zero-width space (<U+200B>) character.

This character is usually inserted by mistake, though it might have legitimate use. Some programs might have problems when this character is used.

See also:

[Zero width space on wikipedia](#)

Invalid XML markup

New in version 2.8.

The XML markup is invalid.

XML tags mismatch

XML tags in translation do not match source.

This usually means resulting output will look different. In most cases this is not desired result from translation, but occasionally it is desired.

Source checks

Source checks can help developers to improve quality of source strings.

Optional plural

The string is optionally used as plural, but not using plural forms. In case your translation system supports this, you should use plural aware variant of it.

For example with Gettext in Python it could be:

```
from gettext import gettext
print gettext('Selected %d file', 'Selected %d files', files) % files
```

Ellipsis

The string uses three dots (. . .) instead of an ellipsis character (. . .).

Using Unicode character is in most cases better approach and looks better when rendered.

See also:

[Ellipsis on wikipedia](#)

Multiple failing checks

More translations of this string have some failed quality checks. This is usually indication that something could be done about improving the source string.

This check can be quite often caused by missing full stop at the end of sentence or similar minor issues which translators tend to fix in translations, while it would be better to fix it in a source string.

Application developer guide

Using Weblate for translating your projects can bring you quite a lot of benefits. It's only up to you how much of that you will use.

3.1 Starting with internationalization

You have a project and want to translate it into several languages? This guide will help you to do so. We will showcase several usual situations, but most of the examples are generic and can be applied to other scenarios as well.

Before translating any software, you should realize that languages around world are really different and you should not make any assumption based on your experience. For most of languages it will look weird if you try to concatenate sentence out of translated segments. You also should properly handle plural forms because many languages have complex rules for that and the internationalization framework you end up using should support this.

Last but not least, sometimes it might be necessary to add some context to the translated string. Imagine translator would get string `Sun` to translate. Without context most people would translate that as our closest star, but you might be actually used as abbreviated name of day of week...

3.1.1 Translating software using GNU Gettext

[GNU Gettext](#) is one of the most widely used tool for internationalization of free software. It provides simple yet flexible way to localize the software. It has great support for plurals, it can add further context to the translated string and there are quite a lot of tools built around it. Of course it has great support in Weblate (see [GNU Gettext](#) file format description).

Note: If you are about to use it in proprietary software, please consult licensing first, it might not be suitable for you.

GNU Gettext can be used from variety of languages (C, Python, PHP, Ruby, Javascript and much more) and usually the UI frameworks already come with some support for it. The standard usage is though the `gettext()` function call, which is often aliased to `_()` to make the code simpler and easier to read.

Additionally it provides `pgettext()` call to provide additional context to translators and `ngettext()` which can handle plural types as defined for target language.

As a widely spread tool, it has many wrappers which make it's usage really simple, instead of manual invoking of Gettext described below, you might want to try one of them, for example [intltool](#).

Sample program

The simple program in C using Gettext might look like following:

```
#include <libintl.h>
#include <locale.h>
#include <stdio.h>
#include <stdlib.h>

int main(void)
{
    int count = 1;
    setlocale(LC_ALL, "");
    bindtextdomain("hello", "/usr/share/locale");
    textdomain("hello");
    printf(
        ngettext(
            "Orangutan has %d banana.\n",
            "Orangutan has %d bananas.\n",
            count
        ),
        count
    );
    printf("%s\n", gettext("Thank you for using Weblate."));
    exit(0);
}
```

Extracting translatable strings

Once you have code using the gettext calls, you can use **xgettext** to extract message from it:

```
$ xgettext main.c -o po/hello.pot
```

This creates template file, which you can use for starting new translations (using **msginit**) or updating existing ones after code change (you would use **msgmerge** for that). The resulting file is simply structured text file:

```
# SOME DESCRIPTIVE TITLE.
# Copyright (C) YEAR THE PACKAGE'S COPYRIGHT HOLDER
# This file is distributed under the same license as the PACKAGE package.
# FIRST AUTHOR <EMAIL@ADDRESS>, YEAR.
#
#, fuzzy
msgid ""
msgstr ""
"Project-Id-Version: PACKAGE VERSION\n"
"Report-Msgid-Bugs-To: \n"
"POT-Creation-Date: 2015-10-23 11:02+0200\n"
"PO-Revision-Date: YEAR-MO-DA HO:MI+ZONE\n"
"Last-Translator: FULL NAME <EMAIL@ADDRESS>\n"
"Language-Team: LANGUAGE <LL@li.org>\n"
"Language: \n"
"MIME-Version: 1.0\n"
"Content-Type: text/plain; charset=CHARSET\n"
"Content-Transfer-Encoding: 8bit\n"
"Plural-Forms: nplurals=INTEGER; plural=EXPRESSION;\n"

#: main.c:14
#, c-format
```



```
msgid "Orangutan has %d banana.\n"
msgid_plural "Orangutan has %d bananas.\n"
msgstr[0] ""
msgstr[1] ""

#: main.c:20
msgid "Thank you for using Weblate."
msgstr ""
```

The each `msgid` line defines string to translate, the special empty string in the beginning is the file header containing metadata about the translation.

Starting new translation

With the template in place, we can start first translation:

```
$ msginit -i po/hello.pot -l cs --no-translator -o po/cs.po
Created cs.po.
```

The just created `cs.po` has already some information filled in. Most importantly it got proper plural forms definition for chosen language and you can see number of plurals have changed according to that:

```
# Czech translations for PACKAGE package.
# Copyright (C) 2015 THE PACKAGE'S COPYRIGHT HOLDER
# This file is distributed under the same license as the PACKAGE package.
# Automatically generated, 2015.
#
msgid ""
msgstr ""
"Project-Id-Version: PACKAGE VERSION\n"
"Report-Msgid-Bugs-To: \n"
"POT-Creation-Date: 2015-10-23 11:02+0200\n"
"PO-Revision-Date: 2015-10-23 11:02+0200\n"
"Last-Translator: Automatically generated\n"
"Language-Team: none\n"
"Language: cs\n"
"MIME-Version: 1.0\n"
"Content-Type: text/plain; charset=ASCII\n"
"Content-Transfer-Encoding: 8bit\n"
"Plural-Forms: nplurals=3; plural=(n==1) ? 0 : (n>=2 && n<=4) ? 1 : 2;\n"

#: main.c:14
#, c-format
msgid "Orangutan has %d banana.\n"
msgid_plural "Orangutan has %d bananas.\n"
msgstr[0] ""
msgstr[1] ""
msgstr[2] ""

#: main.c:20
msgid "Thank you for using Weblate."
msgstr ""
```

Updating strings

Once you add more strings or change some strings in your program, you execute again **xgettext** which regenerates the template file:

```
$ xgettext main.c -o po/hello.pot
```

Then you can update individual translation files to match newly created templates (this includes reordering the strings to match new template):

```
$ msgmerge --previous --update po/cs.po po/hello.pot
```

Importing to Weblate

To import such translation into Weblate, all you need to define are following fields when creating component (see *Component configuration* for detailed description of the fields):

Field	Value
Source code repository	URL of the VCS repository with your project
File mask	po/*.po
Base file for new translations	po/hello.pot
File format	Choose <i>Gettext PO file</i>
New language	Choose <i>Automatically add language file</i>

And that's it, you're now ready to start translating your software!

See also:

You can find more complex of using Gettext in the Weblate Hello project on GitHub: [<https://github.com/WeblateOrg/hello>](https://github.com/WeblateOrg/hello).

3.1.2 Translating documentation using Sphinx

Sphinx is a tool for creating beautiful documentation. It uses simple reStructuredText syntax and can generate output in many formats. If you're looking for an example, this documentation is also build using it. The very useful companion for using Sphinx is the [Read the Docs](#) service, which will build and publish your documentation for free.

I will not focus on writing documentation itself, you you need guidance with that, just follow instructions on the [Sphinx](#) website. Once you have documentation ready, translating it is quite easy as Sphinx comes with support for this and it is quite nicely covered in their [Internationalization Quick Guide](#). It's matter of few configuration directives and invoking of the `sphinx-intl` tool.

If you are using Read the Docs service, you can start building translated documentation on the Read the docs. Their [Localization of Documentation](#) covers pretty much everything you need - creating another project, set it's language and link it from master project as a translation.

Now all you need is translating the documentation content. As Sphinx splits the translation files per source file, you might end up with dozen of files, which might be challenging to import using the Weblate's web interface. For that reason, there is `import_project` management command.

Depending on exact setup, importing of the translation might look like:

```
$ ./manage.py import_project --name-template 'Documentation: %s' \
  --file-format po \
  project https://github.com/project/docs.git master \
  'docs/locale/*/LC_MESSAGES/**/*.po'
```

If you have more complex document structure, importing different folders is not directly supported, you currently have to list them separately:

```
$ ./manage.py import_project --name-template 'Directory 1: %s' \
  --file-format po \
  project https://github.com/project/docs.git master \
  'docs/locale/*/LC_MESSAGES/dir1/**/*.po'
$ ./manage.py import_project --name-template 'Directory 2: %s' \
  --file-format po \
  project https://github.com/project/docs.git master \
  'docs/locale/*/LC_MESSAGES/dir2/**/*.po'
```

See also:

The [Odorik](#) python module documentation is built using Sphinx, Read the Docs and translated using Weblate.

3.2 Managing translations

3.2.1 Adding new translations

Weblate can add new language files to your project automatically for most of the *Supported formats*. This feature needs to be enabled in the *Component configuration*. In case this is not enabled (or available for your file format) the files have to be added manually to the VCS.


Weblate will automatically detect new languages which are added to the VCS repository and makes them available for translation. This makes adding new translations incredibly easy:

1. Add the translation file to VCS.
2. Let Weblate update the repository (usually set up automatically, see *Updating repositories*).

3.3 Reviewing source strings

3.3.1 Activity reports

You can check activity reports for translations, project or individual users.



Hosted Weblate Dashboard Your subscriptions Projects Documentation Michal Čihař

Weblate / master / source strings

Strings to check

- All strings 1387
- Strings with any failing checks 3
- The translations in several languages have failing checks 3
- Strings with comments 5

Project Information

Project website	http://weblate.org/
Mailing list for translators	weblate@lists.cihar.com
Instructions for translators	http://weblate.org/contribute/
Translation license	GPL-3.0+
Repository	git://github.com/nijel/weblate.git
Repository branch	master 676ceee
Repository with Weblate translations	git://git.weblate.org/weblate.git

Powered by Weblate 2.8-dev About Weblate Contact us Documentation Donate to Weblate!

One of the most interesting check here is the *Multiple failing checks* - it fires whenever there is failure on multiple translations of given string. Usually this is something to look for as this is string where translators have problems doing the translation properly. It might be just wrong punctuation at the end of sentence or something more problematic.

The detailed listing then shows you overview per language:

Source
Priority
Failing checks

XML Localization Interchange File Format (XLIFF)

Medium ✎

multiple_failures 1 ×

Language	Status	Checks	Edit
Galician	❌		Edit
Turkish	✅		Edit
Thai	❌		Edit
Portuguese (Brazil)	✅	Unchanged translation ×	Edit
German	✅		Edit
Danish	❌		Edit
Greek	✅		Edit
Esperanto	❌		Edit
Russian	❌		Edit
Romanian	❌		Edit
Belarusian	❌		Edit
Bulgarian	❌		Edit
Ukrainian	✅		Edit
Asturian	❌		Edit
Breton	❌		Edit
Japanese	✅		Edit
Occitan	❌		Edit
Catalan	❌		Edit
Czech	✅		Edit
Portuguese	❌		Edit
Vietnamese	❌		Edit
English (United Kingdom)	❌		Edit
Armenian	❌		Edit
Hungarian	✅	Unchanged translation ×	Edit
Hebrew	❌		Edit
Polish	❌		Edit
Swahili	❌		Edit
Italian	❌		Edit
Arabic	❌		Edit
Azerbaijani	❌		Edit
Indonesian	❌		Edit
Dutch	✅		Edit
Spanish	✅		Edit
French	✅		Edit
Frisian	❌		Edit
Swedish	❌		Edit
Persian	❌		Edit
Finnish	✅		Edit
Serbian	❌		Edit
Albanian	❌		Edit
Korean	❌		Edit
Slovak	❌		Edit
Slovenian	✅		Edit
Norwegian Bokmål	✅	Unchanged translation ×	Edit
Belarusian (latin)	❌		Edit
Klingon	❌		Edit
Colognian	❌		Edit
Acholi	❌		Edit
Traditional Chinese	✅		Edit
Simplified Chinese	✅		Edit

Check flags

Please enter a comma separated list of check flags, see [documentation](#) for more details.

Save

Priority

Medium

Strings with higher priority are offered first to translators.

Save

Source string location

webplate/html/dictionary.html:29

Source string age

4 months ago

Translation file

webplate/locale/gl/LC_MESSAGES/django.po, translation unit 300


3.3.4 String comments

Weblate allows translators to comment on both translation and source strings. Each *Component configuration* can be configured to receive such comments on email address and sending this to developers mailing list is usually best approach. This way you can monitor when translators find problems and fix them quickly.


3.4 Promoting the translation

Weblate provides you widgets to share on your website or other sources to promote the translation project. It also has a nice welcome page for new contributors to give them basic information about the translation. Additionally you can share information about translation using Facebook or Twitter. All these possibilities can be found on the *Share* tab. Example of status badges for Weblate itself are show below.

Shields.IO badge often used to quickly see status of a project: Small badge often used to quickly see status of a project: Big badge with status details useful for inclusion on a web page:



Small badge with status useful for inclusion



on a web page:

All these badges come with links to simple page which explains users how to

translate using Weblate:



Get involved in Weblate!

Hi, and thank you for your interest!

Weblate is being translated using [Weblate](#), a web tool designed to ease translating for both developers and translators.

[Translation project for Weblate](#) currently contains 1104 strings for translation and is [being translated into 33 languages](#). Overall, these translations are 62.3% complete.

If you would like to contribute to translation of Weblate, you need to [register on this server](#).

Once you have activated your account just proceed to the [translation section](#).

3.5 Translation progress reporting

It is often useful to be able to see how translation progresses over given period. For this purpose Weblate includes reporting features, where you can obtain summaries of contributions to given component over time. You can find the reporting tool in the *Tools* menu for a translation component:

The screenshot shows the Weblate interface. At the top, there is a navigation bar with links: Overview, History, Activity, Tools (selected), and Share. A dropdown menu for 'Tools' is open, showing options: Data exports, Commit, Repository maintenance, Source strings review, Manage users, and Translation reports (highlighted). Below the menu, there are two reporting forms. The first form, titled 'Credits', has a description: 'Credits list all translators who have contributed to a given time period. It can be useful for including in your documentation or application to thank translators.' It includes a 'Report format' dropdown set to 'reStructuredText', a 'Starting date' field with '2000-01-01', an 'Ending date' field with '2100-01-01', and a 'Generate' button. The second form, titled 'Contributor stats', has a description: 'Reports number of strings and words translated by each translator.' It also includes a 'Report format' dropdown set to 'reStructuredText', a 'Starting date' field with '2000-01-01', an 'Ending date' field with '2100-01-01', and a 'Generate' button.

Several reporting tools are available on this page and all can produce output in HTML, reStructuredText or JSON. The first two formats are suitable for embedding into existing documentation, while JSON is useful for further processing of the data.

3.5.1 Translator credits

Generates document usable for crediting translators - sorted by language and listing all contributors to given language:

```
* Czech
    * Michal Čihař <michal@cihar.com>
```



```
* Weblate Admin <admin@example.com>

* Dutch

* Weblate Admin <admin@example.com>
```

And it will get rendered as:

- Czech
 - Michal Čihař <michal@cihar.com>
 - Weblate Admin <admin@example.com>
- Dutch
 - Weblate Admin <admin@example.com>

3.5.2 Contributor stats

Generates number of words and units translated by translators:

Name	Email	Words	Count
Michal Čihař	michal@cihar.com	2332	421
Weblate Admin	admin@example.com	25	8

And it will get rendered as:

Name	Email	Words	Count
Michal Čihař	michal@cihar.com	2332	421
Weblate Admin	admin@example.com	25	8

Administrators guide

4.1 Quick setup guide

Note: This is just a quick guide for installing and starting to use Weblate for testing purposes. Please check [Installation instructions](#) for more real world setup instructions.

4.1.1 Installing from sources

1. Install all required dependencies, see [Software requirements](#).
2. Grab Weblate sources (either using Git or download a tarball) and unpack them, see [Installing Weblate](#).
3. Copy `weblate/settings_example.py` to `weblate/settings.py` and adjust it to match your setup. You will at least need to configure database connection (possibly adding user and creating the database). Check [Configuration](#) for Weblate specific configuration options.
4. Create database which will be used by Weblate, see [Creating database for Weblate](#).
5. Build Django tables, static files and initial data (see [Filling up the database](#) and [Serving static files](#)):

```
./manage.py migrate
./manage.py collectstatic
./scripts/generate-locales # If you are using Git checkout
```

6. Configure webserver to serve Weblate, see [Running server](#).

4.1.2 Using prebuilt appliance

1. Download the appliance and start it. You need to choose format depending on your target environment.
2. Everything should be set up immediately after boot, though you will want to adjust some settings to improve security, see [SUSE Studio appliance](#).

4.1.3 Installing on OpenShift

1. You can install Weblate on OpenShift PaaS directly from its git repository using the OpenShift Client Tools:

```
rhc -awebate app create -t python-2.7 --from-code https://github.com/nijel/weblate.git
```

2. After installation everything should be preconfigured and you can immediately start to add a translation project as described below. For more information, including on how to retrieve the generated admin password, see [Weblate on OpenShift](#).

4.1.4 Adding translation

1. Open admin interface (<http://localhost/admin/>) and create project you want to translate. See [Project configuration](#) for more details.

All you need to specify here is project name and its website.

2. Create component which is the real object for translating - it points to VCS repository and selects which files to translate. See [Component configuration](#) for more details.

The important fields here being component name, VCS repository address and mask for finding translatable files. Weblate supports wide range of formats including Gettext PO files, Android resource strings, OS X string properties, Java properties or Qt Linguist files, see [Supported formats](#) for more details.

3. Once above is completed (it can be lengthy process depending on size of your VCS repository and number of messages to translate), you can start translating.

4.2 Installation instructions

4.2.1 Hardware requirements

Weblate should run on any contemporary hardware without problems, following are minimal configuration required to run Weblate on single host (Weblate, database and web server):

- 1 GB of RAM memory
- 2 CPU cores
- 1 GB of storage space

The more memory you have, the better - it will be used for caching on all levels (filesystem, database and Weblate).

Note: The actual requirements for your installation heavily vary on size of translations managed by Weblate.

4.2.2 Software requirements

Python (2.7, 3.4 or newer) <https://www.python.org/>

Django (>= 1.9) <https://www.djangoproject.com/>

Translate-toolkit (>= 1.14.0) <http://toolkit.translatehouse.org/>

Six (>= 1.7.0) <https://pypi.python.org/pypi/six>

Git (>= 1.6) <https://git-scm.com/>

Mercurial (>= 2.8) (optional for Mercurial repositories support) <https://www.mercurial-scm.org/>

python-social-auth (>= 0.2.0) <http://psa.matiasaguirre.net/>

Whoosh (>= 2.5, 2.5.7 is recommended, 2.6.0 is broken) <https://bitbucket.org/mchaput/whoosh/wiki/Home>

PIL or Pillow library <http://python-pillow.org/>

lxml (**>= 3.1.0**) <http://lxml.de/>

defusedxml (**>= 0.4**) <https://bitbucket.org/tiran/defusedxml>

dateutil <http://labix.org/python-dateutil>

django_compressor <https://github.com/django-compressor/django-compressor>

django-crispy-forms (**>=1.4.0**) <http://django-crispy-forms.readthedocs.io/>

Django REST Framework (**>=3.3**) <http://www.django-rest-framework.org/>

libravatar (**optional for federated avatar support**) <https://pypi.python.org/pypi/pyLibravatar>

pyuca (**>= 1.1**) (**optional for proper sorting of strings**) <https://github.com/jtauber/pyuca>

babel (**optional for Android resources support**) <http://babel.pocoo.org/>

Database backend Any database supported in Django will work, check their documentation for more details.

pytz (**optional, but recommended by Django**) <https://pypi.python.org/pypi/pytz/>

python-bidi (**optional for proper rendering of badges in RTL languages**) <https://github.com/MeirKriheli/python-bidi>

hub (**optional for sending pull requests to GitHub**) <https://hub.github.com/>

git-review (**optional for Gerrit support**) <https://pypi.python.org/pypi/git-review>

git-svn (**optional for Subversion support**) <https://git-scm.com/docs/git-svn>

Requirements on Debian or Ubuntu

On recent Debian or Ubuntu, most of requirements are already packaged, to install them you can use apt-get:

```
apt-get install python-pip python-django translate-toolkit \
    python-whoosh python-pil python-libravatar \
    python-babel git mercurial python-social-auth \
    python-django-compressor python-django-crispy-forms \
    python-djangorestframework python-dateutil

# Optional for database backend

apt-get install python-pymysql      # For MySQL on Ubuntu
apt-get install python-mysqldb     # For MySQL on Debian
apt-get install python-psycopg2    # For PostgreSQL
```

On older versions, some required dependencies are missing or outdated, so you need to install several Python modules manually using pip:

```
# Dependencies for python-social-auth
apt-get install python-requests-oauthlib python-six python-openid

# In case python-social-auth package is missing
pip install python-social-auth

# In case your distribution has python-django older than 1.7
pip install Django

# In case python-django-crispy-forms package is missing
pip install django-crispy-forms

# In case python-whoosh package is missing or older than 2.5
```

```
pip install Whoosh

# In case your python-django-compressor package is missing,
# try installing it by older name or using pip:
apt-get install python-compressor
pip install django_compressor
```

For proper sorting of a unicode strings, it is recommended to install pyuca:

```
pip install pyuca
```

Depending on how you intend to run Weblate and what you already have installed, you might need additional components:

```
# Web server option 1: nginx and uwsgi
apt-get install nginx uwsgi uwsgi-plugin-python

# Web server option 2: Apache with mod_wsgi
apt-get install apache2 libapache2-mod-wsgi

# Caching backend: memcached
apt-get install memcached

# Database option 1: mariadb
apt-get install mariadb-server

# Database option 2: mysql
apt-get install mysql-server

# Database option 3: postgresql
apt-get install postgresql

# SMTP server
apt-get install exim4

# GitHub PR support: hub
# See https://hub.github.com/
```

Requirements on openSUSE

Most of requirements are available either directly in openSUSE or in `devel:languages:python` repository:

```
zypper install python-Django translate-toolkit \
    python-Whoosh python-Pillow python-python-social-auth \
    python-babel Git mercurial python-pyuca \
    python-dateutil

# Optional for database backend
zypper install python-MySQL-python # For MySQL
zypper install python-psycopg2    # For PostgreSQL
```

Depending on how you intend to run Weblate and what you already have installed, you might need additional components:

```
# Web server option 1: nginx and uwsgi
zypper install nginx uwsgi uwsgi-plugin-python

# Web server option 2: Apache with mod_wsgi
```

```
zypper install apache2 apache2-mod_wsgi

# Caching backend: memcached
zypper install memcached

# Database option 1: mariadb
zypper install mariadb

# Database option 2: mysql
zypper install mysql

# Database option 3: postgresql
zypper install postgresql

# SMTP server
zypper install postfix

# GitHub PR support: hub
# See https://hub.github.com/
```

Requirements on OSX

If your python was not installed using brew, make sure you have this in your `.bash_profile` file or executed somehow:

```
export PYTHONPATH="/usr/local/lib/python2.7/site-packages:$PYTHONPATH"
```

This configuration makes the installed libraries available to Python.

Requirements using pip installer

Most requirements can be also installed using pip installer:

```
pip install -r requirements.txt
```

Also you will need header files for `python-dev`, `libxml2`, `libxslt`, `libjpeg` and `libfreetype6` to compile some of the required Python modules.

All optional dependencies (see above) can be installed using:

```
pip install -r requirements-optional.txt
```

On Debian or Ubuntu you can install them using:

```
apt-get install libxml2-dev libxslt-dev libfreetype6-dev libjpeg-dev python-dev
```

On openSUSE or SLES you can install them using:

```
zypper install libxslt-devel libxml2-devel freetype-devel libjpeg-devel python-devel
```

4.2.3 Installing Weblate

It is recommended to run latest version from Git. It is maintained stable and production ready.

To get latest sources using Git use:

```
git clone https://github.com/nijel/weblate.git
```

Alternatively you can use released archives. You can either download them from our website <<https://weblate.org/>> or use pip installer.

Installing Weblate by pip

If you decide to install Weblate using pip installer, you will notice some differences. Most importantly the command line interface is installed to the system path as **weblate** instead of **./manage.py** as used in this documentation. Also when invoking this command, you will have to specify settings, either by `DJANGO_SETTINGS` or on the command line, for example:

```
weblate --settings=yourproject.settings migrate
```

See also:

Invoking management commands

4.2.4 Filesystem permissions

Weblate process needs to be able to read and write to the directory where it keeps data - `DATA_DIR`.

The default configuration places them in same tree as Weblate sources, however you might prefer to move these to better location such as `/var/lib/weblate`.

Weblate tries to create these directories automatically, but it will fail when it does not have permissions to do so.

You should also take care when running *Management commands*, as they should be run under same user as Weblate itself is running, otherwise permissions on some files might be wrong.

See also:

Serving static files

4.2.5 Creating database for Weblate

It is recommended to run Weblate on some database server. Using SQLite backend is really good for testing purposes only.

See also:

Use powerful database engine, Django's databases

Creating database in PostgreSQL

It is usually good idea to run Weblate in separate database and separate user:

```
# If PostgreSQL was not installed before, set the master password
sudo -u postgres psql postgres -c "\password postgres"

# Create database user called "weblate"
sudo -u postgres createuser -D -P weblate

# Create database "weblate" owned by "weblate"
sudo -u postgres createdb -O weblate weblate
```


Creating database in MySQL

When using MySQL, don't forget to create database with UTF-8 encoding:

```
# Grant all privileges to weblate user
GRANT ALL PRIVILEGES ON weblate.* TO 'weblate'@'localhost' IDENTIFIED BY 'password';

# Create database on MySQL >= 5.7.7
CREATE DATABASE weblate CHARACTER SET utf8mb4;
# Use utf8 for older versions
# CREATE DATABASE weblate CHARACTER SET utf8;
```

4.2.6 Other configurations

Outgoing mail

Weblate sends out emails on various occasions - for account activation and on various notifications configured by users. For this it needs access to the SMTP server, which will handle this.

The mail server setup is configured using settings `EMAIL_HOST`, `EMAIL_HOST_PASSWORD`, `EMAIL_HOST_USER` and `EMAIL_PORT`. Their names are quite self-explaining, but you can find our more information in the [Django documentation](#) on them.

4.2.7 Installation

See also:

Sample configuration

Copy `weblate/settings_example.py` to `weblate/settings.py` and adjust it to match your setup. You will probably want to adjust following options:

ADMINS

List of site administrators to receive notifications when something goes wrong, for example notifications on failed merge or Django errors.

See also:

[ADMINS setting documentation](#)

ALLOWED_HOSTS

If you are running Django 1.5 or newer, you need to set this to list of hosts your site is supposed to serve. For example:

```
ALLOWED_HOSTS = ['demo.weblate.org']
```

See also:

[ALLOWED_HOSTS setting documentation](#)

SESSION_ENGINE

Configure how your sessions will be stored. In case you keep default database backed engine you should schedule `./manage.py clearsessions` to remove stale session data from the database.

See also:

[Configuring sessions in Django](#)

DATABASES

Connectivity to database server, please check Django's documentation for more details.

See also:

[Creating database for Weblate DATABASES setting documentation](#), [Django databases support](#)

DEBUG

Disable this for production server. With debug mode enabled, Django will show backtraces in case of error to users, when you disable it, errors will go by email to ADMINS (see above).

Debug mode also slows down Weblate as Django stores much more information internally in this case.

See also:

[DEBUG setting documentation](#)

DEFAULT_FROM_EMAIL

Email sender address for outgoing email, for example registration emails.

See also:

[DEFAULT_FROM_EMAIL setting documentation](#)

SECRET_KEY

Key used by Django to sign some information in cookies, see [Django secret key](#) for more information.

SERVER_EMAIL

Email used as sender address for sending emails to administrator, for example notifications on failed merge.

See also:

[SERVER_EMAIL setting documentation](#)

4.2.8 Filling up the database

After your configuration is ready, you can run `./manage.py migrate` to create database structure. Now you should be able to create translation projects using admin interface.

In case you want to run installation non interactively, you can use `./manage.py migrate --noinput` and then create admin user using `createadmin` command.

You should also login to admin interface (on `/admin/` URL) and adjust default site name to match your domain by clicking on *Sites* and there changing the `example.com` record to match your real domain name.

Once you are done, you should also check *Performance report* in the admin interface which will give you hints for non optimal configuration on your site.

Note: If you are running version from Git, you should also regenerate locale files every time you are upgrading. You can do this by invoking script `./scripts/generate-locales`.

See also:

[Configuration](#), [Access control](#), [Why does links contain example.com as domain?](#), [Set correct site name](#)

4.2.9 Production setup

For production setup you should do following adjustments:

Disable debug mode

Disable Django's debug mode by:

```
DEBUG = False
```

With debug mode Django stores all executed queries and shows users backtraces of errors what is not desired in production setup.

See also:

Installation

Properly configure admins

Set correct admin addresses to ADMINS setting for defining who will receive mail in case something goes wrong on the server, for example:

```
ADMINS = (
    ('Your Name', 'your_email@example.com'),
)
```

See also:

Installation

Set correct site name

Adjust site name in admin interface, otherwise links in RSS or registration emails will not work.

Please open admin interface and edit default site name and domain under the *Sites* > *Sites* (or you can do that directly at `/admin/sites/site/1/` URL under your Weblate installation). You have to change the *Domain name* to match your setup.

Note: This setting should contain only domain name. For configuring protocol (enabling HTTPS) use `ENABLE_HTTPS` and for changing URL use `URL_PREFIX`.

Alternatively you can set the site name from command line using `changesite`. For example for using built in server:

```
./manage.py changesite --set-name 127.0.0.1:8000
```

See also:

Why does links contain example.com as domain?, *changesite*, Django sites documentation

Enable indexing offloading

Enable `OFFLOAD_INDEXING` to prevent locking issues and improve performance. Don't forget to schedule indexing in background job to keep the index up to date.

See also:

Fulltext search, OFFLOAD_INDEXING, Running maintenance tasks

Use powerful database engine

Use powerful database engine (SQLite is usually not good enough for production environment), for example setup for MySQL:

```
DATABASES = {
    'default': {
        'ENGINE': 'django.db.backends.mysql',
        'NAME': 'weblate',
        'USER': 'weblate',
        'PASSWORD': 'weblate',
        'HOST': '127.0.0.1',
        'PORT': '',
    }
}
```

See also:

Installation, Django's databases

Enable caching

If possible, use memcache from Django by adjusting CACHES configuration variable, for example:

```
CACHES = {
    'default': {
        'BACKEND': 'django.core.cache.backends.memcached.MemcachedCache',
        'LOCATION': '127.0.0.1:11211',
    }
}
```

See also:

Avatar caching, Django's cache framework

Avatar caching

In addition to caching of Django, Weblate performs caching of avatars. It is recommended to use separate, file backed cache for this purpose:

```
CACHES = {
    'default': {
        # Default caching backend setup, see above
        'BACKEND': 'django.core.cache.backends.memcached.MemcachedCache',
        'LOCATION': '127.0.0.1:11211',
    },
    'avatar': {
        'BACKEND': 'django.core.cache.backends.filebased.FileBasedCache',
        'LOCATION': os.path.join(BASE_DIR, 'avatar-cache'),
        'TIMEOUT': 604800,
        'OPTIONS': {
            'MAX_ENTRIES': 1000,
        },
    },
}
```

See also:

[ENABLE_AVATARS](#), [Enable caching](#), Django's cache framework

Configure email addresses

Weblate needs to send out emails on several occasions and these emails should have correct sender address, please configure `SERVER_EMAIL` and `DEFAULT_FROM_EMAIL` to match your environment, for example:

```
SERVER_EMAIL = 'admin@example.org'
DEFAULT_FROM_EMAIL = 'weblate@example.org'
```

See also:

[Installation](#), [DEFAULT_FROM_EMAIL](#) setting documentation, [SERVER_EMAIL](#) setting documentation

Allowed hosts setup

Django 1.5 and newer require `ALLOWED_HOSTS` to hold list of domain names your site is allowed to serve, having it empty will block any request.

See also:

[ALLOWED_HOSTS](#) setting documentation

Federated avatar support

By default, Weblate relies on <https://www.libravatar.org/> for avatars. When you install [pyLibavatar](#), you will get proper support for federated avatars.

pyuca library

[pyuca](#) library is optionally used by Weblate to sort Unicode strings. This way language names are properly sorted even in non-ASCII languages like Japanese, Chinese or Arabic or for languages with accented letters.

Django secret key

The `SECRET_KEY` setting is used by Django to sign cookies and you should really use own value rather than using the one coming from example setup.

You can generate new key using `examples/generate-secret-key` shipped with Weblate.

See also:

[SECRET_KEY](#) setting documentation

Static files

If you see purely designed admin interface, the CSS files required for it are not loaded. This is usually if you are running in non-debug mode and have not configured your web server to serve them. Recommended setup is described in the [Serving static files](#) chapter.

See also:

[Running server](#), [Serving static files](#)

Home directory

Changed in version 2.1: This is no longer required, Weblate now stores all its data in [DATA_DIR](#).

The home directory for user which is running Weblate should be existing and writable by this user. This is especially needed if you want to use SSH to access private repositories, but Git might need to access this directory as well (depends on Git version you use).

You can change the directory used by Weblate in `settings.py`, for example to set it to configuration directory under Weblate tree:

```
os.environ['HOME'] = os.path.join(BASE_DIR, 'configuration')
```

Note: On Linux and other UNIX like systems, the path to user's home directory is defined in `/etc/passwd`. Many distributions default to non writable directory for users used for serving web content (such as `apache`, `www-data` or `wwwrun`, so you either have to run Weblate under different user or change this setting.

See also:

[Accessing repositories](#)

Template loading

It is recommended to use cached template loader for Django. It caches parsed templates and avoids need to do the parsing with every single request. You can configure it using following snippet:

```
TEMPLATE_LOADERS = (
    ('django.template.loaders.cached.Loader', (
        'django.template.loaders.filesystem.Loader',
        'django.template.loaders.app_directories.Loader',
    )),
)
```

See also:

[Django documentation on template loading](#)

Running maintenance tasks

For optimal performance, it is good idea to run some maintenance tasks in the background.

On Unix system, this can be scheduled using cron:

```
# Fulltext index updates
*/5 * * * * cd /usr/share/weblate/; ./manage.py update_index

# Cleanup stale objects
@daily cd /usr/share/weblate/; ./manage.py cleanuptrans

# Commit pending changes after 96 hours
@hourly cd /usr/share/weblate/; ./manage.py commit_pending --all --age=96 --verbosity=0
```

See also:

[Enable indexing offloading](#), [update_index](#), [cleanuptrans](#), [commit_pending](#)

4.2.10 Running server

Running Weblate is not different from running any other Django based application. Django is usually executed as uwsgi or fcgi (see examples for different web servers below).

For testing purposes, you can use Django builtin web server:

```
./manage.py runserver
```

Serving static files

Changed in version 2.4: Prior to version 2.4 Weblate didn't properly use Django static files framework and the setup was more complex.

Django needs to collect its static files to a single directory. To do so, execute `./manage.py collectstatic --noinput`. This will copy the static files into directory specified by `STATIC_ROOT` setting (this default to static directory inside `DATA_DIR`).

It is recommended to serve static files directly by your web server, you should use that for following paths:

/static/ Serves static files for Weblate and admin interface (from defined by `STATIC_ROOT`).

/favicon.ico Should be rewritten to rewrite rule to serve `/static/favicon.ico`

/robots.txt Should be rewritten to rewrite rule to serve `/static/robots.txt`

See also:

[Deploying Django](#), [Deploying static files](#)

Sample configuration for Lighttpd

The configuration for Lighttpd web server might look like following (available as `examples/lighttpd.conf`):

```
fastcgi.server = (
    "/weblate.fcgi" => (
        "main" => (
            "socket" => "/var/run/django/weblate.socket",
            "check-local" => "disable",
        )
    ),
)

alias.url = (
    "/static" => "/usr/share/weblate/data/static/",
)

url.rewrite-once = (
    "^(/*static.*)$" => "$1",
    "^/*favicon\\.ico$" => "/static/favicon.ico",
    "^/*robots\\.txt$" => "/static/robots.txt",
    "^(/.*)$" => "/weblate.fcgi$1",
)

expire.url = (
    "/static/" => "access 1 months",
    "/favicon.ico" => "access 1 months",
)
```

Sample configuration for Apache

Following configuration runs Weblate as WSGI, you need to have enabled `mod_wsgi` (available as `examples/apache.conf`):

```
#
# VirtualHost for weblate
#
# This example assumes Weblate is installed in /usr/share/weblate
#
# If using virtualenv, you need to add it to search path as well:
# WSGIPythonPath /usr/share/weblate:/path/to/your/venv/lib/python2.7/site-packages
#
<VirtualHost *:80>
    ServerAdmin admin@weblate.example.org
    ServerName weblate.example.org

    Alias /robots.txt /usr/share/weblate/data/static/robots.txt
    Alias /favicon.ico /usr/share/weblate/data/static/favicon.ico

    Alias /static/ /usr/share/weblate/data/static/

    <Directory /usr/share/weblate/data/static/>
        Require all granted
    </Directory>

    WSGIDaemonProcess weblate.example.org python-path=/usr/share/weblate
    WSGIProcessGroup weblate.example.org
    WSGIApplicationGroup %{GLOBAL}

    WSGIScriptAlias / /usr/share/weblate/weblate/wsgi.py process-group=weblate.example.org
    WSGIPassAuthorization On

    <Directory /usr/share/weblate/weblate>
        <Files wsgi.py>
            Require all granted
        </Files>
    </Directory>
</VirtualHost>
```

This configuration is for Apache 2.4 and later. For earlier versions of Apache, replace *Require all granted* with *Allow from all*.

Sample configuration for nginx

Following configuration runs Weblate as uwsgi under nginx webserver.

Configuration for nginx (also available as `examples/weblate.nginx.conf`):

```
server {
    listen 80;
    server_name weblate;
    root /path/to/weblate/weblate;

    location /favicon.ico {
        alias /path/to/weblate/data/static/favicon.ico;
        expires 30d;
    }
}
```



```

    }

    location /robots.txt {
        alias /path/to/weblate/data/static/robots.txt;
        expires 30d;
    }

    location /static {
        alias /path/to/weblate/data/static/;
        expires 30d;
    }

    location / {
        include uwsgi_params;
        # Needed for long running operations in admin interface
        uwsgi_read_timeout 3600;
        uwsgi_pass 127.0.0.1:8080;
    }
}

```

Configuration for uwsgi (also available as `examples/weblate.uwsgi.ini`):

```

[uwsgi]
plugins      = python
master       = true
protocol     = uwsgi
socket       = 127.0.0.1:8080
wsgi-file    = /path/to/weblate/weblate/wsgi.py
python-path  = /path/to/weblate
# Needed for OAuth/OpenID
buffer-size  = 8192
# Increase number of workers for heavily loaded sites
#workers     = 6
# Needed for background processing
enable-threads = true
# Child processes do not need file descriptors
close-on-exec = true
# Avoid default 0000 umask
umask = 0022

```

Running Weblate under path

Changed in version 1.3: This is supported since Weblate 1.3.

Sample Apache configuration to serve Weblate under `/weblate`. Again using `mod_wsgi` (also available as `examples/apache-path.conf`):

```

# Example Apache configuration for running Weblate under /weblate path

WSGIProxyPath /usr/share/weblate
# If using virtualenv, you need to add it to search path as well:
# WSGIProxyPath /usr/share/weblate:/path/to/your/venv/lib/python2.7/site-packages
<VirtualHost *:80>
    ServerAdmin admin@image.weblate.org
    ServerName image.weblate.org

    Alias /weblate/robots.txt /usr/share/weblate/data/static/robots.txt
    Alias /weblate/favicon.ico /usr/share/weblate/data/static/favicon.ico

```

```
Alias /weblate/static/ /usr/share/weblate/data/static/

<Directory /usr/share/weblate/data/static/>
    Require all granted
</Directory>

WSGIScriptAlias /weblate /usr/share/weblate/weblate/wsgi.py
WSGIPassAuthorization On

<Directory /usr/share/weblate/weblate>
    <Files wsgi.py>
        Require all granted
    </Files>
</Directory>

</VirtualHost>
```

Additionally you will have to adjust `weblate/settings.py`:

```
URL_PREFIX = '/weblate'
```

4.2.11 Monitoring Weblate

Weblate provides `/healthz/` URL to be used in simple health checks, for example using Kubernetes.

4.2.12 Migrating Weblate to another server

Migrating Weblate to another server should be pretty easy, however it stores data in few locations which you should migrate carefully. The best approach is to stop migrated Weblate for the migration.

Migrating database

Depending on your database backend, you might have several options to migrate the database. The most straightforward one is to dump the database on one server and import it on the new one. Alternatively you can use replication in case your database supports it.

The best approach is to use database native tools as they are usually most effective (eg. `mysqldump` or `pg_dump`). If you want to migrate between different databases, the only option might be to use Django management to dump and import the database:

```
# Export current data
./manage.py dumpdata > /tmp/weblate.dump
# Import dump
./manage.py loaddata /tmp/weblate.dump
```

Migrating VCS repositories

The VCS repositories stored under `DATA_DIR` need to be migrated as well. You can simply copy them or use `rsync` to do the migration more effectively.

Migrating fulltext index

For the fulltext index (stored in `DATA_DIR`) it is better not to migrate it, but rather to generate fresh one using `rebuild_index`.

Other notes

Don't forget to move other services which Weblate might have been using like memcached, cron jobs or custom authentication backends.

4.3 Weblate deployments

Weblate comes with support for deployment using several technologies. This section brings overview of them.

4.3.1 SUSE Studio appliance

Weblate appliance provides preconfigured Weblate running with MySQL database as backend and Apache as web server. It is provided in many formats suitable for any form of virtualization, cloud or hardware installation.

It comes with standard set of passwords you will want to change:

Username	Password	Scope	Description
root	linux	System	Administrator account, use for local or SSH login
root		MySQL	MySQL administrator
weblate	weblate	MySQL	Account in MySQL database for storing Weblate data
admin	admin	Weblate	Weblate/Django admin user

The appliance is built using SUSE Studio and is based on openSUSE 12.3.

You should also adjust some settings to match your environment, namely:

- *Disable debug mode*
- *Set correct site name*
- *Configure email addresses*

4.3.2 Weblate and Docker

With dockerized weblate deployment you can get your personal weblate instance up and running in seconds. All of Weblate's dependencies are already included. PostgreSQL is configured default database, but you can switch it to MySQL or MariaDB.

Deployment

Following examples assume you have working Docker environment, with docker-compose installed. Please check Docker documentation for instructions on this.

1. Clone weblate-docker repo:

```
git clone https://github.com/WeblateOrg/docker.git weblate-docker
cd weblate-docker
```

2. Optionally change the database provider in `docker-compose.yml`.

3. Change the predefined passwords for the database in the `weblate/environment`.

4. Build Weblate containers:

```
docker-compose build
```

5. Create Weblate database:

```
docker-compose run --rm weblate migrate
```

6. Prepare static files:

```
docker-compose run --rm weblate collectstatic
```

7. Create admin user (this command will print your random password for admin, you can change it later):

```
docker-compose run --rm weblate createadmin
```

8. Start Weblate containers:

```
docker-compose up
```

Enjoy your Weblate deployment, it's accessible on port 8000 of the container.

See also:

[Invoking management commands](#)

Select your machine - local or cloud providers

With `docker-machine` you can create your Weblate deployment either on your local machine or on any large number of cloud-based deployments on e.g. Amazon AWS, Digitalocean and many more providers.

4.3.3 Weblate on OpenShift

This repository contains a configuration for the OpenShift platform as a service product, which facilitates easy installation of Weblate on OpenShift Online (<https://www.openshift.com/>), OpenShift Enterprise (<https://enterprise.openshift.com/>) and OpenShift Origin (<https://www.openshift.org/>).

Prerequisites

1. OpenShift Account

You need an account for OpenShift Online (<https://www.openshift.com/>) or another OpenShift installation you have access to.

You can register a free account on OpenShift Online, which allows you to host up to 3 applications free of charge.

2. OpenShift Client Tools

In order to follow the examples given in this documentation you need to have the OpenShift Client Tools (RHC) installed: <https://developers.openshift.com/en/managing-client-tools.html>

While there are other possibilities to create and configure OpenShift applications, this documentation is based on the OpenShift Client Tools (RHC) because they provide a consistent interface for all described operations.

Installation

You can install Weblate on OpenShift directly from Weblate's github repository with the following command:

```
rhc -aweblate app create -t python-2.7 --from-code https://github.com/nijel/weblate.git --no-git
```

The `-a` option defines the name of your weblate installation, `weblate` in this instance. You are free to specify a different name.

Optionally you can specify tag identifier right of the `#` sign to identify the version of Weblate to install (for example specify `https://github.com/nijel/weblate.git#weblate-2.0` to install Weblate 2.0). For a list of available versions see here: <https://github.com/nijel/weblate/tags>. Please note that only version 2.0 and newer can be installed on OpenShift, as older versions don't include the necessary configuration files. The `--no-git` option skips the creation of a local git repository.

You can also specify which database you want to use:

```
# For MySQL
rhc -aweblate app create -t python-2.7 -t mysql-5.5 --from-code https://github.com/nijel/weblate.git

# For PostgreSQL
rhc -aweblate app create -t python-2.7 -t postgresql-9.2 --from-code https://github.com/nijel/weblate.git
```

Default Configuration

After installation on OpenShift Weblate is ready to use and preconfigured as follows:

- SQLite embedded database (DATABASES)
- Random admin password
- Random Django secret key (SECRET_KEY)
- Indexing offloading if the cron cartridge is installed (`OFFLOAD_INDEXING`)
- Committing of pending changes if the cron cartridge is installed (`commit_pending`)
- Weblate machine translations for suggestions bases on previous translations (`MACHINE_TRANSLATION_SERVICES`)
- Weblate directories (STATIC_ROOT, `DATA_DIR`, `TTF_PATH`, Avatar cache) set according to OpenShift requirements/conventions
- Django site name and ALLOWED_HOSTS set to DNS name of your OpenShift application
- Email sender addresses set to `no-reply@<OPENSHIFT_CLOUD_DOMAIN>`, where `<OPENSHIFT_CLOUD_DOMAIN>` is the domain OpenShift runs under. In case of OpenShift Online it's `rhcloud.com`.

See also:

Customize Weblate Configuration

Retrieve Admin Password

You can retrieve the generated admin password with the following command:

```
rhc -aweblate ssh credentials
```

Indexing Offloading

To enable the preconfigured indexing offloading you need to add the cron cartridge to your application and restart it:

```
rhc -aweblate add-cartridge cron
rhc -aweblate app stop
rhc -aweblate app start
```

The fulltext search index will then be updated every 5 minutes. Restarting with `rhc restart` instead will not enable indexing offloading in Weblate. You can verify that indexing offloading is indeed enabled by visiting the URL `/admin/performance/` of your application.

Pending Changes

Weblate's OpenShift configuration contains a cron job which periodically commits pending changes older than a certain age (24h by default). To enable the cron job you need to add the cron cartridge and restart Weblate as described in the previous section. You can change the age parameter by setting the environment variable `WEBLATE_PENDING_AGE` to the desired number of hours, e.g.:

```
rhc -aweblate env set WEBLATE_PENDING_AGE=48
```

Customize Weblate Configuration

You can customize the configuration of your Weblate installation on OpenShift through environment variables. Override any of Weblate's setting documented under [Configuration](#) using `rhc env set` by prepending the settings name with `WEBLATE_`. The variable content is put verbatim to the configuration file, so it is parsed as Python string, after replacing environment variables in it (eg. `$PATH`). To put literal `$` you need to escape it as `$$`.

For example override the `ADMINS` setting like this:

```
rhc -aweblate env set WEBLATE_ADMINS='(("John Doe", "jdoe@example.org"),)'
```

To change site title, do not forget to include additional quotes:

```
rhc -aweblate env set WEBLATE_SITE_TITLE='"Custom Title"'
```

New settings will only take effect after restarting Weblate:

```
rhc -aweblate app stop
rhc -aweblate app start
```

Restarting using `rhc -aweblate app restart` does not work. For security reasons only constant expressions are allowed as values. With the exception of environment variables which can be referenced using `${ENV_VAR}`. For example:

```
rhc -aweblate env set WEBLATE_PRE_COMMIT_SCRIPTS='("${OPENSIFT_DATA_DIR}/examples/hook-generate-mo",
```

You can check the effective settings Weblate is using by running:

```
rhc -aweblate ssh settings
```

This will also print syntax errors in your expressions. To reset a setting to its preconfigured value just delete the corresponding environment variable:

```
rhc -aweblate env unset WEBLATE_ADMINS
```

See also:

Configuration

Updating

It is recommended that you try updates on a clone of your Weblate installation before running the actual update. To create such a clone run:

```
rhc -aweblate2 app create --from-app weblate
```

Visit the newly given URL with a browser and wait for the install/update page to disappear.

You can update your Weblate installation on OpenShift directly from Weblate's github repository by executing:

```
rhc -aweblate2 ssh update https://github.com/nijel/weblate.git
```

The identifier right of the # sign identifies the version of Weblate to install. For a list of available versions see here: <https://github.com/nijel/weblate/tags>. Please note that the update process will not work if you modified the git repository of your weblate installation. You can force an update by specifying the `--force` option to the update script. However any changes you made to the git repository of your installation will be discarded:

```
rhc -aweblate2 ssh update --force https://github.com/nijel/weblate.git
```

The `--force` option is also needed when downgrading to an older version. Please note that only version 2.0 and newer can be installed on OpenShift, as older versions don't include the necessary configuration files.

The update script takes care of the following update steps as described under *Generic upgrade instructions*.

- Install any new requirements
- `manage.py migrate`
- `manage.py setupgroups --move`
- `manage.py setuplang`
- `manage.py rebuild_index --all`
- `manage.py collectstatic --noinput`

4.3.4 Bitnami Weblate stack

Bitnami provides Weblate stack for many platforms at <https://bitnami.com/stack/weblate>. The setup will be adjusted during installation, see <https://bitnami.com/stack/weblate/README.txt> for more documentation.

4.4 Upgrading Weblate

4.4.1 Upgrading

Generic upgrade instructions

Before upgrading, please check current *Software requirements* as they might have changed. Once all requirements are installed or updated, please adjust your `settings.py` to match changes in the configuration (consult `settings_example.py` for correct values).

To upgrade database structure, you should run:

```
./manage.py migrate
```

To collect new static files, run:

```
./manage.py collectstatic --noinput
```

To upgrade default set of privileges definitions (optional), run:

```
./manage.py setupgroups
```

To upgrade default set of language definitions (optional), run:

```
./manage.py setuplang
```

Changed in version 1.2: Since version 1.2 the migration is done using South module, to upgrade to 1.2, please see [Version specific instructions](#).

Changed in version 1.9: Since version 1.9, Weblate also supports Django 1.7 migrations, please check [Upgrading to Django 1.7](#) for more information.

Changed in version 2.3: Since version 2.3, Weblate supports only Django native migrations, South is no longer supported, please check [Upgrading to Django 1.7](#) for more information.

Version specific instructions

Upgrade from 0.5 to 0.6

On upgrade to version 0.6 you should run `./manage.py syncdb` and `./manage.py setupgroups --move` to setup access control as described in installation section.

Upgrade from 0.6 to 0.7

On upgrade to version 0.7 you should run `./manage.py syncdb` to setup new tables and `./manage.py rebuild_index` to build index for fulltext search.

Upgrade from 0.7 to 0.8

On upgrade to version 0.8 you should run `./manage.py syncdb` to setup new tables, `./manage.py setupgroups` to update privileges setup and `./manage.py rebuild_index` to rebuild index for fulltext search.

Upgrade from 0.8 to 0.9

On upgrade to version 0.9 file structure has changed. You need to move `repos` and `whoosh-index` to `weblate` folder. Also running `./manage.py syncdb`, `./manage.py setupgroups` and `./manage.py setuplang` is recommended to get latest updates of privileges and language definitions.

Upgrade from 0.9 to 1.0

On upgrade to version 1.0 one field has been added to database, you need to invoke following SQL command to adjust it:


```
ALTER TABLE `trans_subproject` ADD `template` VARCHAR(200);
```

Upgrade from 1.0 (1.1) to 1.2

On upgrade to version 1.2, the migration procedure has changed. It now uses South for migrating database. To switch to this new migration schema, you need to run following commands:

```
./manage.py syncdb
./manage.py migrate trans 0001 --fake
./manage.py migrate accounts 0001 --fake
./manage.py migrate lang 0001 --fake
```

Also please note that there are several new requirements and version 0.8 of django-registration is now being required, see [Software requirements](#) for more details.

Once you have done this, you can use [Generic upgrade instructions](#).

Upgrade from 1.2 to 1.3

Since 1.3, `settings.py` is not shipped with Weblate, but only example settings as `settings_example.py` it is recommended to use it as new base for your setup.

Upgrade from 1.4 to 1.5

Several internal modules and paths have been renamed and changed, please adjust your `settings.py` to match that (consult `settings_example.py` for correct values).

- Many modules lost their `weblate.` prefix.
- Checks were moved to submodules.
- Locales were moved to top level directory.

The migration of database structure to 1.5 might take quite long, it is recommended to put your site offline, while the migration is going on.

Note: If you have update in same directory, stale `*.pyc` files might be left around and cause various import errors. To recover from this, delete all of them in Weblate's directory, for example by `find . -name '*.pyc' -delete`.

Upgrade from 1.6 to 1.7

The migration of database structure to 1.7 might take quite long, it is recommended to put your site offline, while the migration is going on.

If you are translating monolingual files, it is recommended to rerun quality checks as they might have been wrongly linked to units in previous versions.

Upgrade from 1.7 to 1.8

The migration of database structure to 1.8 might take quite long, it is recommended to put your site offline, while the migration is going on.

Authentication setup has been changed and some internal modules have changed name, please adjust your `settings.py` to match that (consult `settings_example.py` for correct values).

Also please note that there are several new requirements, see *Software requirements* for more details.

Upgrade from 1.8 to 1.9

Several internal modules and paths have been renamed and changed, please adjust your `settings.py` to match that (consult `settings_example.py` for correct values).

See also:

If you are upgrading to Django 1.7 in same step, please consult *Upgrading to Django 1.7*.

Upgrade from 1.9 to 2.0

Several internal modules and paths have been renamed and changed, please adjust your `settings.py` to match that (consult `settings_example.py` for correct values).

This upgrade also requires you to upgrade python-social-auth from 0.1.x to 0.2.x series, what will most likely need to fake one of their migrations (see *Upgrading PSA with South* for more information):

```
./manage.py migrate --fake default
```

See also:

If you are upgrading to Django 1.7 in same step, please consult *Upgrading to Django 1.7*.

Upgrade from 2.0 to 2.1

The filesystem paths configuration has changed, the `GIT_ROOT` and `WHOOSH_INDEX` are gone and now all data resides in `DATA_DIR`. The existing data should be automatically migrated by supplied migration, but in case of non standard setup, you might need to move these manually.

See also:

If you are upgrading to Django 1.7 in same step, please consult *Upgrading to Django 1.7*.

Upgrade from 2.1 to 2.2

Weblate now supports fulltext search on additional fields. In order to make it work on existing data you need to update fulltext index by:

```
./manage.py rebuild_index --clean --all
```

If you have some monolingual translations, Weblate now allows to edit template (source) strings as well. To see them, you need to reload translations, what will either happen automatically on next repository update or you can force it manually:

```
./manage.py loadpo --all
```

See also:

If you are upgrading to Django 1.7 in same step, please consult [Upgrading to Django 1.7](#).

Upgrade from 2.2 to 2.3

If you have not yet performed upgrade to Django 1.7 and newer, first upgrade to 2.2 following instructions above. Weblate 2.3 no longer supports migration from Django 1.6.

If you were using Weblate 2.2 with Django 1.6, you will now need to fake some migrations:

```
./manage.py migrate --fake accounts 0004_auto_20150108_1424
./manage.py migrate --fake lang 0001_initial
./manage.py migrate --fake trans 0018_auto_20150213_1447
```

Previous Weblate releases contained bug which made some monolingual translations behave inconsistently for fuzzy and not translated strings, if you have such, it is recommended to run:

```
./manage.py fixup_flags --all
```

See also:

[Generic upgrade instructions](#)

Upgrade from 2.3 to 2.4

Handling of static content has been rewritten, please adjust configuration of your webserver accordingly (see [Serving static files](#) for more details). Most importantly:

- /media/ path is no longer used
- /static/ path now holds both admin and Weblate static files

There is now also additional dependency - `django_compressor`, please install it prior to upgrading.

See also:

[Generic upgrade instructions](#)

Upgrade from 2.4 to 2.5

The fulltext index has been changed, so unless you rebuild it, the fulltext search will not work. To rebuild it, execute:

```
./manage.py rebuild_index --clean --all
```

See also:

[Generic upgrade instructions](#)

Upgrade from 2.5 to 2.6

Follow generic upgrade instructions, there is no special change.

Notable configuration or dependencies changes:

- new dependency on Django REST Framework, see [Software requirements](#)

- example configuration now configures Django REST Framework, please adjust your settings accordingly
- the USE_TZ settings is now enabled by default

Note: Weblate now much more relies on correct site name in the database, please see [Set correct site name](#) for instructions how to set it up.

See also:

[Generic upgrade instructions](#)

Upgrade from 2.6 to 2.7

Follow generic upgrade instructions, there is no special change.

Notable configuration or dependencies changes:

- new optional dependency on python-bidi, see [Software requirements](#)
- Google Web Translation was removed, remove it from your configuration

See also:

[Generic upgrade instructions](#)

Upgrade from 2.7 to 2.8

Follow generic upgrade instructions, there is no special change.

Notable configuration or dependencies changes:

- new dependency on defusedxml, see [Software requirements](#)
- there is new quality check: [Invalid XML markup](#)

See also:

[Generic upgrade instructions](#)

4.4.2 Upgrading to Django 1.7

Django 1.7 has a new feature to handle database schema upgrade called “migrations” which is incompatible with South (used before by Weblate).

Before migrating to Django 1.7, you first need to apply all migrations from South. If you already have upgraded Django to 1.7, you can do this using virtualenv and `examples/migrate-south` script:

```
examples/migrate-south --settings weblate.settings
```

Once you have done that, you can run Django migrations and work as usual. For the initial setup, you might need to fake some of the migrations though:

```
./manage.py migrate --fake-initial
```

4.4.3 Migrating from Pootle

As Weblate was originally written as replacement from Pootle, it is supported to migrate user accounts from Pootle. All you need to do is to copy `auth_user` table from Pootle, user profiles will be automatically created for users as they log in and they will be asked to update their settings. Alternatively you can use `importusers` to import dumped user credentials.

4.5 Authentication

4.5.1 User registration

The default setup for Weblate is to use `python-social-auth` for handling new users. This allows them to register using form on the website and after confirming their email they can contribute or by using some third party service to authenticate.

You can also completely disable new users registration using `REGISTRATION_OPEN`.

4.5.2 Authentication backends

By default Weblate uses Django built-in authentication and includes various social authentication options. Thanks to using Django authentication, you can also import user database from other Django based projects (see *Migrating from Pootle*).

Django can be additionally configured to authenticate against other means as well.

4.5.3 Social authentication

Thanks to `python-social-auth`, Weblate support authentication using many third party services such as Facebook, GitHub, Google or Bitbucket.

Please check their documentation for generic configuration instructions:

<http://psa.matiasaguirre.net/docs/configuration/django.html>

Note: By default, Weblate relies on third-party authentication services to provide validated email address, in case some of services you want to use do not support this, please remove `social.pipeline.social_auth.associate_by_email` from `SOCIAL_AUTH_PIPELINE` settings.

Enabling individual backends is quite easy, it's just a matter of adding entry to `AUTHENTICATION_BACKENDS` setting and possibly adding keys needed for given authentication. Please note that some backends do not provide user email by default, you have to request it explicitly, otherwise Weblate will not be able to properly credit users contributions.

OpenID authentication

For OpenID based services it's usually just a matter of enabling them. Following section enables OpenID authentication for OpenSUSE, Fedora and Ubuntu:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    'social.backends.email.EmailAuth',
    'social.backends.suse.OpenSUSEOpenId',
    'social.backends.ubuntu.UbuntuOpenId',
    'social.backends.fedora.FedoraOpenId',
    'weblate.accounts.auth.WeblateUserBackend',
)
```

GitHub authentication

You need to register application on GitHub and then tell Weblate all the secrets:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    'social.backends.github.GithubOAuth2',
    'social.backends.email.EmailAuth',
    'weblate.accounts.auth.WeblateUserBackend',
)

# Social auth backends setup
SOCIAL_AUTH_GITHUB_KEY = 'GitHub Client ID'
SOCIAL_AUTH_GITHUB_SECRET = 'GitHub Client Secret'
SOCIAL_AUTH_GITHUB_SCOPE = ['user:email']
```

See also:

Python Social Auth backends

Google OAuth2

For using Google OAuth2, you need to register application on <<https://console.developers.google.com/>> and enable Google+ API.

The redirect URL is `https://WEBLATE_SERVER/accounts/complete/google-oauth2/`

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    'social.backends.google.GoogleOAuth2',
    'social.backends.email.EmailAuth',
    'weblate.accounts.auth.WeblateUserBackend',
)

# Social auth backends setup
SOCIAL_AUTH_GOOGLE_OAUTH2_KEY = 'Client ID'
SOCIAL_AUTH_GOOGLE_OAUTH2_SECRET = 'Client secret'
```

Facebook OAuth2

As usual with OAuth2 services, you need to register your application with Facebook. Once this is done, you can configure Weblate to use it:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    'social.backends.facebook.FacebookOAuth2',
    'social.backends.email.EmailAuth',
)
```

```

    'weblate.accounts.auth.WeblateUserBackend',
)

# Social auth backends setup
SOCIAL_AUTH_FACEBOOK_KEY = 'key'
SOCIAL_AUTH_FACEBOOK_SECRET = 'secret'
SOCIAL_AUTH_FACEBOOK_SCOPE = ['email', 'public_profile']

```

4.5.4 LDAP authentication

LDAP authentication can be best achieved using *django-auth-ldap* package. You can install it by usual means:

```

# Using PyPI
pip install django-auth-ldap

# Using apt-get
apt-get install python-django-auth-ldap

```

Once you have the package installed, you can hook it to Django authentication:

```

# Add LDAP backed, keep Django one if you want to be able to login
# even without LDAP for admin account
AUTHENTICATION_BACKENDS = (
    'django_auth_ldap.backend.LDAPBackend',
    'weblate.accounts.auth.WeblateUserBackend',
)

# LDAP server address
AUTH_LDAP_SERVER_URI = 'ldaps://ldap.example.net'

# DN to use for authentication
AUTH_LDAP_USER_DN_TEMPLATE = 'cn=%(user)s,o=Example'
# Depending on your LDAP server, you might use different DN
# like:
# AUTH_LDAP_USER_DN_TEMPLATE = 'ou=users,dc=example,dc=com'

# List of attributes to import from LDAP on login
# Weblate stores full user name in the first_name attribute
AUTH_LDAP_USER_ATTR_MAP = {
    'first_name': 'name',
    'email': 'mail',
}

```

See also:

Django Authentication Using LDAP

4.5.5 CAS authentication

CAS authentication can be achieved using a package such as *django-cas-ng*.

Step one is disclosing the email field of the user via CAS. This has to be configured on the CAS server itself and requires you run at least CAS v2 since CAS v1 doesn't support attributes at all.

Step two is updating Weblate to use your CAS server and attributes.

To install *django-cas-ng*:

```
pip install django-cas-ng
```

Once you have the package installed you can hook it up to the Django authentication system by modifying the `settings.py` file:

```
# Add CAS backed, keep Django one if you want to be able to login
# even without LDAP for admin account
AUTHENTICATION_BACKENDS = (
    'django_cas_ng.backends.CASBackend',
    'weblate.accounts.auth.WeblateUserBackend',
)

# CAS server address
CAS_SERVER_URL = 'https://cas.example.net/cas/'

# Add django_cas_ng somewhere in the list of INSTALLED_APPS
INSTALLED_APPS = (
    ...,
    'django_cas_ng'
)
```

Finally, a signal can be used to map the email field to the user object. For this to work you have to import the signal from the *django-cas-ng* package and connect your code with this signal. Doing this inside your settings file can cause problems, therefore it's suggested to put it:

- in your app config's `ready` method (Django 1.7 and higher)
- at the end of your `models.py` file (Django 1.6 and lower)
- in the project's `urls.py` file (when no models exist)

```
from django_cas_ng.signals import cas_user_authenticated
from django.dispatch import receiver
@receiver(cas_user_authenticated)
def update_user_email_address(sender, user=None, attributes=None, **kwargs):
    # If your CAS server does not always include the email attribute
    # you can wrap the next two lines of code in a try/catch block.
    user.email = attributes['email']
    user.save()
```

See also:

Django CAS NG

4.6 Access control

Weblate uses privileges system based on Django. The default setup (after you run *setupgroups*) consists of three groups *Guests*, *Users*, *Owners* and *Managers* which have privileges as described above. All new users are automatically added to *Users* group. The *Guests* groups is used for not logged in users. The *Owners* groups adds special privileges to users owning a project.

Basically *Users* are meant as regular translators and *Managers* for developers who need more control over the translation - they can force committing changes to VCS, push changes upstream (if Weblate is configured to do so) or disable translation (eg. when there are some major changes happening upstream).

To customize this setup, it is recommended to remove privileges from *Users* group and create additional groups with finer privileges (eg. *Translators* group, which will be allowed to save translations and manage suggestions) and add selected users to this group. You can do all this from Django admin interface.

To completely lock down your Weblate installation you can use [LOGIN_REQUIRED_URLS](#) for forcing users to login and [REGISTRATION_OPEN](#) for disallowing new registrations.

For more fine-grained access control, see [Per project access control](#) and [Group-based access control](#).

Warning: Never remove Weblate predefined groups (*Guests*, *Users*, *Owners* and *Managers*). If you do not want to use these features, just remove all privileges from them.

4.6.1 Extra privileges

Weblate defines following extra privileges:

Can upload translation [Users, Managers, Owners] Uploading of translation files.

Can overwrite with translation upload [Users, Managers, Owners] Overwriting existing translations by uploading translation file.

Can define author of translation upload [Managers, Owners] Allows to define custom authorship when uploading translation file.

Can force committing of translation [Managers, Owners] Can force VCS commit in the web interface.

Can see VCS repository URL [Users, Managers, Owners, Guests] Can see VCS repository URL inside Weblate

Can update translation from VCS [Managers, Owners] Can force VCS pull in the web interface.

Can push translations to remote VCS [Managers, Owners] Can force VCS push in the web interface.

Can do automatic translation using other project strings [Managers, Owners] Can do automatic translation based on strings from other components

Can lock whole translation project [Managers, Owners] Can lock translation for updates, useful while doing some major changes in the project.

Can reset translations to match remote VCS [Managers, Owners] Can reset VCS repository to match remote VCS.

Can save translation [Users, Managers, Owners] Can save translation (might be disabled with [Suggestion voting](#)).

Can save template [Users, Managers, Owners] Can edit source strings (usually English)

Can accept suggestion [Users, Managers, Owners] Can accept suggestion (might be disabled with [Suggestion voting](#)).

Can delete suggestion [Users, Managers, Owners] Can delete suggestion (might be disabled with [Suggestion voting](#)).

Can delete comment [Managers, Owners] Can delete comment.

Can vote for suggestion [Users, Managers, Owners] Can vote for suggestion (see [Suggestion voting](#)).

Can override suggestion state [Managers, Owners] Can save translation, accept or delete suggestion when automatic accepting by voting for suggestions is enabled (see [Suggestion voting](#)).

Can import dictionary [Users, Managers, Owners] Can import dictionary from translation file.

Can add dictionary [Users, Managers, Owners] Can add dictionary entries.

Can change dictionary [Users, Managers, Owners] Can change dictionary entries.

Can delete dictionary [Users, Managers, Owners] Can delete dictionary entries.

Can lock translation for translating [Users, Managers, Owners] Can lock translation while translating (see [Translation locking](#)).

Can add suggestion [Users, Managers, Owners, Guests] Can add new suggestions.

Can use machine translation [Users, Managers, Owners] Can use machine translations (see [Machine translation setup](#)).

Can manage ACL rules for a project [Managers, Owners] Can add users to ACL controlled projects (see [Per project access control](#))

Can edit priority [Managers, Owners] Can adjust source string priority

Can edit check flags [Managers, Owners] Can adjust source string check flags

Can download changes [Managers, Owners] Can download changes in a CSV format.

Can display reports [Managers, Owners] Can display detailed translation reports.

Can add translation [Users, Managers, Owners] Can start translations in new language.

Can delete translation [Managers, Owners] Can remove translation.

4.6.2 Per project access control

New in version 1.4: This feature is available since Weblate 1.4.

Note: By enabling ACL, all users are prohibited to access anything within given project unless you add them the permission to do that.

Additionally you can limit users access to individual projects. This feature is enabled by *Enable ACL* at Project configuration. Once you enable this, users without specific privilege (*trans | project | Can access project NAME*) can not access this project. An user group with same name as a project is also automatically created to ease you management of the privilege.

To allow access to this project, you have to add the privilege to do so either directly to given user or group of users in Django admin interface. Or using user management on project page as described in [Managing per project access control](#).

See also:

[Managing users in the Django admin](#)

Note: Even with ACL enabled some summary information will be available about your project:

- Site wide statistics includes counts for all projects
 - Site wide languages summary includes counts for all projects
-

4.6.3 Automatic group assignments

New in version 2.5.

You can configure Weblate to automatically add users to groups based on their email. This automatic assignment happens only at time of account creation.

This can be configured in the Django admin interface (in the *Accounts* section).

4.6.4 Group-based access control

New in version 2.5: This feature is available since Weblate 2.5.

You can designate groups that have exclusive access to a particular language, project or component, or a combination thereof. For example, you can use this feature to designate a language-specific translator team with full privileges for their own language.

This works by “locking” the group(s) in question to the object, the effect of which is twofold.

Firstly, groups that are locked for some object are the *only* groups that have any privileges on that object. If a user is not a member of the locked group, they cannot edit the object, even if their privileges or group membership allows them to edit other (unlocked) objects.

Secondly, privileges of the locked group don’t apply on objects other than those to which the group is locked. If a user is a member of the locked group which grants them edit privileges, they can only edit the object locked to the group, unless something else grants them a general edit privilege.

This can be configured in the Django admin interface. The recommended workflow is as follows:

1. Create a new *group ACL* in the *Group ACL* section. Pick a project, subproject, language, or a combination, which will be locked to this group ACL.
2. Use the + (plus sign) button to the right of *Groups* field to create a new group. In the pop-up window, fill out the group name and assign permissions.
3. Save the newly created group ACL.
4. In the *Users* section of the admin interface, assign users to the newly created group.

For example, you could create a group called `czech_translators`, assign it full privileges, and lock it to Czech language. From that point on, all users in this groups would get full privileges for the Czech language in all projects and components, but not for any other languages. Also, users who are not members of the `czech_translators` group would get no privileges on Czech language in any project.

In order to delete a group ACL, make sure that you first delete the group (or remove its privileges), and only then delete the group ACL. Otherwise, there will be a window of time in which the group is “unlocked” and its permissions apply to all objects. In our example, members of `czech_translators` group would have full privileges for everything that is not locked to other groups.

It is possible to lock multiple groups within a single group ACL. One group can also be locked to multiple objects through multiple group ACLs. As long as a group is recorded in at least one group ACL, it’s considered to be “locked”, and its privileges do not apply outside the locks.

Group ACLs apply in order of specificity. “Component” is considered most specific, “Language” is least specific. Combinations follow the most specific part of the combination: a group ACL that is locked to a particular component is more specific than a group ACL locked to this component’s project and a particular language. That means that members of the component-specific groups will have privileges on the component, and members of the project-and-language-specific groups will not. The latter will, of course, have privileges on their language in all other components of the project.

For project-level actions (such as pushing upstream, setting priority, etc.), you must create a group ACL locked to *only* the project. Combinations, such as project plus language, only apply to actions on individual translations.

4.6.5 Managing users and groups

All users and groups can be managed using Django admin interface, which is available under `/admin/` URL.

Managing per project access control

Note: This feature only works for ACL controlled projects, see *Per project access control*.

Users with *Can manage ACL rules for a project* privilege (see *Access control*) can also manage users in projects with access control enabled on the project page. You can add or remove users to the project or make them owners.

The user management is available in *Tools* menu of a project:

Hosted Weblate

Website

translated 100%

Overview

History

Activity

Tools

Share

Users

Username	Full name	
nijel Owner	Michal Čihař	<div><div>Remove</div><div>Revoke ownership</div></div>
lem9 Owner	Marc Delisle	<div><div>Remove</div><div>Revoke ownership</div></div>
pavolzibrita	Pavol Zibrita	<div><div>Remove</div><div>Make owner</div></div>

Data exports

Commit

Repository maintenance

Failing checks

Ignored checks

Manage users

Add new user

User to add

Please provide username or email. User needs to already have an active account in Weblate.

Add

See also:

Per project access control


4.7 Translation projects

4.7.1 Translation organization

Weblate organizes translatable content into tree like structure. The toplevel object is *Project configuration*, which should hold all translations which belong together (for example translation of an application in several versions and/or documentation). On the next level, there is *Component configuration*, which is actually the component to translate. Here you define VCS repository to use and mask of files to translate. Bellow *Component configuration* there are individual translations, which are handled automatically by Weblate as the translation files (matching mask defined in *Component configuration*) appear in VCS repository.

4.7.2 Administration

Administration of Weblate is done through standard Django admin interface, which is available under `/admin/` URL. Once logged in as user with proper privileges, you can access it using wrench icon in top navigation:



Here you can manage objects stored in the database, such as users, translations and other settings:

Django administration

Welcome, **Michal Čihař**. [View site](#) / [Documentation](#) / [Change password](#) / [Log out](#)

Site administration

Reports		
Status of repositories		
SSH keys		
Performance report		
Accounts		
Profiles	+ Add	Change
Verified emails	+ Add	Change
Authentication and Authorization		
Groups	+ Add	Change
Users	+ Add	Change
Python Social Auth		
Associations	+ Add	Change
Nonces	+ Add	Change
User social auths	+ Add	Change
Sites		
Sites	+ Add	Change
Weblate languages		
Languages	+ Add	Change
Weblate translations		
Advertisements	+ Add	Change
Components	+ Add	Change
Projects	+ Add	Change
Whiteboard messages	+ Add	Change

Recent Actions
My Actions

- [iptv/PHP](#)
Component
- [+ iptv/PHP](#)
Component
- [+ iptv](#)
Project
- [127.0.0.1:8888](#)
Site
- [✗ Cologneian](#)
Language
- [+ Advertisement object](#)
Advertisement
- [✗ nijel4751bd8a87334443](#)
User
- [✗ nijeladecac24b8cc4e9c](#)
User
- [✗ nijelb129e2b3f6544df4](#)
User
- [✗ nijel7e9d081948914b7a](#)
User

In the *Reports* section you can check status of your site, tweak it for *Production setup* or manage SSH keys to access *Accessing repositories*.

All sections below you can manage database objects. The most interesting one is probably *Weblate translations*, where you can manage translatable projects, see *Project configuration* and *Component configuration*.

Another section, *Weblate languages* holds language definitions, see *Language definitions* for more details.

4.7.3 Adding new components

All translation components need to be available as VCS repositories and are organized as project/component structure.


Weblate supports wide range of translation formats (both bilingual and monolingua) supported by translate toolkit, see *Supported formats* for more information.

Adding project

First you have to add project, which will serve as container for all components. Usually you create one project for one piece of software or book (see *Project configuration* for information on individual parameters):

Add Project

Required fields are marked as **bold**, you can find more information in the [documentation](#).

Project name:	<input type="text" value="Weblate"/>
	Name to display
URL slug:	<input type="text" value="weblate"/>
	Name used in URLs and file names.
Project website:	<input type="text" value="http://weblate.org/"/>
	Main website of translated project.
Mailing list:	<input type="text" value="weblate@lists.cihar.com"/>
	Mailing list for translators.
Translation instructions:	<input type="text" value="http://weblate.org/contribute/"/>
	URL with instructions for translators.
<input checked="" type="checkbox"/> Push on commit	
	Whether the repository should be pushed upstream on every commit.
<input checked="" type="checkbox"/> Set Translation-Team header	
	Whether the Translation-Team in file headers should be updated by Weblate.
<input type="checkbox"/> Enable ACL	
	Whether to enable ACL for this project, please check documentation before enabling this.
<input checked="" type="checkbox"/> Enable hooks	
	Whether to allow updating this repository by remote hooks.
Owner:	<input type="text" value="nijel"/> 
	Owner of the project.

See also:

[Project configuration](#)

Bilingual components

Once you have added a project, you can add translation components to it (see *[Component configuration](#)* for information on individual parameters):

Django administration

Welcome, **Michal Čihař**. [Documentation](#) / [Change password](#) / [Log out](#)[Home](#) > [Weblate translations](#) > [Components](#) > Add Component

Add Component

Required fields are marked as **bold**, you can find more information in the [documentation](#).

Importing a new translation can take some time, please check [our documentation](#) for information on how to improve this.

Component name:	<input type="text" value="website"/> Name to display
URL slug:	<input type="text" value="website"/> Name used in URLs and file names.
Project:	<input type="text" value="Weblate"/>
Version control system:	<input type="text" value="Git"/> Version control system to use to access your repository with translations.
Source code repository:	<input type="text" value="git://github.com/nijel/weblate-web.git"/> URL of a repository, use weblate://project/component for sharing with other component.
Repository push URL:	<input type="text" value="git@github.com:nijel/weblate-web.git"/> URL of a push repository, pushing is disabled if empty.
Repository browser:	<input type="text" value="://github.com/nijel/weblate-web/blob/%(branch)s/%(file)s#L%(line)s"/> Link to repository browser, use %(branch)s for branch, %(file)s and %(line)s as filename and line placeholders.
Exported repository URL:	<input type="text" value="git://git.weblate.org/weblate-web.git"/> URL of a repository where users can fetch changes from Weblate
Source string bug report address:	<input type="text" value="weblate@lists.cihar.com"/> Email address where errors in source string will be reported, keep empty for no emails.
Repository branch:	<input type="text" value="master"/> Repository branch to translate
File mask:	<input type="text" value="locale/*/LC_MESSAGES/django.po"/> Path of files to translate, use * instead of language code, for example: po/*.po or locale/*/LC_MESSAGES/django.po.
Monolingual base language file:	<input type="text"/> Filename of translations base file, which contains all strings and their source; this is recommended to use for monolingual translation formats.
<input checked="" type="checkbox"/> Edit base file	Whether users will be able to edit base file for monolingual translations.
Base file for new translations:	<input type="text" value="locale/django.pot"/> Filename of file which is used for creating new translations. For Gettext choose .pot file.
File format:	<input type="text" value="Gettext PO file"/> Automatic detection might fail for some formats and is slightly slower.

4.7. Translation projects

Additional commit file:

Additional file to include in commits; please check documentation for more details.

Post-update script:

See also:

[Component configuration](#)

Monolingual components

For easier translating of monolingual formats, you should provide template file, which contains mapping of message IDs to source language (usually English) (see *[Component configuration](#)* for information on individual parameters):



Django administration

Welcome, **Michal Čihař**. [Documentation](#) / [Change password](#) / [Log out](#)[Home](#) > [Weblate translations](#) > [Components](#) > Add Component

Add Component

Required fields are marked as **bold**, you can find more information in the [documentation](#).

Importing a new translation can take some time, please check [our documentation](#) for information on how to improve this.

Component name:	<input type="text" value="iOS"/> Name to display
URL slug:	<input type="text" value="ios"/> Name used in URLs and file names.
Project:	<input type="text" value="OsmAnd"/> 
Version control system:	<input type="text" value="Git"/> Version control system to use to access your repository with translations.
Source code repository:	<input type="text" value="https://github.com/osmandapp/OsmAnd-ios.git"/> URL of a repository, use weblate://project/component for sharing with other component.
Repository push URL:	<input type="text" value="git@github.com:/osmandapp/OsmAnd-ios.git"/> URL of a push repository, pushing is disabled if empty.
Repository browser:	<input type="text"/> Link to repository browser, use %(branch)s for branch, %(file)s and %(line)s as filename and line placeholders.
Exported repository URL:	<input type="text" value="git://git.weblate.org/osmand-ios.git"/> URL of a repository where users can fetch changes from Weblate
Source string bug report address:	<input type="text"/> Email address where errors in source string will be reported, keep empty for no emails.
Repository branch:	<input type="text" value="master"/> Repository branch to translate
File mask:	<input type="text" value="Resources/*.lproj/Localizable.strings"/> Path of files to translate, use * instead of language code, for example: po/*.po or locale/*/LC_MESSAGES/django.po.
Monolingual base language file:	<input type="text" value="Resources/en.lproj/Localizable.strings"/> Filename of translations base file, which contains all strings and their source; this is recommended to use for monolingual translation formats.
<input type="checkbox"/> Edit base file	Whether users will be able to edit base file for monolingual translations.
Base file for new translations:	<input type="text"/> Filename of file which is used for creating new translations. For Gettext choose .pot file.
File format:	<input type="text" value="OS X Strings (UTF-8)"/>  Automatic detection might fail for some formats and is slightly slower.

4.7. Translation projects

Additional commit file:

 Additional file to include in commits; please check documentation for more details.

Post-update script:

See also:

Component configuration

4.7.4 Project configuration

To add new component to translate, you need to create translation project first. The project is sort of shelf, in which real translations are folded. All components in same project share suggestions and dictionary, also the translations are automatically propagated through the all component in single project (unless disabled in component configuration).

The project has only few attributes giving translators information about project:

Project website URL where translators can find more information about the project.

Mailing list Mailing list where translators can discuss or comment translations.

Translation instructions URL where you have more detailed instructions for translators.

Push on commit Whether any committed changes should be automatically pushed to upstream repository.

Set Translation-Team header Whether Weblate should manage Translation-Team header (this is *GNU Gettext* only feature right now).

Enable ACL Enable per project access control, see *Per project access control* for more details.

Enable hooks Whether unauthenticated *Notification hooks* will be enabled for this repository.

Owners You can also configure project owners, who will always get important notifications about project and will have additional privileges to control translations within this project (see *Access control*).

Source language Language used for source strings in all components. Change this if you are translating from something else than English.

Adjusting interaction

There are also additional features which you can control, like automatic pushing of changes (see also *Pushing changes*) or maintaining of Translation-Team header.

4.7.5 Component configuration

Component is real component for translating. You enter VCS repository location and file mask which files to translate and Weblate automatically fetches the VCS and finds all matching translatable files.

Note: It is recommended to have translation components of reasonable size - split the translation by anything what makes sense in your case (individual applications or addons, book chapters or websites).

Weblate handles just fine translations with 10000 of units, but it is harder to split work and coordinate amongh translators with such big translation. Also when one translator is working on a component, this translation is locked for others, see *Translation locking*.

Should the language definition for translation be missing, empty definition is created and named as “cs_CZ (generated)”. You should adjust the definition and report this back to Weblate authors so that missing language can be included in next release.

The component contains all important parameters for working with VCS and getting translations out of it:

Version control system VCS to use, see *Version control integration* for details.

Source code repository VCS repository used to pull changes, see [Accessing repositories](#) for more details.

This can be either real VCS URL or `weblate://project/component` indicating that the repository should be shared with another component.

Repository push URL Repository URL used for pushing, this is completely optional and push support will be disabled when this is empty. See [Accessing repositories](#) for more details on how to specify repository URL.

Repository browser URL of repository browser to display source files (location where messages are used). When empty no such links will be generated.

For example on GitHub, you would use something like `https://github.com/WeblateOrg/hello/blob/%(branch)`

Exported repository URL URL where changes made by Weblate are exported. This is important when [Continuous translation](#) is not used or when there is need to manually merge changes.

Repository branch Which branch to checkout from the VCS and where to look for translations.

File mask Mask of files to translate including path. It should include one `*` replacing language code (see [Language definitions](#) for information how this is processed). In case your repository contains more than one translation files (eg. more Gettext domains), you need to create separate component for each.

For example `po/*.po` or `locale/*/LC_MESSAGES/django.po`.

Monolingual base language file Base file containing strings definition for [Monolingual components](#).

Edit base file Whether to allow editing of base file for [Monolingual components](#).

Base file for new translations Base file used to generate new translations, eg. `.pot` file with Gettext.

File format Translation file format, see also [Supported formats](#).

Source string bug report address Email address used for reporting upstream bugs. This address will also receive notification about any source string comments made in Weblate.

Locked You can lock the translation to prevent updates by users.

Allow translation propagation You can disable propagation of translations to this component from other components within same project. This really depends on what you are translating, sometimes it's desirable to have same string used.

It's usually good idea to disable this for monolingual translations unless you are using same IDs across whole project.

Post-update script One of scripts defined in [POST_UPDATE_SCRIPTS](#) which is executed after receiving update. This can be used to update the translation files.

Pre-commit script One of scripts defined in [PRE_COMMIT_SCRIPTS](#) which is executed before commit. This can be used to generate some metadata about translation or to generate binary form of a translation.

Post-commit script One of scripts defined in [POST_COMMIT_SCRIPTS](#) which is executed after commit. This can be used to notify external parties about the change.

Post-push script One of scripts defined in [POST_PUSH_SCRIPTS](#) which is executed after push to remote repository. This can be used to generate notify external parties about the change in repository (i.e. create pull request).

Post-add script One of scripts defined in [POST_ADD_SCRIPTS](#) which is executed when new translation has been added. This can be used to adjust additional files in the repository when adding new translation.

Additional commit files Additional files to include in the commit (separated by newline), usually this one is generated by the pre commit or post add scripts described above.

Supply the `%(language)s` in the path like this: `path/to/additinal/%(language)s_file.example`

Save translation history Whether to store history of translation changes in database.

Suggestion voting Enable voting for suggestions, see [Suggestion voting](#).

Autoaccept suggestions Automatically accept voted suggestions, see [Suggestion voting](#).

Quality checks flags Additional flags to pass to quality checks, see [Customizing checks](#).

Translation license License of this translation.

License URL URL where users can find full text of a license.

New language How to handle requests for creating new languages. Please note that availability of choices depends on the file format, see [Supported formats](#).

Merge style You can configure how the updates from upstream repository are handled. This might not be supported for some VCS. See [Merge or rebase](#) for more details.

Commit message Message used when committing translation, see [Commit message formatting](#).

Committer name Name of committer used on Weblate commits, the author will be always the real translator. On some VCS this might be not supported. Default value can be changed by [DEFAULT_COMMITTER_NAME](#).

Committer email Email of committer used on Weblate commits, the author will be always the real translator. On some VCS this might be not supported. Default value can be changed by [DEFAULT_COMMITTER_EMAIL](#).

Language filter Regular expression which is used to filter translation when scanning for file mask. This can be used to limit list of languages managed by Weblate (eg. `^(cs|de|es)$` will include only those there languages. Please note that you need to list language codes as they appear in the filename.

Commit message formatting

The commit message on each commit Weblate does, it can use following format strings in the message:

%(language)s Language code

%(language_name)s Language name

%(component)s Component name

%(project)s Project name

%(total)s Total strings count

%(fuzzy)s Count of strings needing review

%(fuzzy_percent)s Percent of strings needing review

%(translated)s Translated strings count

%(translated_percent)s Translated strings percent

See also:

[Does Weblate support other VCS than Git and Mercurial?](#), [Processing repository with scripts](#)

4.7.6 Importing speed

Fetching VCS repository and importing translations to Weblate can be lengthy process depending on size of your translations. Here are some tips to improve this situation:

Clone Git repository in advance

You can put in place Git repository which will be used by Weblate. The repositories are stored in `vcs` directory in path defined by `DATA_DIR` in `settings.py` in `<project>/<component>` directories.

This can be especially useful if you already have local clone of this repository and you can use `--reference` option while cloning:

```
git clone \
  --reference /path/to/checkout \
  https://github.com/nijel/weblate.git \
  weblate/repos/project/component
```

Optimize configuration

The default configuration is useful for testing and debugging Weblate, while for production setup, you should do some adjustments. Many of them have quite big impact on performance. Please check [Production setup](#) for more details, especially:

- [Enable indexing offloading](#)
- [Enable caching](#)
- [Use powerful database engine](#)
- [Disable debug mode](#)

Disable not needed checks

Some quality checks can be quite expensive and if you don't need them, they can save you some time during import. See [CHECK_LIST](#) for more information how to configure this.

4.7.7 Automatic creation of components

In case you have project with dozen of po files, you might want to import all at once. This can be achieved using `import_project` or `import_json`.

First you need to create project which will contain all components and then it's just a matter of running `import_project` or `import_json`.

See also:

[Management commands](#)

4.7.8 Fulltext search

Fulltext search is based on Whoosh. You can either allow Weblate to directly update index on every change to content or offload this to separate process by `OFFLOAD_INDEXING`.

The first approach (immediate updates) allows more up to date index, but suffers locking issues in some setup (eg. Apache's `mod_wsgi`) and produces more fragmented index.

Offloaded indexing is always better choice for production setup - it only marks which items need to be reindexed and you need to schedule background process (`update_index`) to update index. This leads to faster response of the site and less fragmented index with cost that it might be slightly outdated.

See also:

update_index, OFFLOAD_INDEXING, Fulltext search is too slow, I get “Lock Error” quite often while translating, Rebuilding index has failed with “No space left on device”

4.8 Language definitions

In order to properly present different translation Weblate needs to know some information about used languages. Currently it comes with definitions for about 200 languages and the definition include language name, text direction, plural definitions and language code.

4.8.1 Parsing language codes

While parsing translations, Weblate attempts to map language code (usually ISO 639-1 one) to existing language object. If it can not find exact match, it tries to find best fit in existing languages (eg. it ignores default country code for given language - choosing `cs` instead of `cs_CZ`). Should this fail as well, it will create new language definition using the defaults (left to right text direction, one plural) and naming the language `:guilabel:xx_XX (generated)`. You might want to change this in the admin interface (see [Changing language definitions](#)) and report it to our issue tracker (see [Contributing](#)).

4.8.2 Changing language definitions


You can change language definitions in the admin interface (see [Administration](#)). The *Weblate languages* section allows you to change or add language definitions. While editing make sure that all fields are correct (especially plurals and text direction), otherwise the translators won't be able to properly edit those translations.

4.9 Continuous translation

Weblate provides you great infrastructure for translation to closely follow your development. This way translators can work on translations whole time and are not forced to translate huge amount of new texts before release.

The complete process can be described in following steps:

1. Developers make some changes and push them to the VCS repository.
2. Optionally the translation files are updated (this depends on the file format, see [Why does Weblate still shows old translation strings when I've updated the template?](#)).
3. Weblate pulls changes from the VCS repository, see [Updating repositories](#).
4. Once Weblate detects changes in translations, translators will be notified based on their subscription settings.
5. Translators make translations using Weblate web interface.
6. Once translators are done, Weblate commits the changes to the local repository (see [Lazy commits](#)) and pushes them back if it has permissions to do that (see [Pushing changes](#)).



4.9.1 Updating repositories

You should set up some way how backend repositories are updated from their source. You can either use hooks (see [Notification hooks](#)) or just regularly run `updategit --all`.

Whenever Weblate updates the repository, the *Post-update script* hooks are executed.

With Gettext po files, you might be often bitten by conflict in PO file headers. To avoid it, you can use shipped merge driver (examples/git-merge-gettext-po). To use it just put following configuration to your `.gitconfig`:

```
[merge "merge-gettext-po"]
  name = merge driver for gettext po files
  driver = /path/to/weblate/examples/git-merge-gettext-po %O %A %B
```

And enable its use by defining proper attributes in given repository (eg. in `.git/info/attributes`):

```
*.po merge=merge-gettext-po
```

Note: This merge driver assumes the changes in POT files always are done in branch we're trying to merge.

Avoiding merge conflicts

To avoid merge conflicts you should control when to update translation files in upstream repository to avoid Weblate having changes on same file.

You can achieve this using *Weblate's Web API* to force Weblate push all pending changes and lock translation while you are doing changes on your side.

The script for doing updates can look like:

```
# Lock Weblate translation
wlc lock
# Push changes from Weblate to upstream repository
wlc push
# Pull changes from upstream repository to your local copy
git pull
# Update translation files, this example is for Django
./manage.py makemessages --keep-pot -a
git commit -m 'Locale updates' -- locale
# Push changes to upstream repository
git push
# Tell Weblate to pull changes (not needed if Weblate follows your repo
# automatically)
wlc pull
# Unlock translations
wlc unlock
```


If you have multiple components sharing same repository, you need to lock them all separately:

```
wlc lock foo/bar
wlc lock foo/baz
wlc lock foo/baj
```

Note: The example uses *Weblate Client*, which will need configuration (API keys) to be able to control Weblate remotely. You can achieve same using any HTTP client instead of wlc, eg. curl, see *Weblate's Web API*.

Automatically receiving changes from GitHub

Weblate comes with native support for GitHub. To receive notifications on every push to GitHub repository, you just need to enable Weblate Service in the repository settings (*Webhooks & Services*) as shown on the image below:



To set the base URL of your Weblate installation (for example `https://hosted.weblate.org`) and Weblate will be notified about every push to GitHub repository:

The screenshot shows the 'Services / Manage Weblate' interface. On the left is a sidebar with links: Options, Collaborators, **Webhooks & Services**, and Deploy keys. The main panel has a 'Test service' button in the top right. Below it, text explains that the service notifies Weblate about repository pushes and refreshes translations. A link 'http://weblate.org/' is provided for more info. The 'Install Notes' section states that hooks must be enabled in the Weblate installation and provides a link to the documentation. A 'Url' field contains 'https://hosted.weblate.org'. An 'Active' checkbox is checked, with a note 'We will run this service when an event is triggered.' At the bottom are 'Update service' and 'Delete service' buttons.


You can also use generic *Webhook*, in that case the *Payload URL* would have to be full path to the handler, for example `https://hosted.weblate.org/hooks/github/`.

See also:

POST /hooks/github/, Pushing changes from Hosted Weblate

Automatically receiving changes from Bitbucket

Weblate has support for Bitbucket webhooks, all you need to do is add webhook which triggers on repository push with destination to `/hooks/bitbucket/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/bitbucket/`).



The screenshot shows the 'Settings' page in Weblate. On the left is a sidebar with icons for various settings categories. The main content area is titled 'Settings' and contains a list of settings categories on the left and a form for 'Add new webhook' on the right.

Settings

- GENERAL
 - Repository details
 - Access management
 - Branch management
 - Username aliases
 - Deployment keys
 - Strip changesets
 - Transfer repository
 - Delete repository
- INTEGRATIONS
 - Services
 - Webhooks**
 - Links
- ISSUES
 - Issue tracker settings
- WIKI
 - Wiki settings

Add new webhook

To make sure that your URL can receive requests from Bitbucket, whitelist these IP ranges:

131.103.20.160/27 165.254.145.0/26 104.192.143.0/24

To learn more about how webhooks work, check out the [documentation](#).

Title:

URL:

Triggers: ☒ Repository push ☐ Choose from a full list of triggers

See also:

POST /hooks/bitbucket/, Pushing changes from Hosted Weblate

Automatically receiving changes from GitLab

Weblate has support for GitLab hooks, all you need to do is add project web hook with destination to `/hooks/gitlab/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/gitlab/`).

See also:

POST /hooks/gitlab/, Pushing changes from Hosted Weblate

4.9.2 Pushing changes

Each project can have configured push URL and in such case Weblate offers button to push changes to remote repository in web interface. Weblate can be also configured to automatically push changes on every commit.

If you are using SSH to push, you will need to have a key without a passphrase (or use `ssh-agent` for Django) and the remote server needs to be verified by you via the admin interface first, otherwise pushing will fail.

The push options differ based on used *Version control integration*, please check that chapter for more details.

Note: You can also enable automatic pushing changes on commit, this can be done in project configuration.

See also:

See [Accessing repositories](#) for setting up SSH keys and [Lazy commits](#) for information about when Weblate decides to commit changes.

Pushing changes from Hosted Weblate

For Hosted Weblate there is dedicated push user registered on GitHub, Bitbucket and GitLab (with username *weblate* and named *Weblate push user*). You need to add this user as a collaborator and give him permissions to push to your repository. Let us know when you've done so and we will enable pushing changes from Hosted Weblate for you.

4.9.3 Merge or rebase

By default Weblate merges upstream repository into its own. This is safest way in case you also access underlying repository by other means. In case you don't need this, you can enable rebasing of changes on upstream, what will produce history with less merge commits.

Note: Rebasing can cause you troubles in case of complicated merges, so carefully consider whether you want to enable them or not.

4.9.4 Interacting with others

Weblate makes it easy to interact with others using its API.

See also:

[Weblate's Web API](#)

4.9.5 Lazy commits

Default behaviour (configured by `LAZY_COMMITS`) of Weblate is to group commits from same author into one if possible. This heavily reduces number of commits, however you might need to explicitly tell to do the commits in case you want to get VCS repository in sync, eg. for merge (this is by default allowed for Managers group, see [Access control](#)).

The changes are in this mode committed once any of following conditions is fulfilled:

- somebody else works on the translation
- merge from upstream occurs
- import of translation happens
- translation for a language is completed
- explicit commit is requested

You can also additionally set a cron job to commit pending changes after some delay, see [commit_pending](#) and [Running maintenance tasks](#).

4.9.6 Processing repository with scripts

You can customize way how Weblate manipulates with repository by set of scripts. These include *Post-update script*, *Pre-commit script*, *Post-commit script*, *Post-add script* and *Post-push script* and are briefly described in [Component configuration](#).

Their naming quite clearly tells when given script is executed. The commit related scripts always get one parameter with full path to the translation file which has been changed.

The script is executed with the current directory set to root of VCS repository for given component.

Additionally following environment variables are available:

WL_VCS

Used version control system.

WL_REPO

Upstream repository URL.

WL_PATH

Absolute path to VCS repository.

WL_FILEMASK

File mask for current component.

WL_TEMPLATE

File name of template for monolingual translations (can be empty).

WL_FILE_FORMAT

File format used in current component.

WL_LANGUAGE

Language of currently processed translation (not available for component level hooks).

See also:

[POST_UPDATE_SCRIPTS](#), [PRE_COMMIT_SCRIPTS](#), [POST_COMMIT_SCRIPTS](#), [POST_PUSH_SCRIPTS](#), [Component configuration](#)

Post update repository processing

Post update repository processing can be used to update translation files on the source change. To achieve this, please remember that Weblate only sees files which are committed to the VCS, so you need to commit changes as a part of the script.

For example with gulp you can do it using following code:

```
#!/bin/sh
gulp --gulpfile gulp-i18n-extract.js
git commit -m 'Update source strings' src/languages/en.lang.json
```

Pre commit processing of translations

In many cases you might want to automatically do some changes to translation before it is committed to the repository. The pre commit script is exactly the place to achieve this.

Before using any scripts, you need to list them in [PRE_COMMIT_SCRIPTS](#) configuration variable. Then you can enable them at [Component configuration](#) configuration as *Pre commit script*.

It is passed single parameter consisting of file name of current translation.

The script can also generate additional file to be included in the commit. This can be configured as *Extra commit file* at [Component configuration](#) configuration. You can use following format strings in the filename:

`%(language)s` Language code

Example - generating mo files in repository

Allow usage of the hook in the configuration

```
PRE_COMMIT_SCRIPTS = (
    '/usr/share/weblate/examples/hook-generate-mo',
)
```

To enable it, choose now *hook-generate-mo* as *Pre commit script*. You will also want to add path to generated files to be included in VCS commit, for example `po/%(language)s.mo` as *Extra commit file*.

You can find more example scripts in `examples` folder within Weblate sources, their name start with `hook-`.

4.10 Translation process

4.10.1 Suggestion voting

New in version 1.6: This feature is available since Weblate 1.6.

In default Weblate setup, everybody can add suggestions and logged in users can accept them. You might however want to have more eyes on the translation and require more people to accept them. This can be achieved by suggestion voting. You can enable this on [Component configuration](#) configuration by *Suggestion voting* and *Autoaccept suggestions*. The first one enables voting feature, while the latter allows you to configure threshold at which suggestion will get automatically accepted (this includes own vote from suggesting user).

Note: Once you enable automatic accepting, normal users lose privilege to directly save translations or accept suggestions. This can be overridden by *Can override suggestion state* privilege (see [Access control](#)).

You can combine these with [Access control](#) into one of following setups:

- Users can suggest and vote for suggestions, limited group controls what is accepted - enable voting but not automatic accepting and remove privilege from users to save translations.
- Users can suggest and vote for suggestions, which get automatically accepted once defined number of users agree on this - enable voting and set desired number of votes for automatic accepting.
- Optional voting for suggestions - you can also only enable voting and in this case it can be optionally used by users when they are not sure about translation (they can suggest more of them).

4.10.2 Translation locking

To improve collaboration, it is good to prevent duplicate effort on translation. To achieve this, translation can be locked for single translator. This can be either done manually on translation page or is done automatically when somebody starts to work on translation. The automatic locking needs to be enabled using [AUTO_LOCK](#).

The automatic lock is valid for [AUTO_LOCK_TIME](#) seconds and is automatically extended on every translation made and while user has opened translation page.

User can also explicitly lock translation for [LOCK_TIME](#) seconds.

4.11 Checks and fixups

4.11.1 Custom automatic fixups

You can also implement own automatic fixup in addition to standard ones and include them in `AUTOFIX_LIST`.

The automatic fixes are powerful, but can also cause damage, be careful when writing one.

For example following automatic fixup would replace every occurrence of string `foo` in translation with `bar`:

```
# -*- coding: utf-8 -*-
#
# Copyright © 2012 - 2016 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>.
#

from weblate.trans.autofixes.base import AutoFix
from django.utils.translation import ugettext_lazy as _

class ReplaceFooWithBar(AutoFix):
    '''
    Replaces foo with bar.
    '''

    name = _('Foobar')

    def fix_single_target(self, target, source, unit):
        if 'foo' in target:
            return target.replace('foo', 'bar'), True
        return target, False
```

4.11.2 Customizing checks

Fine tuning existing checks

You can fine tune checks for each source string (in source strings review) or in the *Component configuration* (*Quality checks flags*), here is current list of flags accepted:

skip-review-flag Ignore whether unit is marked for review when importing from VCS. This can be useful for *XLIFF*.

rst-text Treat text as RST document, affects *Unchanged translation*.

xml-text Treat text as XML document, affects *Invalid XML markup* and *XML tags mismatch*.

python-format, c-format, php-format, python-brace-format, javascript-format Treats all string like format strings, affects *Format strings*, *Format strings*, *Format strings*, *Format strings*, *Format strings*, *Unchanged translation*.

ignore-end-space Skip the “Trailing space” quality check.

ignore-inconsistent Skip the “Inconsistent” quality check.

ignore-begin-newline Skip the “Starting newline” quality check.

ignore-zero-width-space Skip the “Zero-width space” quality check.

ignore-escaped-newline Skip the “Mismatched n” quality check.

ignore-same Skip the “Unchanged translation” quality check.

ignore-end-question Skip the “Trailing question” quality check.

ignore-end-ellipsis Skip the “Trailing ellipsis” quality check.

ignore-ellipsis Skip the “Ellipsis” quality check.

ignore-python-brace-format Skip the “Python brace format” quality check.

ignore-end-newline Skip the “Trailing newline” quality check.

ignore-c-format Skip the “C format” quality check.

ignore-javascript-format Skip the “Javascript format” quality check.

ignore-optional-plural Skip the “Optional plural” quality check.

ignore-end-exclamation Skip the “Trailing exclamation” quality check.

ignore-end-colon Skip the “Trailing colon” quality check.

ignore-xml-invalid Skip the “Invalid XML markup” quality check.

ignore-xml-tags Skip the “XML tags mismatch” quality check.

ignore-python-format Skip the “Python format” quality check.

ignore-plurals Skip the “Missing plurals” quality check.

ignore-begin-space Skip the “Starting spaces” quality check.

ignore-bbcode Skip the “Mismatched BBcode” quality check.

ignore-multiple-failures Skip the “Multiple failing checks” quality check.

ignore-php-format Skip the “PHP format” quality check.

ignore-end-stop Skip the “Trailing stop” quality check.

ignore-angularjs-format Skip the “AngularJS interpolation string” quality check.

Note: Generally the rule is named `ignore-*` for any check, using its identifier, so you can use this even for your custom checks.

These flags are understood both in *Component configuration* settings, per source string settings and in translation file itself (eg. in GNU Gettext).

Writing own checks

Weblate comes with wide range of quality checks (see *Quality checks*), though they might not 100% cover all you want to check. The list of performed checks can be adjusted using `CHECK_LIST` and you can also add custom checks. All you need to do is to subclass `trans.checks.Check`, set few attributes and implement either `check` or `check_single` methods (first one if you want to deal with plurals in your code, the latter one does this for you). You will find below some examples.

Checking translation text does not contain “foo”

This is pretty simple check which just checks whether translation does not contain string “foo”.

```
# -*- coding: utf-8 -*-
#
# Copyright © 2012 - 2016 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>.
#
'''
Simple quality check example.
'''

from weblate.trans.checks.base import TargetCheck
from django.utils.translation import ugettext_lazy as _

class FooCheck(TargetCheck):

    # Used as identifier for check, should be unique
    check_id = 'foo'

    # Short name used to display failing check
    name = _('Foo check')

    # Description for failing check
    description = _('Your translation is foo')

    # Real check code
    def check_single(self, source, target, unit):
        return 'foo' in target
```

Checking Czech translation text plurals differ

Check using language information to verify that two plural forms in Czech language are not same.

```
# -*- coding: utf-8 -*-
#
# Copyright © 2012 - 2016 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>.
#
'''
Quality check example for Czech plurals.
'''

from weblate.trans.checks.base import TargetCheck
from django.utils.translation import ugettext_lazy as _

class PluralCzechCheck(TargetCheck):

    # Used as identifier for check, should be unique
    check_id = 'foo'

    # Short name used to display failing check
    name = _('Foo check')

    # Description for failing check
    description = _('Your translation is foo')

    # Real check code
    def check_target_unit(self, sources, targets, unit):
        if self.is_language(unit, ('cs', )):
            return targets[1] == targets[2]
        return False

    def check_single(self, source, target, unit):
        '''
        We don't check target strings here.
        '''
        return False
```

4.12 Machine translation

4.12.1 Machine translation setup

Weblate has builtin support for several machine translation services and it's up to administrator to enable them. The services have different terms of use, so please check whether you are allowed to use them before enabling in Weblate. The individual services are enabled using `MACHINE_TRANSLATION_SERVICES`.

The source language can be configured at *Project configuration*.

Amagama

Special installation of *tmserver* run by Virtaal authors.

To enable this service, add `trans.machine.tmserver.AmagamaTranslation` to `MACHINE_TRANSLATION_SERVICES`.

See also:

[Amagama Translation Memory server](#)

Apertium

A free/open-source machine translation platform providing translation to limited set of languages.

You should get API key from them, otherwise number of requests is rate limited.

To enable this service, add `trans.machine.apertium.ApertiumTranslation` to `MACHINE_TRANSLATION_SERVICES`.

See also:

`MT_APERTIUM_KEY`, [Apertium website](#)

Glosbe

Free dictionary and translation memory for almost every living language.

API is free to use, regarding indicated data source license. There is a limit of call that may be done from one IP in fixed period of time, to prevent from abuse.

To enable this service, add `trans.machine.glosbe.GlosbeTranslation` to `MACHINE_TRANSLATION_SERVICES`.

See also:

[Glosbe website](#)

Google Translate

Machine translation service provided by Google.

This service uses Translation API and you need to obtain API key and enable billing on Google API console.

To enable this service, add `trans.machine.google.GoogleTranslation` to `MACHINE_TRANSLATION_SERVICES`.

See also:

`MT_GOOGLE_KEY`, [Google translate documentation](#)

Bing Translator

Machine translation service provided by Microsoft, it's known as Microsoft Translator as well.

You need to register at Azure market and use Client ID and secret from there.

To enable this service, add `trans.machine.microsoft.MicrosoftTranslation` to `MACHINE_TRANSLATION_SERVICES`.

See also:

`MT_MICROSOFT_ID`, `MT_MICROSOFT_SECRET`, [Bing Translator](#), [Azure datamarket](#)

MyMemory

Huge translation memory with machine translation.

Free, anonymous usage is currently limited to 100 requests/day, or to 1000 requests/day when you provide contact email in `MT_MYMEMORY_EMAIL`. you can also ask them for more.

To enable this service, add `trans.machine.mymemory.MyMemoryTranslation` to `MACHINE_TRANSLATION_SERVICES`.

See also:

`MT_MYMEMORY_EMAIL`, `MT_MYMEMORY_USER`, `MT_MYMEMORY_KEY`, [MyMemory website](#)

tmserver

You can run your own translation memory server which is bundled with Translate-toolkit and let Weblate talk to it. You can also use it with amaGama server, which is enhanced version of tmserver.

First you will want to import some data to the translation memory:

To enable this service, add `trans.machine.tmserver.TMServerTranslation` to `MACHINE_TRANSLATION_SERVICES`.

```
build_tmdb -d /var/lib/tm/db -s en -t cs locale/cs/LC_MESSAGES/django.po
build_tmdb -d /var/lib/tm/db -s en -t de locale/de/LC_MESSAGES/django.po
build_tmdb -d /var/lib/tm/db -s en -t fr locale/fr/LC_MESSAGES/django.po
```

Now you can start tmserver to listen to your requests:

```
tmserver -d /var/lib/tm/db
```

And configure Weblate to talk to it:

```
MT_TMSERVER = 'http://localhost:8888/'
```

See also:

`MT_TMSERVER`, [tmserver](#), [a Translation Memory service](#), [Amagama Translation Memory](#)

Weblate

Weblate can be source of machine translation as well. There are two services to provide you results - one does exact search for string, the other one finds all similar strings.

First one is useful for full string translations, the second one for finding individual phrases or words to keep the translation consistent.

To enable these services, add `trans.machine.weblatetm.WeblateSimilarTranslation` (for similar string matching) and/or `trans.machine.weblatetm.WeblateTranslation` (for exact string matching) to `MACHINE_TRANSLATION_SERVICES`.

Note: For similarity matching, it is recommended to have Whoosh 2.5.2 or later, earlier versions can cause infinite looks under some occasions.

4.12.2 Custom machine translation

You can also implement own machine translation services using few lines of Python code. Following example implements translation to fixed list of languages using dictionary Python module:

```
# -*- coding: utf-8 -*-
#
# Copyright © 2012 - 2016 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>.
#
'''
Machine translation example.
'''

from weblate.trans.machine.base import MachineTranslation
import dictionary

class SampleTranslation(MachineTranslation):
    '''
    Sample machine translation interface.
    '''
    name = 'Sample'

    def download_languages(self):
        '''
        Returns list of languages your machine translation supports.
        '''
```

```
'''
    return set(('cs',))

def download_translations(self, language, text, unit, request):
    '''
    Returns tuple with translations.
    '''
    return [(t, 100, self.name, text) for t in dictionary.translate(text)]
```

You can list own class in `MACHINE_TRANSLATION_SERVICES` and Weblate will start using that.

4.13 Configuration

All settings are stored in `settings.py` (as usual for Django).

Note: After changing any of these settings, you need to restart Weblate. In case it is run as `mod_wsgi`, you need to restart Apache to reload the configuration.

See also:

Please check also Django's [documentation](#) for parameters which configure Django itself.

4.13.1 ANONYMOUS_USER_NAME

User name of user for defining privileges of not logged in user.

See also:

Access control

4.13.2 AUTO_LOCK

Enables automatic locking of translation when somebody is working on it.

See also:

Translation locking

4.13.3 AUTO_LOCK_TIME

Time in seconds for how long the automatic lock for translation will be active.

See also:

Translation locking

4.13.4 AUTOFIX_LIST

List of automatic fixups to apply when saving the message.

Available fixes:

trans.autofixes.whitespace.SameBookendingWhitespace Fixes up whitespace in beginning and end of the string to match source.

trans.autofixes.chars.ReplaceTrailingDotsWithEllipsis Replaces trailing dots with ellipsis if source string has it.

trans.autofixes.chars.RemoveZeroSpace Removes zero width space char if source does not contain it.

For example you can enable only few of them:

```
AUTOFIX_LIST = (  
    'weblate.trans.autofixes.whitespace.SameBookendingWhitespace',  
    'weblate.trans.autofixes.chars.ReplaceTrailingDotsWithEllipsis',  
)
```

See also:

Automatic fixups, Custom automatic fixups

4.13.5 BACKGROUND_HOOKS

Whether to run hooks in background. This is generally recommended unless you are debugging.

4.13.6 CHECK_LIST

List of quality checks to perform on translation.

Some of the checks are not useful for all projects, so you are welcome to adjust list of performed on your installation.

For example you can enable only few of them:

```
CHECK_LIST = (  
    'weblate.trans.checks.same.SameCheck',  
    'weblate.trans.checks.chars.BeginNewlineCheck',  
    'weblate.trans.checks.chars.EndNewlineCheck',  
    'weblate.trans.checks.chars.BeginSpaceCheck',  
    'weblate.trans.checks.chars.EndSpaceCheck',  
    'weblate.trans.checks.chars.EndStopCheck',  
    'weblate.trans.checks.chars.EndColonCheck',  
    'weblate.trans.checks.chars.EndQuestionCheck',  
    'weblate.trans.checks.chars.EndExclamationCheck',  
    'weblate.trans.checks.chars.EndEllipsisCheck',  
    'weblate.trans.checks.chars.MaxLengthCheck',  
    'weblate.trans.checks.format.PythonFormatCheck',  
    'weblate.trans.checks.format.PythonBraceFormatCheck',  
    'weblate.trans.checks.format.PHPFormatCheck',  
    'weblate.trans.checks.format.CFormatCheck',  
    'weblate.trans.checks.format.JavascriptFormatCheck',  
    'weblate.trans.checks.consistency.PluralsCheck',  
    'weblate.trans.checks.consistency.ConsistencyCheck',  
    'weblate.trans.checks.chars.NewlineCountingCheck',  
    'weblate.trans.checks.markup.BBCodeCheck',  
    'weblate.trans.checks.chars.ZeroWidthSpaceCheck',  
    'weblate.trans.checks.markup.XMLTagsCheck',  
    'weblate.trans.checks.source.OptionalPluralCheck',  
    'weblate.trans.checks.source.EllipsisCheck',  
    'weblate.trans.checks.source.MultipleFailingCheck',  
)
```


See also:

Quality checks, Customizing checks

4.13.7 DATA_DIR

New in version 2.1: In previous versions the directories were configured separately as *GIT_ROOT* and *WHOOSH_INDEX*.

Directory where Weblate stores all data. This consists of VCS repositories, fulltext index and various configuration files for external tools.

Following subdirectories usually exist:

home Home directory used for invoking scripts.

ssh SSH keys and configuration.

static Default location for Django static files, specified by *STATIC_ROOT*.

vcs Version control repositories.

whoosh Fulltext search index using Whoosh engine.

4.13.8 DEFAULT_COMMITER_EMAIL

New in version 2.4.

Default commiter email when creating translation component (see *Component configuration*), defaults to `noreply@weblate.org`.

See also:

DEFAULT_COMMITER_NAME, Component configuration

4.13.9 DEFAULT_COMMITER_NAME

New in version 2.4.

Default commiter name when creating translation component (see *Component configuration*), defaults to `Weblate`.

See also:

DEFAULT_COMMITER_EMAIL, Component configuration

4.13.10 DEFAULT_TRANSLATION_PROPAGATION

New in version 2.5.

Default setting for translation propagation (see *Component configuration*), defaults to `True`.

See also:

Component configuration

4.13.11 ENABLE_AVATARS

Whether to enable libavatar/gravatar based avatars for users. By default this is enabled.

The avatars are fetched and cached on the server, so there is no risk in leaking private information or slowing down the user experiences with enabling this.

See also:

Avatar caching

4.13.12 ENABLE_HOOKS

Whether to enable anonymous remote hooks.

See also:

Notification hooks

4.13.13 ENABLE_HTTPS

Whether to send links to the Weblate as https or http. This setting affects sent mails and generated absolute URLs.

See also:

Set correct site name

4.13.14 ENABLE_SHARING

Whether to show links to share translation progress on social networks.

4.13.15 GIT_ROOT

Deprecated since version 2.1: This setting is no longer used, use `DATA_DIR` instead.

Path where Weblate will store cloned VCS repositories. Defaults to `repos` subdirectory.

4.13.16 GITHUB_USERNAME

GitHub username that will be used to send pull requests for translation updates.

See also:

Pushing changes to GitHub as pull request

4.13.17 GOOGLE_ANALYTICS_ID

Google Analytics ID to enable monitoring of Weblate using Google Analytics.

4.13.18 HIDE_REPO_CREDENTIALS

Hide repository credentials in the web interface. In case you have repository URL with user and password, Weblate will hide it when showing it to the users.

For example instead of `https://user:password@git.example.com/repo.git` it will show just `https://git.example.com/repo.git`.

4.13.19 LAZY_COMMITS

Delay creating VCS commits until this is necessary. This heavily reduces number of commits generated by Weblate at expense of temporarily not being able to merge some changes as they are not yet committed.

See also:

Lazy commits

4.13.20 LOCK_TIME

Time in seconds for how long the translation will be locked for single translator when locked manually.

See also:

Translation locking

4.13.21 LOGIN_REQUIRED_URLS

List of URL which require login (besides standard rules built into Weblate). This allows you to password protect whole installation using:

```
LOGIN_REQUIRED_URLS = (
    r'/(.*)$',
)
```

4.13.22 LOGIN_REQUIRED_URLS_EXCEPTIONS

List of exceptions for `LOGIN_REQUIRED_URLS`, in case you won't specify this list, the default value will be used, which allows users to access login page.

Some of exceptions you might want to include:

```
LOGIN_REQUIRED_URLS_EXCEPTIONS = (
    r'/accounts/(.*)$', # Required for login
    r'/static/(.*)$',  # Required for development mode
    r'/widgets/(.*)$',  # Allowing public access to widgets
    r'/data/(.*)$',     # Allowing public access to data exports
    r'/hooks/(.*)$',    # Allowing public access to notification hooks
    r'/api/(.*)$',      # Allowing access to API
)
```

4.13.23 MACHINE_TRANSLATION_SERVICES

List of enabled machine translation services to use.

Note: Many of services need additional configuration like API keys, please check their documentation for more details.

```
MACHINE_TRANSLATION_SERVICES = (  
    'weblate.trans.machine.apertium.ApertiumTranslation',  
    'weblate.trans.machine.glosbe.GlosbeTranslation',  
    'weblate.trans.machine.google.GoogleTranslation',  
    'weblate.trans.machine.microsoft.MicrosoftTranslation',  
    'weblate.trans.machine.mymemory.MyMemoryTranslation',  
    'weblate.trans.machine.tmserver.TMServerTranslation',  
    'weblate.trans.machine.weblatetm.WeblateSimilarTranslation',  
    'weblate.trans.machine.weblatetm.WeblateTranslation',  
)
```

See also:

Machine translation setup, Machine translation

4.13.24 MT_APERTIUM_KEY

API key for Apertium Web Service, you can register at <http://api.apertium.org/register.jsp>

See also:

Apertium, Machine translation setup, Machine translation

4.13.25 MT_GOOGLE_KEY

API key for Google Translate API, you can register at <https://cloud.google.com/translate/docs>

See also:

Google Translate, Machine translation setup, Machine translation

4.13.26 MT_MICROSOFT_ID

Client ID for Microsoft Translator service.

See also:

Bing Translator, Machine translation setup, Machine translation, Azure datamarket

4.13.27 MT_MICROSOFT_SECRET

Client secret for Microsoft Translator service.

See also:

Bing Translator, Machine translation setup, Machine translation, Azure datamarket

4.13.28 MT_MYMEMORY_EMAIL

MyMemory identification email, you can get 1000 requests per day with this.

See also:

MyMemory, *Machine translation setup*, *Machine translation*, *MyMemory: API technical specifications*

4.13.29 MT_MYMEMORY_KEY

MyMemory access key for private translation memory, use together with *MT_MYMEMORY_USER*.

See also:

MyMemory, *Machine translation setup*, *Machine translation*, *MyMemory: API key generator*

4.13.30 MT_MYMEMORY_USER

MyMemory user id for private translation memory, use together with *MT_MYMEMORY_KEY*.

See also:

MyMemory, *Machine translation setup*, *Machine translation*, *MyMemory: API key generator*

4.13.31 MT_TMSERVER

URL where tmserver is running.

See also:

tmserver, *Machine translation setup*, *Machine translation*, *tmserver*, a Translation Memory service

4.13.32 NEARBY_MESSAGES

How many messages around current one to show during translating.

4.13.33 OFFLOAD_INDEXING

Offload updating of fulltext index to separate process. This heavily improves responsiveness of online operation on expense of slightly outdated index, which might still point to older content.

While enabling this, don't forget scheduling runs of *update_index* in cron or similar tool.

This is recommended setup for production use.

See also:

Fulltext search

4.13.34 PIWIK_SITE_ID

ID of a site in Piwik you want to track.

See also:

PIWIK_URL

4.13.35 PIWIK_URL

URL of a Piwik installation you want to use to track Weblate users. For more information about Piwik see <<https://piwik.org/>>.

See also:

PIWIK_SITE_ID

4.13.36 POST_ADD_SCRIPTS

New in version 2.4.

List of scripts which are allowed as post add scripts. The script needs to be later enabled in the *Component configuration*.

Weblate comes with few example hook scripts which you might find useful:

examples/hook-update-linguas Updates LINGUAS file or ALL_LINGUAS in configure script.

See also:

Processing repository with scripts

4.13.37 POST_UPDATE_SCRIPTS

New in version 2.3.

List of scripts which are allowed as post update scripts. The script needs to be later enabled in the *Component configuration*.

Weblate comes with few example hook scripts which you might find useful:

examples/hook-update-resx Updates resx file to match template by adding new translations and removing obsolete ones.

examples/hook-cleanup-android Removes obsolete units from Android resource strings.

See also:

Processing repository with scripts

4.13.38 PRE_COMMIT_SCRIPTS

List of scripts which are allowed as pre commit scripts. The script needs to be later enabled in the *Component configuration*.

For example you can allow script which does some cleanup:

```
PRE_COMMIT_SCRIPTS = (  
    '/usr/local/bin/cleanup-translation',  
)
```

Weblate comes with few example hook scripts which you might find useful:

examples/hook-generate-mo Generates MO file from a PO file

examples/hook-unwrap-po Unwraps lines in a PO file.

examples/hook-sort-properties Sort and cleanups Java properties file.

examples/hook-replace-single-quotes Replaces single quotes in a file.

See also:

Processing repository with scripts

4.13.39 POST_COMMIT_SCRIPTS

New in version 2.4.

List of scripts which are allowed as post commit scripts. The script needs to be later enabled in the *Component configuration*.

See also:

Processing repository with scripts

4.13.40 POST_PUSH_SCRIPTS

New in version 2.4.

List of scripts which are allowed as post push scripts. The script needs to be later enabled in the *Component configuration*.

See also:

Processing repository with scripts

4.13.41 REGISTRATION_CAPTCHA

A boolean (either `True` or `False`) indicating whether registration of new accounts is protected by captcha. This setting is optional, and a default of `True` will be assumed if it is not supplied.

4.13.42 REGISTRATION_OPEN

A boolean (either `True` or `False`) indicating whether registration of new accounts is currently permitted. This setting is optional, and a default of `True` will be assumed if it is not supplied.

4.13.43 SELF_ADVERTISEMENT

Enables self advertisement of Weblate in case there are no configured ads.

See also:

Advertisement

4.13.44 SIMPLIFY_LANGUAGES

Use simple language codes for default language/country combinations. For example `fr_FR` translation will use `fr` language code. This is usually desired behavior as it simplifies listing of the languages for these default combinations.

Disable this if you are having different translations for both variants.

4.13.45 SITE_TITLE

Site title to be used in website and emails as well.

4.13.46 TTF_PATH

Path to Droid fonts used for widgets and charts.

4.13.47 URL_PREFIX

This settings allows you to run Weblate under some path (otherwise it relies on being executed from webserver root). To use this setting, you also need to configure your server to strip this prefix. For example with WSGI, this can be achieved by setting `WSGIScriptAlias`.

Note: This setting does not work with Django's builtin server, you would have to adjust `urls.py` to contain this prefix.

4.13.48 WHOOSH_INDEX

Deprecated since version 2.1: This setting is no longer used, use `DATA_DIR` instead.

Directory where Whoosh fulltext indices will be stored. Defaults to `whoosh-index` subdirectory.

4.14 Sample configuration

Following example is shipped as `weblate/settings_example.py` with Weblate:

```
# -*- coding: utf-8 -*-
#
# Copyright © 2012 - 2016 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>.
#

from __future__ import unicode_literals
import platform
import os
from logging.handlers import SysLogHandler
```



```

import django

#
# Safety check for running with too old Django version
#

if django.VERSION < (1, 4, 0):
    raise Exception(
        'Weblate needs Django 1.4 or newer, you are using %s!' %
        django.get_version()
    )

#
# Django settings for Weblate project.
#

DEBUG = True

ADMINS = (
    # ('Your Name', 'your_email@example.com'),
)

MANAGERS = ADMINS

DATABASES = {
    'default': {
        # Use 'postgresql_psycopg2', 'mysql', 'sqlite3' or 'oracle'.
        'ENGINE': 'django.db.backends.sqlite3',
        # Database name or path to database file if using sqlite3.
        'NAME': 'weblate.db',
        # Database user, not used with sqlite3.
        'USER': 'weblate',
        # Database password, not used with sqlite3.
        'PASSWORD': 'weblate',
        # Set to empty string for localhost. Not used with sqlite3.
        'HOST': '127.0.0.1',
        # Set to empty string for default. Not used with sqlite3.
        'PORT': '',
    }
}

BASE_DIR = os.path.dirname(os.path.abspath(__file__))

# Data directory
DATA_DIR = os.path.join(BASE_DIR, '..', 'data')

# Local time zone for this installation. Choices can be found here:
# http://en.wikipedia.org/wiki/List_of_tz_zones_by_name
# although not all choices may be available on all operating systems.
# On Unix systems, a value of None will cause Django to use the same
# timezone as the operating system.
# If running in a Windows environment this must be set to the same as your
# system time zone.
TIME_ZONE = 'UTC'

# Language code for this installation. All choices can be found here:
# http://www.i18nguy.com/unicode/language-identifiers.html
LANGUAGE_CODE = 'en-us'

```

```
LANGUAGES = (
    ('az', 'Azərbaycan'),
    ('be', ''),
    ('be@latin', 'Беларуская'),
    ('br', 'Brezhoneg'),
    ('ca', 'Català'),
    ('cs', 'Čeština'),
    ('da', 'Dansk'),
    ('de', 'Deutsch'),
    ('en', 'English'),
    ('el', 'Ελληνική'),
    ('es', 'Español'),
    ('fi', 'Suomi'),
    ('fr', 'Français'),
    ('fy', 'Frysk'),
    ('gl', 'Galego'),
    ('he', ''),
    ('hu', 'Magyar'),
    ('id', 'Indonesia'),
    ('it', 'Italiano'),
    ('ja', ''),
    ('ko', ''),
    ('ksh', 'Kölsch'),
    ('nb', 'Norsk bokmål'),
    ('nl', 'Nederlands'),
    ('pl', 'Polski'),
    ('pt', 'Português'),
    ('pt-br', 'Português brasileiro'),
    ('ru', ''),
    ('sk', 'Slovenčina'),
    ('sl', 'Slovenščina'),
    ('sr', ''),
    ('sv', 'Svenska'),
    ('tr', 'Türkçe'),
    ('uk', ''),
    ('zh-hans', ''),
    ('zh-hant', ''),
)

SITE_ID = 1

# If you set this to False, Django will make some optimizations so as not
# to load the internationalization machinery.
USE_I18N = True

# If you set this to False, Django will not format dates, numbers and
# calendars according to the current locale.
USE_L10N = True

# If you set this to False, Django will not use timezone-aware datetimes.
USE_TZ = True

# URL prefix to use, please see documentation for more details
URL_PREFIX = ''

# Absolute filesystem path to the directory that will hold user-uploaded files.
# Example: "/home/media/media.lawrence.com/media/"
MEDIA_ROOT = os.path.join(BASE_DIR, 'media')
```

```

# URL that handles the media served from MEDIA_ROOT. Make sure to use a
# trailing slash.
# Examples: "http://media.lawrence.com/media/", "http://example.com/media/"
MEDIA_URL = '%s/media/' % URL_PREFIX

# Absolute path to the directory static files should be collected to.
# Don't put anything in this directory yourself; store your static files
# in apps' "static/" subdirectories and in STATICFILES_DIRS.
# Example: "/home/media/media.lawrence.com/static/"
STATIC_ROOT = os.path.join(DATA_DIR, 'static')

# URL prefix for static files.
# Example: "http://media.lawrence.com/static/"
STATIC_URL = '%s/static/' % URL_PREFIX

# Additional locations of static files
STATICFILES_DIRS = (
    # Put strings here, like "/home/html/static" or "C:/www/django/static".
    # Always use forward slashes, even on Windows.
    # Don't forget to use absolute paths, not relative paths.
)

# List of finder classes that know how to find static files in
# various locations.
STATICFILES_FINDERS = (
    'django.contrib.staticfiles.finders.FileSystemFinder',
    'django.contrib.staticfiles.finders.AppDirectoriesFinder',
    'compressor.finders.CompressorFinder',
)

# Make this unique, and don't share it with anybody.
# You can generate it using examples/generate-secret-key
SECRET_KEY = 'jm8fqjlg+5!#xu%e-oh#7!$aa7!6avf7ud*_v=chdrb9qdc06('

TEMPLATES = [
    {
        'BACKEND': 'django.template.backends.django.DjangoTemplates',
        'DIRS': [
            os.path.join(BASE_DIR, 'html'),
        ],
        'OPTIONS': {
            'context_processors': [
                'django.contrib.auth.context_processors.auth',
                'django.template.context_processors.debug',
                'django.template.context_processors.i18n',
                'django.template.context_processors.request',
                'django.template.context_processors.csrf',
                'django.contrib.messages.context_processors.messages',
                'weblate.trans.context_processors.weblate_context',
            ],
            'loaders': [
                ('django.template.loaders.cached.Loader', [
                    'django.template.loaders.filesystem.Loader',
                    'django.template.loaders.app_directories.Loader',
                ]),
            ],
        },
    ],
]

```

```
]

# GitHub username for sending pull requests.
# Please see the documentation for more details.
GITHUB_USERNAME = None

# Authentication configuration
AUTHENTICATION_BACKENDS = (
    'weblate.accounts.auth.EmailAuth',
    # 'social.backends.google.GoogleOAuth2',
    # 'social.backends.github.GithubOAuth2',
    # 'social.backends.bitbucket.BitbucketOAuth',
    # 'social.backends.suse.OpenSUSEOpenId',
    # 'social.backends.ubuntu.UbuntuOpenId',
    # 'social.backends.fedora.FedoraOpenId',
    # 'social.backends.facebook.FacebookOAuth2',
    'weblate.accounts.auth.WeblateUserBackend',
)

# Social auth backends setup
SOCIAL_AUTH_GITHUB_KEY = ''
SOCIAL_AUTH_GITHUB_SECRET = ''
SOCIAL_AUTH_GITHUB_SCOPE = ['user:email']

SOCIAL_AUTH_BITBUCKET_KEY = ''
SOCIAL_AUTH_BITBUCKET_SECRET = ''
SOCIAL_AUTH_BITBUCKET_VERIFIED_EMAILS_ONLY = True

SOCIAL_AUTH_FACEBOOK_KEY = ''
SOCIAL_AUTH_FACEBOOK_SECRET = ''
SOCIAL_AUTH_FACEBOOK_SCOPE = ['email', 'public_profile']

SOCIAL_AUTH_GOOGLE_OAUTH2_KEY = ''
SOCIAL_AUTH_GOOGLE_OAUTH2_SECRET = ''

# Social auth settings
SOCIAL_AUTH_PIPELINE = (
    'social.pipeline.social_auth.social_details',
    'social.pipeline.social_auth.social_uid',
    'social.pipeline.social_auth.auth_allowed',
    'social.pipeline.social_auth.associate_by_email',
    'social.pipeline.social_auth.social_user',
    'social.pipeline.user.get_username',
    'weblate.accounts.pipeline.require_email',
    'social.pipeline.mail.mail_validation',
    'social.pipeline.social_auth.associate_by_email',
    'weblate.accounts.pipeline.verify_open',
    'weblate.accounts.pipeline.verify_username',
    'social.pipeline.user.create_user',
    'social.pipeline.social_auth.associate_user',
    'social.pipeline.social_auth.load_extra_data',
    'weblate.accounts.pipeline.user_full_name',
    'weblate.accounts.pipeline.store_email',
)

# Custom authentication strategy
SOCIAL_AUTH_STRATEGY = 'weblate.accounts.strategy.WeblateStrategy'
```

```

SOCIAL_AUTH_EMAIL_VALIDATION_FUNCTION = \
    'weblate.accounts.pipeline.send_validation'
SOCIAL_AUTH_EMAIL_VALIDATION_URL = '%s/accounts/email-sent/' % URL_PREFIX
SOCIAL_AUTH_LOGIN_ERROR_URL = '%s/accounts/login/' % URL_PREFIX
SOCIAL_AUTH_EMAIL_FORM_URL = '%s/accounts/email/' % URL_PREFIX
SOCIAL_AUTH_NEW_ASSOCIATION_REDIRECT_URL = \
    '%s/accounts/profile/#auth' % URL_PREFIX
SOCIAL_AUTH_PROTECTED_USER_FIELDS = ('email',)
SOCIAL_AUTH_SLUGIFY_USERNAMES = True

# Middleware
MIDDLEWARE_CLASSES = (
    'django.contrib.sessions.middleware.SessionMiddleware',
    'django.contrib.auth.middleware.SessionAuthenticationMiddleware',
    'django.middleware.common.CommonMiddleware',
    'django.middleware.locale.LocaleMiddleware',
    'django.middleware.csrf.CsrfViewMiddleware',
    'django.contrib.auth.middleware.AuthenticationMiddleware',
    'django.contrib.messages.middleware.MessageMiddleware',
    'django.middleware.clickjacking.XFrameOptionsMiddleware',
    'social.apps.django_app.middleware.SocialAuthExceptionMiddleware',
    'weblate.accounts.middleware.RequireLoginMiddleware',
)

ROOT_URLCONF = 'weblate.urls'

INSTALLED_APPS = (
    'django.contrib.auth',
    'django.contrib.contenttypes',
    'django.contrib.sessions',
    'django.contrib.sites',
    'django.contrib.messages',
    'django.contrib.staticfiles',
    'django.contrib.admin',
    'django.contrib.admindocs',
    'django.contrib.sitemaps',
    'social.apps.django_app.default',
    'crispy_forms',
    'compressor',
    'rest_framework',
    'rest_framework.authtoken',
    'weblate.trans',
    'weblate.lang',
    'weblate.accounts',
    # Needed for javascript localization
    'weblate',
)

# Path to locales
LOCALE_PATHS = (os.path.join(BASE_DIR, 'locale'), )

# Custom exception reporter to include some details
DEFAULT_EXCEPTION_REPORTER_FILTER = \
    'weblate.trans.debug.WeblateExceptionReporterFilter'

# Default logging of Weblate messages
# - to syslog in production (if available)
# - otherwise to console

```

```
# - you can also choose 'logfile' to log into separate file
#   after configuring it below

# Detect if we can connect to syslog
HAVE_SYSLOG = False
if platform.system() != 'Windows':
    try:
        SysLogHandler(address='/dev/log', facility=SysLogHandler.LOG_LOCAL2)
        HAVE_SYSLOG = True
    except IOError:
        HAVE_SYSLOG = False

if DEBUG or not HAVE_SYSLOG:
    DEFAULT_LOG = 'console'
else:
    DEFAULT_LOG = 'syslog'

# A sample logging configuration. The only tangible logging
# performed by this configuration is to send an email to
# the site admins on every HTTP 500 error when DEBUG=False.
# See http://docs.djangoproject.com/en/stable/topics/logging for
# more details on how to customize your logging configuration.
LOGGING = {
    'version': 1,
    'disable_existing_loggers': False,
    'filters': {
        'require_debug_false': {
            '()': 'django.utils.log.RequireDebugFalse'
        }
    },
    'formatters': {
        'syslog': {
            'format': 'weblate[%(process)d]: %(levelname)s %(message)s'
        },
        'simple': {
            'format': '%(levelname)s %(message)s'
        },
        'logfile': {
            'format': '%(asctime)s %(levelname)s %(message)s'
        },
    },
    'handlers': {
        'mail_admins': {
            'level': 'ERROR',
            'filters': ['require_debug_false'],
            'class': 'django.utils.log.AdminEmailHandler'
        },
        'console': {
            'level': 'DEBUG',
            'class': 'logging.StreamHandler',
            'formatter': 'simple'
        },
        'syslog': {
            'level': 'DEBUG',
            'class': 'logging.handlers.SysLogHandler',
            'formatter': 'syslog',
            'address': '/dev/log',
            'facility': SysLogHandler.LOG_LOCAL2,
```

```

    },
    # Logging to a file
    # 'logfile': {
    #     'level': 'DEBUG',
    #     'class': 'logging.handlers.RotatingFileHandler',
    #     'filename': "/var/log/weblate/weblate.log",
    #     'maxBytes': 100000,
    #     'backupCount': 3,
    #     'formatter': 'logfile',
    # },
},
'loggers': {
    'django.request': {
        'handlers': ['mail_admins', DEFAULT_LOG],
        'level': 'ERROR',
        'propagate': True,
    },
    # Logging database queries
    # 'django.db.backends': {
    #     'handlers': [DEFAULT_LOG],
    #     'level': 'DEBUG',
    # },
    'weblate': {
        'handlers': [DEFAULT_LOG],
        'level': 'DEBUG',
    }
}
}

# Logging of management commands to console
if (os.environ.get('DJANGO_IS_MANAGEMENT_COMMAND', False) and
    'console' not in LOGGING['loggers']['weblate']['handlers']):
    LOGGING['loggers']['weblate']['handlers'].append('console')

# Remove syslog setup if it's not present
if not HAVE_SYSLOG:
    del LOGGING['handlers']['syslog']

# Machine translation API keys

# Apertium Web Service, register at http://api.apertium.org/register.jsp
MT_APERTIUM_KEY = None

# Microsoft Translator service, register at
# https://datamarket.azure.com/developer/applications/
MT_MICROSOFT_ID = None
MT_MICROSOFT_SECRET = None

# MyMemory identification email, see
# http://mymemory.translated.net/doc/spec.php
MT_MYMEMORY_EMAIL = None

# Optional MyMemory credentials to access private translation memory
MT_MYMEMORY_USER = None
MT_MYMEMORY_KEY = None

# Google API key for Google Translate API
MT_GOOGLE_KEY = None

```

```
# tmserver URL
MT_TMSERVER = None

# Title of site to use
SITE_TITLE = 'Weblate'

# Whether site uses https
ENABLE_HTTPS = False

# URL of login
LOGIN_URL = '%s/accounts/login/' % URL_PREFIX

# URL of logout
LOGOUT_URL = '%s/accounts/logout/' % URL_PREFIX

# Default location for login
LOGIN_REDIRECT_URL = '%s/' % URL_PREFIX

# Anonymous user name
ANONYMOUS_USER_NAME = 'anonymous'

# Sending HTML in mails
EMAIL_SEND_HTML = True

# Subject of emails includes site title
EMAIL_SUBJECT_PREFIX = '[{0}] '.format(SITE_TITLE)

# Enable remote hooks
ENABLE_HOOKS = True

# Whether to run hooks in background
BACKGROUND_HOOKS = True

# Number of nearby messages to show in each direction
NEARBY_MESSAGES = 5

# Enable lazy commits
LAZY_COMMITS = True

# Offload indexing
OFFLOAD_INDEXING = False

# Translation locking
AUTO_LOCK = True
AUTO_LOCK_TIME = 60
LOCK_TIME = 15 * 60

# Render forms using bootstrap
CRISPY_TEMPLATE_PACK = 'bootstrap3'

# List of quality checks
# CHECK_LIST = (
#     'weblate.trans.checks.same.SameCheck',
#     'weblate.trans.checks.chars.BeginNewlineCheck',
#     'weblate.trans.checks.chars.EndNewlineCheck',
#     'weblate.trans.checks.chars.BeginSpaceCheck',
#     'weblate.trans.checks.chars.EndSpaceCheck',
#     'weblate.trans.checks.chars.EndStopCheck',
```



```

# 'weblate.trans.checks.chars.EndColonCheck',
# 'weblate.trans.checks.chars.EndQuestionCheck',
# 'weblate.trans.checks.chars.EndExclamationCheck',
# 'weblate.trans.checks.chars.EndEllipsisCheck',
# 'weblate.trans.checks.chars.MaxLengthCheck',
# 'weblate.trans.checks.format.PythonFormatCheck',
# 'weblate.trans.checks.format.PythonBraceFormatCheck',
# 'weblate.trans.checks.format.PHPFormatCheck',
# 'weblate.trans.checks.format.CFormatCheck',
# 'weblate.trans.checks.format.JavascriptFormatCheck',
# 'weblate.trans.checks.consistency.PluralsCheck',
# 'weblate.trans.checks.consistency.ConsistencyCheck',
# 'weblate.trans.checks.chars.NewlineCountingCheck',
# 'weblate.trans.checks.markup.BBCodeCheck',
# 'weblate.trans.checks.chars.ZeroWidthSpaceCheck',
# 'weblate.trans.checks.markup.XMLValidityCheck',
# 'weblate.trans.checks.markup.XMLTagsCheck',
# 'weblate.trans.checks.source.OptionalPluralCheck',
# 'weblate.trans.checks.source.EllipsisCheck',
# 'weblate.trans.checks.source.MultipleFailingCheck',
# )

# List of automatic fixups
# AUTOFIX_LIST = (
#     'weblate.trans.autofixes.whitespace.SameBookendingWhitespace',
#     'weblate.trans.autofixes.chars.ReplaceTrailingDotsWithEllipsis',
#     'weblate.trans.autofixes.chars.RemoveZeroSpace',
# )

# List of scripts to use in custom processing
# POST_UPDATE_SCRIPTS = (
# )
# PRE_COMMIT_SCRIPTS = (
# )

# List of machine translations
# MACHINE_TRANSLATION_SERVICES = (
#     'weblate.trans.machine.apertium.ApertiumTranslation',
#     'weblate.trans.machine.glosbe.GlosbeTranslation',
#     'weblate.trans.machine.google.GoogleTranslation',
#     'weblate.trans.machine.microsoft.MicrosoftTranslation',
#     'weblate.trans.machine.mymemory.MyMemoryTranslation',
#     'weblate.trans.machine.tmserver.AmagamaTranslation',
#     'weblate.trans.machine.tmserver.TMServerTranslation',
#     'weblate.trans.machine.weblatetm.WeblateSimilarTranslation',
#     'weblate.trans.machine.weblatetm.WeblateTranslation',
# )

# E-mail address that error messages come from.
SERVER_EMAIL = 'noreply@weblate.org'

# Default email address to use for various automated correspondence from
# the site managers. Used for registration emails.
DEFAULT_FROM_EMAIL = 'noreply@weblate.org'

# List of URLs your site is supposed to serve
ALLOWED_HOSTS = []

```

```
# Example configuration to use memcached for caching
# CACHES = {
#     'default': {
#         'BACKEND': 'django.core.cache.backends.memcached.MemcachedCache',
#         'LOCATION': '127.0.0.1:11211',
#     },
#     'avatar': {
#         'BACKEND': 'django.core.cache.backends.filebased.FileBasedCache',
#         'LOCATION': os.path.join(BASE_DIR, 'avatar-cache'),
#         'TIMEOUT': 3600,
#         'OPTIONS': {
#             'MAX_ENTRIES': 1000,
#         },
#     },
# }

# REST framework settings for API
REST_FRAMEWORK = {
    # Use Django's standard `django.contrib.auth` permissions,
    # or allow read-only access for unauthenticated users.
    'DEFAULT_PERMISSION_CLASSES': [
        'rest_framework.permissions.IsAuthenticatedOrReadOnly'
    ],
    'DEFAULT_AUTHENTICATION_CLASSES': (
        'rest_framework.authentication.TokenAuthentication',
        'rest_framework.authentication.SessionAuthentication',
    ),
    'DEFAULT_THROTTLE_CLASSES': (
        'rest_framework.throttling.AnonRateThrottle',
        'rest_framework.throttling.UserRateThrottle'
    ),
    'DEFAULT_THROTTLE_RATES': {
        'anon': '100/day',
        'user': '1000/day'
    },
    'DEFAULT_PAGINATION_CLASS': (
        'rest_framework.pagination.PageNumberPagination'
    ),
    'PAGE_SIZE': 20,
    'VIEW_DESCRIPTION_FUNCTION': 'weblate.api.views.get_view_description',
}

# Example for restricting access to logged in users
# LOGIN_REQUIRED_URLS = (
#     r'/(.*)$',
# )

# In such case you will want to include some of the exceptions
# LOGIN_REQUIRED_URLS_EXCEPTIONS = (
#     r'/accounts/(.*)$', # Required for login
#     r'/static/(.*)$',   # Required for development mode
#     r'/widgets/(.*)$',  # Allowing public access to widgets
#     r'/data/(.*)$',     # Allowing public access to data exports
#     r'/hooks/(.*)$',    # Allowing public access to notification hooks
#     r'/api/(.*)$',      # Allowing access to API
# )

# Force sane test runner
```

```
TEST_RUNNER = 'django.test.runner.DiscoverRunner'
```

4.15 Management commands

Note: Running management commands under different user than is running your webserver can cause wrong permissions on some files, please check *Filesystem permissions* for more details.

Django comes with management script (available as `./manage.py` in sources or installed as **weblate** when Weblate is installed). It provides various management commands and Weblate extends it with several additional commands.

4.15.1 Invoking management commands

As mentioned before, invocation depends on how you have installed Weblate.

If you are using source code directly (either tarball or Git checkout), the management script is `./manage.py` in Weblate sources. Execution can be done as:

```
python ./manage.py list_versions
```

If you've installed Weblate using PIP installer or by `./setup.py` script, the **weblate** is installed to your path and you can use it to control Weblate:

```
weblate list_versions
```

For Docker image, the script is installed same as above, you can execute it using **docker exec**:

```
docker exec <container> weblate list_versions
```

With **docker-compose** this is quite similar, you just have to use **docker-compose run**:

```
docker-compose run <container> weblate list_versions
```

See also:

Weblate and Docker, Installing Weblate by pip

4.15.2 `add_suggestions <project> <component> <language> <file>`

manage.py add_suggestions

New in version 2.5.

Imports translation from the file as a suggestions to given translation. It skips translations which are same as existing ones, only different ones are added.

You should specify existing user using `--author` parameter (you can create one in the admin interface if needed).

Example:

```
./manage.py --author michal@cihar.com add_suggestions weblate master cs /tmp/suggestions-cs.po
```

4.15.3 auto_translate <project> <component> <language>

manage.py auto_translate

New in version 2.5.

Performs automatic translation based on other component translations.

By default it uses all other components from current project, but you can specify other source component by `--source` parameter.

All changes are by default authored by anonymous user, you can specify another username by `--user`.

The `--overwrite` and `--inconsistent` parameters control which strings will be updated.

You can also specify `--add` and if the language doesn't exist in the component, it will be automatically added (if supported).

Example:

```
./manage.py --user nijel --inconsistent --source phpmyadmin/master phpmyadmin 4-5 cs
```

See also:

Automatic translation

4.15.4 changesite

manage.py changesite

New in version 2.4.

You can use this to changes site name from command line with `--set-name` parameter. The `--get-name` prints currently configured site name.

See also:

Set correct site name

4.15.5 checkgit <project|project/component>

manage.py checkgit

Prints current state of backend git repository.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

4.15.6 commitgit <project|project/component>

manage.py commitgit

Commits any possible pending changes to backend git repository.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

4.15.7 `commit_pending` <project|project/component>

`manage.py commit_pending`

Commits pending changes older than given age (using `--age` parameter, defaults to 24 hours).

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

This is most useful if executed periodically from cron or similar tool:

```
./manage.py commit_pending --all --age=48
```

See also:

Running maintenance tasks

4.15.8 `cleanuptrans`

`manage.py cleanuptrans`

Cleanups orphaned checks and translation suggestions.

See also:

Running maintenance tasks

4.15.9 `createadmin`

`manage.py createadmin`

Creates `admin` account with random password. You can specify `--password` to provide password on the command line.

4.15.10 `dumpuserdata` <file.json>

`manage.py dumpuserdata`

Dumps userdata to file for later use by `importuserdata`

This is useful when migrating or merging Weblate instances.

4.15.11 `import_json` <json-file>

`manage.py import_json`

New in version 2.7.

Batch import of components based on JSON data.

You need to specify `--project` to define where the components will be imported.

Additionally you can specify `--main-component` to use VCS repository from this component for all.

The imported JSON file structure pretty much corresponds to the component object (see [GET /api/components/\(string:project\)/\(string:component\)/](#)). You always have to include fields `name` and `filemask`.

Example of JSON file:

```
[
  {
    "slug": "po",
    "name": "Gettext PO",
    "file_format": "po",
    "filemask": "po/*.po"
  },
  {
    "name": "Android",
    "filemask": "android/values-*/strings.xml",
    "template": "android/values/strings.xml",
    "repo": "weblate://test/test"
  }
]
```

See also:

import_project

4.15.12 import_project <project> <gitrepo> <branch> <filemask>

manage.py import_project

Batch imports components into project based on file mask.

<project> names an existing project, into which the components should be imported.

The <gitrepo> defines URL of Git repository to use, and <branch> the git branch. To import additional translation components, from an existing Weblate component, use a *weblate://<project>/<component>* URL for the <gitrepo>.

The repository is searched for directories matching a double wildcard (**) in the <filemask>. Each of these is then added as a component, named after the matched directory. Existing components will be skipped.

To customise the component's name, use the `--name-template` option. Its parameter is a python formatting string, which will expect the match from <filemask>.

By format string passed by the `--base-file-template` option you can customize base file for monolingual translations.

You can also specify file format to use (see *Supported formats*) by the `--file-format` parameter. The default is autodetection.

You can specify language filtering (see *Component configuration*) by the `--language-regex` parameter. It has to be valid regular expression.

With `--main-component` you can specify which component will be chosen as main - the one actually containing VCS repository.

Using `--license` and `--license-url` you can specify license and it's URL for imported components.

In case you need to specify version control system to use, you can do this using `--vcs` parameter. The default version control is Git.

You can override parsing of component name from matched files by `--component-regexp`. This is a regular expression which will be matched against file name (as matched by <filemask>) and has to contain named group *name*. This can be also used for excluding files in case they do not match this expression. For example: `.*/(?P<name>[^-]*)\.po`

By default the import does skip already existing projects. This is to allow repeated importing of same repository. However if you want to force importing additional components even if name or slug matches existing one, you can do

it by passing `--no-skip-duplicates`. This is generally useful for components with long names, which will get truncated on import and many of them will get same name or slug.

To give you some examples, let's try importing two projects.

As first we import The Debian Handbook translations, where each language has separate folder with translations of each chapter:

```
./manage.py import_project \
    debian-handbook \
    git://anonscm.debian.org/debian-handbook/debian-handbook.git \
    squeeze/master \
    '*/**.po'
```

Another example can be Tanaguru tool, where we need to specify file format, base file template and has all components and translations located in single folder:

```
./manage.py import_project \
    --file-format=properties \
    --base-file-template=web-app/tgol-web-app/src/main/resources/i18n/%s-I18N.properties \
    tanaguru \
    https://github.com/Tanaguru/Tanaguru \
    master \
    web-app/tgol-web-app/src/main/resources/i18n/**-I18N_*.properties
```

Example of more complex parsing of filenames to get correct component and language out of file name like `src/security/Numerous_security_holes_in_0.10.1.de.po`:

```
./manage.py import_project \
    --component-regex 'wiki/src/security/(?P<name>.*)\.([^.]*)\.po$' \
    tails \
    git://git.tails.boum.org/tails master \
    'wiki/src/security/**/*.po'
```

Filtering only translations in chosen language:

```
./manage.py import_project \
    --language-regex '^(cs|sk)$' \
    weblate \
    https://github.com/nijel/weblate.git \
    'weblate/locale/*/LC_MESSAGES/**/*.po'
```

See also:

More detailed examples can be found in the *Starting with internationalization* chapter, alternatively you might want to use `import_json`.

4.15.13 importuserdata <file.json>

manage.py importuserdata

Imports userdata from file created by `dumpuserdata`

4.15.14 importusers --check <file.json>

manage.py importusers

Imports users from JSON dump of Django auth_users database.

With `--check` it will just check whether given file can be imported and report possible conflicts on usernames or emails.

You can dump users from existing Django installation using:

```
./manage.py dumpdata auth.User > users.json
```

4.15.15 list_ignored_checks

manage.py list_ignored_checks

Lists most frequently ignored checks. This can be useful for tuning your setup, if users have to ignore too many of consistency checks.

4.15.16 list_translators <project|project/component>

manage.py list_translators

Renders the list of translators by language for the given project:

```
[French]
Jean Dupont <jean.dupont@example.com>
[English]
John Doe <jd@example.com>
```

You can use the `-language-code` version to use language code instead of language name.

You can either define which project or component to use (eg. `weblate/master`) or use `--all` to list translators from all existing components.

4.15.17 list_versions

manage.py list_versions

Lists versions of Weblate dependencies.

4.15.18 loadpo <project|project/component>

manage.py loadpo

Reloads translations from disk (eg. in case you did some updates in VCS repository).

You can use `--force` to force update even if the files should be up to date. Additionally you can limit languages to process with `--lang`.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

4.15.19 lock_translation <project|project/component>

manage.py lock_translation

Locks given component for translating. This is useful in case you want to do some maintenance on underlying repository.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

See also:

`unlock_translation`

4.15.20 `pushgit` <project|project/component>

`manage.py pushgit`

Pushes committed changes to upstream VCS repository. With `--force-commit` it also commits any pending changes.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

4.15.21 `rebuild_index` <project|project/component>

`manage.py rebuild_index`

Rebuilds index for fulltext search. This might be lengthy operation if you have huge set of translation units.

You can use `--clean` to remove all words from database prior updating.

With `--optimize` the index will not be processed again, only it's content will be optimized (removing stale entries and merging possibly split index files).

See also:

`Fulltext search`

4.15.22 `update_index`

`manage.py update_index`

Updates index for fulltext search when `OFFLOAD_INDEXING` is enabled.

It is recommended to run this frequently (eg. every 5 minutes) to have index uptodate.

See also:

`Fulltext search`, `Running maintenance tasks`, `Enable indexing offloading`

4.15.23 `unlock_translation` <project|project/component>

`manage.py unlock_translation`

Unlocks given component for translating. This is useful in case you want to do some maintenance on underlying repository.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

See also:

`lock_translation`

4.15.24 setupgroups

manage.py setupgroups

Configures default groups and (if called with `--move`) assigns all users to default group.

The option `--no-privs-update` disables update of existing groups (only adds new ones).

See also:

Access control

4.15.25 setuplang

manage.py setuplang

Setups list of languages (it has own list and all defined in `translate-toolkit`).

The option `--no-update` disables update of existing languages (only adds new ones).

4.15.26 updatechecks <project|project/component>

manage.py updatechecks

Updates all check for all units. This could be useful only on upgrades which do major changes to checks.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

4.15.27 updategit <project|project/component>

manage.py updategit

Fetches remote VCS repositories and updates internal cache.

You can either define which project or component to update (eg. `weblate/master`) or use `--all` to update all existing components.

4.16 Whiteboard messages

You can use whiteboard messages to give some information to your translators. The message can be site-wide or targeted on translation component or language.

This can be useful for various things from announcing purpose of the website to specifying targets for translations.

The whiteboard can currently be specified only in the admin interface:

Django administration

WELCOME, WEBLATE ADMIN. [VIEW SITE](#) / [DOCUMENTATION](#) / [CHANGE PASSWORD](#) / [LOG OUT](#)

Home › Weblate translations › Whiteboard messages › Translations will be used only if they reach 60%.

Change Whiteboard message



HISTORY

Required fields are marked as **bold**, you can find more information in the [documentation](#).



Message:

Translations will be used only if they reach 60%.



Project:

Hello  

Component:

-----  

Language:

-----  

Delete

Save and add another

Save and continue editing

SAVE

The whiteboard messages are then shown based on specified context:

No context specified

Shown on dashboard (landing page).

Project specified

Shown on project, all its components and translations.

Component specified

Shown on component and all its translations.

Language specified

Shown on language overview and all translations in this language.

You can see how it looks on the language overview page:

Weblate
 Dashboard
 Your translations
 Projects
 Documentation
 Weblate Admin

Languages / Czech

Czech translators rock!

Overview
History
Activity
Glossaries
Tools

Project	Translated	Words	Fuzzy	Checks	Suggestions
Hello/Android	<div><div></div></div> 25.0%	13.3%	0.0%	0	0
Hello/Webate	<div><div></div></div> 100.0%	100.0%	0.0%	4	0

- Good translations
 - Translations with falling checks
 - Fuzzy translations

Powered by Weblate 2.5-dev
 About Weblate
 Contact us
 Documentation
 Donate to Weblate!

And on the project page:

Weblate
 Dashboard
 Your translations
 Projects
 Documentation
 Weblate Admin

Hello

translated 7%

Translations will be used only if they reach 60%.

Overview
History
Activity
Tools
Share

Components

Component	Translated
Android	<div><div></div></div> 62.5%
Webate	<div><div></div></div> 3.7%

- Good translations
 - Translations with falling checks
 - Fuzzy translations

4.17 Advertisement

Weblate allows you to place advertisements inside emails and web pages. You can add them in the admin interface, defining placement and timespan, when it should be shown.

Active advertisements are chosen randomly to be displayed inside defined placement.

When no advertisements are enabled, you can enable `SELF_ADVERTISEMENT` to show advertisements for Weblate.

4.18 Component Lists

Weblate allows you to specify multiple lists of components. These will then appear as options on the user dashboard, and users can pick a list to be their default view when they log in. See [Dashboard](#) to learn more about this feature.

The names and contents of component lists can be specified in the admin interface, in *Component lists* section. Each component list must have a name that is displayed to the user, and a slug that represents it in the URL.

Frequently Asked Questions

5.1 Configuration

5.1.1 How to create automatic workflow?

Weblate can handle all the translation things semi-automatically for you. If you will give it push access to your repository, the translations can live without interaction unless some merge conflict occurs.

1. Set up your git repository to tell Weblate whenever there is any change, see *Notification hooks* for information how to do it.
2. Set push URL at your *Component configuration* in Weblate, this will allow Weblate to push changes to your repository.
3. Enable push on commit on your *Project configuration* in Weblate, this will make Weblate push changes to your repository whenever they are committed at Weblate.
4. Optionally setup cron job for *commit_pending*.

See also:

Continuous translation, Avoiding merge conflicts

5.1.2 How to access repositories over SSH?

Please see *Accessing repositories* for information about setting up SSH keys.

5.1.3 How to fix merge conflicts in translations?

The merge conflicts happen time to time when the translation file is changed in both Weblate and upstream repository. You can usually avoid this by merging Weblate translations prior to doing some changes in the translation files (eg. before executing msgmerge). Just tell Weblate to commit all pending translations (you can do it in the *Repository maintenance* in the *Tools* menu) and merge the repository (if automatic push is not enabled).

If you've already ran to the merge conflict, the easiest way is to solve all conflicts locally at your workstation - simply add Weblate as remote repository, merge it into upstream and fix conflicts. Once you push changes back, Weblate will be able to use merged version without any other special actions.

```
# Add remote
git remote add weblate git://git.weblate.org/debian-handbook.git
```

```
# Update remotes
git remote update

# Merge Weblate changes
git merge weblate/master

# Resolve conflicts
edit ....
git add ...
...
git commit

# Push changes to upstream repository, Weblate will fetch merge from there
git push
```

See also:

How to export Git repository weblate uses?

5.1.4 How do I translate several branches at once?

Weblate supports pushing translation changes within one *Project configuration*. For every *Component configuration* which has it enabled (the default behavior), the change made is automatically propagated to others. This way the translations are kept synchronized even if the branches themselves have already diverged quite a lot and it is not possible to simply merge translation changes between them.

Once you merge changes from Weblate, you might have to merge these branches (depending on your development workflow) discarding differences:

```
git merge -s ours origin/maintenance
```

5.1.5 How to export Git repository weblate uses?

There is nothing special about the repository, it lives under `DATA_DIR` directory and is named as `vcs/<project>/<component>/`. If you have SSH access to this machine, you can use the repository directly.

For anonymous access you might want to run git server and let it serve the repository to outside world.

5.1.6 What are options of pushing changes back upstream?

This heavily depends on your setup, Weblate is quite flexible in this area. Here are examples of workflows used with Weblate:

- Weblate automatically pushes and merges changes (see *How to create automatic workflow?*)
- You tell manually Weblate to push (it needs push access to upstream repository)
- Somebody manually merges changes from Weblate git repository into upstream repository
- Somebody rewrites history produced by Weblate (eg. by eliminating merge commits), merges changes and tells Weblate to reset content on upstream repository.

Of course you are free to mix all of these as you wish.

5.1.7 How can I check if my Weblate is configured properly?

Weblate includes set of configuration checks, which you can see in admin interface, just follow *Performance report* link in admin interface or directly open `/admin/performance/` URL.

5.1.8 Why does links contain example.com as domain?

Weblate uses Django sites framework and it defines site name inside the database. You need to set the domain name to match your installation.

See also:

Set correct site name

5.1.9 Why are all commits committed by Weblate <noreply@weblate.org>?

This is default commiter name configured when you create translation component. You can also change it in the administration at any time.

The author of every commit (when underlaying VCS supports it) is still recorded correctly as an user who has made the translation.

See also:

Component configuration

5.1.10 Why do I get warning about not reflected changes on database migration?

When running `./manage.py migrate`, you can get following warning:

Your models have changes that are not yet reflected in a migration, and so won't be applied.

This is expected as Weblate generates choices for some fields and Django migrations can not reflect this. You can safely ignore this warning.

5.2 Usage

5.2.1 How do I review others translations?

- You can subscribe to any changes made in *Subscriptions* and then check other contributions in email.
- There is review tool available at bottom of translation view, where you can choose to browse translations made by others since given date.

5.2.2 How do I provide feedback on source string?

On context tabs below translation, you can use *Source* tab to provide feedback on source string or discuss it with other translators.

5.2.3 How can I use existing translations while translating?

Weblate provides you several ways to utilize existing translations while translating:

- You can use import functionality to load compendium as translations, suggestions or translations needing review. This is best approach for one time translation using compedium or similar translation database.
- You can setup *tmserver* with all databases you have and let Weblate use it. This is good for case when you want to use it for several times during translating.
- Another option is to translate all related projects in single Weblate instance, what will make it automatically pick up translation from other projects as well.

See also:

Machine translation setup, Machine translation

5.2.4 Does Weblate update translation files besides translations?

Weblate tries to limit changes in translation files to minimum. For some file formats it might unfortunately lead to reformatting the file. If you want to keep the file formatted in your way, please use pre commit hook for that.

For monolingual files (see *Supported formats*) Weblate might add new translation units which are present in the *template* and not in actual translations. It does not however perform any automatic cleanup of stale strings as it might have unexpected outcome. If you want to do this, please install pre commit hook which will handle the cleanup according to your needs.

Weblate also will not try to update bilingual files in any way, so if you need `po` files being updated from `pot`, you need to do it on your own.

See also:

Processing repository with scripts

5.2.5 Where do language definition come from and how can I add own?

Basic set of language definitions is included within Weblate and Translate-toolkit. This covers more than 150 languages and includes information about used plural forms or text direction.

You are free to define own language in administrative interface, you just need to provide information about it.

5.2.6 Can Weblate highlight change in a fuzzy string?

Weblate supports this, however it needs the data to show the difference.

For Gettext PO files, you have to pass parameter `--previous` to **msgmerge** when updating PO files, for example:

```
msgmerge --previous -U po/cs.po po/phpmyadmin.pot
```

For monolingual translations, Weblate can find the previous string by ID, so it shows the differences automatically.

5.2.7 Why does Weblate still shows old translation strings when I've updated the template?

Weblate does not try to manipulate with the translation files in any other way than allowing translators to translate. So it also does not update the translatable files when the template or source code has been changed. You simply have to do this manually and push changes to the repository, Weblate will then pick up the changes automatically.

Note: It is usually good idea to merge changed done in Weblate before updating translation files as otherwise you will usually end up with some conflicts to merge.

For example with Gettext PO files, you can update the translation files using the **msgmerge** tool:

```
msgmerge -U locale/cs/LC_MESSAGES/django.mo locale/django.pot
```

In case you can want to do the update automatically, you can add custom script to handle this to *POST_UPDATE_SCRIPTS* and enable it in the *Component configuration*.

5.3 Troubleshooting

5.3.1 Requests sometimes fail with too many open files error

This happens sometimes when your Git repository grows too much and you have more of them. Compressing the Git repositories will improve this situation.

The easiest way to do this is to run:

```
# Go to DATA_DIR directory
cd data/vcs
# Compress all Git repositories
for d in */* ; do
    pushd $d
    git gc
    popd
done
```

See also:

DATA_DIR

5.3.2 Fulltext search is too slow

Depending on various conditions (frequency of updates, server restarts and other), fulltext index might get too fragmented over time. It is recommended to optimize it to time:

```
./manage.py rebuild_index --optimize
```

In case it does not help (or if you have removed lot of strings) it might be better to rebuild it from scratch:

```
./manage.py rebuild_index --clean
```

See also:

rebuild_index

5.3.3 I get “Lock Error” quite often while translating

This is usually caused by concurrent updates to fulltext index. In case you are running multi threaded server (eg. *mod_wsgi*), this happens quite often. For such setup it is recommended to enable *OFFLOAD_INDEXING*.

See also:

Fulltext search

5.3.4 Rebuilding index has failed with “No space left on device”

Whoosh uses temporary directory to build indices. In case you have small /tmp (eg. using ramdisk), this might fail. Change used temporary directory by passing as TEMP variable:

```
TEMP=/path/to/big/temp ./manage.py rebuild_index --clean
```

See also:

rebuild_index

5.3.5 Database operations fail with “too many SQL variables”

This can happen with SQLite database as it is not powerful enough for some relations used within Weblate. The only way to fix this is to use some more capable database, see *Use powerful database engine* for more information.

See also:

Use powerful database engine, Django’s databases

5.4 Features

5.4.1 Does Weblate support other VCS than Git and Mercurial?

Weblate currently does not have native support for anything else than *Git* (with extended support for *GitHub* and *Subversion*) and *ref:vcs-mercurial*, but it is possible to write backends for other VCSes.

You can also use *Git remote helpers* in Git to access other VCSes.

Note: For native support of other VCS, Weblate requires distributed VCS and could be probably adjusted to work with anything else than Git and Mercurial, but somebody has to implement this support.

See also:

Version control integration

5.4.2 How does Weblate credit translators?

Every change made in Weblate is committed into VCS under translators name. This way every single change has proper authorship and you can track it down using standard VCS tools you use for code.

Additionally, when translation file format supports it, the file headers are updated to include translator name.

See also:

list_translators

5.4.3 Why does Weblate force to have show all po files in single tree?

Weblate was designed in a way that every po file is represented as single component. This is beneficial for translators, that they know what they are actually translating. If you feel your project should be translated as one, consider merging these po files. It will make life easier even for translators not using Weblate.

Note: In case there will be big demand for this feature, it might be implemented in future versions, but it's definitely not a priority for now.

Supported formats

Weblate supports any translation format understood by Translate-toolkit, however each format being slightly different, there might be some issues with not well tested formats.

See also:

[Supported formats in translate-toolkit](#)

Note: When choosing file format for your application, it's better to stick some well established format in toolkit/platform you use. This way your translators can use whatever tools they are get used to and will more likely contribute to your project.

Weblate does support both monolingual and bilingual formats. Bilingual formats store two languages in single file - source and translation (typical examples is *GNU Gettext*, *XLIFF* or *Apple OS X strings*). On the other side, monolingual formats identify the string by ID and each language file contains only mapping of those to given language (typically *Android string resources*). Some file formats are used in both variants, see detailed description below.

For correct use of monolingual files, Weblate requires access to file containing complete list of strings to translate with their source - this file is called *Monolingual base language file* within Weblate, though the naming might vary in your application.

6.1 Automatic detection

Weblate can automatically detect several widely spread file formats, but this detection can harm your performance and will limit features specific to given file format (for example automatic adding of new translations).

6.2 GNU Gettext

Most widely used format in translating free software. This was first format supported by Weblate and still has best support.

Weblate supports contextual information stored in the file, adjusting its headers or linking to corresponding source files.

The bilingual gettext PO file typically looks like:

```
#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "Monday"
msgstr "Pondělí"
```

```
#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "Tuesday"
msgstr "Úterý"

#: weblate/accounts/avatar.py:163
msgctxt "No known user"
msgid "None"
msgstr "Žádný"
```

See also:

[Gettext on Wikipedia](#), [Gettext in translate-toolkit documentation](#)

6.2.1 Monolingual Gettext

Some projects decide to use Gettext as monolingual formats - they code just IDs in their source code and the string needs to be translated to all languages, including English. Weblate does support this, though you have to choose explicitly this file format when importing components into Weblate.

The monolingual gettext PO file typically looks like:

```
#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-monday"
msgstr "Pondělí"

#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-tuesday"
msgstr "Úterý"

#: weblate/accounts/avatar.py:163
msgid "none-user"
msgstr "Žádný"
```

While the base language file will be:

```
#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-monday"
msgstr "Monday"

#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-tuesday"
msgstr "Tuesday"

#: weblate/accounts/avatar.py:163
msgid "none-user"
msgstr "None"
```

6.3 XLIFF

XML based format created to standardize translation files, but in the end it is one of many standards in this area.

XLIFF is usually used as bilingual, but Weblate supports it as monolingual as well.

Note: If the translation unit doesn't have `approved="yes"` it will be imported into Weblate as needing review (what matches XLIFF specification).

You can override this by adding `skip-review-flag` flag to the component, see [Component configuration](#), what will make Weblate ignore this and all strings will appear as approved.

See also:

[XLIFF on Wikipedia](#), [XLIFF in translate-toolkit documentation](#)

6.4 Java properties

Native Java format for translations.

Java properties are usually used as monolingual.

This format supports creating new languages. When a new language is created, a new empty file will be added to the repository. Only keys that are defined will be written to the newly created file. The Weblate maintainer needs to make sure that this is the expected behaviour with the framework in use.

Weblate supports ISO-8859-1, UTF-8 and UTF-16 variants of this format.

See also:

[Java properties on Wikipedia](#), [Java properties in translate-toolkit documentation](#)

6.5 Qt Linguist .ts

Translation format used in Qt based applications.

Qt Linguist files are used as both bilingual and monolingual.

See also:

[Qt Linguist manual](#), [Qt .ts in translate-toolkit documentation](#)

6.6 Android string resources

Android specific file format for translating applications.

Android string resources are monolingual, the *Monolingual base language file* file being stored in different location than others `res/values/strings.xml`.

See also:

[Android string resources documentation](#), [Android string resources in translate-toolkit documentation](#)

Note: Android *string-array* structures are not currently supported. To work around this, you can break your string arrays apart:

```
<string-array name="several_strings">
  <item>First string</item>
  <item>Second string</item>
</string-array>
```

become:

```
<string-array name="several_strings">
  <item>@string/several_strings_0</item>
  <item>@string/several_strings_1</item>
</string-array>
<string name="several_strings_0">First string</string>
<string name="several_strings_1">Second string</string>
```

The *string-array* that points to the *string* elements should be stored in a different file, and not localized.

This script may help pre-process your existing strings.xml files and translations:
<https://gist.github.com/paour/11291062>

6.7 Apple OS X strings

Apple specific file format for translating applications, used for both OS X and iPhone/iPad application translations.

Apple OS X strings are usually used as bilingual.

See also:

[Apple Strings Files documentation](#), [Apple strings in translate-toolkit documentation](#)

Note: You need translate-toolkit 1.12.0 or newer for proper support of Apple OS X strings. Older versions might produce corrupted files.

6.8 PHP strings

PHP translations are usually monolingual, so it is recommended to specify base file with English strings.

Example file:

```
<?php
$LANG['foo'] = 'bar';
$LANG['foo1'] = 'foo bar';
$LANG['foo2'] = 'foo bar baz';
$LANG['foo3'] = 'foo bar baz bag';
```

Note: Translate-toolkit currently has some limitations in processing PHP files, so please double check that your files won't get corrupted before using Weblate in production setup.

Following things are known to be broken:

- Adding new units to translation, every translation has to contain all strings (even if empty).
 - Handling of special chars like newlines.
-

See also:

[PHP files in translate-toolkit documentation](#)

6.9 JSON files

New in version 2.0.

JSON is format used mostly for translating applications implemented in Javascript.

JSON translations are usually monolingual, so it is recommended to specify base file with English strings.

Note: Weblate currently supports only simple JSON files with key value mappings, more complex formats like the ones used by Chrome extensions are currently not supported by translate-toolkit and will produce invalid results.

If you are using nested dictionaries structure in your translations, you can workaround above limitation by using `examples/hook-json_restore_hierarchy` as `PRE_COMMIT_SCRIPTS`.

Example file:

```
{
  "Hello, world!\n": "Ahoj světe!\n",
  "Orangutan has %d banana.\n": "",
  "Try Weblate at http://demo.weblate.org/!\n": "",
  "Thank you for using Weblate.": ""
}
```

See also:

[JSON in translate-toolkit documentation](#)

6.10 .Net Resource files

New in version 2.3.

.Net Resource (.resx) file is a monolingual XML file format used in Microsoft .Net Applications.

Note: You need translate-toolkit 1.13.0 or newer to include support for this format.

6.11 CSV files

New in version 2.4.

CSV files can contain simple list of source and translation. Weblate supports following files:

- Files with header defining fields (source, translation, location, ...)
- Files with two field - source and translation (in this order), choose *Simple CSV file* as file format
- Files with fields as defined by translate-toolkit: location, source, target, id, fuzzy, context, translator_comments, developer_comments

Example file:

```
Thank you for using Weblate.,Děkujeme za použití Weblate.
```

6.12 Others

As already mentioned, all Translate-toolkit formats are supported, but they did not (yet) receive deeper testing.

See also:

[Supported formats in translate-toolkit](#)

Version control integration

Weblate currently supports *Git* (with extended support for *GitHub*) and *Mercurial* as version control backends.

7.1 Accessing repositories

The VCS repository you want to use has to be accessible to Weblate. With publicly available repository you just need to enter correct URL (for example `git://github.com/nijel/weblate.git` or `https://github.com/nijel/weblate.git`), but for private repositories the setup might be more complex.

7.1.1 Weblate internal URLs

To share one repository between different components you can use special URL like `weblate://project/component`. This way the component will share the VCS repository configuration with referenced component and the VCS repository will be stored just once on the disk.

7.1.2 SSH repositories

Most frequently used method to access private repositories is based on SSH. To have access to such repository, you generate SSH key for Weblate and authorize it to access the repository.

You can generate or display key currently used by Weblate in the admin interface (follow *SSH keys* link on main admin page). Once you've done this, Weblate should be able to access your repository.

Note: The keys need to be without password to make it work, so be sure they are well protected against malicious usage.

Before connecting to the repository, you also need to verify SSH host keys of servers you are going to access in the same section of the admin interface.

Note: On GitHub, you can add the key to only one repository. See following sections for other solutions for GitHub.

7.1.3 HTTPS repositories

To access protected HTTPS repositories, you need to include user and password in the URL. Don't worry, Weblate will strip this information when showing URL to the users (if they are allowed to see the repository URL at all).

For example the GitHub URL with authentication might look like `https://user:your_access_token@github.com/nijel`

7.1.4 Using proxy

If you need to access http/https VCS repositories using a proxy server, you need to configure VCS to use it.

This can be configured using the `http_proxy`, `https_proxy`, and `all_proxy` environment variables (check `cURL` documentation for more details) or by enforcing it in VCS configuration, for example:

```
git config --global http.proxy http://user:password@proxy.example.com:80
```

Note: The proxy setting needs to be done in context which is used to execute Weblate. For the environment it should be set for both server and cron jobs. The VCS configuration has to be set for the user which is running Weblate.

See also:

[curl manpage](#), [git config documentation](#)

7.2 Git

Git is first VCS backend that was available in Weblate and is still the most stable and tested one.

See also:

See [Accessing repositories](#) for information how to access different kind of repositories.

7.2.1 GitHub repositories

You can access GitHub repositories by SSH as mentioned above, but in case you need to access more repositories, you will hit GitHub limitation on the SSH key usage (one key can be used only for one repository). There are several ways to workaround this limitation.

For smaller deployments, you can use HTTPS authentication using personal access token and your account, see [Creating an access token for command-line use](#).

For bigger setup, it is usually better to create dedicated user for Weblate, assign him the SSH key generated in Weblate and grant him access to all repositories you want.

7.2.2 Git remote helpers

You can also use Git [remote helpers](#) for supporting other VCS as well, but this usually leads to smaller or bigger problems, so be prepared to debug them.

At this time, helpers for Bazaar and Mercurial are available within separate repositories on GitHub: [git-remote-hg](#) and [git-remote-bzr](#). You can download them manually and put somewhere in your search path (for example `~/bin`). You also need to have installed appropriate version control programs as well.

Once you have these installed, you can use such remotes to specify repository in Weblate.

To clone `gnuhello` project from Launchpad with Bazaar use:

```
bzr::lp:gnuhello
```

For `hello` repository from `selenic.com` with Mercurial use:

```
hg::http://selenic.com/repo/hello
```

Warning: Please be prepared to some inconvenience when using Git remote helpers, for example with Mercurial, the remote helper sometimes tends to create new tip when pushing changes back.

7.3 GitHub

New in version 2.3.

This just adds thin layer on top of *Git* to allow push translation changes as pull requests instead of pushing directory to the repository. It currently uses the *hub* tool to do the integration.

There is no need to use this to access Git repositories, ordinary *Git* works same, the only difference is how pushing to repository is handled. With *Git* changes are pushed directly to the repository, while *GitHub* creates pull requests.

Note: This feature is currently not available on Hosted Weblate due to technical limitations. See *Pushing changes from Hosted Weblate* for available options.

7.3.1 Pushing changes to GitHub as pull request

If you are translating a project that's hosted on GitHub and don't want to push translations to the repository, you can have them sent as a pull request instead.

You need to configure the *hub* command line tool and set `GITHUB_USERNAME` for this to work.

See also:

`GITHUB_USERNAME`, *Setting up hub* for configuration instructions

7.3.2 Setting up hub

Pushing changes to GitHub as pull request requires a configured *hub* installation on your server. Follow the installation instructions at <https://hub.github.com/> and perform an action with *hub* to finish the configuration, for example:

```
hub clone octocat/Spoon-Knife
```

The *hub* will ask you for your GitHub credentials, retrieve a token and store it into `~/.config/hub`.

Note: Use the username you configured *hub* with as `GITHUB_USERNAME`.

7.4 Mercurial

New in version 2.1.

Mercurial is another VCS you can use directly in Weblate.

Note: It should work with any Mercurial version, but there are sometimes incompatible changes to the command line interface which break Weblate.

See also:

See [Accessing repositories](#) for information how to access different kind of repositories.

7.5 Subversion

New in version 2.8.

Thanks to [git-svn](#), Weblate can work with [subversion](#) repositories. Git-svn is a Perl script that enables the usage of subversion with a git client, enabling users to have a full clone of the internal repository and commit locally.

Note: Weblate supports only subversion repositories with standard layout (branches/, tags/ and trunk/).

7.5.1 Credentials

Weblate expects you to have accepted the certificate upfront and inserted your credential, if needed. It will look into the DATA_DIR directory. To insert your credential and accept the certificate, you can run svn once with the *\$HOME* environment variable set to the DATA_DIR:

```
HOME=${DATA_DIR} svn co https://svn.example.com/example
```

See also:

[DATA_DIR](#)

Weblate's Web API

8.1 REST API

New in version 2.6: The API is available since Weblate 2.6.

The API is accessible on the `/api/` URL and it is based on [Django REST framework](#). You can use it directly or by *Weblate Client*.

8.1.1 Authentication and generic parameters

The public project API is available without authentication, though unauthenticated requests are heavily throttled (by default to 100 requests per day), so it is recommended to use authentication. The authentication is using token, which you can get in your profile. Use it in the `Authorization` header:

ANY /

Generic request behaviour for the API, the headers, status codes and parameters here apply to all endpoints as well.

Query Parameters

- **format** – Response format (overrides [Accept](#)). Possible values depends on REST framework setup, by default `json` and `api` are supported. The latter provides web browser interface for API.

Request Headers

- [Accept](#) – the response content type depends on [Accept](#) header
- [Authorization](#) – optional token to authenticate

Response Headers

- [Content-Type](#) – this depends on [Accept](#) header of request
- [Allow](#) – list of allowed HTTP methods on object

Response JSON Object

- **detail** (*string*) – verbose description of failure (for HTTP status codes other than 200 OK)
- **count** (*int*) – total item count for object lists
- **next** (*string*) – next page URL for object lists
- **previous** (*string*) – previous page URL for object lists

- **results** (*array*) – results for object lists
- **url** (*string*) – URL to access this resource using API
- **web_url** (*string*) – URL to access this resource using web browser

Status Codes

- **200 OK** – when request was correctly handled
- **400 Bad Request** – when form parameters are missing
- **403 Forbidden** – when access is denied
- **429 Too Many Requests** – when throttling is in place

Authentication examples

Example request:

```
GET /api/ HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
Authorization: Token YOUR-TOKEN
```

Example response:

```
HTTP/1.0 200 OK
Date: Fri, 25 Mar 2016 09:46:12 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, HEAD, OPTIONS

{
  "projects": "http://example.com/api/projects/",
  "components": "http://example.com/api/components/",
  "translations": "http://example.com/api/translations/",
  "languages": "http://example.com/api/languages/"
}
```

CURL example:

```
curl \
-H "Authorization: Token TOKEN" \
https://example.com/api/
```

Passing Parameters Examples

For the **POST** method the parameters can be specified either as form submission (*application/x-www-form-urlencoded*) or as JSON (*application/json*).

Form request example:

```
POST /api/projects/hello/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/x-www-form-urlencoded
```

```
Authorization: Token TOKEN

operation=pull
```

JSON request example:

```
POST /api/projects/hello/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{"operation": "pull"}
```

CURL example:

```
curl \
  -d operation=pull \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/components/hello/weblate/repository/
```

CURL JSON example:

```
curl \
  --data-binary '{"operation": "pull"}' \
  -H "Content-Type: application/json" \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/components/hello/weblate/repository/
```

8.1.2 API Entry Point

GET /api/
The API root entry point.

Example request:

```
GET /api/ HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
Authorization: Token YOUR-TOKEN
```

Example response:

```
HTTP/1.0 200 OK
Date: Fri, 25 Mar 2016 09:46:12 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, HEAD, OPTIONS

{
  "projects": "http://example.com/api/projects/",
  "components": "http://example.com/api/components/",
  "translations": "http://example.com/api/translations/",
  "languages": "http://example.com/api/languages/"
}
```

8.1.3 Languages

GET `/api/languages/`
Returns listing of all languages.

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Language object attributes are documented at `GET /api/languages/(string:language)/`.

GET `/api/languages/(string:language)/`
Returns information about language.

Parameters

- **language** (*string*) – Language code

Response JSON Object

- **code** (*string*) – Language code
- **direction** (*string*) – Text direction
- **nplurals** (*int*) – Number of plurals
- **pluralequation** (*string*) – Gettext plural equation

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Example JSON data:

```
{
  "code": "en",
  "direction": "ltr",
  "name": "English",
  "nplurals": 2,
  "pluralequation": "n != 1",
  "url": "http://example.com/api/languages/en/",
  "web_url": "http://example.com/languages/en/"
}
```

8.1.4 Projects

GET `/api/projects/`
Returns listing of projects.

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Project object attributes are documented at `GET /api/projects/(string:project)/`.

GET `/api/projects/(string:project)/`
Returns information about project.

Parameters

- **project** (*string*) – Project URL slug

Response JSON Object

- **name** (*string*) – project name
- **slug** (*string*) – project slug
- **source_language** (*object*) – source language object, see [GET /api/languages/\(string:language\)/](#)
- **web** (*string*) – project website
- **components_list_url** (*string*) – URL to components list, see [GET /api/projects/\(string:project\)/components/](#)
- **repository_url** (*string*) – URL to repository status, see [GET /api/projects/\(string:project\)/repository/](#)

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Example JSON data:

```
{
  "name": "Hello",
  "slug": "hello",
  "source_language": {
    "code": "en",
    "direction": "ltr",
    "name": "English",
    "nplurals": 2,
    "pluralequation": "n != 1",
    "url": "http://example.com/api/languages/en/",
    "web_url": "http://example.com/languages/en/"
  },
  "url": "http://example.com/api/projects/hello/",
  "web": "http://weblate.org/",
  "web_url": "http://example.com/projects/hello/"
}
```

GET /api/projects/(string:project)/repository/

Returns information about VCS repository status. This endpoint contains only overall summary for all repositories for project. To get more detailed status use [GET /api/components/\(string:project\)/\(string:component\)/repository/](#).

Parameters

- **project** (*string*) – Project URL slug

Response JSON Object

- **needs_commit** (*boolean*) – whether there are any pending changes to commit
- **needs_merge** (*boolean*) – whether there are any upstream changes to merge
- **needs_push** (*boolean*) – whether there are any local changes to push

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Example JSON data:

```
{
  "needs_commit": true,
  "needs_merge": false,
  "needs_push": true
}
```

POST /api/projects/ (string: project) /repository/

Performs given operation on the VCS repository.

Parameters

- **project** (*string*) – Project URL slug

Request JSON Object

- **operation** – Operation to perform, one of push, pull, commit, reset

Response JSON Object

- **result** (*boolean*) – result of the operation

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

CURL example:

```
curl \
  -d operation=pull \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/components/hello/weblate/repository/
```

JSON request example:

```
POST /api/projects/hello/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{"operation": "pull"}
```

JSON response example:

```
HTTP/1.0 200 OK
Date: Tue, 12 Apr 2016 09:32:50 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, POST, HEAD, OPTIONS

{"result": true}
```

GET /api/projects/ (string: project) /components/

Returns list of translation components in given project.

Parameters

- **project** (*string*) – Project URL slug

Response JSON Object

- **results** (*array*) – array of component objects, see [GET /api/components/\(string:project\)/\(string:component\)/](#)

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

8.1.5 Components**GET /api/components/**

Returns listin of translation components.

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Component object attributes are documented at [GET /api/components/\(string:project\)/\(string:component\)](#)

GET /api/components/(string: project) /

string: component/ Returns information about translation component.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

Response JSON Object

- **branch** (*string*) – VCS repository branch
- **file_format** (*string*) – file format of translations
- **filemask** (*string*) – mask of translation files in the repository
- **git_export** (*string*) – URL of the exported VCS repository with translations
- **license** (*string*) – license for translations
- **license_url** (*string*) – URL of license for translations
- **name** (*string*) – name of component
- **slug** (*string*) – slug of component
- **project** (*object*) – the translation project, see [GET /api/projects/\(string:project\)/](#)
- **repo** (*string*) – VCS repository URL
- **template** (*string*) – base file for monolingual translations
- **new_base** (*string*) – base file for adding new translations
- **vcs** (*string*) – version control system
- **repository_url** (*string*) – URL to repository status, see [GET /api/components/\(string:project\)/\(string:component\)/repository/](#)
- **translations_url** (*string*) – URL to translations list, see [GET /api/components/\(string:project\)/\(string:component\)/translations/](#)

- **lock_url** (*string*) – URL to lock status, see `GET /api/components/(string:project)/(string:component)/lock/`

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Example JSON data:

```
{
  "branch": "master",
  "file_format": "po",
  "filemask": "po/*.po",
  "git_export": "",
  "license": "",
  "license_url": "",
  "name": "Weblate",
  "slug": "weblate",
  "project": {
    "name": "Hello",
    "slug": "hello",
    "source_language": {
      "code": "en",
      "direction": "ltr",
      "name": "English",
      "nplurals": 2,
      "pluralequation": "n != 1",
      "url": "http://example.com/api/languages/en/",
      "web_url": "http://example.com/languages/en/"
    },
    "url": "http://example.com/api/projects/hello/",
    "web": "http://weblate.org/",
    "web_url": "http://example.com/projects/hello/"
  },
  "repo": "file:///home/nijel/work/weblate-hello",
  "template": "",
  "new_base": "",
  "url": "http://example.com/api/components/hello/weblate/",
  "vcs": "git",
  "web_url": "http://example.com/projects/hello/weblate/"
}
```

GET `/api/components/(string: project) /string: component/lock/` Returns component lock status.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

Response JSON Object

- **locked** (*boolean*) – whether component is locked for updates

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Example JSON data:


```
{
  "locked": false
}
```

POST `/api/components/ (string: project) /`
string: `component/lock/` Sets component lock status.

Response is same as `GET /api/components/ (string:project) / (string:component) /lock/`.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

Request JSON Object

- **lock** – Boolean whether to lock or not.

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

GET `/api/components/ (string: project) /`
string: `component/repository/` Returns information about VCS repository status.

The response is same as for `GET /api/projects/ (string:project) /repository/`.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

Response JSON Object

- **needs_commit** (*boolean*) – whether there are any pending changes to commit
- **needs_merge** (*boolean*) – whether there are any upstream changes to merge
- **needs_push** (*boolean*) – whether there are any local changes to push
- **remote_commit** – Remote commit information
- **status** – VCS repository status as reported by VCS
- **merge_failure** – Text describing merge failure, null if there is none

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

POST `/api/components/ (string: project) /`
string: `component/repository/` Performs given operation on the VCS repository.

See `POST /api/projects/ (string:project) /repository/` for documentation.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

Request JSON Object

- **operation** – Operation to perform, one of push, pull, commit, reset

Response JSON Object

- **result** (*boolean*) – result of the operation

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

GET `/api/components/ (string: project) /`
string: `component/monolingual_base/` Downloads base file for monolingual translations.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

GET `/api/components/ (string: project) /`
string: `component/new_template/` Downloads template file for new translations.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

GET `/api/components/ (string: project) /`
string: `component/translations/` Returns list of translation objects in given component.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

Response JSON Object

- **results** (*array*) – array of translation objects, see [GET /api/translations/ \(string:project\) / \(string:component\) / \(string:language\) /](#)

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

GET `/api/components/ (string: project) /`
string: `component/statistics/` Returns paginated statistics for all translations within component.

New in version 2.7.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug

Response JSON Object

- **results** (*array*) – array of translation statis objects, see [GET /api/translations/\(string:project\)/\(string:component\)/\(string:language\)/stats](#)

8.1.6 Translations

GET /api/translations/

Returns list of translations.

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Translation object attributes are documented at [GET /api/translations/\(string:project\)/\(string:component\)](#)

GET /api/translations/(string: project) /

string: component/string: language/ Returns information about translation.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug
- **language** (*string*) – Translation language code

Response JSON Object

- **component** (*object*) – component object, see [GET /api/components/\(string:project\)/\(string:component\)/](#)
- **failing_checks** (*int*) – number of units with failing check
- **failing_checks_percent** (*float*) – percentage of failing check units
- **failing_checks_words** (*int*) – number of words with failing check
- **filename** (*string*) – translation filename
- **fuzzy** (*int*) – number of units marked for review
- **fuzzy_percent** (*float*) – percentage of units marked for review
- **fuzzy_words** (*int*) – number of words marked for review
- **have_comment** (*int*) – number of units with comment
- **have_suggestion** (*int*) – number of units with suggestion
- **is_template** (*boolean*) – whether translation is monolingual base
- **language** (*object*) – source language object, see [GET /api/languages/\(string:language\)/](#)
- **language_code** (*string*) – language code used in the repository, this can be different from language code in the language object
- **last_author** (*string*) – name of last author
- **last_change** (*timestamp*) – last change timestamp
- **revision** (*string*) – hash revision of the file
- **share_url** (*string*) – URL for sharing leading to engage page
- **total** (*int*) – total number of units

- **total_words** (*int*) – total number of words
- **translate_url** (*string*) – URL for translating
- **translated** (*int*) – number of translated units
- **translated_percent** (*float*) – percentage of translated units
- **translated_words** (*int*) – number of translated words
- **repository_url** (*string*) – URL to repository status, see `GET /api/translations/(string:project)/(string:component)/(string:language)/repositories/`
- **file_url** (*string*) – URL to file object, see `GET /api/translations/(string:project)/(string:component)/(string:language)/files/`

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

Example JSON data:

```
{
  "component": {
    "branch": "master",
    "file_format": "po",
    "filemask": "po/*.po",
    "git_export": "",
    "license": "",
    "license_url": "",
    "name": "Weblate",
    "new_base": "",
    "project": {
      "name": "Hello",
      "slug": "hello",
      "source_language": {
        "code": "en",
        "direction": "ltr",
        "name": "English",
        "nplurals": 2,
        "pluralequation": "n != 1",
        "url": "http://example.com/api/languages/en/",
        "web_url": "http://example.com/languages/en/"
      },
      "url": "http://example.com/api/projects/hello/",
      "web": "http://weblate.org/",
      "web_url": "http://example.com/projects/hello/"
    },
    "repo": "file:///home/nijel/work/weblate-hello",
    "slug": "weblate",
    "template": "",
    "url": "http://example.com/api/components/hello/weblate/",
    "vcs": "git",
    "web_url": "http://example.com/projects/hello/weblate/"
  },
  "failing_checks": 3,
  "failing_checks_percent": 75.0,
  "failing_checks_words": 11,
  "filename": "po/cs.po",
  "fuzzy": 0,
  "fuzzy_percent": 0.0,
```

```

"fuzzy_words": 0,
"have_comment": 0,
"have_suggestion": 0,
"is_template": false,
"language": {
  "code": "cs",
  "direction": "ltr",
  "name": "Czech",
  "nplurals": 3,
  "pluralequation": "(n==1) ? 0 : (n>=2 && n<=4) ? 1 : 2",
  "url": "http://example.com/api/languages/cs/",
  "web_url": "http://example.com/languages/cs/"
},
"language_code": "cs",
"last_author": "Weblate Admin",
"last_change": "2016-03-07T10:20:05.499",
"revision": "7ddfafe6daaf57fc8654cc852ea6be212b015792",
"share_url": "http://example.com/engage/hello/cs/",
"total": 4,
"total_words": 15,
"translate_url": "http://example.com/translate/hello/weblate/cs/",
"translated": 4,
"translated_percent": 100.0,
"translated_words": 15,
"url": "http://example.com/api/translations/hello/weblate/cs/",
"web_url": "http://example.com/projects/hello/weblate/cs/"
}

```

GET `/api/translations/ (string: project) /`

string: *component/string: language/file/* Download current translation file as stored in VCS (without `format` parameter) or converted to one of standard formats (currently supported are Gettext PO, MO, Xliff or TBX).

Note: This API endpoint uses different logic for output than rest of API as it operates on whole file rather than on data. Set of accepted `format` parameters differ and without such parameter you get translation file as stored in VCS.

Query Parameters

- **format** – File format to use, if not specified no format conversion happens, supported file formats: `po`, `mo`, `xliff`, `xliff12`, `tbx`

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug
- **language** (*string*) – Translation language code

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

POST `/api/translations/ (string: project) /`

string: *component/string: language/file/* Upload new file with translations.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug
- **language** (*string*) – Translation language code

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

CURL example:

```
curl -X POST \
  -F file=@strings.xml \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/translations/hello/android/cs/file/
```

GET `/api/translations/ (string: project) / string: component/string: language/repository/` Returns information about VCS repository status.

The response is same as for `GET /api/components/ (string:project) / (string:component) / repository/`.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug
- **language** (*string*) – Translation language code

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

POST `/api/translations/ (string: project) / string: component/string: language/repository/` Performs given operation on the VCS repository.

See `POST /api/projects/ (string:project) / repository/` for documentation.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug
- **language** (*string*) – Translation language code

Request JSON Object

- **operation** – Operation to perform, one of push, pull, commit, reset

Response JSON Object

- **result** (*boolean*) – result of the operation

See also:

Additional common headers, parameters and status codes are documented at [Authentication and generic parameters](#).

GET `/api/translations/ (string: project) / string: component/string: language/statistics/` Returns detailed translation statistics.

New in version 2.7.

Parameters

- **project** (*string*) – Project URL slug
- **component** (*string*) – Component URL slug
- **language** (*string*) – Translation language code

Response JSON Object

- **code** – language code
- **failing** – number of failing checks
- **failing_percent** – percentage of failing checks
- **fuzzy** – number of strings needing review
- **fuzzy_percent** – percentage of strings needing review
- **total_words** – total number of words
- **translated_words** – number of translated words
- **last_author** – name of last author
- **last_change** – date of last change
- **name** – language name
- **total** – total number of strings
- **translated** – number of translated strings
- **translated_percent** – percentage of translated strings
- **url** – URL to access the translation (engagement URL)
- **url_translate** – URL to access the translation (real translation URL)

8.2 Notification hooks

Notification hooks allow external applications to notify Weblate that VCS repository has been updated.

You can use repository endpoints for project, component and translation to update individual repositories, see [POST /api/projects/\(string:project\)/repository/](#) for documentation.

GET /hooks/update/ (string: project) /
string: *component/* Deprecated since version 2.6: Please use [POST /api/components/\(string:project\)/\(string:component\)/repository/](#) instead which works properly with authentication for ACL limited projects.

Triggers update of a component (pulling from VCS and scanning for translation changes).

GET /hooks/update/ (string: project) /
 Deprecated since version 2.6: Please use [POST /api/projects/\(string:project\)/repository/](#) instead which works properly with authentication for ACL limited projects.

Triggers update of all components in a project (pulling from VCS and scanning for translation changes).

POST /hooks/github/
 Special hook for handling GitHub notifications and automatically updating matching components.

Note: GitHub includes direct support for notifying Weblate, just enable Weblate service hook in repository settings and set URL to URL of your Weblate installation.

See also:

Automatically receiving changes from GitHub For instruction on setting up GitHub integration

<https://help.github.com/articles/creating-webhooks> Generic information about GitHub Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST `/hooks/gitlab/`

Special hook for handling GitLab notifications and automatically updating matching components.

See also:

Automatically receiving changes from GitLab For instruction on setting up GitLab integration

http://docs.gitlab.com/ce/web_hooks/web_hooks.html Generic information about GitLab Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST `/hooks/bitbucket/`

Special hook for handling Bitbucket notifications and automatically updating matching components.

See also:

Automatically receiving changes from Bitbucket For instruction on setting up Bitbucket integration

<https://confluence.atlassian.com/bitbucket/manage-webhooks-735643732.html> Generic information about Bitbucket Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

8.3 Exports

Weblate provides various exports to allow you further process the data.

GET `/exports/stats/ (string: project) /`
`string: component/`

Query Parameters

- **jsonp** (*string*) – JSONP callback function to wrap the data

Deprecated since version 2.6: Please use `GET /api/components/(string:project)/(string:component)/stats` and `GET /api/translations/(string:project)/(string:component)/(string:language)/statistics` instead, it allows to access ACL controlled projects as well.

Retrieves statistics for given component in JSON format. Optionally as JSONP when you specify the callback in the `jsonp` parameter.

Example request:

```
GET /exports/stats/weblate/master/ HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
```


Example response:

```

HTTP/1.1 200 OK
Vary: Accept
Content-Type: application/json

[
  {
    "code": "cs",
    "failing": 0,
    "failing_percent": 0.0,
    "fuzzy": 0,
    "fuzzy_percent": 0.0,
    "last_author": "Michal \u010ciha\u0159",
    "last_change": "2012-03-28T15:07:38+00:00",
    "name": "Czech",
    "total": 436,
    "total_words": 15271,
    "translated": 436,
    "translated_percent": 100.0,
    "translated_words": 3201,
    "url": "http://hosted.weblate.org/engage/weblate/cs/",
    "url_translate": "http://hosted.weblate.org/projects/weblate/master/cs/"
  },
  {
    "code": "nl",
    "failing": 21,
    "failing_percent": 4.8,
    "fuzzy": 11,
    "fuzzy_percent": 2.5,
    "last_author": null,
    "last_change": null,
    "name": "Dutch",
    "total": 436,
    "total_words": 15271,
    "translated": 319,
    "translated_percent": 73.2,
    "translated_words": 3201,
    "url": "http://hosted.weblate.org/engage/weblate/nl/",
    "url_translate": "http://hosted.weblate.org/projects/weblate/master/nl/"
  },
  {
    "code": "el",
    "failing": 11,
    "failing_percent": 2.5,
    "fuzzy": 21,
    "fuzzy_percent": 4.8,
    "last_author": null,
    "last_change": null,
    "name": "Greek",
    "total": 436,
    "total_words": 15271,
    "translated": 312,
    "translated_percent": 71.6,
    "translated_words": 3201,
    "url": "http://hosted.weblate.org/engage/weblate/el/",
    "url_translate": "http://hosted.weblate.org/projects/weblate/master/el/"
  }
]

```

8.4 RSS feeds

Changes in translations are exported in RSS feeds.

GET `/exports/rss/ (string: project) / string: component/ string: language/` Retrieves RSS feed with recent changes for a translation.

GET `/exports/rss/ (string: project) / string: component/` Retrieves RSS feed with recent changes for a component.

GET `/exports/rss/ (string: project) /` Retrieves RSS feed with recent changes for a project.

GET `/exports/rss/language/ (string: language) /` Retrieves RSS feed with recent changes for a language.

GET `/exports/rss/` Retrieves RSS feed with recent changes for Weblate instance.

See also:

[RSS on wikipedia](#)

Weblate Client

New in version 2.7: The `wlc` utility is fully supported since Weblate 2.7. If you are using older version some incompatibilities with API might occur.

9.1 Instalation

The Weblate Client is shipped separately, you need to install `wlc` to have it, it also includes Python module `wlc`:

```
pip3 install wlc
```

9.2 Synopsis

```
wlc [parameter] <command> [options]
```

Commands actually indicate which operation should be performed.

9.3 Description

Weblate Client is Python library and command line utility to manage Weblate remotely using *Weblate's Web API*. The command line utility can be invoked as `wlc` and is build on `wlc`.

9.3.1 Global options

The program accepts following global options, which must be entered before subcommand.

--format {csv,json,text,html}
Specify output format.

--url URL
Specify API URL. Overrides value from configuration file, see *Files*. The URL should end with `/api/`, for example `https://hosted.weblate.org/api/`.

--key KEY
Specify API user key to use. Overrides value from configuration file, see *Files*. You can figure out your key in your profile in Weblate.

--config PATH
Override path to configuration file, see *Files*.

--config-section SECTION
Override section to use in configuration file, see *Files*.

9.3.2 Subcommands

Currently following subcommands are available:

version
Prints current version.

list-languages
List used languages in Weblate.

list-projects
List projects in Weblate.

list-components
List components in Weblate.

list-translations
List translations in Weblate.

show
Shows Weblate object (translation, component or project).

ls
Lists Weblate object (translation, component or project).

commit
Commits changes in Weblate object (translation, component or project).

pull
Pulls remote repository changes into Weblate object (translation, component or project).

push
Pushes changes in Weblate object into remote repository (translation, component or project).

repo
Displays repository status for given Weblate object (translation, component or project).

statistics
Displays detailed statistics for given Weblate object (translation or component).

lock-status
New in version 0.5: Supported since wlc 0.5.
Displays lock status.

lock
New in version 0.5: Supported since wlc 0.5.
Locks component from translating in Weblate.

unlock
New in version 0.5: Supported since wlc 0.5.
Unlocks component from translating in Weblate.

9.4 Files

.weblate Per project configuration file

~/.config/weblate User configuration file

/etc/xdg/weblate Global configuration file

The program follows XDG specification, so you can adjust placement of config files by environment variables `XDG_CONFIG_HOME` or `XDG_CONFIG_DIRS`.

Following settings can be configured in the `[weblate]` section (you can customize this by `--config-section`):

key

API KEY to access Weblate.

url

API server URL, defaults to `http://127.0.0.1:8000/api/`.

translation

Path of default translation, component or project.

The configuration file is INI file, for example:

```
[weblate]
url = https://hosted.weblate.org/api/
key = APIKEY
translation = weblate/master
```

Additionally API keys can be stored in the `[keys]` section:

```
[keys]
https://hosted.weblate.org/api/ = APIKEY
```

This allows you to store keys in your personal settings, while having `.weblate` configuration in the VCS repository so that `wlc` knows to which server it should talk.

9.5 Examples

Print current program version:

```
$ wlc version
version: 0.1
```

List all projects:

```
$ wlc list-projects
name: Hello
slug: hello
source_language: en
url: http://example.com/api/projects/hello/
web: http://weblate.org/
web_url: http://example.com/projects/hello/
```

You can also let `wlc` know current project and it will then operate on it:

```
$ cat .weblate
[weblate]
url = https://hosted.weblate.org/api/
```

```
translation = weblate/master

$ wlc show
branch: master
file_format: po
filemask: weblate/locale/*/LC_MESSAGES/django.po
git_export: git://git.weblate.org/weblate.git
license: GPL-3.0+
license_url: https://spdx.org/licenses/GPL-3.0+
name: master
new_base: weblate/locale/django.pot
project: weblate
repo: git://github.com/nijel/weblate.git
slug: master
template:
url: https://hosted.weblate.org/api/components/weblate/master/
vcs: git
web_url: https://hosted.weblate.org/projects/weblate/master/
```

With such setup it is easy to commit pending changes in current project:

```
$ wlc commit
```

Weblate's Python API

10.1 Instalation

The Python API is shipped separately, you need to install `wlc` to have it, it also include *Weblate Client*:

```
pip install wlc
```

10.2 wlc

10.2.1 WeblateException

exception `wlc.WeblateException`
Base class for all exceptions.

10.2.2 Weblate

Weblate(`key='', url=None, config=None`):

Parameters

- **key** (*string*) – User key
- **url** (*string*) – API server URL, if not specified default is used
- **config** (*WeblateConfig*) – Configuration object, overrides any other parameters.

Access class to the API, define API key and optionally API URL.

`wlc.get` (*path*)

Parameters **path** (*string*) – Request path

Return type object

Performs single API GET call.

`wlc.post` (*path, **kwargs*)

Parameters **path** (*string*) – Request path

Return type object

Performs single API GET call.

10.3 `wlc.config`

10.3.1 `WeblateConfig`

`class wlc.config.WeblateConfig(section='wlc')`

Parameters `section` (*string*) – Configuration section to use
Configuration file parser following XDG specification.

`load(path=None)`

Parameters `path` (*string*) – Path where to load configuration.

Loads configuration from a file, if none is specified it loads from `wlc` configuration file placed in XDG configuration path (`~/.config/wlc` and `/etc/xdg/wlc`).

10.4 `wlc.main`

`wlc.main.main(settings=None, stdout=None, args=None)`

Parameters

- **settings** (*list of tuples*) – settings to override
- **stdout** (*file*) – stdout for printing output, uses `sys.stdout` as default
- **args** (*list*) – command line arguments to process, uses `sys.args` as default

Main entry point for command line interface.

`@wlc.main.register_command(command)`

Decorator to register *Command* class in main parser used by `main()`.

10.4.1 `Command`

`class wlc.main.Command(args, config, stdout=None)`

Main class for invoking commands.

11.1 weblate 2.8

Released on Aug 31st 2016.

- Documentation improvements.
- Translations.
- Updated bundled javascript libraries.
- Added list_translators management command.
- Django 1.8 is no longer supported.
- Fixed compatibility with Django 1.10.
- Added Subversion support.
- Separated XML validity check from XML mismatched tags.
- Fixed API to honor HIDE_REPO_CREDENTIALS settings.
- Show source change in zen mode.
- Alt+PageUp/PageDown/Home/End now works in zen mode as well.
- Add tooltip showing exact time of changes.
- Add option to select filters and search from translation page.
- Added UI for translation removal.
- Improved behavior when inserting placeables.
- Fixed auto locking issues in zen mode.

11.2 weblate 2.7

Released on Jul 10th 2016.

- Removed Google web translate machine translation.
- Improved commit message when adding translation.
- Fixed Google Translate API for Hebrew language.
- Compatibility with Mercurial 3.8.

- Added import_json management command.
- Correct ordering of listed translations.
- Show full suggestion text, not only a diff.
- Extend API (detailed repository status, statistics, ...).
- Testsuite no longer requires network access to test repositories.

11.3 weblate 2.6

Released on Apr 28th 2016.

- Fixed validation of subprojects with language filter.
- Improved support for XLIFF files.
- Fixed machine translation for non English sources.
- Added REST API.
- Django 1.10 compatibility.
- Added categories to whiteboard messages.

11.4 weblate 2.5

Released on Mar 10th 2016.

- Fixed automatic translation for project owners.
- Improved performance of commit and push operations.
- New management command to add suggestions from command line.
- Added support for merging comments on file upload.
- Added support for some GNU extensions to C printf format.
- Documentation improvements.
- Added support for generating translator credits.
- Added support for generating contributor stats.
- Site wide search can search only in one language.
- Improve quality checks for Armenian.
- Support for starting translation components without existing translations.
- Support for adding new translations in Qt TS.
- Improved support for translating PHP files.
- Performance improvements for quality checks.
- Fixed sitewide search for failing checks.
- Added option to specify source language.
- Improved support for XLIFF files.
- Extended list of options for import_project.

- Improved targeting for whiteboard messages.
- Support for automatic translation across projects.
- Optimized fulltext search index.
- Added management command for auto translation.
- Added placeables highlighting.
- Added keyboard shortcuts for placeables, checks and machine translations.
- Improved translation locking.
- Added quality check for AngularJS interpolation.
- Added extensive group based ACLs.
- Clarified terminology on strings needing review (formerly fuzzy).
- Clarified terminology on strings needing action and not translated strings.
- Support for Python 3.
- Dropped support for Django 1.7.
- Dropped dependency on msginit for creating new Gettext po files.
- Added configurable dashboard views.
- Improved notifications on parse errors.
- Added option to import components with duplicate name to import_project.
- Improved support for translating PHP files
- Added XLIFF export for dictionary.
- Added XLIFF and Gettext PO export for all translations.
- Documentation improvements.
- Added support for configurable automatic group assignments.
- Improved adding of new translations.

11.5 weblate 2.4

Released on Sep 20th 2015.

- Improved support for PHP files.
- Ability to add ACL to anonymous user.
- Improved configurability of import_project command.
- Added CSV dump of history.
- Avoid copy/paste errors with whitespace chars.
- Added support for Bitbucket webhooks.
- Tigher control on fuzzy strings on translation upload.
- Several URLs have changed, you might have to update your bookmarks.
- Hook scripts are executed with VCS root as current directory.

- Hook scripts are executed with environment variables describing current component.
- Add management command to optimize fulltext index.
- Added support for error reporting to Rollbar.
- Projects now can have multiple owners.
- Project owners can manage themselves.
- Added support for javascript-format used in Gettext PO.
- Support for adding new translations in XLIFF.
- Improved file format autodetection.
- Extended keyboard shortcuts.
- Improved dictionary matching for several languages.
- Improved layout of most of pages.
- Support for adding words to dictionary while translating.
- Added support for filtering languages to be managed by Weblate.
- Added support for translating and importing CSV files.
- Rewritten handling of static files.
- Direct login/registration links to third party service if that's the only one.
- Commit pending changes on account removal.
- Add management command to change site name.
- Add option to configure default committer.
- Add hook after adding new translation.
- Add option to specify multiple files to add to commit.

11.6 weblate 2.3

Released on May 22nd 2015.

- Dropped support for Django 1.6 and South migrations.
- Support for adding new translations when using Java Property files
- Allow to accept suggestion without editing.
- Improved support for Google OAuth2.
- Added support for Microsoft .resx files.
- Tuned default robots.txt to disallow big crawling of translations.
- Simplified workflow for accepting suggestions.
- Added project owners who always receive important notifications.
- Allow to disable editing of monolingual template.
- More detailed repository status view.
- Direct link for editing template when changing translation.

- Allow to add more permissions to project owners.
- Allow to show secondary language in zen mode.
- Support for hiding source string in favor of secondary language.

11.7 weblate 2.2

Released on Feb 19th 2015.

- Performance improvements.
- Fulltext search on location and comments fields.
- New SVG/javascript based activity charts.
- Support for Django 1.8.
- Support for deleting comments.
- Added own SVG badge.
- Added support for Google Analytics.
- Improved handling of translation file names.
- Added support for monolingual JSON translations.
- Record component locking in a history.
- Support for editing source (template) language for monolingual translations.
- Added basic support for Gerrit.

11.8 weblate 2.1

Released on Dec 5th 2014.

- Added support for Mercurial repositories.
- Replaced Glyphicon font by Awesome.
- Added icons for social authentication services.
- Better consistency of button colors and icons.
- Documentation improvements.
- Various bugfixes.
- Automatic hiding of columns in translation listing for small screens.
- Changed configuration of filesystem paths.
- Improved SSH keys handling and storage.
- Improved repository locking.
- Customizable quality checks per source string.
- Allow to hide completed translations from dashboard.

11.9 weblate 2.0

Released on Nov 6th 2014.

- New responsive UI using Bootstrap.
- Rewritten VCS backend.
- Documentation improvements.
- Added whiteboard for site wide messages.
- Configurable strings priority.
- Added support for JSON file format.
- Fixed generating mo files in certain cases.
- Added support for GitLab notifications.
- Added support for disabling translation suggestions.
- Django 1.7 support.
- ACL projects now have user management.
- Extended search possibilities.
- Give more hints to translators about plurals.
- Fixed Git repository locking.
- Compatibility with older Git versions.
- Improved ACL support.
- Added buttons for per language quotes and other special chars.
- Support for exporting stats as JSONP.

11.10 weblate 1.9

Released on May 6th 2014.

- Django 1.6 compatibility.
- No longer maintained compatibility with Django 1.4.
- Management commands for locking/unlocking translations.
- Improved support for Qt TS files.
- Users can now delete their account.
- Avatars can be disabled.
- Merged first and last name attributes.
- Avatars are now fetched and cached server side.
- Added support for shields.io badge.

11.11 weblate 1.8

Released on November 7th 2013.

- Please check manual for upgrade instructions.
- Nicer listing of project summary.
- Better visible options for sharing.
- More control over anonymous users privileges.
- Supports login using third party services, check manual for more details.
- Users can login by email instead of username.
- Documentation improvements.
- Improved source strings review.
- Searching across all units.
- Better tracking of source strings.
- Captcha protection for registration.

11.12 weblate 1.7

Released on October 7th 2013.

- Please check manual for upgrade instructions.
- Support for checking Python brace format string.
- Per component customization of quality checks.
- Detailed per translation stats.
- Changed way of linking suggestions, checks and comments to units.
- Users can now add text to commit message.
- Support for subscribing on new language requests.
- Support for adding new translations.
- Widgets and charts are now rendered using Pillow instead of Pango + Cairo.
- Add status badge widget.
- Dropped invalid text direction check.
- Changes in dictionary are now logged in history.
- Performance improvements for translating view.

11.13 weblate 1.6

Released on July 25th 2013.

- Nicer error handling on registration.
- Browsing of changes.

- Fixed sorting of machine translation suggestions.
- Improved support for MyMemory machine translation.
- Added support for Amagama machine translation.
- Various optimizations on frequently used pages.
- Highlights searched phrase in search results.
- Support for automatic fixups while saving the message.
- Tracking of translation history and option to revert it.
- Added support for Google Translate API.
- Added support for managing SSH host keys.
- Various form validation improvements.
- Various quality checks improvements.
- Performance improvements for import.
- Added support for voting on suggestions.
- Cleanup of admin interface.

11.14 weblate 1.5

Released on April 16th 2013.

- Please check manual for upgrade instructions.
- Added public user pages.
- Better naming of plural forms.
- Added support for TBX export of glossary.
- Added support for Bitbucket notifications.
- Activity charts are now available for each translation, language or user.
- Extended options of import_project admin command.
- Compatible with Django 1.5.
- Avatars are now shown using libravatar.
- Added possibility to pretty print JSON export.
- Various performance improvements.
- Indicate failing checks or fuzzy strings in progress bars for projects or languages as well.
- Added support for custom pre-commit hooks and committing additional files.
- Rewritten search for better performance and user experience.
- New interface for machine translations.
- Added support for monolingual po files.
- Extend amount of cached metadata to improve speed of various searches.
- Now shows word counts as well.

11.15 weblate 1.4

Released on January 23rd 2013.

- Fixed deleting of checks/comments on unit deletion.
- Added option to disable automatic propagation of translations.
- Added option to subscribe for merge failures.
- Correctly import on projects which needs custom ttkit loader.
- Added sitemaps to allow easier access by crawlers.
- Provide direct links to string in notification emails or feeds.
- Various improvements to admin interface.
- Provide hints for production setup in admin interface.
- Added per language widgets and engage page.
- Improved translation locking handling.
- Show code snippets for widgets in more variants.
- Indicate failing checks or fuzzy strings in progress bars.
- More options for formatting commit message.
- Fixed error handling with machine translation services.
- Improved automatic translation locking behaviour.
- Support for showing changes from previous source string.
- Added support for substring search.
- Various quality checks improvements.
- Support for per project ACL.
- Basic unit tests coverage.

11.16 weblate 1.3

Released on November 16th 2012.

- Compatibility with PostgreSQL database backend.
- Removes languages removed in upstream git repository.
- Improved quality checks processing.
- Added new checks (BB code, XML markup and newlines).
- Support for optional rebasing instead of merge.
- Possibility to relocate Weblate (eg. to run it under /weblate path).
- Support for manually choosing file type in case autodetection fails.
- Better support for Android resources.
- Support for generating SSH key from web interface.
- More visible data exports.

- New buttons to enter some special characters.
- Support for exporting dictionary.
- Support for locking down whole Weblate installation.
- Checks for source strings and support for source strings review.
- Support for user comments for both translations and source strings.
- Better changes log tracking.
- Changes can now be monitored using RSS.
- Improved support for RTL languages.

11.17 weblate 1.2

Released on August 14th 2012.

- Weblate now uses South for database migration, please check upgrade instructions if you are upgrading.
- Fixed minor issues with linked git repos.
- New introduction page for engaging people with translating using Weblate.
- Added widgets which can be used for promoting translation projects.
- Added option to reset repository to origin (for privileged users).
- Project or component can now be locked for translations.
- Possibility to disable some translations.
- Configurable options for adding new translations.
- Configuration of git commits per project.
- Simple antispam protection.
- Better layout of main page.
- Support for automatically pushing changes on every commit.
- Support for email notifications of translators.
- List only used languages in preferences.
- Improved handling of not known languages when importing project.
- Support for locking translation by translator.
- Optionally maintain Language-Team header in po file.
- Include some statistics in about page.
- Supports (and requires) django-registration 0.8.
- Caching of counted units with failing checks.
- Checking of requirements during setup.
- Documentation improvements.

11.18 weblate 1.1

Released on July 4th 2012.

- Improved several translations.
- Better validation while creating component.
- Added support for shared git repositories across components.
- Do not necessary commit on every attempt to pull remote repo.
- Added support for offloading indexing.

11.19 weblate 1.0

Released on May 10th 2012.

- Improved validation while adding/saving component.
- Experimental support for Android component files (needs patched tkit).
- Updates from hooks are run in background.
- Improved installation instructions.
- Improved navigation in dictionary.

11.20 weblate 0.9

Released on April 18th 2012.

- Fixed import of unknown languages.
- Improved listing of nearby messages.
- Improved several checks.
- Documentation updates.
- Added definition for several more languages.
- Various code cleanups.
- Documentation improvements.
- Changed file layout.
- Update helper scripts to Django 1.4.
- Improved navigation while translating.
- Better handling of po file renames.
- Better validation while creating component.
- Integrated full setup into syncdb.
- Added list of recent changes to all translation pages.
- Check for not translated strings ignores format string only messages.

11.21 weblate 0.8

Released on April 3rd 2012.

- Replaced own full text search with Whoosh.
- Various fixes and improvements to checks.
- New command updatechecks.
- Lot of translation updates.
- Added dictionary for storing most frequently used terms.
- Added /admin/report/ for overview of repositories status.
- Machine translation services no longer block page loading.
- Management interface now contains also useful actions to update data.
- Records log of changes made by users.
- Ability to postpone commit to Git to generate less commits from single user.
- Possibility to browse failing checks.
- Automatic translation using already translated strings.
- New about page showing used versions.
- Django 1.4 compatibility.
- Ability to push changes to remote repo from web interface.
- Added review of translations done by others.

11.22 weblate 0.7

Released on February 16th 2012.

- Direct support for GitHub notifications.
- Added support for cleaning up orphaned checks and translations.
- Displays nearby strings while translating.
- Displays similar strings while translating.
- Improved searching for string.

11.23 weblate 0.6

Released on February 14th 2012.

- Added various checks for translated messages.
- Tunable access control.
- Improved handling of translations with new lines.
- Added client side sorting of tables.
- Please check upgrading instructions in case you are upgrading.

11.24 weblate 0.5

Released on February 12th 2012.

- **Support for machine translation using following online services:**
 - Apertium
 - Microsoft Translator
 - MyMemory
- Several new translations.
- Improved merging of upstream changes.
- Better handle concurrent git pull and translation.
- Propagating works for fuzzy changes as well.
- Propagating works also for file upload.
- Fixed file downloads while using FastCGI (and possibly others).

11.25 weblate 0.4

Released on February 8th 2012.

- Added usage guide to documentation.
- Fixed API hooks not to require CSRF protection.

11.26 weblate 0.3

Released on February 8th 2012.

- Better display of source for plural translations.
- New documentation in Sphinx format.
- Displays secondary languages while translating.
- Improved error page to give list of existing projects.
- New per language stats.

11.27 weblate 0.2

Released on February 7th 2012.

- Improved validation of several forms.
- Warn users on profile upgrade.
- Remember URL for login.
- Naming of text areas while entering plural forms.
- Automatic expanding of translation area.

11.28 weblate 0.1

Released on February 6th 2012.

- Initial release.

Contributing

There are dozens of ways to contribute to Weblate. We welcome any help, be it coding help, graphics design, documentation or sponsorship.

12.1 Code and development

Weblate is being developed on GitHub <<https://github.com/nijel/weblate>>. You are welcome to fork the code and open pull requests. Patches in any other form are welcome as well. The code should follow PEP-8 coding guidelines.

We do write testsuite for our code, so please add testcases for any new functionality and verify that it works. You can see current test results on Travis <<https://travis-ci.org/nijel/weblate>> and coverage on Codecov <<https://codecov.io/github/nijel/weblate>>.

The issue tracker is hosted on GitHub as well: <<https://github.com/nijel/weblate/issues>>

12.2 Starting with our codebase

If you are looking for some bugs which should be good for starting with our codebase, you can find them labelled with *newbie* tag:

<https://github.com/nijel/weblate/labels/newbie>

12.3 Earning money by coding

We're using Bountysource to fund our development, you can participate on this as well by implementing issues with bounties:

<https://github.com/nijel/weblate/labels/bounty>

12.4 Translating

Weblate is being translated using Weblate on <<https://hosted.weblate.org/>>, feel free to join us in effort to make Weblate available in as many world languages as possible.

12.5 Funding Weblate development

You can fund further Weblate development on [Bountysource](#). Funds collected there are used to fund free hosting for free software projects and further development of Weblate. Please check the [Bountysource](#) page for details such as funding goals and rewards you can get for funding.

12.5.1 Backers who have funded Weblate

List of Weblate supporters from [Bountysource](#):

- Yashiro Ccs
- Cheng-Chia Tseng

License

Copyright (C) 2012 - 2016 Michal Čihař <michal@cihar.com>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

Indices and tables

- `genindex`
- `search`

/	POST /api/components/(string:project)/(string:component)/, 155
ANY /, 147	POST /api/projects/(string:project)/repository/, 152
/api	POST /api/translations/(string:project)/(string:component)/, 159
GET /api/, 149	POST /api/translations/(string:project)/(string:component)/, 160
GET /api/components/, 153	
GET /api/components/(string:project)/(string:component)/, 153	
GET /api/components/(string:project)/(string:component)/lock/, 154	/exports
GET /api/components/(string:project)/(string:component)/monolingual_base/, 156	GET /exports/rss/, 164
GET /api/components/(string:project)/(string:component)/new_template/, 156	GET /exports/rss/(string:project)/, 164
GET /api/components/(string:project)/(string:component)/repository/, 155	GET /exports/rss/(string:project)/(string:component)/, 164
GET /api/components/(string:project)/(string:component)/statistics/, 156	GET /exports/rss/language/(string:language)/, 164
GET /api/components/(string:project)/(string:component)/translations/, 156	GET /exports/stats/(string:project)/(string:component)/, 162
GET /api/languages/, 150	/hooks
GET /api/languages/(string:language)/, 150	GET /hooks/update/(string:project)/, 161
GET /api/projects/, 150	GET /hooks/update/(string:project)/(string:component)/, 161
GET /api/projects/(string:project)/, 150	POST /hooks/bitbucket/, 162
GET /api/projects/(string:project)/components/, 152	POST /hooks/github/, 161
GET /api/projects/(string:project)/repository/, 151	POST /hooks/gitlab/, 162
GET /api/translations/, 157	
GET /api/translations/(string:project)/(string:component)/(string:language)/, 157	
GET /api/translations/(string:project)/(string:component)/(string:language)/file/, 159	
GET /api/translations/(string:project)/(string:component)/(string:language)/repository/, 160	
GET /api/translations/(string:project)/(string:component)/(string:language)/statistics/, 160	
POST /api/components/(string:project)/(string:component)/lock/, 155	

W

wlc, [169](#)
wlc.config, [170](#)
wlc.main, [170](#)

Symbols

`-config PATH`
wlc command line option, 165

`-config-section SECTION`
wlc command line option, 166

`-format {csv,json,text,html}`
wlc command line option, 165

`-key KEY`
wlc command line option, 165

`-url URL`
wlc command line option, 165

`.Net Resource`
file format, 141

A

`add_sugessstions`
django-admin command, 117

`Android`
file format, 139

`ANONYMOUS_USER_NAME`
setting, 97

`API`, 147, 164, 168

`Apple strings`
file format, 140

`AUTO_LOCK`
setting, 97

`AUTO_LOCK_TIME`
setting, 97

`auto_translate`
django-admin command, 118

`AUTOFIX_LIST`
setting, 97

B

`BACKGROUND_HOOKS`
setting, 98

`bilingual`
translation, 137

C

`changesite`

django-admin command, 118

`CHECK_LIST`
setting, 98

`checkgit`
django-admin command, 118

`cleanuptrans`
django-admin command, 119

`Comma separated values`
file format, 141

`Command (class in wlc.main)`, 170

`commit`
wlc command line option, 166

`commit_pending`
django-admin command, 119

`commitgit`
django-admin command, 118

`createadmin`
django-admin command, 119

`CSV`
file format, 141

D

`DATA_DIR`
setting, 99

`DEFAULT_COMMITER_EMAIL`
setting, 99

`DEFAULT_COMMITER_NAME`
setting, 99

`DEFAULT_TRANSLATION_PROPAGATION`
setting, 99

`django-admin command`
add_sugessstions, 117
auto_translate, 118
changesite, 118
checkgit, 118
cleanuptrans, 119
commit_pending, 119
commitgit, 118
createadmin, 119
dumpuserdata, 119
import_json, 119

- import_project, 120
- importuserdata, 121
- importusers, 121
- list_ignored_checks, 122
- list_translators, 122
- list_versions, 122
- loadpo, 122
- lock_translation, 122
- pushgit, 123
- rebuild_index, 123
- setupgroups, 124
- setuplang, 124
- unlock_translation, 123
- update_index, 123
- updatechecks, 124
- updategit, 124
- DJANGO_SETTINGS, 42
- dumpuserdata
 - django-admin command, 119

E

- ENABLE_AVATARS
 - setting, 99
- ENABLE_HOOKS
 - setting, 100
- ENABLE_HTTPS
 - setting, 100
- ENABLE_SHARING
 - setting, 100
- environment variable
 - DJANGO_SETTINGS, 42
 - WL_FILE_FORMAT, 88
 - WL_FILEMASK, 88
 - WL_LANGUAGE, 88
 - WL_PATH, 88
 - WL_REPO, 88
 - WL_TEMPLATE, 88
 - WL_VCS, 88

F

- file format
 - .Net Resource, 141
 - Android, 139
 - Apple strings, 140
 - Comma separated values, 141
 - CSV, 141
 - Gettext, 137
 - Java properties, 139
 - JSON, 141
 - PHP strings, 140
 - PO, 137
 - Qt, 139
 - RESX, 141
 - string resources, 139

- TS, 139
- XLIFF, 138

G

- get() (in module wlc), 169
- Gettext
 - file format, 137
- GIT_ROOT
 - setting, 100
- GITHUB_USERNAME
 - setting, 100
- GOOGLE_ANALYTICS_ID
 - setting, 100

H

- HIDE_REPO_CREDENTIALS
 - setting, 100

I

- import_json
 - django-admin command, 119
- import_project
 - django-admin command, 120
- importuserdata
 - django-admin command, 121
- importusers
 - django-admin command, 121
- iPad
 - translation, 140
- iPhone
 - translation, 140

J

- Java properties
 - file format, 139
- JSON
 - file format, 141

L

- LAZY_COMMITS
 - setting, 101
- list-components
 - wlc command line option, 166
- list-languages
 - wlc command line option, 166
- list-projects
 - wlc command line option, 166
- list-translations
 - wlc command line option, 166
- list_ignored_checks
 - django-admin command, 122
- list_translators
 - django-admin command, 122
- list_versions

- django-admin command, 122
- load() (wlc.config.WeblateConfig method), 170
- loadpo
 - django-admin command, 122
- lock
 - wlc command line option, 166
- lock-status
 - wlc command line option, 166
- LOCK_TIME
 - setting, 101
- lock_translation
 - django-admin command, 122
- LOGIN_REQUIRED_URLS
 - setting, 101
- LOGIN_REQUIRED_URLS_EXCEPTIONS
 - setting, 101
- ls
 - wlc command line option, 166

M

- MACHINE_TRANSLATION_SERVICES
 - setting, 101
- main() (in module wlc.main), 170
- monolingual
 - translation, 137
- MT_APERTIUM_KEY
 - setting, 102
- MT_GOOGLE_KEY
 - setting, 102
- MT_MICROSOFT_ID
 - setting, 102
- MT_MICROSOFT_SECRET
 - setting, 102
- MT_MYMEMORY_EMAIL
 - setting, 102
- MT_MYMEMORY_KEY
 - setting, 103
- MT_MYMEMORY_USER
 - setting, 103
- MT_TMSERVER
 - setting, 103

N

- NEARBY_MESSAGES
 - setting, 103

O

- OFFLOAD_INDEXING
 - setting, 103

P

- PHP strings
 - file format, 140

- PIWIK_SITE_ID
 - setting, 103
- PIWIK_URL
 - setting, 103
- PO
 - file format, 137
- post() (in module wlc), 169
- POST_ADD_SCRIPTS
 - setting, 104
- POST_COMMIT_SCRIPTS
 - setting, 105
- POST_PUSH_SCRIPTS
 - setting, 105
- POST_UPDATE_SCRIPTS
 - setting, 104
- PRE_COMMIT_SCRIPTS
 - setting, 104
- pull
 - wlc command line option, 166
- push
 - wlc command line option, 166
- pushgit
 - django-admin command, 123
- Python, 168

Q

- Qt
 - file format, 139

R

- rebuild_index
 - django-admin command, 123
- register_command() (in module wlc.main), 170
- REGISTRATION_CAPTCHA
 - setting, 105
- REGISTRATION_OPEN
 - setting, 105
- repo
 - wlc command line option, 166
- REST, 147
- RESX
 - file format, 141

S

- SELF_ADVERTISEMENT
 - setting, 105
- setting
 - ANONYMOUS_USER_NAME, 97
 - AUTO_LOCK, 97
 - AUTO_LOCK_TIME, 97
 - AUTOFIX_LIST, 97
 - BACKGROUND_HOOKS, 98
 - CHECK_LIST, 98
 - DATA_DIR, 99

- DEFAULT_COMMITER_EMAIL, 99
- DEFAULT_COMMITER_NAME, 99
- DEFAULT_TRANSLATION_PROPAGATION, 99
- ENABLE_AVATARS, 99
- ENABLE_HOOKS, 100
- ENABLE_HTTPS, 100
- ENABLE_SHARING, 100
- GIT_ROOT, 100
- GITHUB_USERNAME, 100
- GOOGLE_ANALYTICS_ID, 100
- HIDE_REPO_CREDENTIALS, 100
- LAZY_COMMITS, 101
- LOCK_TIME, 101
- LOGIN_REQUIRED_URLS, 101
- LOGIN_REQUIRED_URLS_EXCEPTIONS, 101
- MACHINE_TRANSLATION_SERVICES, 101
- MT_APERTIUM_KEY, 102
- MT_GOOGLE_KEY, 102
- MT_MICROSOFT_ID, 102
- MT_MICROSOFT_SECRET, 102
- MT_MYMEMORY_EMAIL, 102
- MT_MYMEMORY_KEY, 103
- MT_MYMEMORY_USER, 103
- MT_TMSERVER, 103
- NEARBY_MESSAGES, 103
- OFFLOAD_INDEXING, 103
- PIWIK_SITE_ID, 103
- PIWIK_URL, 103
- POST_ADD_SCRIPTS, 104
- POST_COMMIT_SCRIPTS, 105
- POST_PUSH_SCRIPTS, 105
- POST_UPDATE_SCRIPTS, 104
- PRE_COMMIT_SCRIPTS, 104
- REGISTRATION_CAPTCHA, 105
- REGISTRATION_OPEN, 105
- SELF_ADVERTISEMENT, 105
- SIMPLIFY_LANGUAGES, 105
- SITE_TITLE, 105
- TTF_PATH, 106
- URL_PREFIX, 106
- WHOOSH_INDEX, 106
- setupgroups
 - django-admin command, 124
- setuplang
 - django-admin command, 124
- show
 - wlc command line option, 166
- SIMPLIFY_LANGUAGES
 - setting, 105
- SITE_TITLE
 - setting, 105
- statistics
 - wlc command line option, 166
- string resources

- file format, 139

T

- translation
 - bilingual, 137
 - iPad, 140
 - iPhone, 140
 - monolingual, 137

TS

- file format, 139

TTF_PATH

- setting, 106

U

- unlock
 - wlc command line option, 166
- unlock_translation
 - django-admin command, 123
- update_index
 - django-admin command, 123
- updatechecks
 - django-admin command, 124
- updategit
 - django-admin command, 124
- URL_PREFIX
 - setting, 106

V

- version
 - wlc command line option, 166

W

- WeblateConfig (class in wlc.config), 170
- WeblateException, 169
- WHOOSH_INDEX
 - setting, 106
- wlc, 164
- wlc (module), 169
- wlc command line option
 - config PATH, 165
 - config-section SECTION, 166
 - format {csv,json,text,html}, 165
 - key KEY, 165
 - url URL, 165
- commit, 166
- list-components, 166
- list-languages, 166
- list-projects, 166
- list-translations, 166
- lock, 166
- lock-status, 166
- ls, 166
- pull, 166
- push, 166

- repo, [166](#)
- show, [166](#)
- statistics, [166](#)
- unlock, [166](#)
- version, [166](#)
- wlc.config (module), [170](#)
- wlc.main (module), [170](#)

X

- XLIFF
 - file format, [138](#)