



The Weblate Manual

Hedhje Në Qarkullim 4.8

Michal Čihař

21 gush, 2021

1	Dokumentime përdoruesi	1
1.1	Gjëra elementare Weblate	1
1.2	Regjistrim dhe profil përdoruesi	1
1.3	Përkthim duke përdorur Weblate-in	10
1.4	Shkarkim dhe ngarkim përkthimesh	19
1.5	Fjalorth	23
1.6	Checks and fixups	25
1.7	Kërkim	46
1.8	Rrjedha pune përkthimi	52
1.9	Pyetje të Bëra Rëndon	55
1.10	Formate të mbuluar kartelash	62
1.11	Integrim kontrolli versioni	83
1.12	Weblate's REST API	90
1.13	Klient Weblate	134
1.14	API Python e Weblate-it	138
2	Dokumentime përgjegjësi	141
2.1	Udhëzime formësimi	141
2.2	Sendërtime Weblate	200
2.3	Upgrading Weblate	201
2.4	Kopjeruajtje dhe zhvendosje e Weblate	208
2.5	Mirëfilltësim	214
2.6	Kontroll hyrjesh	224
2.7	Projekte përkthimi	234
2.8	Language definitions	250
2.9	Përkthim në vazhdimësi	253
2.10	Licencim përkthimesh	262
2.11	Procesi i përkthimit	264
2.12	Checks and fixups	270
2.13	Përkthim nga makina	278
2.14	Shtesa	285
2.15	Kujtesë Përkthimesh	300
2.16	Formësim	302
2.17	Sample configuration	331
2.18	Management commands	347
2.19	Lajmërimi	358
2.20	Lista Përbërësish	360
2.21	Optional Weblate modules	361
2.22	Përshtatje e Weblate-it	366
2.23	Ndërfaqe administrimi	368
2.24	Getting support for Weblate	376

2.25	Dokumente ligjore	379
3	Dokumentime kontribuesi	381
3.1	Dhënie ndihmese te Weblate	381
3.2	Starting contributing code to Weblate	383
3.3	Kod burim i Weblate-it	387
3.4	Diagnostikim Weblate-i	388
3.5	Gjërat e brendshme të Weblate-it	389
3.6	Developing addons	391
3.7	Pjesa e dukshme e Weblate-it	393
3.8	Njoftim problemesh në Weblate	394
3.9	Weblate testsuite and continuous integration	394
3.10	Skema të dhënash	396
3.11	Releasing Weblate	400
3.12	Security and privacy	401
3.13	Rreth Weblate-it	401
3.14	Licencë	402
4	Historik Ndryshimesh	403
4.1	Weblate 4.8	403
4.2	Weblate 4.7.2	403
4.3	Weblate 4.7.1	404
4.4	Weblate 4.7	404
4.5	Weblate 4.6.2	404
4.6	Weblate 4.6.1	405
4.7	Weblate 4.6	405
4.8	Weblate 4.5.3	406
4.9	Weblate 4.5.2	406
4.10	Weblate 4.5.1	406
4.11	Weblate 4.5	407
4.12	Weblate 4.4.2	408
4.13	Weblate 4.4.1	408
4.14	Weblate 4.4	408
4.15	Weblate 4.3.2	409
4.16	Weblate 4.3.1	409
4.17	Weblate 4.3	410
4.18	Weblate 4.2.2	411
4.19	Weblate 4.2.1	411
4.20	Weblate 4.2	411
4.21	Weblate 4.1.1	412
4.22	Weblate 4.1	412
4.23	Weblate 4.0.4	413
4.24	Weblate 4.0.3	414
4.25	Weblate 4.0.2	414
4.26	Weblate 4.0.1	414
4.27	Weblate 4.0	415
4.28	Weblate 3.x series	415
4.29	Weblate 2.x series	427
4.30	Seritë Weblate 1.x	438
4.31	Weblate 0.x series	442
	Tregues Modulesh Python	446
	HTTP Routing Table	447
	Tregues	450

1.1 Gjëra elementare Weblate

1.1.1 Project and component structure

In Weblate translations are organized into projects and components. Each project can contain number of components and those contain translations into individual languages. The component corresponds to one translatable file (for example *GNU gettext* or *Burime vargjesë Android*). The projects are there to help you organize component into logical sets (for example to group all translations used within one application).

Internally, each project has translations to common strings propagated across other components within it by default. This lightens the burden of repetitive and multi version translation. The translation propagation can be disabled per *Component configuration* using *Lejo përhapje përkthimesh* in case the translations should diverge.

Shihni edhe:

`../devel/integration`

1.2 Regjistrim dhe profil përdoruesi

1.2.1 Regjistrim

Everybody can browse projects, view translations or suggest translations by default. Only registered users are allowed to actually save changes, and are credited for every translation made.

You can register by following a few simple steps:

1. Plotësoni formularin e regjistrimit me të dhënat tuaja.
2. Activate registration by following the link in the e-mail you receive.
3. Optionally adjust your profile to choose which languages you know.


1.2.2 Pult

When you sign in, you will see an overview of projects and components, as well as their respective translation progression.

Të reja në versionin 2.5.

Components of projects you are watching are shown by default, and cross-referenced with your preferred languages.

Ndihmëz: You can switch to different views using the navigation tabs.



The screenshot shows the Weblate user interface. At the top is a dark navigation bar with the Weblate logo and links to Dashboard, Projects, Languages, and Checks. Below this is a user profile section with a 'Your profile' link. A row of tabs includes Languages, Preferences (which is active), Notifications, Account, Profile, Licenses, Audit log, and API access. The Preferences panel is open, showing various settings: 'Hide completed translations on the dashboard' (unchecked), 'Translation editor mode' (Full editor), 'Zen editor mode' (Top to bottom), 'Number of nearby strings' (15), 'Show secondary translations in the Zen mode' (checked), 'Hide source if a secondary translation exists' (unchecked), 'Editor link' (empty field), 'Special characters' (empty field), and 'Default dashboard view' (Watched translations selected). A 'Save' button is at the bottom of the panel.

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

Menuja ka këto mundësi:

- *Projects > Browse all projects* in the main menu showing translation status for each project on the Weblate instance.
- Selecting a language in the main menu *Languages* will show translation status of all projects, filtered by one of

your primary languages.

- *Watched translations* in the Dashboard will show translation status of only those projects you are watching, filtered by your primary languages.

In addition, the drop-down can also show any number of *component lists*, sets of project components preconfigured by the Weblate administrator, see [Lista Përbërësish](#).

You can configure your personal default dashboard view in the *Preferences* section of your user profile settings.

Shënim: When Weblate is configured for a single project using `SINGLE_PROJECT` in the `settings.py` file (see [Formësim](#)), the dashboard will not be shown, as the user will be redirected to a single project or component instead.

1.2.3 Profil përdoruesi

The user profile is accessible by clicking your user icon in the top-right of the top menu, then the *Settings* menu.

The user profile contains your preferences. Name and e-mail address is used in VCS commits, so keep this info accurate.

Shënim: All language selections only offer currently translated languages.

Ndihmëz: Request or add other languages you want to translate by clicking the button to make them available too.

Gjuhë

1.2.4 Interface language

Choose the language you want to display the UI in.

Gjuhë të përkthyer

Choose which languages you prefer to translate, and they will be offered on the main page of watched projects, so that you have easier access to these all translations in each of those languages.

[Dashboard](#)
[Projects](#)
[Languages](#)
[Checks](#)

Dashboard

[Watched translations](#) 13
 [Suggested translations](#) 5
 [Insights](#)
[Search](#)

Component	Translated	Untranslated	Untranslated words	Checks	Suggestions
WeblateOrg/Android — Czech MIT	76%	3	3		
WeblateOrg/Django — Hungarian GPL-3.0	69%	8	109	1	
WeblateOrg/Django — Czech GPL-3.0	96%	1	12	4	
WeblateOrg/Django — Hebrew GPL-3.0	92%	2	15		
WeblateOrg/Djangojs — Hungarian GPL-3.0	96%	2	6		
WeblateOrg/Djangojs — Hebrew GPL-3.0	✓				
WeblateOrg/Djangojs — Czech GPL-3.0	✓				
WeblateOrg/Language names — Czech GPL-3.0	✓				
WeblateOrg/Language names — Hungarian GPL-3.0	81%	4	5		
WeblateOrg/Language names — Hebrew GPL-3.0	✓				
WeblateOrg/WeblateOrg — Hungarian GPL-3.0	✓				
WeblateOrg/WeblateOrg — Czech GPL-3.0	✓				
WeblateOrg/WeblateOrg — Hebrew GPL-3.0	✓				

Powered by Weblate 4.8
 [About Weblate](#)
[Legal](#)
[Contact](#)
[Documentation](#)
[Donate to Weblate](#)

Gjuhë dytësore

You can define which secondary languages are shown to you as a guide while translating. An example can be seen in the following image, where the Hebrew language is shown as secondarily:

The screenshot shows the Weblate web interface. At the top, there's a navigation bar with 'Weblate', 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below it, a breadcrumb trail shows 'WeblateOrg / Django / Czech / Translate'. A status bar indicates 'translated 96%'. The main area shows a string list with 'Files' selected. The translation editor is open, showing the source string 'Files' and the target string 'Soubory'. The editor includes a 'Needs editing' checkbox and buttons for 'Save', 'Suggest', and 'Skip'. The sidebar on the right contains several panels: 'Glossary' (showing no related strings), 'String information' (with fields for Screenshot context, Explanation, Labels, and Flags), and a list of 'Nearby strings' (16 items). The 'Other languages' panel shows a list of languages: Hebrew, Hungarian, and English, with Hebrew selected as the secondary language.

1.2.5 Parapëlqime

Pamje parazgjedhje e pultit

On the *Preferences* tab, you can pick which of the available dashboard views to present by default. If you pick the *Component list*, you have to select which component list will be displayed from the *Default component list* drop-down.

Shihni edhe:

Lista Përbërësish

Lidhje përpunuesi

A source code link is shown in the web-browser configured in the *Component configuration* by default.

Ndihmëz: By setting the *Editor link*, you use your local editor to open the VCS source code file of translated strings. You can use *Template markup*.

Usually something like `editor://open/?file={{filename}}&line={{line}}` is a good option.

Shihni edhe:

You can find more info on registering custom URL protocols for the editor in the [Nette documentation](#).

1.2.6 Njoftime

Subscribe to various notifications from the *Notifications* tab. Notifications for selected events on watched or administered projects will be sent to you per e-mail.

Some of the notifications are sent only for events in your languages (for example about new strings to translate), while some trigger at component level (for example merge errors). These two groups of notifications are visually separated in the settings.

You can toggle notifications for watched projects and administered projects and it can be further tweaked (or muted) per project and component. Visit the component overview page and select appropriate choice from the *Watching* menu.

In case *Automatically watch projects on contribution* is enabled you will automatically start watching projects upon translating a string. The default value depends on `DEFAULT_AUTO_WATCH`.

Shënim: S'do të merrni njoftime për veprimet tuaja.

Web

late

Dashboard

Projects ▾

Languages ▾

Checks ▾

+

Your profile

Languages

Preferences

Notifications

Account

Profile

Licenses

Audit log

API access

Watched projects

☒ Automatically watch projects on contribution

Whenever you translate a string in a project, you will start watching it.

Watched projects

Search...

Available:

WeblateOrg

Chosen:

WeblateOrg

You can receive notifications for watched projects and they are shown on the dashboard by default.

Add all projects you want to translate to see them as watched projects on the dashboard.

Save

Notification settings

Other projects

Watched projects

Managed projects

Component wide notifications

You will receive a notification for every such event in your watched projects.

Repository failure

Do not notify

Repository operation

Do not notify

Component locking

Do not notify

Changed license

Do not notify

Parse error

Do not notify

Comment on own translation

Instant notification

Mentioned in comment

Instant notification

New language

Do not notify

New translation component

Do not notify

New announcement

Instant notification

New alert

Do not notify

Translation notifications

You will only receive these notifications for your translated languages in your watched projects.

New string

Do not notify

New contributor

Do not notify

New suggestion

Do not notify

New comment

Do not notify

Changed string

Do not notify

Translated string

Do not notify

Approved string

Do not notify

Pending suggestions

Do not notify

Strings needing action

Do not notify

Save

Powered by

Web

late 4.8

About Weblate

Legal

Contact

Documentation

Donate to Weblate

1.2.7 Llogari

The *Account* tab lets you set up basic account details, connect various services you can use to sign in into Weblate, completely remove your account, or download your user data (see *Eksportim të dhënash përdoruesi në Weblate*).

Shënim: The list of services depends on your Weblate configuration, but can be made to include popular sites such as GitLab, GitHub, Google, Facebook, or Bitbucket or other OAuth 2.0 providers.

Webplate

Dashboard

Projects ▾

Languages ▾

Checks ▾

+

▾

▾

...

Your profile

Languages

Preferences

Notifications

Account

Profile

Licenses

Audit log

API access

Account

Username

testuser

Username may only contain letters, numbers or the following characters: @ . + - _

Full name

Weblate Test

E-mail






weblate@example.org

You can add another e-mail address below.


Your name and e-mail will appear as commit authorship.

Save

Current user identities

Identity	User ID	Action
 Password	testuser	Change password
 E-mail	weblate@example.org	Disconnect
 Google	weblate@example.org	Disconnect
 GitHub	123456	Disconnect
 Bitbucket	weblate	Disconnect

Add new association

 E-mail

Removal

Account removal deletes all your private data.

Remove my account

User data

You can download all your private data.

Download user data

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

1.2.8 Profil

Krejt fushat në këtë faqe janë opsionale dhe mund të fshihen kur të doni, dhe duke i plotësuar, na jepni pranimin për t'i ndarë këto të dhëna me të tjerë kudo ku shfaqet profili juaj i përdoruesit.

Avatar can be shown for each user (depending on `ENABLE_AVATARS`). These images are obtained using <https://gravatar.com/>.

1.2.9 Licenca

1.2.10 Përdorim API

You can get or reset your API access token here.

1.2.11 Auditim regjistri

Audit log keeps track of the actions performed with your account. It logs IP address and browser for every important action with your account. The critical actions also trigger a notification to a primary e-mail address.

Shihni edhe:

Running behind reverse proxy

1.3 Përkthim duke përdorur Weblate-in

Thank you for interest in translating using Weblate. Projects can either be set up for direct translation, or by way of accepting suggestions made by users without accounts.

Përgjithësisht, ka dy mënyra përkthimi:

- Projekti pranon përkthime të drejtpërdrejta
- The project only accepts suggestions, which are automatically validated once a defined number of votes is reached

Please see *Rrjedha pune përkthimi* for more info on translation workflow.

Mundësi për dukshmëri projekti përkthimi:

- Publicly visible and anybody can contribute
- Visible only to a certain group of translators

Shihni edhe:

Kontroll hyrjesh, Rrjedha pune përkthimi

1.3.1 Projekte përkthimi

Translation projects hold related components; resources for the same software, book, or project.

WebplateOrg translated 85%

Components Languages Info Search Insights Files Tools Manage Share Not watching

Component	Translated	Untranslated	Untranslated words	Checks	Suggestions	Comments
Android	79%	30	30	3		
Language names	95%	4	5			
Glossary WeblateOrg	✓					

Add new translation component

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

1.3.2 Lidhje përkthimi

Having navigated to a component, a set of links lead to its actual translation. The translation is further divided into individual checks, like *Not translated strings* or *Strings needing action*. If the whole project is translated, without error, *All strings* is still available. Alternatively you can use the search field to find a specific string or term.

W

Weblate

Dashboard

Projects ▾

Languages ▾

Checks ▾

🔧

+

🌐

...

WebOrg / Django / Czech

translated 96%

Overview

Info

Search

Insights ▾

Files ▾

Tools ▾

Manage ▾

Share ▾

👁 Watching ▾

Translation status

26 Strings

96%

183 Words

93%

Browse

Translate

Strings status

26

All strings — 183 words

Browse

Edit

Zen

25

Translated strings — 171 words

Browse

Edit

Zen

1

Strings needing action — 12 words

Browse

Edit

Zen

1

Not translated strings — 12 words

Browse

Edit

Zen

1

Strings needing action without suggestions — 12 words

Browse

Edit

Zen

3

Strings with any failing checks — 11 words

Browse

Edit

Zen

3

Translated strings with any failing checks — 11 words

Browse

Edit

Zen

1

Failed check: Unchanged translation — 4 words

Browse

Edit

Zen

1

Failed check: Mismatched full stop — 4 words

Browse

Edit

Zen

1

Failed check: Python format — 3 words

Browse

Edit

Zen

Other components

Component	Translated	Untranslated	Untranslated words	Checks	Suggestions	Comments
<div><div>🔧</div><div>Android</div><div><div>MIT</div></div></div>	76%	3	3			
<div><div>🔧</div><div>Language names</div><div><div>GPL-3.0</div></div></div>	✓					
<div><div>🔧</div><div>Glossary</div><div><div>WebOrg</div><div><div>GPL-3.0</div></div></div></div>	✓					
<div><div>🔧</div><div>Djangojs</div><div><div>GPL-3.0</div></div></div>	✓					

Browse all components

Powered by Weblate 4.8

About Weblate

Legal

Contact

Documentation

Donate to Weblate

1.3.3 Sugjerime

Shënim: Actual permissions might vary depending on your Weblate configuration.

Anonymous users can only (by default) forward suggestions. Doing so is still available to signed-in users, in cases where uncertainty about the translation arises, prompting other translators to review it.

The suggestions are scanned on a daily basis to remove duplicates and suggestions matching the current translation.

12

Kapitulli 1. Dokumentime përdoruesi

1.3.4 Komente

Three types of comments can be posted: for translations, source strings, or to report source string bugs when this functionality is turned on using *Aktivizo shqyrtime burimi*. Choose the one suitable to topic you want to discuss. Source string comments are in any event good for providing feedback on the original string, for example that it should be rephrased or to ask questions about it.

You can use Markdown syntax in all comments and mention other users using `@mention`.

Shihni edhe:

report-source, *Shqyrtim vargresh burim*, *Aktivizo shqyrtime burimi*

1.3.5 Variante

Variants are used to group different length variants of the string. The frontend of your project can then use different strings depending on the screen or window size.

Shihni edhe:

variants, *Variante*

1.3.6 Etiketa

Labels are used to categorize strings within a project to further customize the localization workflow (for example to define categories of strings).

Shihni edhe:

labels

1.3.7 Translating

On the translation page, the source string and an editing area for its translation are shown. Should the translation be plural, multiple source strings and editing areas are shown, each described and labeled in the amount of plural forms the translated language has.

All special whitespace characters are underlined in red and indicated with grey symbols. More than one subsequent space is also underlined in red to alert the translator to a potential formatting issue.

Various bits of extra info can be shown on this page, most of which coming from the project source code (like context, comments or where the message is being used). Translation fields for any secondary languages translators select in the preferences will be shown (see *Gjuhë dytësore*) above the source string.

Below the translation, translators will find suggestion made by others, to be accepted (✓), accepted with changes (⇒), or deleted (🗑).

Shumësa

Words changing form to account of their numeric designation are called plurals. Each language has its own definition of plurals. English, for example, supports one. In the singular definition of for example «car», implicitly one car is referenced, in the plural definition, «cars» two or more cars are referenced (or the concept of cars as a noun). Languages like for example Czech or Arabic have more plurals and also their rules for plurals are different.

Weblate has full support for each of these forms, in each respective language (by translating every plural separately). The number of fields and how it is in turn used in the translated application or project depends on the configured plural formula. Weblate shows the basic info, and the [Language Plural Rules](#) by the Unicode Consortium is a more detailed description.

Shihni edhe:

Formulë shumësi

Weblate
 Dashboard Projects Languages Checks

WeblateOrg / Django / Czech / Translate
 translated 96%

1/1

Custom search

'%(count)s word'

Zen

Position and priority

English

Singular

%(count)s word

Plural

%(count)s words

Czech, One

%(count)s slovo

Czech, Few

%(count)s slova

Czech, Other

%(count)s slov

Plural formula: (n==1) ? 0 : (n>=2 && n<=4) ? 1 : 2

☐ Needs editing

Save

Suggest

Skip

Nearby strings 20
 Comments
 Automatic suggestions
 Other languages 3

History

New comment

Comment on this string for fellow translators and developers to read.

Scope

Translation comment, discussions with other translators

Is your comment specific to this translation or generic for all of them?

New comment

You can use Markdown and mention users by @username.

Save

Glossary

English Czech
 No related strings found in the glossary.
 Add term to glossary

String information

Screenshot context
 No screenshot currently associated.
 Add screenshot

Explanation
 No explanation currently provided.

Labels
 No labels currently set.

Flags
 python-format

Source string location
 weblate/templates/translation.ht
ml:149

String age
 13 seconds ago

Source string age
 14 seconds ago

Translation file
 weblate/locale/cs/LC_MESSAGE
S/django.po, string 5

Shkurtore tastiere

Ndryshuar në versionin 2.18: The keyboard shortcuts have been revamped in 2.18 to less likely collide with browser or system defaults.

Gjatë përkthimit mund të përdoren shkurtoret vijuese të tastierës:

Keyboard shortcut	Përshkrim
Alt+Home	Navigate to first translation in current search.
Alt+End	Navigate to last translation in current search.
Alt+PageUp or Ctrl ↑ or Alt ↑ or Cmd ↑	Navigate to previous translation in current search.
Alt+PageDown or Ctrl+↓ or Alt+↓ or Cmd+↓	Navigate to next translation in current search.
Alt+Enter or Ctrl+Enter or Cmd+Enter	Ruaje përkthimin e tanishëm.
Ctrl+Shift+Enter or Cmd+Shift+Enter	Unmark translation as needing edit and submit it.
Ctrl+E or Cmd+E	Fokuso përpunues përkthimesh.
Ctrl+U or Cmd+U	Fokuso përpunues komentesh.
Ctrl+M or Cmd+M	Shows <i>Automatic suggestions</i> tab, see Sugjerime të automatizuara .
Ctrl+1 to Ctrl+9 or Cmd+1 to Cmd+9	Copies placeable of given number from source string.
Ctrl+M+1 to 9 or Cmd+M+1 to 9	Copy the machine translation of given number to current translation.
Ctrl+I+1 to 9 or Cmd+I+1 to 9	Ignore one item in the list of failing checks.
Ctrl+J or Cmd+J	Shows the <i>Nearby strings</i> tab.
Ctrl+S or Cmd+S	Focus search field.
Ctrl+O or Cmd+O	Copy source string.
Ctrl+Y or Cmd+Y	Toggle the <i>Needs editing</i> flag.

Tastierë pamore

A small visual keyboard row is shown just above the translation field. This can be useful to keep local punctuation in mind (as the row is local to each language), or have characters otherwise hard to type handy.

The shown symbols factor into three categories:

- User configured characters defined in the [Profil përdoruesi](#)
- Per-language characters provided by Weblate (e.g. quotes or RTL specific characters)
- Characters configured using `SPECIAL_CHARS`

The screenshot displays the Weblate web interface for a project named 'Django' in the 'Hebrew' language. The main area shows a translation of the string 'Files' from English to Hebrew. The Hebrew text 'קבצים' is entered in the input field. The interface includes a top navigation bar with links to Dashboard, Projects, Languages, and Checks. A right sidebar provides additional context, including a Glossary, String information (Screenshot context, Explanation, Labels, Flags), Source string location, String age, Source string age, and Translation file.

Translation

English

Files

Hebrew

קבצים

Needs editing ⓘ

5/100 · 5

RTL LTR

Save Suggest Skip

Nearby strings 16 Comments Automatic suggestions Other languages 3

History

Language	Translated string
Czech	Soubory
Hungarian	Fájlok
English	Files

Glossary

English Hebrew

No related strings found in the glossary.

+ Add term to glossary

String information ⓘ

Screenshot context

No screenshot currently associated.

+ Add screenshot

Explanation

No explanation currently provided.

Labels

No labels currently set.

Flags

No flags currently set.

Source string location

weblate/templates/translation.html:45 · weblate/trans/forms.py:1404

String age

27 seconds ago

Source string age

28 seconds ago

Translation file

weblate/locale/he/LC_MESSAGES/django.po, string 1

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

Kontekst përkthimi

This contextual description provides related info about the current string.

Attribute vargu Things like message ID, context (`msgctxt`) or location in source code.

Foto ekrani Screenshots can be uploaded to Weblate to better inform translators of where and how the string is used, see [Visual context for strings](#).

Vargje atypari Displays neighbouring messages from the translation file. These are usually also used in a similar context and prove useful in keeping the translation consistent.

Hasje të tjera In case a message appears in multiple places (e.g. multiple components), this tab shows all of them if they are found to be inconsistent (see [Jo i njëtrajtshëm](#)). You can choose which one to use.

Kujtesë përkthimesh Look at similar strings translated in past, see [Kujtesë Përkthimesh](#).

Fjalorth Displays terms from the project glossary used in the current message.

Ndryshime së fundi List of people whom have changed this message recently using Weblate.

Projekt Project info like instructions for translators, or a directory or link to the string in the version control system repository the project uses.

If you want direct links, the translation format has to support it.

Historik përkthimi

Every change is by default (unless turned off in component settings) saved in the database, and can be reverted. Optionally one can still also revert anything in the underlying version control system.

Gjatësie vargu të përkthyer

Weblate can limit the length of a translation in several ways to ensure the translated string is not too long:

- The default limitation for translation is ten times longer than the source string. This can be turned off by `LIMIT_TRANSLATION_LENGTH_BY_SOURCE_LENGTH`. In case you are hitting this, it might be also caused by a monolingual translation erroneously set up as bilingual one, making Weblate mistaking the translation key for the actual source string. See [Formate dygjuhësh dhe njëgjuhësh](#) for more info.
- Maximal length in characters defined by translation file or flag, see [Gjatësi maksimum e përkthimit](#).
- Maximal rendered size in pixels defined by flags, see [Madhësi maksimum e përkthimit](#).

1.3.8 Sugjerime të automatizuara


Based on configuration and your translated language, Weblate provides suggestions from several machine translation tools and [Kujtesë Përkthimesh](#). All machine translations are available in a single tab of each translation page.

Shihni edhe:

You can find the list of supported tools in [Përkthim nga makina](#).

1.3.9 Përkthim i automatizuar

You can use automatic translation to bootstrap translation based on external sources. This tool is called *Automatic translation* accessible in the *Tools* menu, once you have selected a component and a language:



Two modes of operation are possible:

- Using other Weblate components as a source for translations.
- Using selected machine translation services with translations above a certain quality threshold.

You can also choose which strings are to be auto-translated.

Sinjalizim: Be mindful that this will overwrite existing translations if employed with wide filters such as *All strings*.

Useful in several situations like consolidating translation between different components (for example the application and its website) or when bootstrapping a translation for a new component using existing translations (translation memory).

Shihni edhe:

Keeping translations same across components

1.3.10 Rate limiting

To avoid abuse of the interface, rate limiting is applied to several operations like searching, sending contact forms or translating. If affected by it, you are blocked for a certain period until you can perform the operation again.

Default limits and fine-tuning is described in the administrative manual, see [Rate limiting](#).

1.3.11 Kërkoni dhe zëvendësoni

Change terminology effectively or perform bulk fixing of the strings using *Search and replace* in the *Tools* menu.

Ndihmëz: Don't worry about messing up the strings. This is a two-step process showing a preview of edited strings before the actual change is confirmed.

1.3.12 Përpunim në masë

Bulk editing allows performing one operation on number of strings. You define strings by searching for them and set up something to be done for matching ones. The following operations are supported:

- Changing string state (for example to approve all unreviewed strings).
- Adjust translation flags (see [Customizing behavior using flags](#))
- Adjust string labels (see labels)

Ndihmëz: This tool is called *Bulk edit* accessible in the *Tools* menu of each project, component or translation.

Shihni edhe:

[Bulk edit addon](#)

1.4 Shkarkim dhe ngarkim përkthimesh

You can export files from a translation, make changes, and import them again. This allows working offline, and then merging changes back into the existing translation. This works even if it has been changed in the meantime.

Shënim: Available options might be limited by [access control](#) settings.

1.4.1 Shkarkim përkthimesh

From the project or component dashboard, translatable files can be downloaded in the *Files* menu.

The first option is to download the file in the original format as it is stored in the repository. In this case, any pending changes in the translation are getting committed and the up-to-date file is yield without any conversions.

You can also download the translation converted into one of the widely used localization formats. The converted files will be enriched with data provided in Weblate; such as additional context, comments or flags. Several file formats are available via the *Files* ↓ *Customize download* menu:

- PO gettext
- XLIFF me zgjerime gettext
- XLIFF 1.1

- TermBase eXchange
- Translation Memory eXchange
- gettext MO (only available when translation is using gettext PO)
- CSV
- Excel Open XML
- JSON (only available for monolingual translations)
- Android String Resource (only available for monolingual translations)
- iOS strings (only available for monolingual translations)

Ndihmëz: The content available in the converted files differs based on file format features, you can find overview in *Translation types capabilities*.

The screenshot shows the Weblate web interface for a project named 'Django' in the 'Czech' language. The 'Files' dropdown menu is open, showing options: 'Download translation', 'Customize download' (highlighted), and 'Upload translation'. Below the menu, there is a table of 'Quick downloads' with columns for file format, file type, and file size. The 'Customize download' section is also visible, showing a 'File format' dropdown set to 'All strings' and a 'File format' section with radio buttons for various formats: 'gettext PO' (selected), 'XLIFF 1.1 with gettext extensions', 'XLIFF 1.1', 'TBX', 'TMX', 'gettext MO', 'CSV', 'XLSX', 'JSON', 'Android String Resource', and 'iOS strings'. A 'Download' button is at the bottom of the 'Customize download' section.

Quick downloads	File in original format as translated in the repository	File type	File size
26	All strings, converted files enriched with comments; suitable for offline translation	CSV	gettext MO
1	Strings needing action, converted files enriched with comments; suitable for offline translation	CSV	gettext MO


Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

Shihni edhe:

```
GET /api/translations/(string:project)/(string:component)/(string:language)/file/
```

1.4.2 Ngarkim përkthimesh

When you have made your changes, use *Upload translation* in the *Files* menu.



The screenshot shows the Weblate web interface. At the top, there's a navigation bar with 'Weblate' logo, 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below it, a breadcrumb trail shows 'WeblateOrg / Django / Czech' with a 'translated 96%' indicator. A secondary navigation bar includes 'Overview', 'Info', 'Search', 'Insights', 'Files', 'Tools', 'Manage', and 'Share'. The 'Files' menu is open, showing options: 'Download translation', 'Customize download', and 'Upload translation' (which is highlighted). The main content area is titled 'Upload' and contains a message: 'The uploaded file will be merged with the current translation. If you want to overwrite already translated strings, don't forget to turn it on.' Below this, there's a 'File' section with a 'Choose File' button and 'No file chosen' text. The 'File upload mode' section has four radio buttons: 'Add as translation', 'Add as suggestion', 'Add as translation needing edit', and 'Replace existing translation file'. The 'Processing of strings needing edit' section has a dropdown menu set to 'Do not import'. The 'Conflict handling' section has a dropdown menu set to 'Update translated strings' with a note: 'Whether to overwrite existing translations if the string is already translated.' Below these are input fields for 'Author name' (containing 'Weblate Test') and 'Author e-mail' (containing 'weblate@example.org'). At the bottom is an 'Upload' button.

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

Formate të mbuluar kartelash

Any file in a supported file format can be uploaded, but it is still recommended to use the same file format as the one used for translation, otherwise some features might not be translated properly.

Shihni edhe:

Formate të mbuluar kartelash

The uploaded file is merged to update the translation, overwriting existing entries by default (this can be turned off or on in the upload dialog).

Import methods

These are the choices presented when uploading translation files:

Shtojë si përkthim (translate) Imported translations are added as translations. This is the most common usecase, and the default behavior.

Only translations are used from the uploaded file and no additional content.

Shtojë si sugjerim (suggest) Imported translations are added as suggestions, do this when you want to have your uploaded strings reviewed.

Only translations are used from the uploaded file and no additional content.

Shtojë si përkthim që lyp përpunim (fuzzy) Imported translations are added as translations needing edit. This can be useful when you want translations to be used, but also reviewed.

Only translations are used from the uploaded file and no additional content.

Zëvendëso kartelë ekzistuese përkthimi (replace) Existing file is replaced with new content. This can lead to loss of existing translations, use with caution.

Përditëso vargje burim (source) Updates source strings in bilingual translation file. This is similar to what *Përditësoni kartela PO, që të përputhen me POT (msgmerge)* does.

This option is supported only for some file formats.

Add new strings (add) Adds new strings to the translation. It skips the one which already exist.

In case you want to both add new strings and update existing translations, upload the file second time with *Add as translation*.

This option is available only with *Administroni vargje* turned on.

Only source, translation and key (context) are used from the uploaded file.

Shihni edhe:

```
POST /api/translations/(string:project)/(string:component)/(string:language)/file/
```

Trajtim përplasje

Defines how to deal with uploaded strings which are already translated.

Vargje që lypin përpunim

There is also an option for how to handle strings needing edit in the imported file. Such strings can be handle in one of the three following ways: «Do not import», «Import as string needing edit», or «Import as translated».

Overriding authorship

With admin permissions, you can also specify authorship of uploaded file. This can be useful in case you've received the file in another way and want to merge it into existing translations while properly crediting the actual author.

1.5 Fjalorth

Each project can include one or more glossaries as a shorthand for storing terminology. Glossary easify maintaining consistency of the translation.

A glossary for each language can be managed on its own, but they are stored together as a single component which helps project admins and multilingual translators to maintain some cross-language consistency as well. Terms from the glossary containing words from the currently translated string are displayed in the sidebar of the translation editor.

1.5.1 Administrim fjalorthësh

Ndryshuar në versionin 4.5: Glossaries are now regular translation components and you can use all Weblate features on them — commenting, storing in a remote repository, or adding explanations.

Use any component as a glossary by turning on *Përdore si fjalorth*. You can create multiple glossaries for one project.

An empty glossary for a given project is automatically created with the project. Glossaries are shared among all components of the same project, and optionally with other projects using *Ndaje te projekte* from the respective glossary component.

The glossary component looks like any other component in Weblate with added colored label:

Translation status

2	Strings	100%
3	Words	100%

Buttons: Add new glossary term, Browse, Translate

Strings status

2	All strings — 3 words	Browse	Edit	Zen
2	Translated strings — 3 words	Browse	Edit	Zen

Other components

Component	Translated	Untranslated	Untranslated words	Checks	Suggestions	Comments
Django	96%	1	12	3		
Language names	✓					

Buttons: Browse all components

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

You can browse all glossary terms:

Navigation: All strings, Source string, Add new glossary term

English	Czech
machine translation	strojový překlad
project	projekt

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

or edit them as any translations.

1.5.2 Glossary terms

Glossary terms are translated the same way regular strings are. You can toggle additional features using the *Tools* menu for each term.

The screenshot shows the Weblate web interface. At the top, there's a navigation bar with 'Weblate', 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below it, the breadcrumb is 'WeblateOrg / Glossary WeblateOrg / Czech / Translate'. A status bar shows 'translated 100%'. The main area is titled 'Glossary term' and contains a form for editing a term. The 'English' field has 'project' and the 'Czech' field has 'projekt'. There are buttons for 'Save', 'Suggest', and 'Skip'. A 'Tools' dropdown menu is open, showing options: 'Delete string', 'Mark as read-only', 'Mark as forbidden translation', 'Mark as terminology', and 'Add variant of this string'. On the right, a sidebar shows 'Glossary' with a table of terms and 'String information' with details like 'String age' and 'Source string age'. At the bottom, there's a footer with 'Powered by Weblate 4.8' and links to 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

Untranslatable terms

Të reja në versionin 4.5.

Flagging certain glossary term translations *read-only* by bulk-editing, typing in the flag, or by using *Tools* ↓ *Mark as read-only* means they can not be translated. Use this for brand names or other terms that should not be changed in other languages. Such terms are visually highlighted in the glossary sidebar.

Shihni edhe:

Customizing behavior using flags

Forbidden translations

Të reja në versionin 4.5.

Flagging certain glossary term translations as `forbidden`, by bulk-editing, typing in the flag, or by using *Tools* ↓ *Mark as forbidden translation* means they are **not** to be used. Use this to clarify translation when some words are ambiguous or could have unexpected meanings.

Shihni edhe:

Customizing behavior using flags

Terminologji

Të reja në versionin 4.5.

Flagging certain glossary terms as `terminology` by bulk-editing, typing in the flag, or by using *Tools* ↓ *Mark as terminology* adds entries for them to all languages in the glossary. Use this for important terms that should be well thought out, and retain a consistent meaning across all languages.

Shihni edhe:

Customizing behavior using flags

Variante

Variants are a generic way to group strings together. All term variants are listed in the glossary sidebar when translating.

Ndihmëz: You can use this to add abbreviations or shorter expressions for a term.

Shihni edhe:

variants

1.6 Checks and fixups

The quality checks help catch common translator errors, ensuring the translation is in good shape. The checks can be ignored in case of false positives.

Once submitting a translation with a failing check, this is immediately shown to the user:

[Dashboard](#)
[Projects](#)
[Languages](#)
[Checks](#)

[WeblateOrg](#) / [Django](#) / [Czech](#) / [Translate](#)
translated 96%

The translation has been saved, however there are some newly failing checks: Missing plurals, Python format

1/1

Custom search

'%(count)s word'

Position

Zen

Translation

English

Singular

%(count)s word

Plural

%(count)s words

Czech, One

Czech, Few

několik slov

Czech, Other

%(count)s slov

Plural formula: (n==1) ? 0 : (n>=2 && n<=4) ? 1 : 2

Needs editing

Save

Suggest

Skip

Things to check

Python format

Following format strings are missing: %(count)s

Dismiss

For all languages

Missing plurals

Some plural forms are not translated

Dismiss

For all languages

Glossary

English

Czech

No related strings found in the glossary.

Add term to glossary

Nearby strings

Comments

Automatic suggestions

Other languages

History

New comment

Comment on this string for fellow translators and developers to read.

Scope

Translation comment, discussions with other translators

Is your comment specific to this translation or generic for all of them?

New comment

You can use Markdown and mention users by @username.

Save

String information

Screenshot context

No screenshot currently associated.

Add screenshot

Explanation

No explanation currently provided.

Labels

No labels currently set.

Flags

python-format

Source string location

weblate/templates/translation.html:149

String age

20 seconds ago

Source string age

21 seconds ago

Translation file

weblate/locale/cs/LC_MESSAGES/django.po, string 5

pending

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

26

Kapitulli 1. Dokumentime përdoruesi

1.6.1 Automatic fixups

In addition to *Kontrolle cilësie*, Weblate can fix some common errors in translated strings automatically. Use it with caution to not have it add errors.

Shihni edhe:

AUTOFIX_LIST

1.6.2 Kontrolle cilësie

Weblate employs a wide range of quality checks on strings. The following section describes them all in further detail. There are also language specific checks. Please file a bug if anything is reported in error.

Shihni edhe:

CHECK_LIST, *Customizing behavior using flags*

1.6.3 Kontrolle përkthimi

Executed upon every translation change, helping translators maintain good quality translations.

Markup BBCode

Summary BBcode te përkthimi s'përputhet me burimin

Fokus translated strings

Check class `weblate.checks.markup.BBCodeCheck`

Flag to ignore `ignore-bbcode`

BBCode represents simple markup, like for example highlighting important parts of a message in bold font, or italics. This check ensures they are also found in translation.

Shënim: The method for detecting BBcode is currently quite simple so this check might produce false positives.

Fjalë të njëpasnjëshme të përsëdytura

Të reja në versionin 4.1.

Summary Teksti përmban të njëjtin fjalë dy herë, njëra pas tjetrës:

Fokus translated strings

Check class `weblate.checks.duplicate.DuplicateCheck`

Flag to ignore `ignore-duplicate`

Checks that no consecutive duplicate words occur in a translation. This usually indicates a mistake in the translation.

Ndihmëz: This check includes language specific rules to avoid false positives. In case it triggers falsely in your case, let us know. See *Njoftim problemesh në Weblate*.

S'ndjek fjalorthin

Të reja në versionin 4.5.

Summary Përkthimi s'ndjek zërat e përcaktuar në fjalorth.

Fokus translated strings

Check class `weblate.checks.glossary.GlossaryCheck`

Flag to enable `check-glossary`

Flag to ignore `ignore-check-glossary`

This check has to be turned on using `check-glossary` flag (see [Customizing behavior using flags](#)). Please consider following prior to enabling it:

- It does exact string matching, the glossary is expected to contain terms in all variants.
- Checking each string against glossary is expensive, it will slow down any operation in Weblate which involves running checks like importing strings or translating.

Shihni edhe:

Fjalorth, Customizing behavior using flags, Flamuj përkthimi

Hapësirë dyshe

Summary Përkthimi përmban hapësira dyshe

Fokus translated strings

Check class `weblate.checks.chars.DoubleSpaceCheck`

Flag to ignore `ignore-double-space`

Checks that double space is present in translation to avoid false positives on other space-related checks.

Check is false when double space is found in source meaning double space is intentional.

Vargje të formatuar

Checks that formatting in strings are replicated between both source and translation. Omitting format strings in translation usually causes severe problems, so the formatting in strings should usually match the source.

Weblate supports checking format strings in several languages. The check is not enabled automatically, only if a string is flagged appropriately (e.g. *c-format* for C format). Gettext adds this automatically, but you will probably have to add it manually for other file formats or if your PO files are not generated by **xgettext**.

This can be done per unit (see [Additional info on source strings](#)) or in [Component configuration](#). Having it defined per component is simpler, but can lead to false positives in case the string is not interpreted as a formatting string, but format string syntax happens to be used.

Ndihmëz: In case specific format check is not available in Weblate, you can use generic [Vendmbajtëse](#).

Besides checking, this will also highlight the formatting strings to easily insert them into translated strings:

The screenshot shows the Weblate web interface for the project 'Django / Czech / Translate'. The main area displays the translation of the string '%(count)s word' from English to Czech. The English section shows 'Singular' and 'Plural' forms. The Czech section shows 'One', 'Few', and 'Other' forms, each with a text input field and a character count. A 'Plural formula' is also provided. The interface includes a 'Save' button, a 'Suggest' button, and a 'Skip' button. The sidebar on the right contains a 'Glossary' section, a 'String information' section with details like 'Screenshot context', 'Explanation', 'Labels', 'Flags', 'Source string location', 'String age', 'Source string age', and 'Translation file', and a 'Nearby strings' section with a list of 20 strings.

Varg ndërshtënie AngularJS

Summary Vargu i ndërshtënies AngularJS s'përputhet me burimin

Fokus translated strings

Check class `weblate.checks.angularjs.AngularJSInterpolationCheck`

Flag to enable `angularjs-format`

Flag to ignore `ignore-angularjs-format`

Named format string example `Your balance is {{amount}} {{ currency }}`

Shihni edhe:

Vargje të formatuar, AngularJS text interpolation

Format C

Summary Vargu në format C nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.CFormatCheck`

Flag to enable `c-format`

Flag to ignore `ignore-c-format`

Simple format string example Ka %d mollë

Position format string example Your balance is %1\$d %2\$s

Shihni edhe:

Vargje të formatuar, [C format strings](#), [C printf format](#)

Format C#

Summary Vargu në format C# nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.CSharpFormatCheck`

Flag to enable `c-sharp-format`

Flag to ignore `ignore-c-sharp-format`

Position format string example Ka {0} mollë

Shihni edhe:

Vargje të formatuar, [C# String Format](#)

ECMAScript template literals

Summary ECMAScript template literals do not match source

Fokus translated strings

Check class `weblate.checks.format.ESTemplateLiteralsCheck`

Flag to enable `es-format`

Flag to ignore `ignore-es-format`

Interpolation example Ka \${number} mollë

Shihni edhe:

Vargje të formatuar, [Template literals](#)

Ndërshtënie i18next

Të reja në versionin 4.0.

Summary Ndërshtënia i18next nuk përputhen me burimin

Fokus translated strings

Check class `weblate.checks.format.I18NextInterpolationCheck`

Flag to enable `i18next-interpolation`

Flag to ignore `ignore-i18next-interpolation`

Interpolation example Ka `{{number}}` mollë

Nesting example Ka `$t(number)` mollë

Shihni edhe:

Vargje të formatuar, i18next interpolation

Format Java

Summary Vargu në format Java nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.JavaFormatCheck`

Flag to enable `java-format`

Flag to ignore `ignore-java-format`

Simple format string example Ka `%d` mollë

Position format string example Your balance is `%1$d %2$s`

Shihni edhe:

Vargje të formatuar, Java Format Strings

Java MessageFormat

Summary Vargu në format Java MessageFormat nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.JavaMessageFormatCheck`

Flag to enable uncodintionally `java-messageformat`

Flag to enable autodetection `auto-java-messageformat` enables check only if there is a format string in the source

Flag to ignore `ignore-java-messageformat`

Position format string example Ka `{0}` mollë

Shihni edhe:

Vargje të formatuar, Java MessageFormat

Format JavaScript

Summary Vargu në format JavaScript nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.JavaScriptFormatCheck`

Flag to enable `javascript-format`

Flag to ignore `ignore-javascript-format`

Simple format string example Ka %d mollë

Shihni edhe:

Vargje të formatuar, *JavaScript formatting strings*

Format Lua

Summary Vargu në format Lua s'përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.LuaFormatCheck`

Flag to enable `lua-format`

Flag to ignore `ignore-lua-format`

Simple format string example Ka %d mollë

Shihni edhe:

Vargje të formatuar, *Lua formatting strings*

Object Pascal format

Summary Vargu në format objekti Pascal nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.ObjectPascalFormatCheck`

Flag to enable `object-pascal-format`

Flag to ignore `ignore-object-pascal-format`

Simple format string example Ka %d mollë

Shihni edhe:

Vargje të formatuar, *Object Pascal formatting strings* *Free Pascal formatting strings* *Delphi formatting strings*

Vendmbajtëse përqindjeje

Të reja në versionin 4.0.

Summary Vendmbajtëset përqindje s'përputhen me burimin

Fokus translated strings

Check class `weblate.checks.format.PercentPlaceholdersCheck`

Flag to enable `percent-placeholders`

Flag to ignore `ignore-percent-placeholders`

Simple format string example Ka %number% mollë

Shihni edhe:

[Vargje të formatuar](#),

Format Perl

Summary Vargu në format Perl nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.PperlFormatCheck`

Flag to enable `perl-format`

Flag to ignore `ignore-perl-format`

Simple format string example Ka %d mollë

Position format string example Your balance is %1\$d %2\$s

Shihni edhe:

[Vargje të formatuar](#), [Perl sprintf](#), [Perl Format Strings](#)

Format PHP

Summary Vargu në format PHP nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.PHPFormatCheck`

Flag to enable `php-format`

Flag to ignore `ignore-php-format`

Simple format string example Ka %d mollë

Position format string example Your balance is %1\$d %2\$s

Shihni edhe:

[Vargje të formatuar](#), [PHP sprintf documentation](#), [PHP Format Strings](#)

Format kllapash Python

Summary Vargu në format kllapash Python nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.PythonBraceFormatCheck`

Flag to enable `python-brace-format`

Flag to ignore `ignore-python-brace-format`

Simple format string ``Ka {} mollë

Named format string example Your balance is {amount} {currency}

Shihni edhe:

[Vargje të formatuar](#), [Python brace format](#), [Python Format Strings](#)

Format Python

Summary Vargu në format Python nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.PythonFormatCheck`

Flag to enable `python-format`

Flag to ignore `ignore-python-format`

Simple format string `Ka %d mollë`

Named format string example `Your balance is %(amount) %(currency)`

Shihni edhe:

Vargje të formatuar, [Python string formatting](#), [Python Format Strings](#)

Format Qt

Summary Varg në format Qt nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.qt.QtFormatCheck`

Flag to enable `qt-format`

Flag to ignore `ignore-qt-format`

Position format string example `Ka %1 mollë`

Shihni edhe:

Vargje të formatuar, [Qt QString::arg\(\)](#)

Format shumësi Qt

Summary Varg në format shumësi Qt nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.qt.QtPluralCheck`

Flag to enable `qt-plural-format`

Flag to ignore `ignore-qt-plural-format`

Plural format string example `Ka %Ln kumbull(a)`

Shihni edhe:

Vargje të formatuar, [Qt i18n guide](#)

Format Ruby

Summary Varg në format Ruby nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.ruby.RubyFormatCheck`

Flag to enable `ruby-format`

Flag to ignore `ignore-ruby-format`

Simple format string example `Ka %d mollë`

Position format string example `Your balance is %1$f %2$s`

Named format string example `Your balance is %+.2<amount>f %<currency>s`

Named template string `Your balance is %{amount} %{currency}`

Shihni edhe:

Vargje të formatuar, *Ruby Kernel#sprintf*

Format Schema

Summary Vargu në format Schema nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.SchemeFormatCheck`

Flag to enable `scheme-format`

Flag to ignore `ignore-scheme-format`

Simple format string example `There are ~d apples`

Shihni edhe:

Vargje të formatuar, *Srfi 28*, *Chicken Scheme format*, *Guile Scheme formatted output*

Formatim i18n Vue

Summary Fomatimi i18n Vue nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.format.VueFormattingCheck`

Flag to enable `vue-format`

Flag to ignore `ignore-vue-format`

Named formatting `Ka {count} mollë`

Formatim i18n Rails `Ka %{count} mollë`

Linked locale messages `@:message.dio @:message.the_world!`

Shihni edhe:

Vargje të formatuar, *Vue I18n Formatting*, *Vue I18n Linked locale messages*

Është përkthyer

Summary Ky varg është përkthyer në të kaluarën

Fokus all strings

Check class `weblate.checks.consistency.TranslatedCheck`

Flag to ignore `ignore-translated`

Means a string has been translated already. This can happen when the translations have been reverted in VCS or lost otherwise.

Jo i njëtrajtshëm

Summary Ky varg ka më shumë se një përkthim në këtë projekt ose s'është i përkthyer në disa përbërës.

Fokus all strings

Check class `weblate.checks.consistency.ConsistencyCheck`

Flag to ignore `ignore-inconsistent`

Weblate checks translations of the same string across all translation within a project to help you keep consistent translations.

The check fails on differing translations of one string within a project. This can also lead to inconsistencies in displayed checks. You can find other translations of this string on the *Other occurrences* tab.

Shënim: This check also fires in case the string is translated in one component and not in another. It can be used as a quick way to manually handle strings which are not translated in some components just by clicking on the *Use this translation* button displayed on each line in the *Other occurrences* tab.

You can use *Përkthim i automatizuar* addon to automate translating of newly added strings which are already translated in another component.

Shihni edhe:

Keeping translations same across components

Është përdorur shkronjë Kashida

Të reja në versionin 3.5.

Summary S'duhen përdorur shkronja zbukuruese kashida

Fokus translated strings

Check class `weblate.checks.chars.KashidaCheck`

Flag to ignore `ignore-kashida`

The decorative Kashida letters should not be used in translation. These are also known as Tatweel.

Shihni edhe:

[Kashida on Wikipedia](#)

Lidhje Markdown

Të reja në versionin 3.5.

Summary Lidhje Markdown nuk përputhen me burimin

Fokus translated strings

Check class `weblate.checks.markup.MarkdownLinkCheck`

Flag to enable `md-text`

Flag to ignore `ignore-md-link`

Lidhje Markdown s'përputhen me burimin.

Shihni edhe:

[Markdown links](#)

Referenca Markdown

Të reja në versionin 3.5.

Summary Referenca lidhjesh Markdown nuk përputhen me burimin

Fokus translated strings

Check class `weblate.checks.markup.MarkdownRefLinkCheck`

Flag to enable `md-text`

Flag to ignore `ignore-md-reflink`

Referenca lidhjesh Markdown s'përputhen me burimin.

Shihni edhe:

[Markdown links](#)

Sintaksë Markdown

Të reja në versionin 3.5.

Summary Sintaksë Markdown nuk përputhet me burimin

Fokus translated strings

Check class `weblate.checks.markup.MarkdownSyntaxCheck`

Flag to enable `md-text`

Flag to ignore `ignore-md-syntax`

Sintaksë Markdown nuk përputhet me burimin

Shihni edhe:

[Markdown span elements](#)

Gjatësi maksimum e përkthimit

Summary Përkthimi s'duhet të tejkalojë gjatësinë e dhënë

Fokus translated strings

Check class `weblate.checks.chars.MaxLengthCheck`

Flag to enable `max-length`

Flag to ignore `ignore-max-length`

Checks that translations are of acceptable length to fit available space. This only checks for the length of translation characters.

Unlike the other checks, the flag should be set as a `key:value` pair like `max-length:100`.

Ndihmëz: This check looks at number of chars, what might not be the best metric when using proportional fonts to render the text. The *Madhësi maksimum e përkthimit* check does check actual rendering of the text.

The `replacements` flag might be also useful to expand placeables before checking the string.

Madhësi maksimum e përkthimit

Summary Teksti i shfaqur për përkthimin s'duhet të kalojë madhësinë e dhënë

Fokus translated strings

Check class `weblate.checks.render.MaxSizeCheck`

Flag to enable `max-size`

Flag to ignore `ignore-max-size`

Të reja në versionin 3.7.

Translation rendered text should not exceed given size. It renders the text with line wrapping and checks if it fits into given boundaries.

This check needs one or two parameters - maximal width and maximal number of lines. In case the number of lines is not provided, one line text is considered.

You can also configure used font by `font-*` directives (see *Customizing behavior using flags*), for example following translation flags say that the text rendered with ubuntu font size 22 should fit into two lines and 500 pixels:

```
max-size:500:2, font-family:ubuntu, font-size:22
```

Ndihmëz: You might want to set `font-*` directives in *Component configuration* to have the same font configured for all strings within a component. You can override those values per string in case you need to customize it per string.

The `replacements` flag might be also useful to expand placeables before checking the string.

Shihni edhe:

Administrim shkronjash, Customizing behavior using flags, Gjatësi maksimum e përkthimit

Mospërputhje n

Summary Number of `\n` in translation does not match source

Fokus translated strings

Check class `weblate.checks.chars.EscapedNewlineCountingCheck`

Flag to ignore `ignore-escaped-newline`

Usually escaped newlines are important for formatting program output. Check fails if the number of `\n` literals in translation do not match the source.

Mospërputhje dy pikash

Summary Originali dhe përkthimi nuk mbarojnë që të dy me dy pika

Fokus translated strings

Check class `weblate.checks.chars.EndColonCheck`

Flag to ignore `ignore-end-colon`

Checks that colons are replicated between both source and translation. The presence of colons is also checked for various languages where they do not belong (Chinese or Japanese).

Shihni edhe:

[Colon on Wikipedia](#)

Mospërputhje tre pikash

Summary Originali dhe përkthimi nuk mbarojnë që të dy me shumëpikësh

Fokus translated strings

Check class `weblate.checks.chars.EndEllipsisCheck`

Flag to ignore `ignore-end-ellipsis`

Checks that trailing ellipses are replicated between both source and translation. This only checks for real ellipsis (...) not for three dots (. . .).

An ellipsis is usually rendered nicer than three dots in print, and sounds better with text-to-speech.

Shihni edhe:

[Ellipsis on Wikipedia](#)

Mospërputhje pikëçuditjesh

Summary Originali dhe përkthimi nuk mbarojnë që të dy me pikëçuditje

Fokus translated strings

Check class `weblate.checks.chars.EndExclamationCheck`

Flag to ignore `ignore-end-exclamation`

Checks that exclamations are replicated between both source and translation. The presence of exclamation marks is also checked for various languages where they do not belong (Chinese, Japanese, Korean, Armenian, Limbu, Myanmar or Nko).

Shihni edhe:

[Exclamation mark on Wikipedia](#)

Mospërputhje pike

Summary Origjinali dhe përkthimi nuk mbarojnë që të dy me pikë

Fokus translated strings

Check class `weblate.checks.chars.EndStopCheck`

Flag to ignore `ignore-end-stop`

Checks that full stops are replicated between both source and translation. The presence of full stops is checked for various languages where they do not belong (Chinese, Japanese, Devanagari or Urdu).

Shihni edhe:

[Full stop on Wikipedia](#)

Mospërputhje pikëpyetjesh

Summary Origjinali dhe përkthimi nuk mbarojnë që të dy me pikëpyetje

Fokus translated strings

Check class `weblate.checks.chars.EndQuestionCheck`

Flag to ignore `ignore-end-question`

Checks that question marks are replicated between both source and translation. The presence of question marks is also checked for various languages where they do not belong (Armenian, Arabic, Chinese, Korean, Japanese, Ethiopic, Vai or Coptic).

Shihni edhe:

[Question mark on Wikipedia](#)

Mospërputhje pikëpresjesh

Summary Origjinali dhe përkthimi nuk mbarojnë që të dy me pikëpresje

Fokus translated strings

Check class `weblate.checks.chars.EndSemicolonCheck`

Flag to ignore `ignore-end-semicolon`

Checks that semicolons at the end of sentences are replicated between both source and translation. This can be useful to keep formatting of entries such as desktop files.

Shihni edhe:

[Semicolon on Wikipedia](#)

Mospërputhje ndërprerjesh rreshti

Summary Numri i shenjave për rresht të ri te përkthimi nuk përputhet me atë të burimit

Fokus translated strings

Check class `weblate.checks.chars.NewLineCountCheck`

Flag to ignore `ignore-newline-count`

Usually newlines are important for formatting program output. Check fails if the number of `\n` literals in translation do not match the source.

Mungon shumë

Summary S'janë përkthyer disa forma shumësi

Fokus translated strings

Check class `weblate.checks.consistency.PluralsCheck`

Flag to ignore `ignore-plurals`

Checks that all plural forms of a source string have been translated. Specifics on how each plural form is used can be found in the string definition.

Failing to fill in plural forms will in some cases lead to displaying nothing when the plural form is in use.

Vendmbajtëse

Të reja në versionin 3.9.

Summary Përkthimit i mungojnë disa vendmbajtëse

Fokus translated strings

Check class `weblate.checks.placeholders.PlaceholderCheck`

Flag to enable `placeholders`

Flag to ignore `ignore-placeholders`

Ndryshuar në versionin 4.3: Mund të përdorni shprehje të rregullt si vendmbajtëse.

Translation is missing some placeholders. These are either extracted from the translation file or defined manually using `placeholders` flag, more can be separated with colon, strings with space can be quoted:

```
placeholders:$URL$:$TARGET$:"some long text"
```

In case you have some syntax for placeholders, you can use a regular expression:

```
placeholders:r"%[^\% ]%"
```

Shihni edhe:

[Customizing behavior using flags](#)

Hapësirë pikësimi

Të reja në versionin 3.9.

Summary Mungon shenjë hapësire të pandërprerë përpara shenje të dyfishtë pikësimi

Fokus translated strings

Check class `weblate.checks.chars.PunctuationSpacingCheck`

Flag to ignore `ignore-punctuation-spacing`

Checks that there is non breakable space before double punctuation sign (exclamation mark, question mark, semicolon and colon). This rule is used only in a few selected languages like French or Breton, where space before double punctuation sign is a typographic rule.

Shihni edhe:

[French and English spacing on Wikipedia](#)

Shprehje e rregullt

Të reja në versionin 3.9.

Summary Përkthimi s'përputhet me shprehje të rregullt:

Fokus translated strings

Check class `weblate.checks.placeholders.RegexCheck`

Flag to enable `regex`

Flag to ignore `ignore-regex`

Translation does not match regular expression. The expression is either extracted from the translation file or defined manually using `regex` flag:

```
regex: ^foo|bar$
```

Shumës i njëjtë

Summary Disa forma shumësi janë përkthyer në të njëjtën mënyrë

Fokus translated strings

Check class `weblate.checks.consistency.SamePluralsCheck`

Flag to ignore `ignore-same-plurals`

Check that fails if some plural forms are duplicated in the translation. In most languages they have to be different.

Shenjë rresht i ri në fillim

Summary Originali dhe përkthimi nuk fillojnë që të dy me simbol rreshti të ri

Fokus translated strings

Check class `weblate.checks.chars.BeginNewlineCheck`

Flag to ignore `ignore-begin-newline`

Newlines usually appear in source strings for good reason, omissions or additions can lead to formatting problems when the translated text is put to use.

Shihni edhe:

Shenjë rresht i ri në fund

Hapësira fillimi

Summary Burimi dhe përkthimi nuk fillojnë që të dy me të njëjtën numër hapësirash

Fokus translated strings

Check class `weblate.checks.chars.BeginSpaceCheck`

Flag to ignore `ignore-begin-space`

A space in the beginning of a string is usually used for indentation in the interface and thus important to keep.

Shenjë rresht i ri në fund

Summary Origjinali dhe përkthimi nuk mbarojnë që të dy me simbol rreshti të ri

Fokus translated strings

Check class `weblate.checks.chars.EndNewlineCheck`

Flag to ignore `ignore-end-newline`

Newlines usually appear in source strings for good reason, omissions or additions can lead to formatting problems when the translated text is put to use.

Shihni edhe:

Shenjë rresht i ri në fillim

Hapësirë në fund

Summary Origjinali dhe përkthimi nuk mbarojnë që të dy me hapësirë

Fokus translated strings

Check class `weblate.checks.chars.EndSpaceCheck`

Flag to ignore `ignore-end-space`

Checks that trailing spaces are replicated between both source and translation.

Trailing space is usually utilized to space out neighbouring elements, so removing it might break layout.

Përkthim i pandryshuar

Summary Burimi dhe përkthimi janë identikë

Fokus translated strings

Check class `weblate.checks.same.SameCheck`

Flag to ignore `ignore-same`

Happens if the source and corresponding translation strings is identical, down to at least one of the plural forms. Some strings commonly found across all languages are ignored, and various markup is stripped. This reduces the number of false positives.

This check can help find strings mistakenly untranslated.

The default behavior of this check is to exclude words from the built-in blacklist from the checking. These are words which are frequently not being translated. This is useful to avoid false positives on short strings, which consist only of single word which is same in several languages. This blacklist can be disabled by adding `strict-same` flag to string or component.

Shihni edhe:

Component configuration, Customizing behavior using flags

HTML jo e parrezik

Të reja në versionin 3.9.

Summary Përkthimi përdor elementë HTML jo të parrezik

Fokus translated strings

Check class `weblate.checks.markup.SafeHTMLCheck`

Flag to enable `safe-html`

Flag to ignore `ignore-safe-html`

The translation uses unsafe HTML markup. This check has to be enabled using `safe-html` flag (see [Customizing behavior using flags](#)). There is also accompanied autofixer which can automatically sanitize the markup.

Shihni edhe:

The HTML check is performed by the [Bleach](#) library developed by Mozilla.

URL

Të reja në versionin 3.5.

Summary Përkthimi s'përmban URL

Fokus translated strings

Check class `weblate.checks.markup.URLCheck`

Flag to enable `url`

Flag to ignore `ignore-url`

The translation does not contain an URL. This is triggered only in case the unit is marked as containing URL. In that case the translation has to be a valid URL.

Markup XML

Summary Etiketa XML të përkthimi nuk përputhen me burimin

Fokus translated strings

Check class `weblate.checks.markup.XMLTagsCheck`

Flag to ignore `ignore-xml-tags`

This usually means the resulting output will look different. In most cases this is not a desired result from changing the translation, but occasionally it is.

Checks that XML tags are replicated between both source and translation.

Sintaksë XML

Të reja në versionin 2.8.

Summary Përkthimi s'është XML e vlefshme

Fokus translated strings

Check class `weblate.checks.markup.XMLValidityCheck`

Flag to ignore `ignore-xml-invalid`

Ka elementë të pavlefshëm shkrimi XML.

Hapësirë me gjerësi zero

Summary Përkthimi përmban shenjë ekstra hapësire me gjerësi zero

Fokus translated strings

Check class `weblate.checks.chars.ZeroWidthSpaceCheck`

Flag to ignore `ignore-zero-width-space`

Zero-width space (<U+200B>) characters are used to break messages within words (word wrapping).

As they are usually inserted by mistake, this check is triggered once they are present in translation. Some programs might have problems when this character is used.

Shihni edhe:

[Zero width space on Wikipedia](#)

1.6.4 Kontrolle burimi

Source checks can help developers improve the quality of source strings.

Tre pika

Summary Vargu përdor tre pika (...) në vend të shenjës shumëpikësh (...)

Fokus Vargje të burimit

Check class `weblate.checks.source.EllipsisCheck`

Flag to ignore `ignore-ellipsis`

This fails when the string uses three dots (. . .) when it should use an ellipsis character (...).

Using the Unicode character is in most cases the better approach and looks better rendered, and may sound better with text-to-speech.

Shihni edhe:

[Ellipsis on Wikipedia](#)

I papërkthyer prej kohësh

Të reja në versionin 4.1.

Summary Ky varg s'është përkthyer prej kohësh

Fokus Vargje të burimit

Check class `weblate.checks.source.LongUntranslatedCheck`

Flag to ignore `ignore-long-untranslated`

When the string has not been translated for a long time, it is can indicate problem in a source string making it hard to translate.

Dështime të shumta kontrollesh

Summary Përkthimet në disa nga gjuhët kanë dështime kontrollesh

Fokus Vargje të burimit

Check class `weblate.checks.source.MultipleFailingCheck`

Flag to ignore `ignore-multiple-failures`

Numerous translations of this string have failing quality checks. This is usually an indication that something could be done to improve the source string.

This check failing can quite often be caused by a missing full stop at the end of a sentence, or similar minor issues which translators tend to fix in translation, while it would be better to fix it in the source string.

Ndryshore të shumta të paemërtuara

Të reja në versionin 4.1.

Summary Te vargu ka ndryshore të shumta të paemërtuara, duke e bërë të pamundur renditjen e tyre nga përkthyesit

Fokus Vargje të burimit

Check class `weblate.checks.format.MultipleUnnamedFormatsCheck`

Flag to ignore `ignore-unnamed-format`

Te vargu ka ndryshore të shumta të paemërtuara, duke e bërë të pamundur renditjen e tyre nga përkthyesit.

Consider using named variables instead to allow translators to reorder them.

Pa forma shumësi

Summary Vargu është përdorur si shumës, por nuk përdoren forma shumësi

Fokus Vargje të burimit

Check class `weblate.checks.source.OptionalPluralCheck`

Flag to ignore `ignore-optional-plural`

The string is used as a plural, but does not use plural forms. In case your translation system supports this, you should use the plural aware variant of it.

Për shembull, me Gettext në Python do të ishte:

```
from gettext import ngettext
print ngettext("Selected %d file", "Selected %d files", files) % files
```

1.7 Kërkim

Të reja në versionin 3.9.

Advanced queries using boolean operations, parentheses, or field specific lookup can be used to find the strings you want.

When no field is defined, the lookup happens on *Source*, *Translate* and *Context* fields.

The screenshot shows the Weblate dashboard with a dark header bar containing navigation links: Weblate, Dashboard, Projects, Languages, and Checks. Below the header, there are tabs for 'Watched translations' (0), 'Suggested translations' (0), 'Insights', and a 'Search' button. The main content area is titled 'Search' and includes a search bar with a dropdown menu set to 'All strings'. Below the search bar is an 'Advanced query builder' section with fields for 'Source strings', 'Search for...', and 'String has suggestion'. There are also filters for 'Exact' and 'String changed after'. A 'Query examples' section lists various search queries with their corresponding Weblate query syntax and an 'Add' button for each. The footer of the interface includes the text 'Powered by Weblate 4.8' and links to 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

Search

All strings ▾

Sort By ▾

Advanced query builder

Source strings ▾ Search for... ☐ Exact Add String has suggestion ▾ Add

String changed after ▾ mm/dd/yyyy ☐ Add

Query examples

Review strings changed by other users	<code>changed:>=2021-07-21 AND NOT changed_by:testuser</code>	Add
Translated strings	<code>state:>=translated</code>	Add
Strings with comments	<code>has:comment</code>	Add
Strings with any failing checks	<code>has:check</code>	Add
Strings with suggestions from others	<code>has:suggestion AND NOT suggestion_author:testuser</code>	Add
Approved strings with suggestions	<code>state:approved AND has:suggestion</code>	Add
All untranslated strings added the past month	<code>added:>=2021-07-21 AND state:<=needs-editing</code>	Add
Translated strings in a certain language	<code>is:translated AND language:cs</code>	Add

Search

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

1.7.1 Kërkim i thjeshtë

Any phrase typed into the search box is split into words. Strings containing any of them are shown. To look for an exact phrase, put «the searchphrase» into quotes (both single (') and double (") quotes will work): "this is a quoted string" or 'another quoted string'.

1.7.2 Fusha

source:TEXT Source string case insensitive search.

target:TEXT Target string case insensitive search.

context:TEXT Context string case insensitive search.

key:TEXT Key string case insensitive search.

note:TEXT Comment string case insensitive search.

location:TEXT Location string case insensitive search.

priority:NUMBER Përparësi vargu.

added:DATETIME Timestamp for when the string was added to Weblate.

state:TEXT State search (approved, translated, needs-editing, empty, read-only), supports *Operatorë fushash*.

pending:BOOLEAN String pending for flushing to VCS.

has:TEXT Search for string having attributes - plural, context, suggestion, comment, check, dismissed-check, translation, variant, screenshot, flags, explanation, glossary, note.

is:TEXT Search for string states (pending, translated, untranslated).

language:TEXT String target language.

component:TEXT Component slug or name case insensitive search, see *Component slug* and *Emër përbërësi*.

project:TEXT Identifikues projekti, shihni *Identifikues URL-je*.

changed_by:TEXT String was changed by author with given username.

changed:DATETIME String content was changed on date, supports *Operatorë fushash*.

change_time:DATETIME String was changed on date, supports *Operatorë fushash*, unlike changed this includes event which don't change content and you can apply custom action filtering using *change_action*.

change_action:TEXT Filters on change action, useful together with *change_time*. Accepts English name of the change action, either quoted and with spaces or lowercase and spaces replaced by a hyphen. See *Searching for changes* for examples.

check:TEXT Për vargun ka kontroll të dështuar.

dismissed_check:TEXT String has dismissed check.

comment:TEXT Kërko te komente përdoruesi.

comment_author:TEXT Filtrojini sipas autori komentesh.

suggestion:TEXT Kërko te sugjerime.

suggestion_author:TEXT Filtroji sipas autori sugjerimesh.

explanation:TEXT Search in explanations.

1.7.3 Operatorë buelanë

You can combine lookups using AND, OR, NOT and parentheses to form complex queries. For example: `state:translated AND (source:hello OR source:bar)`

1.7.4 Operatorë fushash

You can specify operators, ranges or partial lookups for date or numeric searches:

state:>=translated State is translated or better (approved).

ndryshuar më: 2019 Ndryshuar në vitin 2019.

changed:[2019-03-01 to 2019-04-01] Changed between two given dates.

1.7.5 Exact operators

You can do an exact match query on different string fields using = operator. For example, to search for all source strings exactly matching `hello world`, use: `source:="hello world"`. For searching single word expressions, you can skip quotes. For example, to search for all source strings matching `hello`, you can use: `source:=hello`.

1.7.6 Searching for changes

Të reja në versionin 4.4.

Searching for history events can be done using `change_action` and `change_time` operators.

For example, searching for strings marked for edit in 2018 can be entered as `change_time:2018 AND change_action:marked-for-edit` or `change_time:2018 AND change_action:"Marked for edit"`.

1.7.7 Shprehje të rregullta

Anywhere text is accepted you can also specify a regular expression as `r"regexp"`.

For example, to search for all source strings which contain any digit between 2 and 5, use `source:r"[2-5]"`.

1.7.8 Predefined queries

You can select out of predefined queries on the search page, this allows you to quickly access the most frequent searches:

W

Weblate

Dashboard

Projects

Languages

Checks

WebplateOrg

Django

Czech

Translate

translated 96%

K

<

1 / 1

>

>I

Custom search '%(count)s word'

Zen

Not translated strings • state:empty

Strings needing action • state:<translated

Translated strings • state:>=translated

Strings marked for edit • state:needs-editing

Strings with suggestions • has:suggestion

Strings with variants • has:variant

Strings with labels • has:label

Strings with context • has:context

Strings needing action without suggestions • state:<translated AND NOT has:suggestion

Strings with comments • has:comment

Strings with any failing checks • has:check

Approved strings • state:approved

Strings waiting for review • state:translated

Translation

English

Singular

%(count)s word

Plural

%(count)s words

Czech, One

%(count)s slovo

Czech, Few

%(count)s slova

Czech, Other

%(count)s slov

Plural formula: (n==1) ? 0 : (n>=2 && n<=4) ? 1 : 2

☐ Needs editing

Save

Suggest

Skip

Nearby strings 20

Comments

Automatic suggestions

Other languages 3

History

New comment

Comment on this string for fellow translators and developers to read.

Scope

Translation comment, discussions with other translators

Is your comment specific to this translation or generic for all of them?

New comment

You can use Markdown and mention users by @username.

Save

Explanation

No explanation currently provided.

Labels

No labels currently set.

Flags

python-format

Source string location

weblate/templates/translation.html:149

String age

13 seconds ago

Source string age

14 seconds ago

Translation file

weblate/locale/cs/LC_MESSAGES/django.po, string 5

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

50

Kapitulli 1. Dokumentime përdoruesi

1.7.9 Renditje përfundimesh

There are many options to order the strings according to your needs:

The screenshot shows the Weblate web interface. At the top, there's a navigation bar with 'Weblate', 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below it, the breadcrumb 'WeblateOrg / Django / Czech / Translate' is visible, along with a 'translated 96%' indicator. The main area shows a string being translated from English to Czech. The English string is 'The string uses three dots (...) instead of an ellipsis character (...)'. The Czech string is empty. A dropdown menu is open, showing various sorting options: 'Position and priority', 'Position', 'Priority', 'Labels', 'Source string', 'Translated string', 'Age of string', 'Number of words', 'Number of comments', 'Number of failing checks', and 'Key'. Below the string input, there are buttons for 'Save', 'Suggest', and 'Skip'. At the bottom, there's a 'New comment' section with a text area and a 'Save' button. On the right side, there's a sidebar with 'Nearby strings', 'Comments', 'Automatic suggestions', and 'Other languages'. The 'Comments' tab is active, showing a list of comments with fields for 'Explanation', 'Labels', 'Flags', 'Source string location', 'String age', 'Source string age', and 'Translation file'.

1.8 Rrjedha pune përkthimi

Using Weblate is a process that brings your users closer to you, by bringing you closer to your translators. It is up to you to decide how many of its features you want to make use of.

The following is not a complete list of ways to configure Weblate. You can base other workflows on the most usual examples listed here.

1.8.1 Hyrje për përkthim

The *access control* is not discussed in detail as a whole in the workflows, as most of its options can be applied to any workflow. Please consult the respective documentation on how to manage access to translations.

In the following chapters, *any user* means a user who has access to the translation. It can be any authenticated user if the project is public, or a user that has a *Translate* permission for the project.

1.8.2 Translation states

Each translated string can be in one of following states:

Të papërkthyer Translation is empty, it might or not be stored in the file, depending on the file format.

Lyp përpunim Translation needs editing, this is usually the result of a source string change, fuzzy matching or translator action. The translation is stored in the file, depending on the file format it might be marked as needing edit (for example as it gets a *fuzzy* flag in the Gettext file).

Në pritje të shqyrtimit Translation is made, but not reviewed. It is stored in the file as a valid translation.

I miratuar Translation has been approved in the review. It can no longer be changed by translators, but only by reviewers. Translators can only add suggestions to it.

Sugjerime Suggestions are stored in Weblate only and not in the translation file.

The states are represented in the translation files when possible.

Ndihmëz: In case file format you use does not support storing states, you might want to use *Vëru shenjë përkthimeve të pandryshuara si “Lyp përditësim”* addon to flag unchanged strings as needing editing.

Shihni edhe:

Translation types capabilities, Rrjedha pune përkthimi

1.8.3 Përkthim i drejtpërdrejtë

This is most usual setup for smaller teams, anybody can directly translate. This is also the default setup in Weblate.

- Përkthime mund të përpunojë *cilido përdorues*.
- Suggestions are optional ways to suggest changes, when translators are not sure about the change.

Setting	Vlerë	Shënim
Aktivizoni shqyrtime	off	Formësuar në shkallë projekti.
Enable suggestions	on	It is useful for users to be able to suggest when they are not sure.
Votim sugjerimesh	off	
Vetëprano sugjerime	0	
Grup përkthyesish	<i>Përdorues</i>	Or <i>Translate</i> with <i>per-project access control</i> .
Grup shqyrtuesish	N/A	Not used.

1.8.4 Peer review

With this workflow, anybody can add suggestions, and need approval from additional member(s) before it is accepted as a translation.

- Sugjerime mund të shtojë *cilido përdorues*.
- Për sugjerime mund të votojë *cilido përdorues*.
- Suggestions become translations when given a predetermined number of votes.

Setting	Vlerë	Shënim
Aktivizoni shqyrtime	off	Formësuar në shkallë projekti.
Enable suggestions	on	
Votim sugjerimesh	off	
Vetëprano sugjerime	1	You can set higher value to require more peer reviews.
Grup përkthyesish	<i>Përdorues</i>	Or <i>Translate</i> with <i>per-project access control</i> .
Grup shqyrtuesish	N/A	Not used, all translators review.

1.8.5 Shqyrtues enkas

Të reja në versionin 2.18: The proper review workflow is supported since Weblate 2.18.


With dedicated reviewers you have two groups of users, one able to submit translations, and one able to review them to ensure translations are consistent and that the quality is good.

- *Any user* can edit unapproved translations.
- *Shqyrtuesi* mund të miratojë / shmtratojë vargje.
- *Reviewer* can edit all translations (including approved ones).
- Suggestions can also be used to suggest changes for approved strings.

Setting	Vlerë	Shënim
Aktivizoni shqyrtime	on	Formësuar në shkallë projekti.
Enable suggestions	off	It is useful for users to be able to suggest when they are not sure.
Votim sugjerimesh	off	
Vetëprano sugjerime	0	
Grup përkthyesish	<i>Përdorues</i>	Or <i>Translate</i> with <i>per-project access control</i> .
Grup shqyrtuesish	<i>Shqyrtues</i>	Or <i>Review</i> with <i>per-project access control</i> .

1.8.6 Turning on reviews

Reviews can be turned on in the project configuration, from the *Workflow* subpage of project settings (to be found in the *Manage* → *Settings* menu):




Shënim: Depending on Weblate configuration, the setting might not be available to you. For example on Hosted Weblate this is not available for projects hosted for free.

1.8.7 Quality gateway for the source strings

In many cases the original source language strings are coming from developers, because they write the code and provide initial strings. However developers are often not a native speakers in the source language and do not provide desired quality of the source strings. The intermediate translation can help you in addressing this - there is additional quality gateway for the strings between developers and translators and users.

By setting *Kartelë gjuhe ndërmjetëse*, this file will be used as source for the strings, but it will be edited to source language to polish it. Once the string is ready in the source language, it will be also available for translators to translate into additional languages.



Shihni edhe:

Kartelë gjuhe ndërmjetëse, Kartelë njëgjuhëshe gjuhe bazë, Formate dygjuhësh dhe njëgjuhësh

1.8.8 Shqyrtim vargjes burim

With *Aktivizo shqyrtime burimi* enabled, the review process can be applied on the source strings. Once enabled, users can report issues in the source strings. The actual process depends on whether you use bilingual or monolingual formats.

For monolingual formats, the source string review behaves similarly as with *Shqyrtues enkas* - once issue is reported on the source string, it is marked as *Needs editing*.

The bilingual formats do not allow direct editing of the source strings (these are typically extracted directly from the source code). In this case *Source needs review* label is attached to strings reported by translators. You should review such strings and either edit them in the source or remove the label.

Shihni edhe:

Formate dygjuhësh dhe njëgjuhësh, Shqyrtues enkas, labels, Komentë

1.9 Pyetje të Bëra Rëndom

1.9.1 Formësim

Si të krijohet një rrjedhë pune e automatizuar?

Weblate can handle all the translation things semi-automatically for you. If you give it push access to your repository, the translations can happen without interaction, unless some merge conflict occurs.

1. Set up your Git repository to tell Weblate when there is any change, see *Hook-e njoftimesh* for info on how to do it.
2. Set a push URL at your *Component configuration* in Weblate, this allows Weblate to push changes to your repository.
3. Turn on *Push on commit* on your *Component configuration* in Weblate, this will make Weblate push changes to your repository whenever they happen at Weblate.

Shihni edhe:

Përkthim në vazhdimësi, Shmangie përplasjesh përzierje

How to access repositories over SSH?

Please see *Hyrje në depo* for info on setting up SSH keys.

How to fix merge conflicts in translations?

Merge conflicts happen from time to time when the translation file is changed in both Weblate and the upstream repository concurrently. You can usually avoid this by merging Weblate translations prior to making changes in the translation files (e.g. before running msgmerge). Just tell Weblate to commit all pending translations (you can do it in *Repository maintenance* in the *Manage* menu) and merge the repository (if automatic push is not on).

If you've already encountered a merge conflict, the easiest way to solve all conflicts locally on your machine, is to add Weblate as a remote repository, merge it into upstream and fix any conflicts. Once you push changes back, Weblate will be able to use the merged version without any other special actions.

Shënim: Depending on your setup, access to the Weblate repository might require authentication. When using the built-in *Git exporter* in Weblate, you authenticate with your username and the API key.

```
# Commit all pending changes in Weblate, you can do this in the UI as well:
wlc commit
# Lock the translation in Weblate, again this can be done in the UI as well:
wlc lock
# Add Weblate as remote:
git remote add weblate https://hosted.weblate.org/git/project/component/
# You might need to include credentials in some cases:
git remote add weblate https://username:APIKEY@hosted.weblate.org/git/project/
↪component/

# Update weblate remote:
git remote update weblate

# Merge Weblate changes:
git merge weblate/main

# Resolve conflicts:
edit ...
git add ...
...
git commit

# Push changes to upstream repository, Weblate will fetch merge from there:
git push

# Open Weblate for translation:
wlc unlock
```

If you're using multiple branches in Weblate, you can do the same to all of them:

```
# Add and update Weblate remotes
git remote add weblate-one https://hosted.weblate.org/git/project/one/
git remote add weblate-second https://hosted.weblate.org/git/project/second/
git remote update weblate-one weblate-second

# Merge QA_4_7 branch:
git checkout QA_4_7
git merge weblate-one/QA_4_7
... # Resolve conflicts
git commit

# Merge main branch:
git checkout main
git merge weblate-second/main
... # Resolve conflicts
git commit

# Push changes to the upstream repository, Weblate will fetch the merge from there:
git push
```

In case of gettext PO files, there is a way to merge conflicts in a semi-automatic way:

Fetch and keep a local clone of the Weblate Git repository. Also get a second fresh local clone of the upstream Git repository (i. e. you need two copies of the upstream Git repository: An intact and a working copy):

```
# Add remote:
git remote add weblate /path/to/weblate/snapshot/
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
# Update Weblate remote:
git remote update weblate

# Merge Weblate changes:
git merge weblate/main

# Resolve conflicts in the PO files:
for PO in `find . -name '*.po'` ; do
    msgcat --use-first /path/to/weblate/snapshot/$PO\
            /path/to/upstream/snapshot/$PO -o $PO.merge
    msgmerge --previous --lang=${PO%.po} $PO.merge domain.pot -o $PO
    rm $PO.merge
    git add $PO
done
git commit

# Push changes to the upstream repository, Weblate will fetch merge from there:
git push
```

Shihni edhe:

How to export the Git repository that Weblate uses?, Përkthim në vazhdimësi, Shmangie përplasjesh përzierjeje, Klient Weblate

How do I translate several branches at once?

Weblate supports pushing translation changes within one *Project configuration*. For every *Component configuration* which has it turned on (the default behavior), the change made is automatically propagated to others. This way translations are kept synchronized even if the branches themselves have already diverged quite a lot, and it is not possible to simply merge translation changes between them.

Once you merge changes from Weblate, you might have to merge these branches (depending on your development workflow) discarding differences:

```
git merge -s ours origin/maintenance
```

Shihni edhe:

Keeping translations same across components

How to translate multi-platform projects?

Weblate supports a wide range of file formats (see *Formate të mbuluar kartelash*) and the easiest approach is to use the native format for each platform.

Once you have added all platform translation files as components in one project (see *Adding translation projects and components*), you can utilize the translation propagation feature (turned on by default, and can be turned off in the *Component configuration*) to translate strings for all platforms at once.

Shihni edhe:

Keeping translations same across components

How to export the Git repository that Weblate uses?

There is nothing special about the repository, it lives under the `DATA_DIR` directory and is named `vcs/<project>/<component>/`. If you have SSH access to this machine, you can use the repository directly.

For anonymous access, you might want to run a Git server and let it serve the repository to the outside world.

Alternatively, you can use *Git exporter* inside Weblate to automate this.

What are the options for pushing changes back upstream?

This heavily depends on your setup, Weblate is quite flexible in this area. Here are examples of some workflows used with Weblate:

- Weblate automatically pushes and merges changes (see *Si të krijohet një rrjedhë pune e automatizuar?*).
- You manually tell Weblate to push (it needs push access to the upstream repository).
- Somebody manually merges changes from the Weblate git repository into the upstream repository.
- Somebody rewrites history produced by Weblate (e.g. by eliminating merge commits), merges changes, and tells Weblate to reset the content in the upstream repository.

Of course you are free to mix all of these as you wish.

How can I limit Weblate access to only translations, without exposing source code to it?

You can use `git submodule` for separating translations from source code while still having them under version control.

1. Krijoni një depo me kartelat tuaja të përkthimit.
2. Shtoni te kodi juaj këtë si një nënmodul:

```
git submodule add git@example.com:project-translations.git path/to/translations
```

3. Link Weblate to this repository, it no longer needs access to the repository containing your source code.
4. You can update the main repository with translations from Weblate by:

```
git submodule update --remote path/to/translations
```

Please consult the `git submodule` documentation for more details.

How can I check whether my Weblate is set up properly?

Weblate includes a set of configuration checks which you can see in the admin interface, just follow the *Performance report* link in the admin interface, or open the `/manage/performance/` URL directly.

Why are all commits committed by Weblate <noreply@weblate.org>?

This is the default committer name, configured when you create a translation component. You can change it in the administration at any time.

The author of every commit (if the underlying VCS supports it) is still recorded correctly as the user that made the translation.

Shihni edhe:

Component configuration

1.9.2 Usage

Si t'i shqyrtoj përkthimet e të tjerëve?

- There are several review based workflows available in Weblate, see *Rrjedha pune përkthimi*.
- You can subscribe to any changes made in *Njoftime* and then check others contributions as they come in by e-mail.
- There is a review tool available at the bottom of the translation view, where you can choose to browse translations made by others since a given date.

Shihni edhe:

Rrjedha pune përkthimi

How do I provide feedback on a source string?

On context tabs below translation, you can use the *Comments* tab to provide feedback on a source string, or discuss it with other translators.

Shihni edhe:

report-source, *Komente*

How can I use existing translations while translating?

- All translations within Weblate can be used thanks to shared translation memory.
- You can import existing translation memory files into Weblate.
- Use the import functionality to load compendium as translations, suggestions or translations needing review. This is the best approach for a one-time translation using a compendium or a similar translation database.
- You can set up *tmsserver* with all databases you have and let Weblate use it. This is good when you want to use it several times during translation.
- Another option is to translate all related projects in a single Weblate instance, which will make it automatically pick up translations from other projects as well.

Shihni edhe:

Përkthim nga makina, Sugjerime të automatizuara, Kujtesë Përkthimesh

Does Weblate update translation files besides translations?

Weblate tries to limit changes in translation files to a minimum. For some file formats it might unfortunately lead to reformatting the file. If you want to keep the file formatted your way, please use a pre-commit hook for that.

Shihni edhe:

updating-target-files

Where do language definitions come from and how can I add my own?

The basic set of language definitions is included within Weblate and Translate-toolkit. This covers more than 150 languages and includes info about plural forms or text direction.

You are free to define your own languages in the administrative interface, you just need to provide info about it.

Shihni edhe:

Language definitions

Can Weblate highlight changes in a fuzzy string?

Weblate supports this, however it needs the data to show the difference.

For Gettext PO files, you have to pass the parameter `--previous` to **msgmerge** when updating PO files, for example:

```
msgmerge --previous -U po/cs.po po/phpmyadmin.pot
```

For monolingual translations, Weblate can find the previous string by ID, so it shows the differences automatically.

Why does Weblate still show old translation strings when I've updated the template?

Weblate does not try to manipulate the translation files in any way other than allowing translators to translate. So it also does not update the translatable files when the template or source code have been changed. You simply have to do this manually and push changes to the repository, Weblate will then pick up the changes automatically.

Shënim: It is usually a good idea to merge changes done in Weblate before updating translation files, as otherwise you will usually end up with some conflicts to merge.

For example with gettext PO files, you can update the translation files using the **msgmerge** tool:

```
msgmerge -U locale/cs/LC_MESSAGES/django.mo locale/django.pot
```

In case you want to do the update automatically, you can install add-on *Përditësoni kartela PO, që të përputhen me POT (msgmerge)*.

Shihni edhe:

updating-target-files

1.9.3 Diagnostikim

Requests sometimes fail with «too many open files» error

This happens sometimes when your Git repository grows too much and you have many of them. Compressing the Git repositories will improve this situation.

Rruga më e lehtë për ta bërë këtë është të xhirohet:

```
# Go to DATA_DIR directory
cd data/vcs
# Compress all Git repositories
for d in */* ; do
    pushd $d
    git gc
    popd
done
```

Shihni edhe:

DATA_DIR

When accessing the site I get a «Bad Request (400)» error

This is most likely caused by an improperly configured `ALLOWED_HOSTS`. It needs to contain all hostnames you want to access on your Weblate. For example:

```
ALLOWED_HOSTS = ["weblate.example.com", "weblate", "localhost"]
```

Shihni edhe:

Allowed hosts setup

What does mean «There are more files for the single language (en)»?

This typically happens when you have translation file for source language. Weblate keeps track of source strings and reserves source language for this. The additional file for same language is not processed.

- Në rast se dëshirohet përkthimi në gjuhën burim, ju lutemi, ndryshoni *Gjuhë burimi* te rregullimet e përbërësve.
- Në rast se s'dëshirohet përkthimi në gjuhën burim, ju lutemi, hiqeni prej depos.
- In case the translation file for the source language is needed, but should be ignored by Weblate, please adjust the *Filtër gjuhësh* to exclude it.

Ndihmëz: You might get similar error message for other languages as well. In that case the most likely reason is that several files map to single language in Weblate.

This can be caused by using obsolete language codes together with new one (j_a and j_p for Japanese) or including both country specific and generic codes (f_r and f_r_FR). See *Parsing language codes* for more details.

1.9.4 Veçori

Does Weblate support other VCSes than Git and Mercurial?

Weblate currently does not have native support for anything other than *Git* (with extended support for *GitHub*, *Gerrit* and *Subversion*) and *Mercurial*, but it is possible to write backends for other VCSes.

You can also use *Git remote helpers* in Git to access other VCSes.

Weblate also supports VCS-less operation, see *Kartela vendore*.

Shënim: For native support of other VCSes, Weblate requires using distributed VCS, and could probably be adjusted to work with anything other than Git and Mercurial, but somebody has to implement this support.

Shihni edhe:

Integrim kontrolli versioni

How does Weblate credit translators?

Every change made in Weblate is committed into VCS under the translators name. This way every single change has proper authorship, and you can track it down using the standard VCS tools you use for code.

Additionally, when the translation file format supports it, the file headers are updated to include the translator's name.

Shihni edhe:

`list_translators`, `../devel/reporting`

Why does Weblate force showing all PO files in a single tree?

Weblate was designed in a way that every PO file is represented as a single component. This is beneficial for translators, so they know what they are actually translating.

Ndryshuar në versionin 4.2: Translators can translate all the components of a project into a specific language as a whole.

Why does Weblate use language codes such `sr_Latn` or `zh_Hant`?

These are language codes defined by [RFC 5646](#) to better indicate that they are really different languages instead previously wrongly used modifiers (for `@latin` variants) or country codes (for Chinese).

Weblate still understands legacy language codes and will map them to current one - for example `sr@latin` will be handled as `sr_Latn` or `zh@CN` as `zh_Hans`.

Shënim: Weblate defaults to POSIX style language codes with underscore, see [Language definitions](#) for more details.

Shihni edhe:

[Language definitions](#), [Stil kodi gjuhe](#), [Shtim përkthimesh të reja](#)

1.10 Formate të mbuluar kartelash

Weblate supports most translation format understood by [translate-toolkit](#), however each format being slightly different, some issues with formats that are not well tested can arise.

Shihni edhe:

[Translation Related File Formats](#)

Shënim: When choosing a file format for your application, it's better to stick some well established format in the toolkit/platform you use. This way your translators can additionally use whatever tools they are used to, and will more likely contribute to your project.

1.10.1 Formate dygjuhësh dhe njëgjuhësh

Both monolingual and bilingual formats are supported. Bilingual formats store two languages in single file—source and translation (typical examples are *GNU gettext*, *XLIFF* or *Vargje Apple iOS*). On the other side, monolingual formats identify the string by ID, and each language file contains only the mapping of those to any given language (typically *Burime vargjes Android*). Some file formats are used in both variants, see the detailed description below.

For correct use of monolingual files, Weblate requires access to a file containing complete list of strings to translate with their source—this file is called *Kartelë njëgjuhëshe gjuhe bazë* within Weblate, though the naming might vary in your paradigm.

Additionally this workflow can be extended by utilizing *Kartelë gjuhe ndërmjetëse* to include strings provided by developers, but not to be used as is in the final strings.

1.10.2 Pikasje e vetvetishme

Weblate can automatically detect several widespread file formats, but this detection can harm your performance and will limit features specific to given file format (for example automatic addition of new translations).

1.10.3 Translation types capabilities

Capabilities of all supported formats:

Format	Linguality	Shumësa	Komente	Kontekst	Vendndodhje	Flags	Additional states
<i>GNU gettext</i>	dygjuhëshe	po	po	po	po	po ⁹	lyp përpunim
<i>Monolingual gettext</i>	mono	po	po	po	po	po ⁷	lyp përpunim
<i>XLIFF</i>	të dyja	po	po	po	po	po ¹⁰	lyp përpunim, i miratuar
<i>Veti Java</i>	të dyja	no	po	no	no	no	
<i>mi18n lang files</i>	mono	no	po	no	no	no	
<i>Veti GWT</i>	mono	po	po	no	no	no	
<i>Përkthime Joomla</i>	mono	no	po	no	po	no	
<i>Qt Linguist .ts</i>	të dyja	po	po	no	po	po ⁷	lyp përpunim
<i>Burime vargjes Android</i>	mono	po	po ⁷	no	no	po ⁷	
<i>Vargje Apple iOS</i>	dygjuhëshe	no	po	no	no	no	
<i>Vargje PHP</i>	mono	no ¹¹	po	no	no	no	
<i>Kartela JSON</i>	mono	no	no	no	no	no	
<i>Kartela JSON i18next</i>	mono	po	no	no	no	no	
<i>go-i18n JSON files</i>	mono	po	no	no	no	no	

vazhdon në faqen pasuese

Tabela 1 – vazhduar nga faqja e mëparshme

Format	Linguality	Shumësa	Komente	Kontekst	Vendndodhje	Flags	Additional states
<i>Kartelë ARB</i>	mono	po	po	no	no	no	
<i>JSON WebExtension</i>	mono	po	po	no	no	no	
<i>Kartela burimesh .XML</i>	mono	no	po	no	no	po ⁹	
<i>Kartela CSV</i>	të dyja	no	po	po	po	no	lyp përpunim
<i>Kartela YAML</i>	mono	no	po	no	no	no	
<i>Kartela Ruby YAML</i>	mono	po	po	no	no	no	
<i>Kartela DTD</i>	mono	no	no	no	no	no	
<i>Kartelë XML e sheshitë</i>	mono	no	no	no	no	po ⁹	
<i>Kartela Windows RC</i>	mono	no	po	no	no	no	
<i>Excel Open XML</i>	mono	no	po	po	po	no	lyp përpunim
<i>Kartela tejtëdhënash shitoreje aplikacionesh</i>	mono	no	no	no	no	no	
<i>Kartela titrash</i>	mono	no	no	no	po	no	
<i>Kartela HTML</i>	mono	no	no	no	no	no	
<i>Format OpenDocument</i>	mono	no	no	no	no	no	
<i>Format IDML</i>	mono	no	no	no	no	no	
<i>Përkthime INI</i>	mono	no	no	no	no	no	
<i>Inno Setup INI translations</i>	mono	no	no	no	no	no	
<i>TermBase eXchange format</i>	dygjuhëshe	no	po	no	no	po ⁹	
<i>Kartela tekst</i>	mono	no	no	no	no	no	
<i>Stringsdict format</i>	mono	po	po	no	no	no	
<i>Fluent format</i>	mono	no ¹²	po	no	no	no	

Vargje vetëm për lexim

Të reja në versionin 3.10.

Read-only strings from translation files will be included, but can not be edited in Weblate. This feature is natively supported by few formats (*XLIFF* and *Burime vargjeshe Android*), but can be emulated in others by adding a read-only flag, see *Customizing behavior using flags*.

1.10.4 GNU gettext

Most widely used format for translating libre software.

Contextual info stored in the file is supported by adjusting its headers or linking to corresponding source files.

The bilingual gettext PO file typically looks like this:

```
#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "Monday"
msgstr "Pondělí"

#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "Tuesday"
msgstr "Úterý"

#: weblate/accounts/avatar.py:163
msgctxt "No known user"
msgid "None"
msgstr "Žádný"
```

Typical Weblate <i>Component configuration</i>	
Filemask	po/* .po
Kartelë njëgjuhëshe gjuhe bazë	<i>Empty</i>
Gjedhe për përkthime të reja	po/messages.pot
Format kartelash	<i>Gettext PO file</i>

Shihni edhe:

devel/gettext, devel/sphinx, *Gettext on Wikipedia*, *PO Files*, *Përditësoni ndryshoren ALL_LINGUAS te kartela «configure»*, *Përshatni përfundimin e gettext-it*, *Përditëso kartelën LINGUAS*, *Prodho kartela MO*, *Përditësoni kartela PO, që të përputhen me POT (msgmerge)*

¹ Shihni *Formate dygjuhësh dhe njëgjuhësh*

² Plurals are necessary to properly localize strings with variable count.

³ Comments can be used to pass additional info about the string to translate.

⁴ Context is used to differentiate identical strings used in different scopes (for example *Sun* can be used as an abbreviated name of the day «Sunday» or as the name of our closest star).

⁵ Location of a string in source code might help proficient translators figure out how the string is used.

⁸ Shihni *Customizing behavior using flags*

⁶ Additional states supported by the file format in addition to «Not translated» and «Translated».

⁹ The gettext type comments are used as flags.

¹⁰ The flags are extracted from the non-standard attribute `weblate-flags` for all XML based formats. Additionally `max-length:N` is supported through the `maxwidth` attribute as defined in the XLIFF standard, see *Specifying translation flags*.

⁷ XML comment placed before the `<string>` element, parsed as a developer comment.

¹¹ The plurals are supported only for Laravel which uses in string syntax to define them, see *Localization in Laravel*.

¹² Plurals are handled in the syntax of the strings and not exposed as plurals in Weblate.

Monolingual gettext

Some projects decide to use gettext as monolingual formats—they code just the IDs in their source code and the string then needs to be translated to all languages, including English. This is supported, though you have to choose this file format explicitly when importing components into Weblate.

The monolingual gettext PO file typically looks like this:

```
#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-monday"
msgstr "Pondělí"

#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-tuesday"
msgstr "Úterý"

#: weblate/accounts/avatar.py:163
msgid "none-user"
msgstr "Žádný"
```

While the base language file will be:

```
#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-monday"
msgstr "Monday"

#: weblate/media/js/bootstrap-datepicker.js:1421
msgid "day-tuesday"
msgstr "Tuesday"

#: weblate/accounts/avatar.py:163
msgid "none-user"
msgstr "None"
```

Typical Weblate <i>Component configuration</i>	
Filemask	po/* .po
Kartelë njëgjuhëshe gjuhe bazë	po/en .po
Gjedhe për përkthime të reja	po/messages .pot
Format kartelash	<i>Gettext PO file (monolingual)</i>

1.10.5 XLIFF

XML-based format created to standardize translation files, but in the end it is one of [many standards](#), in this area.

XML Localization Interchange File Format (XLIFF) is usually used as bilingual, but Weblate supports it as monolingual as well.

Shihni edhe:

XML Localization Interchange File Format (XLIFF) specification

Translation states

Ndryshuar në versionin 3.3: Weblate ignored the `state` attribute prior to the 3.3 release.

The `state` attribute in the file is partially processed and mapped to the «Needs edit» state in Weblate (the following states are used to flag the string as needing edit if there is a target present: `new`, `needs-translation`, `needs-adaptation`, `needs-l10n`). Should the `state` attribute be missing, a string is considered translated as soon as a `<target>` element exists.

If the translation string has `approved="yes"`, it will also be imported into Weblate as «Approved», anything else will be imported as «Waiting for review» (which matches the XLIFF specification).

While saving, Weblate doesn't add those attributes unless necessary:

- The `state` attribute is only added in case string is marked as needing edit.
- The `approved` attribute is only added in case string has been reviewed.
- In other cases the attributes are not added, but they are updated in case they are present.

That means that when using the XLIFF format, it is strongly recommended to turn on the Weblate review process, in order to see and change the approved state of strings.

Similarly upon importing such files (in the upload form), you should choose *Import as translated* under *Processing of strings needing edit*.

Shihni edhe:

Shqyrtues enkas

Hapësira të zbrazëta dhe rreshta të rinj në XLIFF

Generally types or amounts of whitespace is not differentiated between in XML formats. If you want to keep it, you have to add the `xml:space="preserve"` flag to the string.

Për shembull:

```
<trans-unit id="10" approved="yes">
  <source xml:space="preserve">hello</source>
  <target xml:space="preserve">Hello, world!
</target>
</trans-unit>
```

Specifying translation flags

You can specify additional translation flags (see *Customizing behavior using flags*) by using the `weblate-flags` attribute. Weblate also understands `maxwidth` and `font` attributes from the XLIFF specification:

```
<trans-unit id="10" maxwidth="100" size-unit="pixel" font="ubuntu;22:bold">
  <source>Hello %s</source>
</trans-unit>
<trans-unit id="20" maxwidth="100" size-unit="char" weblate-flags="c-format">
  <source>Hello %s</source>
</trans-unit>
```

The `font` attribute is parsed for font family, size and weight, the above example shows all of that, though only font family is required. Any whitespace in the font family is converted to underscore, so `Source Sans Pro` becomes `Source_Sans_Pro`, please keep that in mind when naming the font group (see *Administrim shkronjash*).

String keys

Weblate identifies the units in the XLIFF file by `resname` attribute in case it is present and falls back to `id` (together with `file` tag if present).

The `resname` attribute is supposed to be human friendly identifier of the unit making it more suitable for Weblate to display instead of `id`. The `resname` has to be unique in the whole XLIFF file. This is required by Weblate and is not covered by the XLIFF standard - it does not put any uniqueness restrictions on this attribute.

Typical Weblate <i>Component configuration</i> for bilingual XLIFF	
Filemask	<code>localizations/*.xliff</code>
Kartelë njëgjuhëshe gjuhe bazë	<i>Empty</i>
Gjedhe për përkthime të reja	<code>localizations/en-US.xliff</code>
Format kartelash	<i>Kartelë përkthimi XLIFF</i>

Typical Weblate <i>Component configuration</i> for monolingual XLIFF	
File mask	<code>localizations/*.xliff</code>
Kartelë njëgjuhëshe gjuhe bazë	<code>localizations/en-US.xliff</code>
Gjedhe për përkthime të reja	<code>localizations/en-US.xliff</code>
Format kartelash	<i>Kartelë përkthimi XLIFF</i>

Shihni edhe:

[XLIFF on Wikipedia](#), [XLIFF](#), [font attribute in XLIFF 1.2](#), [maxwidth attribute in XLIFF 1.2](#)

1.10.6 Vetë Java

Format i brendshëm Java për përkthimet.

Java properties are usually used as monolingual translations.

Weblate supports ISO-8859-1, UTF-8 and UTF-16 variants of this format. All of them support storing all Unicode characters, it is just differently encoded. In the ISO-8859-1, the Unicode escape sequences are used (for example `zkou\u0161ka`), all others encode characters directly either in UTF-8 or UTF-16.

Shënim: Loading escape sequences works in UTF-8 mode as well, so please be careful choosing the correct encoding set to match your application needs.

Typical Weblate <i>Component configuration</i>	
Filemask	<code>src/app/Bundle_*.properties</code>
Kartelë njëgjuhëshe gjuhe bazë	<code>src/app/Bundle.properties</code>
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Vetë Java (ISO-8859-1)</i>

Shihni edhe:

[Java properties on Wikipedia](#), [Mozilla and Java properties files](#), [mi18n lang files](#), [Vetë GWT](#), [updating-target-files](#), [Formaton kartelën e vetive Java](#), [Spastro kartela përkthimi](#)

1.10.7 mi18n lang files

Të reja në versionin 4.7.

File format used for JavaScript localization by [mi18n](#). Syntactically it matches *Veti Java*.

Typical Weblate <i>Component configuration</i>	
Filemask	*.lang
Kartelë njëgjuhëshe gjuhe bazë	en-US.lang
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>mi18n lang file</i>

Shihni edhe:

[mi18n Mozilla](#) and Java properties files, *Veti Java*, [updating-target-files](#), *Formaton kartelën e vetive Java*, *Spastro kartela përkthimi*

1.10.8 Vetit GWT

Format i brendshëm GWT për përkthimet.

GWT properties are usually used as monolingual translations.

Typical Weblate <i>Component configuration</i>	
Filemask	src/app/Bundle_*.properties
Kartelë njëgjuhëshe gjuhe bazë	src/app/Bundle.properties
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Veti GWT</i>

Shihni edhe:

[GWT localization guide](#), [GWT Internationalization Tutorial](#), [Mozilla and Java properties files](#), [updating-target-files](#), *Formaton kartelën e vetive Java*, *Spastro kartela përkthimi*

1.10.9 Përkthime INI

Të reja në versionin 4.1.

Format karte INI për përkthime.

INI translations are usually used as monolingual translations.

Typical Weblate <i>Component configuration</i>	
Filemask	language/*.ini
Kartelë njëgjuhëshe gjuhe bazë	language/en.ini
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë INI</i>

Shënim: Weblate only extracts keys from sections within an INI file. In case your INI file lacks sections, you might want to use *Përkthime Joomla* or *Veti Java* instead.

Shihni edhe:

[INI Files](#), *Veti Java*, *Përkthime Joomla*, *Inno Setup INI translations*

1.10.10 Inno Setup INI translations

Të reja në versionin 4.1.

Inno Setup INI file format for translations.

Inno Setup INI translations are usually used as monolingual translations.

Shënim: The only notable difference to *Përkthime INI* is in supporting `%n` and `%t` placeholders for line break and tab.

Typical Weblate <i>Component configuration</i>	
Filemask	language/*.isl
Kartelë njëgjuhëshe gjuhe bazë	language/en.isl
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Inno Setup INI File</i>

Shënim: Only Unicode files (`.isl`) are currently supported, ANSI variant (`.isl`) is currently not supported.

Shihni edhe:

INI Files, *Përkthime Joomla*, *Përkthime INI*

1.10.11 Përkthime Joomla

Të reja në versionin 2.12.

Format i brendshëm Joomla për përkthime.

Joomla translations are usually used as monolingual translations.

Typical Weblate <i>Component configuration</i>	
Filemask	language/*/com_foobar.ini
Kartelë njëgjuhëshe gjuhe bazë	language/en-GB/com_foobar.ini
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë Përkthimi Joomla</i>

Shihni edhe:

Specification of Joomla language files, Mozilla and Java properties files, *Përkthime INI*, *Inno Setup INI translations*

1.10.12 Qt Linguist .ts

Translation format used in Qt based applications.

Qt Linguist files are used as both bilingual and monolingual translations.

Typical Weblate <i>Component configuration</i> when using as bilingual	
Filemask	i18n/app.*.ts
Kartelë njëgjuhëshe gjuhe bazë	<i>Empty</i>
Gjedhe për përkthime të reja	i18n/app.de.ts
Format kartelash	<i>Kartelë Përkthimi Qt Linguist</i>

Typical Weblate <i>Component configuration</i> when using as monolingual	
Filemask	i18n/app.*.ts
Kartelë njëgjuhëshe gjuhe bazë	i18n/app.en.ts
Gjedhe për përkthime të reja	i18n/app.en.ts
Format kartelash	<i>Kartelë Përkthimi Qt Linguist</i>

Shihni edhe:

Qt Linguist manual, Qt .ts, *Formate dygjuhësh dhe njëgjuhësh*

1.10.13 Burime vargjes Android

Android specific file format for translating applications.

Android string resources are monolingual, the *Kartelë njëgjuhëshe gjuhe bazë* is stored in a different location from the others `res/values/strings.xml`.

Typical Weblate <i>Component configuration</i>	
Filemask	res/values-*/strings.xml
Kartelë njëgjuhëshe gjuhe bazë	res/values/strings.xml
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Burim Vargu Android</i>

Shihni edhe:

Android string resources documentation, Android string resources

Shënim: Android *string-array* structures are not currently supported. To work around this, you can break your string arrays apart:

```
<string-array name="several_strings">
  <item>First string</item>
  <item>Second string</item>
</string-array>
```

become:

```
<string-array name="several_strings">
  <item>@string/several_strings_0</item>
  <item>@string/several_strings_1</item>
</string-array>
<string name="several_strings_0">First string</string>
<string name="several_strings_1">Second string</string>
```

The *string-array* that points to the *string* elements should be stored in a different file, and not be made available for translation.

This script may help pre-process your existing strings.xml files and translations: <https://gist.github.com/paour/11291062>

1.10.14 Vargje Apple iOS

Apple specific file format for translating applications, used for both iOS and iPhone/iPad application translations. Apple iOS strings are usually used as bilingual translations.

Typical Weblate <i>Component configuration</i>	
Filemask	Resources/*.lproj/Localizable.strings
Kartelë njëgjuhëshe gjuhe bazë	Resources/en.lproj/Localizable.strings or Resources/Base.lproj/Localizable.strings
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Vargje iOS (UTF-8)</i>

Shihni edhe:

Stringsdict format, Apple «strings files» documentation, Mac OSX strings

1.10.15 Vargje PHP

PHP translations are usually monolingual, so it is recommended to specify a base file with (what is most often the) English strings.

Shembull kartele:

```
<?php
$LANG['foo'] = 'bar';
$LANG['foo1'] = 'foo bar';
$LANG['foo2'] = 'foo bar baz';
$LANG['foo3'] = 'foo bar baz bag';
```

Typical Weblate <i>Component configuration</i>	
Filemask	lang/*/texts.php
Kartelë njëgjuhëshe gjuhe bazë	lang/en/texts.php
Gjedhe për përkthime të reja	lang/en/texts.php
Format kartelash	<i>PHP strings</i>

Vargje PHP Laravel

Ndryshuar në versionin 4.1.

The Laravel PHP localization files are supported as well with plurals:

```
<?php
return [
    'welcome' => 'Welcome to our application',
    'apples' => 'There is one apple|There are many apples',
];
```

Shihni edhe:

PHP, Localization in Laravel

1.10.16 Kartela JSON

Të reja në versionin 2.0.

Ndryshuar në versionin 2.16: Since Weblate 2.16 and with [translate-toolkit](#) at-least 2.2.4, nested structure JSON files are supported as well.

Ndryshuar në versionin 4.3: The structure of JSON file is properly preserved even for complex situations which were broken in prior releases.

JSON format is used mostly for translating applications implemented in JavaScript.

Weblate currently supports several variants of JSON translations:

- Simple key / value files, used for example by *vue-i18n* or *react-intl*.
- Files with nested keys.
- *Kartela JSON i18next*
- *go-i18n JSON files*
- *JSON WebExtension*
- *Kartelë ARB*

JSON translations are usually monolingual, so it is recommended to specify a base file with (what is most often the) English strings.

Shembull kartele:

```
{
  "Hello, world!\n": "Ahoj světe!\n",
  "Orangutan has %d banana.\n": "",
  "Try Weblate at https://demo.weblate.org/!\n": "",
  "Thank you for using Weblate.": ""
}
```

Nested files are supported as well (see above for requirements), such a file can look like:

```
{
  "weblate": {
    "hello": "Ahoj světe!\n",
    "orangutan": "",
    "try": "",
    "thanks": ""
  }
}
```

Ndihmëz: The *JSON file* and *JSON nested structure file* can both handle same type of files. Both preserve existing JSON structure when translating.

The only difference between them is when adding new strings using Weblate. The nested structure format parses the newly added key and inserts the new string into the matching structure. For example `app.name` key is inserted as:

```
{
  "app": {
    "name": "Weblate"
  }
}
```

Typical Weblate <i>Component configuration</i>	
Filemask	langs/translation-*.json
Kartelë njëgjuhëshe gjuhe bazë	langs/translation-en.json
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>JSON nested structure file</i>

Shihni edhe:

[JSON](#), [updating-target-files](#), [Përshatni përfundim JSON-i](#), [Spastro kartela përkthimi](#),

1.10.17 Kartela JSON i18next

Ndryshuar në versionin 2.17: Since Weblate 2.17 and with [translate-toolkit](#) at-least 2.2.5, i18next JSON files with plurals are supported as well.

[i18next](#) is an internationalization framework written in and for JavaScript. Weblate supports its localization files with features such as plurals.

i18next translations are monolingual, so it is recommended to specify a base file with (what is most often the) English strings.

Shënim: Weblate supports the i18next JSON v3 format. The v2 and v1 variants are mostly compatible, with exception of how plurals are handled.

Shembull kartele:

```
{
  "hello": "Hello",
  "apple": "I have an apple",
  "apple_plural": "I have {{count}} apples",
  "apple_negative": "I have no apples"
}
```

Typical Weblate <i>Component configuration</i>	
Filemask	langs/*.json
Kartelë njëgjuhëshe gjuhe bazë	langs/en.json
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>kartelë JSON i18next</i>

Shihni edhe:

[JSON](#), [i18next JSON Format](#), [updating-target-files](#), [Përshatni përfundim JSON-i](#), [Spastro kartela përkthimi](#)

1.10.18 go-i18n JSON files

Të reja në versionin 4.1.

go-i18n translations are monolingual, so it is recommended to specify a base file with (what is most often the) English strings.

Shënim: Weblate supports the go-i18n JSON v1 format, for flat JSON formats please use [Kartela JSON](#). The v2 format with hash is currently not supported.

Typical Weblate <i>Component configuration</i>	
Filemask	langs/*.json
Kartelë njëgjuhëshe gjuhe bazë	langs/en.json
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>go-i18n JSON file</i>

Shihni edhe:

JSON, go-i18n, updating-target-files, *Përshtatni përfundim JSON-i, Spastro kartela përkthimi,*

1.10.19 Kartelë ARB

Të reja në versionin 4.1.

ARB translations are monolingual, so it is recommended to specify a base file with (what is most often the) English strings.

Typical Weblate <i>Component configuration</i>	
Filemask	lib/l10n/intl_*.arb
Kartelë njëgjuhëshe gjuhe bazë	lib/l10n/intl_en.arb
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë ARB</i>

Shihni edhe:

JSON, Application Resource Bundle Specification, Internationalizing Flutter apps, updating-target-files, *Përshtatni përfundim JSON-i, Spastro kartela përkthimi*

1.10.20 JSON WebExtension

Të reja në versionin 2.16: This is supported since Weblate 2.16 and with [translate-toolkit](#) at-least 2.2.4.

File format used when translating extensions for Mozilla Firefox or Google Chromium.

Shënim: While this format is called JSON, its specification allows to include comments, which are not part of JSON specification. Weblate currently does not support file with comments.

Shembull kartele:

```
{
  "hello": {
    "message": "Ahoj světe!\n",
    "description": "Description",
    "placeholders": {
      "url": {
        "content": "$1",
        "example": "https://developer.mozilla.org"
      }
    }
  },
  "orangutan": {
    "message": "",
    "description": "Description"
  },
  "try": {
    "message": "",
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "description": "Description"
  },
  "thanks": {
    "message": "",
    "description": "Description"
  }
}

```

Typical Weblate <i>Component configuration</i>	
Filemask	<code>_locales/*/messages.json</code>
Kartelë njëgjuhëshe gjuhe bazë	<code>_locales/en/messages.json</code>
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë WebExtension JSON</i>

Shihni edhe:

JSON, Google chrome.i18n, Mozilla Extensions Internationalization

1.10.21 Kartela burimesh .XML

Të reja në versionin 2.3.

A .XML resource (.resx) file employs a monolingual XML file format used in Microsoft .NET applications. It is interchangeable with .resw, when using identical syntax to .resx.

Typical Weblate <i>Component configuration</i>	
Filemask	<code>Resources/Language.*.resx</code>
Kartelë njëgjuhëshe gjuhe bazë	<code>Resources/Language.resx</code>
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>.NET resource file</i>

Shihni edhe:

.NET Resource files (.resx), updating-target-files, *Spastro kartela përkthimi*

1.10.22 Kartela CSV

Të reja në versionin 2.4.

CSV files can contain a simple list of source and translation. Weblate supports the following files:

- Files with header defining fields (location, source, target, ID, fuzzy, context, translator_comments, developer_comments). This is the recommended approach, as it is the least error prone. Choose *CSV file* as a file format.
- Files with two fields—source and translation (in this order). Choose *Simple CSV file* as a file format.
- Headerless files with fields in order defined by the [translate-toolkit](#): location, source, target, ID, fuzzy, context, translator_comments, developer_comments. Choose *CSV file* as a file format.
- Remember to define *Kartelë njëgjuhëshe gjuhe bazë* when your files are monolingual (see *Formate dygjuhësh dhe njëgjuhësh*).

Sinjalizim: The CSV format currently automatically detects the dialect of the CSV file. In some cases the automatic detection might fail and you will get mixed results. This is especially true for CSV files with newlines in the values. As a workaround it is recommended to omit quoting characters.

Shembull karte:le:

```
Thank you for using Weblate.,Děkujeme za použití Weblate.
```

Typical Weblate <i>Component configuration</i> for bilingual CSV	
Filemask	locale/*.csv
Kartelë njëgjuhëshe gjuhe bazë	<i>Empty</i>
Gjedhe për përkthime të reja	locale/en.csv
Format kartelash	<i>Kartelë CSV</i>

Typical Weblate <i>Component configuration</i> for monolingual CSV	
Filemask	locale/*.csv
Kartelë njëgjuhëshe gjuhe bazë	locale/en.csv
Gjedhe për përkthime të reja	locale/en.csv
Format kartelash	<i>Simple CSV file</i>

Shihni edhe:

CSV

1.10.23 Kartela YAML

Të reja në versionin 2.9.

The plain YAML files with string keys and values. Weblate also extract strings from lists or dictionaries.

Shembull karte:le YAML:

```
weblate:
  hello: ""
  orangutan: ""
  try: ""
  thanks: ""
```

Typical Weblate <i>Component configuration</i>	
Filemask	translations/messages/*.yaml
Kartelë njëgjuhëshe gjuhe bazë	translations/messages.en.yaml
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë YAML</i>

Shihni edhe:

YAML, *Kartela Ruby YAML*

1.10.24 Kartela Ruby YAML

Të reja në versionin 2.9.

Ruby i18n YAML files with language as root node.

Shembull karte:le Ruby i18n YAML:

```
cs:
  weblate:
    hello: ""
    orangutan: ""
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
try: ""
thanks: ""
```

Typical Weblate <i>Component configuration</i>	
Filemask	translations/messages.*.yaml
Kartelë njëgjuhëshe gjuhe bazë	translations/messages.en.yaml
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë Ruby YAML</i>

Shihni edhe:YAML, *Kartela YAML*

1.10.25 Kartela DTD

Të reja në versionin 2.18.

Shembull karte DTD:

```
<!ENTITY hello "">
<!ENTITY orangutan "">
<!ENTITY try "">
<!ENTITY thanks "">
```

Typical Weblate <i>Component configuration</i>	
Filemask	locale/*.dtd
Kartelë njëgjuhëshe gjuhe bazë	locale/en.dtd
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë DTD</i>

Shihni edhe:

Mozilla DTD format

1.10.26 Kartelë XML e sheshtë

Të reja në versionin 3.9.

Shembull karte XML të sheshtë:

```
<?xml version='1.0' encoding='UTF-8'?>
<root>
  <str key="hello_world">Hello World!</str>
  <str key="resource_key">Translated value.</str>
</root>
```

Typical Weblate <i>Component configuration</i>	
Filemask	locale/*.xml
Kartelë njëgjuhëshe gjuhe bazë	locale/en.xml
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Kartelë XML e sheshtë</i>

Shihni edhe:

Flat XML

1.10.27 Kartela Windows RC

Ndryshuar në versionin 4.1: Support for Windows RC files has been rewritten.

Shënim: Support for this format is currently in beta, feedback from testing is welcome.

Shembull kartele Windows RC:

```
LANGUAGE LANG_CZECH, SUBLANG_DEFAULT

STRINGTABLE
BEGIN
    IDS_MSG1                "Hello, world!\n"
    IDS_MSG2                "Orangutan has %d banana.\n"
    IDS_MSG3                "Try Weblate at http://demo.weblate.org/!\n"
    IDS_MSG4                "Thank you for using Weblate."
END
```

Typical Weblate <i>Component configuration</i>	
Filemask	lang/*.rc
Kartelë njëgjuhëshe gjuhe bazë	lang/en-US.rc
Gjedhe për përkthime të reja	lang/en-US.rc
Format kartelash	<i>Kartelë RC</i>

Shihni edhe:

Windows RC files

1.10.28 Kartela tejtëdhënash shitoreje aplikacionesh

Të reja në versionin 3.5.

Metadata used for publishing apps in various app stores can be translated. Currently the following tools are compatible:

- Triple-T gradle-play-publisher
- Fastlane
- F-Droid

The metadata consists of several textfiles, which Weblate will present as separate strings to translate.

Typical Weblate <i>Component configuration</i>	
Filemask	fastlane/android/metadata/*
Kartelë njëgjuhëshe gjuhe bazë	fastlane/android/metadata/en-US
Gjedhe për përkthime të reja	fastlane/android/metadata/en-US
Format kartelash	<i>Kartela tejtëdhënash shitoreje aplikacionesh</i>

Ndihmëz: In case you don't want to translate certain strings (for example changelogs), mark them read-only (see *Customizing behavior using flags*). This can be automated by the *Përpunim në masë*.

1.10.29 Kartela titrash

Të reja në versionin 3.7.

Weblate can translate various subtitle files:

- Kartelë titrash SubRip (*.srt)
- Kartelë titrash MicroDVD (*.sub)
- Advanced Substation Alpha subtitles file (*.ass)
- Kartelë titrash SubStation Alpha (*.ssa)

Typical Weblate <i>Component configuration</i>	
Filemask	path/*.srt
Kartelë njëgjuhëshe gjuhe bazë	path/en.srt
Gjedhe për përkthime të reja	path/en.srt
Format kartelash	<i>Kartelë titrash SubRip</i>

Shihni edhe:

[Subtitles](#)

1.10.30 Excel Open XML

Të reja në versionin 3.2.

Excel Open XML (.xlsx) files can be imported and exported.

When uploading XLSX files for translation, be aware that only the active worksheet is considered, and there must be at least a column called `source` (which contains the source string) and a column called `target` (which contains the translation). Additionally there should be the column called `context` (which contains the context path of the translation string). If you use the XLSX download for exporting the translations into an Excel workbook, you already get a file with the correct file format.

1.10.31 Kartela HTML

Të reja në versionin 4.1.

Shënim: Support for this format is currently in beta, feedback from testing is welcome.

The translatable content is extracted from the HTML files and offered for the translation.

Shihni edhe:

[HTML](#)

1.10.32 Kartela tekst

Të reja në versionin 4.6.

Shënim: Support for this format is currently in beta, feedback from testing is welcome.

The translatable content is extracted from the plain text files and offered for the translation. Each paragraph is translated as a separate string.

There are three flavors of this format:

- Kartelë tekst i thjeshtë
- Kartelë tekst DokuWiki
- Kartelë tekst MediaWiki

Shihni edhe:

[Simple Text Documents](#)

1.10.33 Format OpenDocument

Të reja në versionin 4.1.

Shënim: Support for this format is currently in beta, feedback from testing is welcome.

The translatable content is extracted from the OpenDocument files and offered for the translation.

Shihni edhe:

[OpenDocument Format](#)

1.10.34 Format IDML

Të reja në versionin 4.1.

Shënim: Support for this format is currently in beta, feedback from testing is welcome.

The translatable content is extracted from the Adobe InDesign Markup Language files and offered for the translation.

1.10.35 TermBase eXchange format

Të reja në versionin 4.5.

TBX is an XML format for the exchange of terminology data.

Typical Weblate <i>Component configuration</i>	
Filemask	<code>tbx/*.*.tbx</code>
Kartelë njëgjuhëshe gjuhe bazë	<i>Empty</i>
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>TermBase eXchange file</i>

Shihni edhe:

[TBX on Wikipedia](#), [TBX](#), *Fjalorth*

1.10.36 Stringsdict format

Të reja në versionin 4.8.

Shënim: Support for this format is currently in beta, feedback from testing is welcome.

XML based format used by Apple which is able to store plural forms of a string.

Typical Weblate <i>Component configuration</i>	
Filemask	Resources/*.lproj/Localizable.stringsdict
Kartelë njëgjuhëshe gjuhe bazë	Resources/en.lproj/Localizable.stringsdict or Resources/Base.lproj/Localizable.stringsdict
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Stringsdict file</i>

Shihni edhe:

Vargje Apple iOS, Stringsdict File Format,

1.10.37 Fluent format

Të reja në versionin 4.8.

Shënim: Support for this format is currently in beta, feedback from testing is welcome.

Fluent is a monolingual text format that focuses on asymmetric localization: a simple string in one language can map to a complex multi-variant translation in another language.

Typical Weblate <i>Component configuration</i>	
Filemask	locales/*/messages.ftl
Kartelë njëgjuhëshe gjuhe bazë	locales/en/messages.ftl
Gjedhe për përkthime të reja	<i>Empty</i>
Format kartelash	<i>Fluent file</i>

Shihni edhe:

[Project Fluent website](#)

1.10.38 Supporting other formats

Most formats supported by [translate-toolkit](#) which support serializing can be easily supported, but they did not (yet) receive any testing. In most cases some thin layer is needed in Weblate to hide differences in behavior of different [translate-toolkit](#) storages.

To add support for a new format, the preferred approach is to first implement support for it in the [translate-toolkit](#).

Shihni edhe:

[Translation Related File Formats](#)

1.11 Integrim kontrolli versioni

Weblate currently supports *Git* (with extended support for *GitHub*, *Gerrit* and *Subversion*) and *Mercurial* as version control back-ends.

1.11.1 Hyrje në depo

The VCS repository you want to use has to be accessible to Weblate. With a publicly available repository you just need to enter the correct URL (for example `https://github.com/WeblateOrg/weblate.git`), but for private repositories or for push URLs the setup is more complex and requires authentication.

Accessing repositories from Hosted Weblate

For Hosted Weblate there is a dedicated push user registered on GitHub, Bitbucket, Codeberg and GitLab (with the username *weblate*, e-mail `hosted@weblate.org` and, named *Weblate push user*). You need to add this user as a collaborator and give it appropriate permission to your repository (read-only is okay for cloning, write is required for pushing). Depending on service and your organization settings, this happens immediately, or requires confirmation on the Weblate side.

The *weblate* user on GitHub accepts invitations automatically within five minutes. Manual processing might be needed on the other services, so please be patient.

Once the *weblate* user is added, you can configure *Depo kodi burim* and *URL push-i për depon* using the SSH protocol (for example `git@github.com:WeblateOrg/weblate.git`).

Depo SSH

The most frequently used method to access private repositories is based on SSH. Authorize the public Weblate SSH key (see *Kyç SSH Weblate-i*) to access the upstream repository this way.

Sinjalizim: On GitHub, each key can only be used once, see *Depo GitHub* and *Accessing repositories from Hosted Weblate*.

Weblate also stores the host key fingerprint upon first connection, and fails to connect to the host should it be changed later (see *Verifying SSH host keys*).

In case adjustment is needed, do so from the Weblate admin interface:

The screenshot shows the Weblate admin interface. At the top is a navigation bar with 'Weblate' logo and links to 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below this is a sub-header 'Manage / SSH keys'. A menu bar contains links: 'Weblate status', 'Backups', 'Translation memory', 'Performance report', 'SSH keys' (highlighted), 'Alerts', 'Repositories', 'Users', 'Appearance', 'Tools', and 'Billing'. The main content area has three sections: 1. 'Public SSH key' with an info icon, a text box stating 'Weblate uses SSH key to access remote repositories...', a code block showing an SSH public key, and a 'Download private key' button. 2. 'Known host keys' with an info icon and a table listing host keys. 3. 'Add host key' with an info icon, a text box explaining the need for host key verification, input fields for 'Hostname' and 'Port', and a 'Submit' button. At the bottom, a footer contains 'Powered by Weblate 4.8' and links to 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

Hostname	Key type	Fingerprint
github.com	ssh-rsa	nThbg6kXUpJWGi7E1IGOCspRomTxdCARLviKw6E5SY8

Hostname	Port
<input type="text" value="Hostname"/>	<input type="text" value="Port"/>

Kyç SSH Weblate-i

The Weblate public key is visible to all users browsing the *About* page.

Admins can generate or display the public key currently used by Weblate in the connection (from *SSH keys*) on the admin interface landing page.

Shënim: The corresponding private SSH key can not currently have a password, so make sure it is well protected.

Ndihmëz: Make a backup of the generated private Weblate SSH key.

Verifying SSH host keys

Weblate automatically stores the SSH host keys on first access and remembers them for further use.

In case you want to verify the key fingerprint before connecting to the repository, add the SSH host keys of the servers you are going to access in *Add host key*, from the same section of the admin interface. Enter the hostname you are going to access (e.g. `gitlab.com`), and press *Submit*. Verify its fingerprint matches the server you added.

The added keys with fingerprints are shown in the confirmation message:

The screenshot shows the Weblate web interface. At the top, there's a navigation bar with 'Weblate' logo and links for 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below this, a sub-header shows 'Manage / SSH keys'. A yellow notification banner states: 'Added host key for github.com with fingerprint nThbg6kXUpJWGI7E1IGOCspRomTxdCARLviKw6E5SY8 (ssh-rsa), please verify that it is correct.' The main navigation menu includes 'Weblate status', 'Backups', 'Translation memory', 'Performance report', 'SSH keys' (highlighted), 'Alerts', 'Repositories', 'Users', and 'Appearance'. Below the menu, there are links for 'Tools' and 'Billing'.

The 'SSH keys' section contains three main panels:

- Public SSH key:** A panel with a title bar and an info icon. It contains text explaining that Weblate uses SSH keys to access remote repositories and provides a public key for github.com. The key is displayed in a text area:


```
ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAQCSaaQ/mecRQNFHhk0RjyyaT5fLPdrSE0xln8qp33fDwIUuD+PmxTse5SyJ1ACaCxqSXrkHhazbpEwtQKuKhWX66II+GINkH
Weblate
```

 Below the text area is a 'Download private key' button.
- Known host keys:** A panel with a title bar and an info icon. It contains a table with columns 'Hostname', 'Key type', and 'Fingerprint'.

Hostname	Key type	Fingerprint
github.com	ssh-rsa	nThbg6kXUpJWGI7E1IGOCspRomTxdCARLviKw6E5SY8
- Add host key:** A panel with a title bar and an info icon. It contains text explaining that host keys need to be verified. Below this is a form with 'Hostname' (containing 'github.com') and 'Port' (containing 'Port') fields, and a 'Submit' button.

At the bottom of the interface, there is a footer with the text 'Powered by Weblate 4.8' and links for 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

Depo GitHub

Access via SSH is possible (see [Depo SSH](#)), but in case you need to access more than one repository, you will hit a GitHub limitation on allowed SSH key usage (since each key can be used only once).

In case the *Degë push* is not set, the project is forked and changes pushed through a fork. In case it is set, changes are pushed to the upstream repository and chosen branch.

For smaller deployments, use HTTPS authentication with a personal access token and your GitHub account, see [Creating an access token for command-line use](#).

For bigger setups, it is usually better to create a dedicated user for Weblate, assign it the public SSH key generated in Weblate (see [Kyç SSH Weblate-i](#)) and grant it access to all the repositories you want to translate. This approach is also used for Hosted Weblate, there is dedicated *weblate* user for that.

Shihni edhe:

Accessing repositories from Hosted Weblate

URL të brendshme Weblate

Share one repository setup between different components by referring to its placement as `weblate://project/component` in other(linked) components. This way linked components use the VCS repository configuration of the main(referenced) component.

Sinjalizim: Removing main component also removes linked components.

Weblate automatically adjusts the repository URL when creating a component if it finds a component with a matching repository setup. You can override this in the last step of the component configuration.

Arsye për të përdorur këtë:

- Saves disk space on the server, the repository is stored just once.
- Makes the updates faster, only one repository is updated.
- There is just single exported repository with Weblate translations (see *Git exporter*).
- Some addons can operate on multiple components sharing one repository, for example *Kryej «squash» për depozitime Git*.

Depo HTTPS

To access protected HTTPS repositories, include the username and password in the URL. Don't worry, Weblate will strip this info when the URL is shown to users (if even allowed to see the repository URL at all).

For example the GitHub URL with authentication added might look like: `https://user:your_access_token@github.com/WeblateOrg/weblate.git`.

Shënim: If your username or password contains special characters, those have to be URL encoded, for example `https://user%40example.com:%24password%23@bitbucket.org/....`

Përdorim ndërmjetësi

If you need to access HTTP/HTTPS VCS repositories using a proxy server, configure the VCS to use it.

This can be done using the `http_proxy`, `https_proxy`, and `all_proxy` environment variables, (as described in the *cURL documentation*) or by enforcing it in the VCS configuration, for example:

```
git config --global http.proxy http://user:password@proxy.example.com:80
```

Shënim: The proxy configuration needs to be done under user running Weblate (see also *Leje sistemi kartelash*) and with `HOME=$DATA_DIR/home` (see *DATA_DIR*), otherwise Git executed by Weblate will not use it.

Shihni edhe:

The *cURL* manpage, *Git config documentation*

1.11.2 Git

Shihni edhe:

See *Hyrje në depo* for info on how to access different kinds of repositories.

Git with force push

This behaves exactly like Git itself, the only difference being that it always force pushes. This is intended only in the case of using a separate repository for translations.

Sinjalizim: Use with caution, as this easily leads to lost commits in your upstream repository.

Përshtatje formësimi Git

Weblate invokes all VCS commands with `HOME=$DATA_DIR/home` (see *DATA_DIR*), therefore editing the user configuration needs to be done in `DATA_DIR/home/.git`.

Git remote helpers

You can also use Git *remote helpers* for additionally supporting other version control systems, but be prepared to debug problems this may lead to.

At this time, helpers for Bazaar and Mercurial are available within separate repositories on GitHub: *git-remote-hg* and *git-remote-bzr*. Download them manually and put somewhere in your search path (for example `~/bin`). Make sure you have the corresponding version control systems installed.

Once you have these installed, such remotes can be used to specify a repository in Weblate.

To clone the `gnuhello` project from Launchpad using Bazaar:

```
bzr::lp:gnuhello
```

For the `hello` repository from selenic.com using Mercurial:

```
hg::http://selenic.com/repo/hello
```

Sinjalizim: The inconvenience of using Git remote helpers is for example with Mercurial, the remote helper sometimes creates a new tip when pushing changes back.

1.11.3 GitHub

Të reja në versionin 2.3.

This adds a thin layer atop *Git* using the *GitHub API* to allow pushing translation changes as pull requests, instead of pushing directly to the repository.

Git pushes changes directly to a repository, while *GitHub* creates pull requests. The latter is not needed for merely accessing Git repositories.

Shihni edhe:

Pushing changes from Weblate

Pushing changes to GitHub as pull requests

If not wanting to push translations to a GitHub repository, they can be sent as either one or many pull requests instead. You need to configure API credentials to make this work.

Shihni edhe:

GITHUB_USERNAME, GITHUB_TOKEN, GITHUB_CREDENTIALS

1.11.4 GitLab

Të reja në versionin 3.9.

This just adds a thin layer atop *Git* using the *GitLab API* to allow pushing translation changes as merge requests instead of pushing directly to the repository.

There is no need to use this to access Git repositories, ordinary *Git* works the same, the only difference is how pushing to a repository is handled. With *Git* changes are pushed directly to the repository, while *GitLab* creates merge request.

Shihni edhe:

Pushing changes from Weblate

Pushing changes to GitLab as merge requests

If not wanting to push translations to a GitLab repository, they can be sent as either one or many merge requests instead.

You need to configure API credentials to make this work.

Shihni edhe:

GITLAB_USERNAME, GITLAB_TOKEN, GITLAB_CREDENTIALS

1.11.5 Pagure

Të reja në versionin 4.3.2.

This just adds a thin layer atop *Git* using the *Pagure API* to allow pushing translation changes as merge requests instead of pushing directly to the repository.

There is no need to use this to access Git repositories, ordinary *Git* works the same, the only difference is how pushing to a repository is handled. With *Git* changes are pushed directly to the repository, while *Pagure* creates merge request.

Shihni edhe:

Pushing changes from Weblate

Pushing changes to Pagure as merge requests

If not wanting to push translations to a Pagure repository, they can be sent as either one or many merge requests instead.

You need to configure API credentials to make this work.

Shihni edhe:

PAGURE_USERNAME, PAGURE_TOKEN, PAGURE_CREDENTIALS

1.11.6 Gerrit

Të reja në versionin 2.2.

Adds a thin layer atop [Git](#) using the [git-review](#) tool to allow pushing translation changes as Gerrit review requests, instead of pushing them directly to the repository.

The Gerrit documentation has the details on the configuration necessary to set up such repositories.

1.11.7 Mercurial

Të reja në versionin 2.1.

Mercurial is another VCS you can use directly in Weblate.

Shënim: It should work with any Mercurial version, but there are sometimes incompatible changes to the command-line interface which breaks Weblate integration.

Shihni edhe:

See [Hyrje në depo](#) for info on how to access different kinds of repositories.

1.11.8 Subversion

Të reja në versionin 2.8.

Weblate uses [git-svn](#) to interact with [subversion](#) repositories. It is a Perl script that lets subversion be used by a Git client, enabling users to maintain a full clone of the internal repository and commit locally.

Shënim: Weblate tries to detect Subversion repository layout automatically - it supports both direct URLs for branch or repositories with standard layout (branches/, tags/ and trunk/). More info about this is to be found in the [git-svn documentation](#). If your repository does not have a standard layout and you encounter errors, try including the branch name in the repository URL and leaving branch empty.

Ndryshuar në versionin 2.19: Before this, only repositories using the standard layout were supported.

Kredenciale Subversion-i

Weblate expects you to have accepted the certificate up-front (and your credentials if needed). It will look to insert them into the `DATA_DIR` directory. Accept the certificate by using `svn` once with the `$HOME` environment variable set to the `DATA_DIR`:

```
# Use DATA_DIR as configured in Weblate settings.py, it is /app/data in the Docker
HOME=${DATA_DIR}/home svn co https://svn.example.com/example
```

Shihni edhe:

`DATA_DIR`

1.11.9 Kartela vendore

Të reja në versionin 3.8.

Weblate can also operate without a remote VCS. The initial translations are imported by uploading them. Later you can replace individual files by file upload, or add translation strings directly from Weblate (currently available only for monolingual translations).

In the background Weblate creates a Git repository for you and all changes are tracked in. In case you later decide to use a VCS to store the translations, you already have a repository within Weblate can base your integration on.

1.12 Weblate's REST API

Të reja në versionin 2.6: The REST API is available since Weblate 2.6.

The API is accessible on the `/api/` URL and it is based on [Django REST framework](#). You can use it directly or by *Klient Weblate*.

1.12.1 Authentication and generic parameters

The public project API is available without authentication, though unauthenticated requests are heavily throttled (by default to 100 requests per day), so it is recommended to use authentication. The authentication uses a token, which you can get in your profile. Use it in the `Authorization` header:

ANY /

Generic request behaviour for the API, the headers, status codes and parameters here apply to all endpoints as well.

Query Parameters

- **format** – Response format (overrides `Accept`). Possible values depends on REST framework setup, by default `json` and `api` are supported. The latter provides web browser interface for API.
- **page** – Returns given page of paginated results (use `next` and `previous` fields in response to automate the navigation).

Request Headers

- `Accept` – the response content type depends on `Accept` header
- `Authorization` – optional token to authenticate as `Authorization: Token YOUR-TOKEN`

Response Headers

- `Content-Type` – this depends on `Accept` header of request
- `Allow` – list of allowed HTTP methods on object

Response JSON Object

- **detail** (*string*) – verbose description of the result (for HTTP status codes other than `200 OK`)
- **count** (*int*) – total item count for object lists
- **next** (*string*) – next page URL for object lists
- **previous** (*string*) – previous page URL for object lists
- **results** (*array*) – results for object lists
- **url** (*string*) – URL to access this resource using API
- **web_url** (*string*) – URL to access this resource using web browser

Status Codes

- **200 OK** – when request was correctly handled
- **201 Created** – when a new object was created successfully
- **204 No Content** – when an object was deleted successfully
- **400 Bad Request** – when form parameters are missing
- **403 Forbidden** – when access is denied
- **429 Too Many Requests** – when throttling is in place

Authentication examples

Example request:

```
GET /api/ HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
Authorization: Token YOUR-TOKEN
```

Example response:

```
HTTP/1.0 200 OK
Date: Fri, 25 Mar 2016 09:46:12 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, HEAD, OPTIONS

{
  "projects": "http://example.com/api/projects/",
  "components": "http://example.com/api/components/",
  "translations": "http://example.com/api/translations/",
  "languages": "http://example.com/api/languages/"
}
```

CURL example:

```
curl \
  -H "Authorization: Token TOKEN" \
  https://example.com/api/
```

Passing Parameters Examples

For the **POST** method the parameters can be specified either as form submission (*application/x-www-form-urlencoded*) or as JSON (*application/json*).

Form request example:

```
POST /api/projects/hello/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/x-www-form-urlencoded
Authorization: Token TOKEN

operation=pull
```

JSON request example:

```
POST /api/projects/hello/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{"operation": "pull"}
```

CURL example:

```
curl \
  -d operation=pull \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/components/hello/weblate/repository/
```

CURL JSON example:

```
curl \
  --data-binary '{"operation": "pull"}' \
  -H "Content-Type: application/json" \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/components/hello/weblate/repository/
```

API rate limiting

The API requests are rate limited; the default configuration limits it to 100 requests per day for anonymous users and 5000 requests per hour for authenticated users.

Rate limiting can be adjusted in the `settings.py`; see [Throttling in Django REST framework documentation](#) for more details how to configure it.

The status of rate limiting is reported in following headers:

X-RateLimit-Limit	Rate limiting limit of requests to perform
X-RateLimit-Remaining	Remaining limit of requests
X-RateLimit-Reset	Number of seconds until ratelimit window resets

Ndryshuar në versionin 4.1: Added ratelimiting status headers.

Shihni edhe:

Rate limiting, Rate limiting

1.12.2 API Entry Point

GET /api/

The API root entry point.

Example request:

```
GET /api/ HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
Authorization: Token YOUR-TOKEN
```

Example response:

```

HTTP/1.0 200 OK
Date: Fri, 25 Mar 2016 09:46:12 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, HEAD, OPTIONS

{
  "projects": "http://example.com/api/projects/",
  "components": "http://example.com/api/components/",
  "translations": "http://example.com/api/translations/",
  "languages": "http://example.com/api/languages/"
}

```

1.12.3 Përdorues

Të reja në versionin 4.0.

GET /api/users/

Returns a list of users if you have permissions to see manage users. If not, then you get to see only your own details.

Shihni edhe:

Users object attributes are documented at [GET /api/users/\(str:username\)/](#).

POST /api/users/

Creates a new user.

Parameters

- **username** (*string*) – Emër përdoruesi
- **full_name** (*string*) – User full name
- **email** (*string*) – User email
- **is_superuser** (*boolean*) – Is user superuser? (optional)
- **is_active** (*boolean*) – Is user active? (optional)

GET /api/users/(str: username) /

Returns information about users.

Parameters

- **username** (*string*) – User's username

Response JSON Object

- **username** (*string*) – username of a user
- **full_name** (*string*) – full name of a user
- **email** (*string*) – email of a user
- **is_superuser** (*boolean*) – whether the user is a super user
- **is_active** (*boolean*) – whether the user is active
- **date_joined** (*string*) – date the user is created
- **groups** (*array*) – link to associated groups; see [GET /api/groups/\(int:id\)/](#)

Example JSON data:


```
{
  "email": "user@example.com",
  "full_name": "Example User",
  "username": "exampleusername",
  "groups": [
    "http://example.com/api/groups/2/",
    "http://example.com/api/groups/3/"
  ],
  "is_superuser": true,
  "is_active": true,
  "date_joined": "2020-03-29T18:42:42.617681Z",
  "url": "http://example.com/api/users/exampleusername/",
  "statistics_url": "http://example.com/api/users/exampleusername/statistics/"
}
```

PUT `/api/users/(str: username) /`

Changes the user parameters.

Parameters

- **username** (*string*) – User's username

Response JSON Object

- **username** (*string*) – username of a user
- **full_name** (*string*) – full name of a user
- **email** (*string*) – email of a user
- **is_superuser** (*boolean*) – whether the user is a super user
- **is_active** (*boolean*) – whether the user is active
- **date_joined** (*string*) – date the user is created

PATCH `/api/users/(str: username) /`

Changes the user parameters.

Parameters

- **username** (*string*) – User's username

Response JSON Object

- **username** (*string*) – username of a user
- **full_name** (*string*) – full name of a user
- **email** (*string*) – email of a user
- **is_superuser** (*boolean*) – whether the user is a super user
- **is_active** (*boolean*) – whether the user is active
- **date_joined** (*string*) – date the user is created

DELETE `/api/users/(str: username) /`

Deletes all user information and marks the user inactive.

Parameters

- **username** (*string*) – User's username

POST `/api/users/(str: username) /groups/`

Associate groups with a user.

Parameters

- **username** (*string*) – User's username

Form Parameters

- **string** `group_id` – The unique group ID

GET `/api/users/ (str: username) /statistics/`

List statistics of a user.

Parameters

- **username** (*string*) – User's username

Response JSON Object

- **translated** (*int*) – Number of translations by user
- **suggested** (*int*) – Number of suggestions by user
- **uploaded** (*int*) – Number of uploads by user
- **commented** (*int*) – Number of comments by user
- **languages** (*int*) – Number of languages user can translate

GET `/api/users/ (str: username) /notifications/`

List subscriptions of a user.

Parameters

- **username** (*string*) – User's username

POST `/api/users/ (str: username) /notifications/`

Associate subscriptions with a user.

Parameters

- **username** (*string*) – User's username

Request JSON Object

- **notification** (*string*) – Name of notification registered
- **scope** (*int*) – Scope of notification from the available choices
- **frequency** (*int*) – Frequency choices for notifications

GET `/api/users/ (str: username) /notifications/`

int: `subscription_id` / Get a subscription associated with a user.

Parameters

- **username** (*string*) – User's username
- **subscription_id** (*int*) – ID of notification registered

PUT `/api/users/ (str: username) /notifications/`

int: `subscription_id` / Edit a subscription associated with a user.

Parameters

- **username** (*string*) – User's username
- **subscription_id** (*int*) – ID of notification registered

Request JSON Object

- **notification** (*string*) – Name of notification registered
- **scope** (*int*) – Scope of notification from the available choices
- **frequency** (*int*) – Frequency choices for notifications

PATCH `/api/users/ (str: username) /notifications/`

int: `subscription_id` / Edit a subscription associated with a user.

Parameters

- **username** (*string*) – User's username
- **subscription_id** (*int*) – ID of notification registered

Request JSON Object

- **notification** (*string*) – Name of notification registered
- **scope** (*int*) – Scope of notification from the available choices
- **frequency** (*int*) – Frequency choices for notifications

DELETE `/api/users/(str: username)/notifications/`
int: `subscription_id` / Delete a subscription associated with a user.

Parameters

- **username** (*string*) – User's username
- **subscription_id** – Name of notification registered
- **subscription_id** – int

1.12.4 Grupe

Të reja në versionin 4.0.

GET `/api/groups/`

Returns a list of groups if you have permissions to see manage groups. If not, then you get to see only the groups the user is a part of.

Shihni edhe:

Group object attributes are documented at `GET /api/groups/(int:id)/`.

POST `/api/groups/`

Creates a new group.

Parameters

- **name** (*string*) – Emër grupi
- **project_selection** (*int*) – Group of project selection from given options
- **language_selection** (*int*) – Group of languages selected from given options

GET `/api/groups/(int: id) /`

Returns information about group.

Parameters

- **id** (*int*) – Group's ID

Response JSON Object

- **name** (*string*) – name of a group
- **project_selection** (*int*) – integer corresponding to group of projects
- **language_selection** (*int*) – integer corresponding to group of languages
- **roles** (*array*) – link to associated roles; see `GET /api/roles/(int:id)/`
- **projects** (*array*) – link to associated projects; see `GET /api/projects/(string:project)/`
- **components** (*array*) – link to associated components; see `GET /api/components/(string:project)/(string:component)/`
- **componentlist** (*array*) – link to associated componentlist; see `GET /api/component-lists/(str:slug)/`

Example JSON data:

```
{
  "name": "Guests",
  "project_selection": 3,
  "language_selection": 1,
  "url": "http://example.com/api/groups/1/",
  "roles": [
    "http://example.com/api/roles/1/",
    "http://example.com/api/roles/2/"
  ],
  "languages": [
    "http://example.com/api/languages/en/",
    "http://example.com/api/languages/cs/"
  ],
  "projects": [
    "http://example.com/api/projects/demo1/",
    "http://example.com/api/projects/demo/"
  ],
  "componentlist": "http://example.com/api/component-lists/new/",
  "components": [
    "http://example.com/api/components/demo/weblate/"
  ]
}
```

PUT /api/groups/ (int: id) /
Changes the group parameters.

Parameters

- **id** (*int*) – Group's ID

Response JSON Object

- **name** (*string*) – name of a group
- **project_selection** (*int*) – integer corresponding to group of projects
- **language_selection** (*int*) – integer corresponding to group of Languages

PATCH /api/groups/ (int: id) /
Changes the group parameters.

Parameters

- **id** (*int*) – Group's ID

Response JSON Object

- **name** (*string*) – name of a group
- **project_selection** (*int*) – integer corresponding to group of projects
- **language_selection** (*int*) – integer corresponding to group of languages

DELETE /api/groups/ (int: id) /
Deletes the group.

Parameters

- **id** (*int*) – Group's ID

POST /api/groups/ (int: id) /roles/
Associate roles with a group.

Parameters

- **id** (*int*) – Group's ID

Form Parameters

- **string role_id** – The unique role ID

POST /api/groups/(int: id)/components/

Associate components with a group.

Parameters

- **id**(int) – Group's ID

Form Parameters

- **string component_id** – The unique component ID

DELETE /api/groups/(int: id)/components/

int: *component_id* Delete component from a group.

Parameters

- **id**(int) – Group's ID
- **component_id**(int) – The unique component ID

POST /api/groups/(int: id)/projects/

Associate projects with a group.

Parameters

- **id**(int) – Group's ID

Form Parameters

- **string project_id** – The unique project ID

DELETE /api/groups/(int: id)/projects/

int: *project_id* Delete project from a group.

Parameters

- **id**(int) – Group's ID
- **project_id**(int) – The unique project ID

POST /api/groups/(int: id)/languages/

Associate languages with a group.

Parameters

- **id**(int) – Group's ID

Form Parameters

- **string language_code** – The unique language code

DELETE /api/groups/(int: id)/languages/

string: *language_code* Delete language from a group.

Parameters

- **id**(int) – Group's ID
- **language_code**(string) – The unique language code

POST /api/groups/(int: id)/componentlists/

Associate componentlists with a group.

Parameters

- **id**(int) – Group's ID

Form Parameters

- **string component_list_id** – The unique componentlist ID

DELETE /api/groups/(int: id)/componentlists/

int: *component_list_id* Delete componentlist from a group.

Parameters

- **id** (*int*) – Group's ID
- **component_list_id** (*int*) – The unique componentlist ID

1.12.5 Role**GET /api/roles/**

Returns a list of all roles associated with user. If user is superuser, then list of all existing roles is returned.

Shihni edhe:

Roles object attributes are documented at [GET /api/roles/\(int:id\)/](#).

POST /api/roles/

Creates a new role.

Parameters

- **name** (*string*) – Role name
- **permissions** (*array*) – List of codenames of permissions

GET /api/roles/(int: id) /

Returns information about a role.

Parameters

- **id** (*int*) – Role ID

Response JSON Object

- **name** (*string*) – Role name
- **permissions** (*array*) – list of codenames of permissions

Example JSON data:

```
{
  "name": "Access repository",
  "permissions": [
    "vcs.access",
    "vcs.view"
  ],
  "url": "http://example.com/api/roles/1/",
}
```

PUT /api/roles/(int: id) /

Changes the role parameters.

Parameters

- **id** (*int*) – Role's ID

Response JSON Object

- **name** (*string*) – Role name
- **permissions** (*array*) – list of codenames of permissions

PATCH /api/roles/(int: id) /

Changes the role parameters.

Parameters

- **id** (*int*) – Role's ID

Response JSON Object

- **name** (*string*) – Role name
- **permissions** (*array*) – list of codenames of permissions

DELETE /api/roles/ (int: id) /

Deletes the role.

Parameters

- **id** (*int*) – Role's ID

1.12.6 Gjuhë

GET /api/languages/

Returns a list of all languages.

Shihni edhe:

Language object attributes are documented at [GET /api/languages/\(string:language\)/](#).

POST /api/languages/

Creates a new language.

Parameters

- **code** (*string*) – Emër gjuhe
- **name** (*string*) – Emër gjuhe
- **direction** (*string*) – Drejtim teksti
- **plural** (*object*) – Language plural formula and number

GET /api/languages/(string: language) /

Returns information about a language.

Parameters

- **language** (*string*) – Kod gjuhe

Response JSON Object

- **code** (*string*) – Kod gjuhe
- **direction** (*string*) – Drejtim teksti
- **plural** (*object*) – Object of language plural information
- **aliases** (*array*) – Array of aliases for language

Example JSON data:

```
{
  "code": "en",
  "direction": "ltr",
  "name": "English",
  "plural": {
    "id": 75,
    "source": 0,
    "number": 2,
    "formula": "n != 1",
    "type": 1
  },
  "aliases": [
    "english",
    "en_en",
    "base",
    "source",
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "eng"
  ],
  "url": "http://example.com/api/languages/en/",
  "web_url": "http://example.com/languages/en/",
  "statistics_url": "http://example.com/api/languages/en/statistics/"
}

```

PUT `/api/languages/(string: language) /`
Changes the language parameters.

Parameters

- **language** (*string*) – Language's code

Request JSON Object

- **name** (*string*) – Emër gjuhe
- **direction** (*string*) – Drejtim teksti
- **plural** (*object*) – Language plural details

PATCH `/api/languages/(string: language) /`
Changes the language parameters.

Parameters

- **language** (*string*) – Language's code

Request JSON Object

- **name** (*string*) – Emër gjuhe
- **direction** (*string*) – Drejtim teksti
- **plural** (*object*) – Language plural details

DELETE `/api/languages/(string: language) /`
Deletes the language.

Parameters

- **language** (*string*) – Language's code

GET `/api/languages/(string: language)/statistics/`
Returns statistics for a language.

Parameters

- **language** (*string*) – Kod gjuhe

Response JSON Object

- **total** (*int*) – total number of strings
- **total_words** (*int*) – total number of words
- **last_change** (*timestamp*) – last changes in the language
- **recent_changes** (*int*) – total number of changes
- **translated** (*int*) – number of translated strings
- **translated_percent** (*float*) – percentage of translated strings
- **translated_words** (*int*) – number of translated words
- **translated_words_percent** (*int*) – percentage of translated words
- **translated_chars** (*int*) – number of translated characters
- **translated_chars_percent** (*int*) – percentage of translated characters

- **total_chars** (*int*) – number of total characters
- **fuzzy** (*int*) – number of fuzzy (marked for edit) strings
- **fuzzy_percent** (*int*) – percentage of fuzzy (marked for edit) strings
- **failing** (*int*) – number of failing strings
- **failing** – percentage of failing strings

1.12.7 Projekte

GET /api/projects/

Returns a list of all projects.

Shihni edhe:

Project object attributes are documented at [GET /api/projects/\(string:project\)/](#).

POST /api/projects/

Të reja në versionin 3.9.

Creates a new project.

Parameters

- **name** (*string*) – Emër projekti
- **slug** (*string*) – Project slug
- **web** (*string*) – Sajt projekti

GET /api/projects/(string: project) /

Returns information about a project.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Response JSON Object

- **name** (*string*) – emër projekti
- **slug** (*string*) – project slug
- **web** (*string*) – project website
- **components_list_url** (*string*) – URL to components list; see [GET /api/projects/\(string:project\)/components/](#)
- **repository_url** (*string*) – URL to repository status; see [GET /api/projects/\(string:project\)/repository/](#)
- **changes_list_url** (*string*) – URL to changes list; see [GET /api/projects/\(string:project\)/changes/](#)
- **translation_review** (*boolean*) – Aktivizoni shqyrtime
- **source_review** (*boolean*) – Aktivizo shqyrtime burimi
- **set_language_team** (*boolean*) – Caktoni krye «Language-Team»
- **enable_hooks** (*boolean*) – Aktivizoni hook-e
- **instructions** (*string*) – Udhëzime përkthimi
- **language_aliases** (*string*) – Aliase gjuhe

Example JSON data:

```
{
  "name": "Hello",
  "slug": "hello",
  "url": "http://example.com/api/projects/hello/",
  "web": "https://weblate.org/",
  "web_url": "http://example.com/projects/hello/"
}
```

PATCH `/api/projects/(string: project) /`

Të reja në versionin 4.3.

Edit a project by a **PATCH** request.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

PUT `/api/projects/(string: project) /`

Të reja në versionin 4.3.

Edit a project by a **PUT** request.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

DELETE `/api/projects/(string: project) /`

Të reja në versionin 3.9.

Deletes a project.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

GET `/api/projects/(string: project) /changes/`

Returns a list of project changes. This is essentially a project scoped `GET /api/changes/` accepting same params.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Response JSON Object

- **results** (*array*) – array of component objects; see `GET /api/changes/(int:id) /`

GET `/api/projects/(string: project) /repository/`

Returns information about VCS repository status. This endpoint contains only an overall summary for all repositories for the project. To get more detailed status use `GET /api/components/(string:project)/(string:component)/repository/`.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Response JSON Object

- **needs_commit** (*boolean*) – whether there are any pending changes to commit
- **needs_merge** (*boolean*) – whether there are any upstream changes to merge
- **needs_push** (*boolean*) – whether there are any local changes to push

Example JSON data:

```
{
  "needs_commit": true,
  "needs_merge": false,
  "needs_push": true
}
```

POST `/api/projects/(string: project)/repository/`

Performs given operation on the VCS repository.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Request JSON Object

- **operation** (*string*) – Operation to perform: one of push, pull, commit, reset, cleanup, file-sync

Response JSON Object

- **result** (*boolean*) – result of the operation

CURL example:

```
curl \
  -d operation=pull \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/projects/hello/repository/
```

JSON request example:

```
POST /api/projects/hello/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{"operation": "pull"}
```

JSON response example:

```
HTTP/1.0 200 OK
Date: Tue, 12 Apr 2016 09:32:50 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, POST, HEAD, OPTIONS

{"result": true}
```

GET `/api/projects/(string: project)/components/`

Returns a list of translation components in the given project.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Response JSON Object

- **results** (*array*) – array of component objects; see `GET /api/components/(string:project)/(string:component)/`

POST `/api/projects/(string: project)/components/`

Të reja në versionin 3.9.

Ndryshuar në versionin 4.3: The `zipfile` and `docfile` parameters are now accepted for VCS-less components, see [Kartela vendore](#).

Ndryshuar në versionin 4.6: The cloned repositories are now automatically shared within a project using [URL të brendshme Weblate](#). Use `disable_autoshare` to turn off this.

Creates translation components in the given project.

Ndihmëz: Use [URL të brendshme Weblate](#) when creating multiple components from a single VCS repository.

Shënim: Most of the component creation happens in the background. Check the `task_url` attribute of created component and follow the progress there.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Form Parameters

- **file zipfile** – ZIP file to upload into Weblate for translations initialization
- **file docfile** – Dokument për përkthim
- **boolean disable_autoshare** – Disables automatic repository sharing via [URL të brendshme Weblate](#).

Response JSON Object

- **result** (*object*) – Created component object; see [GET /api/components/\(string:project\)/\(string:component\)/](#)

JSON can not be used when uploading the files using the `zipfile` and `docfile` parameters. The data has to be uploaded as *multipart/form-data*.

CURL form request example:

```
curl \
  --form docfile=@strings.html \
  --form name=Weblate \
  --form slug=weblate \
  --form file_format=html \
  --form new_lang=add \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/projects/hello/components/
```

CURL JSON request example:

```
curl \
  --data-binary '{
    "branch": "main",
    "file_format": "po",
    "filemask": "po/*.po",
    "git_export": "",
    "license": "",
    "license_url": "",
    "name": "Weblate",
    "slug": "weblate",
    "repo": "file:///home/nijel/work/weblate-hello",
    "template": "",
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "new_base": "",
    "vcs": "git"
  }' \
-H "Content-Type: application/json" \
-H "Authorization: Token TOKEN" \
http://example.com/api/projects/hello/components/

```

JSON request example:

```

POST /api/projects/hello/components/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{
  "branch": "main",
  "file_format": "po",
  "filemask": "po/*.po",
  "git_export": "",
  "license": "",
  "license_url": "",
  "name": "Weblate",
  "slug": "weblate",
  "repo": "file:///home/nijel/work/weblate-hello",
  "template": "",
  "new_base": "",
  "vcs": "git"
}

```

JSON response example:

```

HTTP/1.0 200 OK
Date: Tue, 12 Apr 2016 09:32:50 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, POST, HEAD, OPTIONS

{
  "branch": "main",
  "file_format": "po",
  "filemask": "po/*.po",
  "git_export": "",
  "license": "",
  "license_url": "",
  "name": "Weblate",
  "slug": "weblate",
  "project": {
    "name": "Hello",
    "slug": "hello",
    "source_language": {
      "code": "en",
      "direction": "ltr",
      "name": "English",
      "url": "http://example.com/api/languages/en/",
      "web_url": "http://example.com/languages/en/"
    }
  },

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "url": "http://example.com/api/projects/hello/",
    "web": "https://weblate.org/",
    "web_url": "http://example.com/projects/hello/"
  },
  "repo": "file:///home/nijel/work/weblate-hello",
  "template": "",
  "new_base": "",
  "url": "http://example.com/api/components/hello/weblate/",
  "vcs": "git",
  "web_url": "http://example.com/projects/hello/weblate/"
}

```

GET /api/projects/ (string: *project*) /languages/
Returns paginated statistics for all languages within a project.

Të reja në versionin 3.8.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Response JSON Object

- **results** (*array*) – array of translation statistics objects
- **language** (*string*) – language name
- **code** (*string*) – language code
- **total** (*int*) – total number of strings
- **translated** (*int*) – number of translated strings
- **translated_percent** (*float*) – percentage of translated strings
- **total_words** (*int*) – total number of words
- **translated_words** (*int*) – number of translated words
- **words_percent** (*float*) – percentage of translated words

GET /api/projects/ (string: *project*) /statistics/
Returns statistics for a project.

Të reja në versionin 3.8.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

Response JSON Object

- **total** (*int*) – total number of strings
- **translated** (*int*) – number of translated strings
- **translated_percent** (*float*) – percentage of translated strings
- **total_words** (*int*) – total number of words
- **translated_words** (*int*) – number of translated words
- **words_percent** (*float*) – percentage of translated words

1.12.8 Përbërës

GET `/api/components/`

Returns a list of translation components.

Shihni edhe:

Component object attributes are documented at `GET /api/components/(string:project)/(string:component)/`.

GET `/api/components/(string: project) /`

string: `component` / Returns information about translation component.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **project** (*object*) – the translation project; see `GET /api/projects/(string:project)/`
- **name** (*string*) – *Emër përbërësi*
- **slug** (*string*) – *Component slug*
- **vcs** (*string*) – *Sistem kontrolli versionesh*
- **repo** (*string*) – *Depo kodi burim*
- **git_export** (*string*) – *URL depoje të eksportuar*
- **branch** (*string*) – *Degë depoje*
- **push_branch** (*string*) – *Degë push*
- **filemask** (*string*) – *File mask*
- **template** (*string*) – *Kartelë njëgjuhëshe gjuhe bazë*
- **edit_template** (*string*) – *Përpunoni kartelën bazë*
- **intermediate** (*string*) – *Kartelë gjuhe ndërmjetëse*
- **new_base** (*string*) – *Gjedhe për përkthime të reja*
- **file_format** (*string*) – *Format kartelash*
- **license** (*string*) – *Licencë përkthimi*
- **agreement** (*string*) – *Marrëveshje kontribuesi*
- **new_lang** (*string*) – *Shtim përkthimi të ri*
- **language_code_style** (*string*) – *Stil kodi gjuhe*
- **source_language** (*object*) – source language object; see `GET /api/languages/(string:language)/`
- **push** (*string*) – *URL push-i për depon*
- **check_flags** (*string*) – *Flamuj përkthimi*
- **priority** (*string*) – *Përparësi*
- **enforced_checks** (*string*) – *Kontrolle me detyrim*
- **restricted** (*string*) – *Restricted access*
- **repoweb** (*string*) – *Shfletues depoje*
- **report_source_bugs** (*string*) – *Adresë njoftimi të metash në vargje burim*

- **merge_style** (*string*) – *Stil përzierjeje*
- **commit_message** (*string*) – *Commit, add, delete, merge and addon messages*
- **add_message** (*string*) – *Commit, add, delete, merge and addon messages*
- **delete_message** (*string*) – *Commit, add, delete, merge and addon messages*
- **merge_message** (*string*) – *Commit, add, delete, merge and addon messages*
- **addon_message** (*string*) – *Commit, add, delete, merge and addon messages*
- **allow_translation_propagation** (*string*) – *Lejo përhapje përkthimesh*
- **enable_suggestions** (*string*) – *Enable suggestions*
- **suggestion_voting** (*string*) – *Votim sugjerimesh*
- **suggestion_autoaccept** (*string*) – *Vetëprano sugjerime*
- **push_on_commit** (*string*) – *Push on commit*
- **commit_pending_age** (*string*) – *Moshë ndryshimesh për depozitim*
- **auto_lock_error** (*string*) – *Kyçe, në rast gabimesh*
- **language_regex** (*string*) – *Filtër gjuhësh*
- **variant_regex** (*string*) – *Shprehje e rregullt variantesh*
- **repository_url** (*string*) – URL to repository status; see `GET /api/components/(string:project)/(string:component)/repository/`
- **translations_url** (*string*) – URL to translations list; see `GET /api/components/(string:project)/(string:component)/translations/`
- **lock_url** (*string*) – URL to lock status; see `GET /api/components/(string:project)/(string:component)/lock/`
- **changes_list_url** (*string*) – URL to changes list; see `GET /api/components/(string:project)/(string:component)/changes/`
- **task_url** (*string*) – URL to a background task (if any); see `GET /api/tasks/(str:uuid)/`

Example JSON data:

```
{
  "branch": "main",
  "file_format": "po",
  "filemask": "po/*.po",
  "git_export": "",
  "license": "",
  "license_url": "",
  "name": "Weblate",
  "slug": "weblate",
  "project": {
    "name": "Hello",
    "slug": "hello",
    "source_language": {
      "code": "en",
      "direction": "ltr",
      "name": "English",
      "url": "http://example.com/api/languages/en/",
      "web_url": "http://example.com/languages/en/"
    },
  },
  "url": "http://example.com/api/projects/hello/",
  "web": "https://weblate.org/",
}
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "web_url": "http://example.com/projects/hello/"
  },
  "source_language": {
    "code": "en",
    "direction": "ltr",
    "name": "English",
    "url": "http://example.com/api/languages/en/",
    "web_url": "http://example.com/languages/en/"
  },
  "repo": "file:///home/nijel/work/weblate-hello",
  "template": "",
  "new_base": "",
  "url": "http://example.com/api/components/hello/weblate/",
  "vcs": "git",
  "web_url": "http://example.com/projects/hello/weblate/"
}

```

PATCH /api/components/ (string: project) /
string: component/ Edit a component by a **PATCH** request.

Parameters

- **project** (string) – Identifikues URL-je projekti
- **component** (string) – Identifikues URL-je përbërësi
- **source_language** (string) – Kod gjuhe burimi projekti (opsionale)

Request JSON Object

- **name** (string) – emër përbërësi
- **slug** (string) – identifikues përbërësi
- **repo** (string) – URL depoje VCS

CURL example:

```

curl \
  --data-binary '{"name": "new name"}' \
  -H "Content-Type: application/json" \
  -H "Authorization: Token TOKEN" \
  PATCH http://example.com/api/projects/hello/components/

```

JSON request example:

```

PATCH /api/projects/hello/components/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{
  "name": "new name"
}

```

JSON response example:

```

HTTP/1.0 200 OK
Date: Tue, 12 Apr 2016 09:32:50 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

Content-Type: application/json
Content-Language: en
Allow: GET, POST, HEAD, OPTIONS

{
  "branch": "main",
  "file_format": "po",
  "filemask": "po/*.po",
  "git_export": "",
  "license": "",
  "license_url": "",
  "name": "new name",
  "slug": "weblate",
  "project": {
    "name": "Hello",
    "slug": "hello",
    "source_language": {
      "code": "en",
      "direction": "ltr",
      "name": "English",
      "url": "http://example.com/api/languages/en/",
      "web_url": "http://example.com/languages/en/"
    },
    "url": "http://example.com/api/projects/hello/",
    "web": "https://weblate.org/",
    "web_url": "http://example.com/projects/hello/"
  },
  "repo": "file:///home/nijel/work/weblate-hello",
  "template": "",
  "new_base": "",
  "url": "http://example.com/api/components/hello/weblate/",
  "vcs": "git",
  "web_url": "http://example.com/projects/hello/weblate/"
}

```

PUT /api/components/(string: *project*) /
string: *component* / Edit a component by a **PUT** request.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Request JSON Object

- **branch** (*string*) – VCS repository branch
- **file_format** (*string*) – format kartele përkthimesh
- **filemask** (*string*) – mask of translation files in the repository
- **name** (*string*) – emër përbërësi
- **slug** (*string*) – identifikues përbërësi
- **repo** (*string*) – URL depoje VCS
- **template** (*string*) – base file for monolingual translations
- **new_base** (*string*) – base file for adding new translations
- **vcs** (*string*) – sistem kontrolli versionesh

DELETE /api/components/(string: *project*) /
string: *component* / Të reja në versionin 3.9.

Fshin një përbërës.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

GET /api/components/ (**string:** *project*) /

string: *component/changes/* Returns a list of component changes. This is essentially a component scoped [GET /api/changes/](#) accepting same params.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **results** (*array*) – array of component objects; see [GET /api/changes/\(int:id\)/](#)

GET /api/components/ (**string:** *project*) /

string: *component/screenshots/* Returns a list of component screenshots.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **results** (*array*) – array of component screenshots; see [GET /api/screenshots/\(int:id\)/](#)

GET /api/components/ (**string:** *project*) /

string: *component/lock/* Returns component lock status.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **locked** (*boolean*) – whether component is locked for updates

Example JSON data:

```
{
  "locked": false
}
```

POST /api/components/ (**string:** *project*) /

string: *component/lock/* Sets component lock status.

Response is same as [GET /api/components/\(string:project\)/\(string:component\)/lock/](#).

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Request JSON Object

- **lock** – Boolean whether to lock or not.

CURL example:

```
curl \
  -d lock=true \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/components/hello/weblate/repository/
```

JSON request example:

```
POST /api/components/hello/weblate/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{"lock": true}
```

JSON response example:

```
HTTP/1.0 200 OK
Date: Tue, 12 Apr 2016 09:32:50 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, POST, HEAD, OPTIONS

{"locked": true}
```

GET `/api/components/(string: project) /`
string: `component/repository/` Returns information about VCS repository status.

The response is same as for `GET /api/projects/(string:project)/repository/`.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **needs_commit** (*boolean*) – whether there are any pending changes to commit
- **needs_merge** (*boolean*) – whether there are any upstream changes to merge
- **needs_push** (*boolean*) – whether there are any local changes to push
- **remote_commit** (*string*) – Remote commit information
- **status** (*string*) – VCS repository status as reported by VCS
- **merge_failure** – Text describing merge failure or null if there is none

POST `/api/components/(string: project) /`
string: `component/repository/` Performs the given operation on a VCS repository.

See `POST /api/projects/(string:project)/repository/` for documentation.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Request JSON Object

- **operation** (*string*) – Operation to perform: one of push, pull, commit, reset, cleanup

Response JSON Object

- **result** (*boolean*) – result of the operation

CURL example:

```
curl \
  -d operation=pull \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/components/hello/weblate/repository/
```

JSON request example:

```
POST /api/components/hello/weblate/repository/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{"operation": "pull"}
```

JSON response example:

```
HTTP/1.0 200 OK
Date: Tue, 12 Apr 2016 09:32:50 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, POST, HEAD, OPTIONS

{"result": true}
```

GET /api/components/(string: *project*) /
string: *component/monolingual_base/* Downloads base file for monolingual translations.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

GET /api/components/(string: *project*) /
string: *component/new_template/* Downloads template file for new translations.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

GET /api/components/(string: *project*) /
string: *component/translations/* Returns a list of translation objects in the given component.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **results** (*array*) – array of translation objects; see *GET /api/translations/(string:project)/(string:component)/(string:language)/*

POST /api/components/(string: *project*) /
string: *component/translations/* Creates new translation in the given component.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Request JSON Object

- **language_code** (*string*) – translation language code; see `GET /api/languages/(string:language)/`

Response JSON Object

- **result** (*object*) – new translation object created

CURL example:

```
curl \
  -d language_code=cs \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/projects/hello/components/
```

JSON request example:

```
POST /api/projects/hello/components/ HTTP/1.1
Host: example.com
Accept: application/json
Content-Type: application/json
Authorization: Token TOKEN
Content-Length: 20

{"language_code": "cs"}
```

JSON response example:

```
HTTP/1.0 200 OK
Date: Tue, 12 Apr 2016 09:32:50 GMT
Server: WSGIServer/0.1 Python/2.7.11+
Vary: Accept, Accept-Language, Cookie
X-Frame-Options: SAMEORIGIN
Content-Type: application/json
Content-Language: en
Allow: GET, POST, HEAD, OPTIONS

{
  "failing_checks": 0,
  "failing_checks_percent": 0,
  "failing_checks_words": 0,
  "filename": "po/cs.po",
  "fuzzy": 0,
  "fuzzy_percent": 0.0,
  "fuzzy_words": 0,
  "have_comment": 0,
  "have_suggestion": 0,
  "is_template": false,
  "is_source": false,
  "language": {
    "code": "cs",
    "direction": "ltr",
    "name": "Czech",
    "url": "http://example.com/api/languages/cs/",
    "web_url": "http://example.com/languages/cs/"
  },
  "language_code": "cs",
  "id": 125,
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

"last_author": null,
"last_change": null,
"share_url": "http://example.com/engage/hello/cs/",
"total": 4,
"total_words": 15,
"translate_url": "http://example.com/translate/hello/weblate/cs/",
"translated": 0,
"translated_percent": 0.0,
"translated_words": 0,
"url": "http://example.com/api/translations/hello/weblate/cs/",
"web_url": "http://example.com/projects/hello/weblate/cs/"
}

```

GET `/api/components/(string: project) /`
string: `component/statistics/` Returns paginated statistics for all translations within component.

Të reja në versionin 2.7.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **results** (*array*) – array of translation statistics objects; see `GET /api/translations/(string:project)/(string:component)/(string:language)/statistics/`

GET `/api/components/(string: project) /`
string: `component/links/` Returns projects linked with a component.

Të reja në versionin 4.5.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Response JSON Object

- **projects** (*array*) – associated projects; see `GET /api/projects/(string:project)/`

POST `/api/components/(string: project) /`
string: `component/links/` Associate project with a component.

Të reja në versionin 4.5.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi

Form Parameters

- **string project_slug** – Project slug

DELETE `/api/components/(string: project) /`
string: `component/links/string: project_slug/` Remove association of a project with a component.

Të reja në versionin 4.5.

Parameters

- **project** (*string*) – Identifikues URL-je projekti

- **component** (*string*) – Identifikues URL-je përbërësi
- **project_slug** (*string*) – Slug of the project to remove

1.12.9 Përkthime

GET `/api/translations/`
Returns a list of translations.

Shihni edhe:

Translation object attributes are documented at `GET /api/translations/(string:project)/(string:component)/(string:language)/`.

GET `/api/translations/(string: project) /`
string: *component/string: language/* Sjell informacion rreth një përkthimi

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

Response JSON Object

- **component** (*object*) – component object; see `GET /api/components/(string:project)/(string:component)/`
- **failing_checks** (*int*) – numër vargjesh që s'i kalojnë kontrollet
- **failing_checks_percent** (*float*) – përqindje vargjesh që s'i kalojnë kontrollet
- **failing_checks_words** (*int*) – numër fjalësh që s'i kalojnë kontrollet
- **filename** (*string*) – emër karteje përkthimi
- **fuzzy** (*int*) – number of fuzzy (marked for edit) strings
- **fuzzy_percent** (*float*) – percentage of fuzzy (marked for edit) strings
- **fuzzy_words** (*int*) – number of words in fuzzy (marked for edit) strings
- **have_comment** (*int*) – numër vargjesh me koment
- **have_suggestion** (*int*) – numër vargjesh me sugjerim
- **is_template** (*boolean*) – whether the translation has a monolingual base
- **language** (*object*) – source language object; see `GET /api/languages/(string:language)/`
- **language_code** (*string*) – language code used in the repository; this can be different from language code in the language object
- **last_author** (*string*) – emër autori të fundit
- **last_change** (*timestamp*) – vullë kohore e ndryshimit të fundit
- **revision** (*string*) – revision hash for the file
- **share_url** (*string*) – URL for sharing leading to engagement page
- **total** (*int*) – total number of strings
- **total_words** (*int*) – total number of words
- **translate_url** (*string*) – URL për përkthim
- **translated** (*int*) – number of translated strings

- **translated_percent** (*float*) – percentage of translated strings
- **translated_words** (*int*) – number of translated words
- **repository_url** (*string*) – URL to repository status; see `GET /api/translations/(string:project)/(string:component)/(string:language)/repository/`
- **file_url** (*string*) – URL to file object; see `GET /api/translations/(string:project)/(string:component)/(string:language)/file/`
- **changes_list_url** (*string*) – URL to changes list; see `GET /api/translations/(string:project)/(string:component)/(string:language)/changes/`
- **units_list_url** (*string*) – URL to strings list; see `GET /api/translations/(string:project)/(string:component)/(string:language)/units/`

Example JSON data:

```
{
  "component": {
    "branch": "main",
    "file_format": "po",
    "filemask": "po/*.po",
    "git_export": "",
    "license": "",
    "license_url": "",
    "name": "Weblate",
    "new_base": "",
    "project": {
      "name": "Hello",
      "slug": "hello",
      "source_language": {
        "code": "en",
        "direction": "ltr",
        "name": "English",
        "url": "http://example.com/api/languages/en/",
        "web_url": "http://example.com/languages/en/"
      },
      "url": "http://example.com/api/projects/hello/",
      "web": "https://weblate.org/",
      "web_url": "http://example.com/projects/hello/"
    },
    "repo": "file:///home/nijel/work/weblate-hello",
    "slug": "weblate",
    "template": "",
    "url": "http://example.com/api/components/hello/weblate/",
    "vcs": "git",
    "web_url": "http://example.com/projects/hello/weblate/"
  },
  "failing_checks": 3,
  "failing_checks_percent": 75.0,
  "failing_checks_words": 11,
  "filename": "po/cs.po",
  "fuzzy": 0,
  "fuzzy_percent": 0.0,
  "fuzzy_words": 0,
  "have_comment": 0,
  "have_suggestion": 0,
  "is_template": false,
  "language": {
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "code": "cs",
    "direction": "ltr",
    "name": "Czech",
    "url": "http://example.com/api/languages/cs/",
    "web_url": "http://example.com/languages/cs/"
  },
  "language_code": "cs",
  "last_author": "Weblate Admin",
  "last_change": "2016-03-07T10:20:05.499",
  "revision": "7ddfafe6daaf57fc8654cc852ea6be212b015792",
  "share_url": "http://example.com/engage/hello/cs/",
  "total": 4,
  "total_words": 15,
  "translate_url": "http://example.com/translate/hello/weblate/cs/",
  "translated": 4,
  "translated_percent": 100.0,
  "translated_words": 15,
  "url": "http://example.com/api/translations/hello/weblate/cs/",
  "web_url": "http://example.com/projects/hello/weblate/cs/"
}

```

DELETE `/api/translations/` (**string:** *project*) /
string: *component* / **string:** *language* / Të reja në versionin 3.9.

Fshin një përkthim.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

GET `/api/translations/` (**string:** *project*) /
string: *component* / **string:** *language* / **changes** / Returns a list of translation changes. This is essentially a translations-scoped `GET /api/changes/` accepting the same parameters.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

Response JSON Object

- **results** (*array*) – array of component objects; see `GET /api/changes/` (*int:id*) /

GET `/api/translations/` (**string:** *project*) /
string: *component* / **string:** *language* / **units** / Returns a list of translation units.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi
- **q** (*string*) – Search query string *Kërkim* (optional)

Response JSON Object

- **results** (*array*) – array of component objects; see `GET /api/units/` (*int:id*) /

POST `/api/translations/(string: project) /`
string: `component/string: language/units/` Add new monolingual unit.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

Request JSON Object

- **key** (*string*) – Name of translation unit
- **value** (*array*) – The translation unit value

Shihni edhe:

[Administroni vargje](#), [adding-new-strings](#)

POST `/api/translations/(string: project) /`
string: `component/string: language/autotranslate/` Trigger automatic translation.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

Request JSON Object

- **mode** (*string*) – Mënyrë përkthim i automatizuar
- **filter_type** (*string*) – Automatic translation filter type
- **auto_source** (*string*) – Automatic translation source - mt or others
- **component** (*string*) – Aktivizoni kontribut te kujtesë e përbashkët përkthimesh për projektin, që të mund të hyni te përbërës të tjerë.
- **engines** (*array*) – Motorë përkthimi nga makina
- **threshold** (*string*) – Prag vlerësimi

GET `/api/translations/(string: project) /`
string: `component/string: language/file/` Download current translation file as it is stored in the VCS (without the `format` parameter) or converted to another format (see [Shkarkim përkthimesh](#)).

Shënim: This API endpoint uses different logic for output than rest of API as it operates on whole file rather than on data. Set of accepted `format` parameter differs and without such parameter you get translation file as stored in VCS.

Query Parameters

- **format** – File format to use; if not specified no format conversion happens; supported file formats: `po`, `mo`, `xliff`, `xliff11`, `tbx`, `csv`, `xlsx`, `json`, `aresource`, `strings`

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

POST `/api/translations/(string: project) /`
string: `component/string: language/file/` Upload new file with translations.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

Form Parameters

- **string conflict** – How to deal with conflicts (ignore, replace-translated or replace-approved)
- **file file** – Uploaded file
- **string email** – Email autori
- **string author** – Emër autori
- **string method** – Upload method (translate, approve, suggest, fuzzy, replace, source, add), see [Import methods](#)
- **string fuzzy** – Fuzzy (marked for edit) strings processing (*empty*, process, approve)

CURL example:

```
curl -X POST \
  -F file=@strings.xml \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/translations/hello/android/cs/file/
```

GET `/api/translations/(string: project) /`
string: `component/string: language/repository/` Returns information about VCS repository status.

The response is same as for `GET /api/components/(string:project)/(string:component)/repository/`.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

POST `/api/translations/(string: project) /`
string: `component/string: language/repository/` Performs given operation on the VCS repository.

See `POST /api/projects/(string:project)/repository/` for documentation.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

Request JSON Object

- **operation** (*string*) – Operation to perform: one of push, pull, commit, reset, cleanup

Response JSON Object

- **result** (*boolean*) – result of the operation

GET `/api/translations/(string: project)/string: component/string: language/statistics/` Returns detailed translation statistics.

Të reja në versionin 2.7.

Parameters

- **project** (*string*) – Identifikues URL-je projekti
- **component** (*string*) – Identifikues URL-je përbërësi
- **language** (*string*) – Kod gjuhe përkthimi

Response JSON Object

- **code** (*string*) – language code
- **failing** (*int*) – numër kontrollesh të dështuar
- **failing_percent** (*float*) – përqindje kontrollesh të dështuar
- **fuzzy** (*int*) – number of fuzzy (marked for edit) strings
- **fuzzy_percent** (*float*) – percentage of fuzzy (marked for edit) strings
- **total_words** (*int*) – total number of words
- **translated_words** (*int*) – number of translated words
- **last_author** (*string*) – emër autori të fundit
- **last_change** (*timestamp*) – datë e ndryshimit të fundit
- **name** (*string*) – language name
- **total** (*int*) – total number of strings
- **translated** (*int*) – number of translated strings
- **translated_percent** (*float*) – percentage of translated strings
- **url** (*string*) – URL to access the translation (engagement URL)
- **url_translate** (*string*) – URL to access the translation (real translation URL)

1.12.10 Njësi

A *unit* is a single piece of a translation which pairs a source string with a corresponding translated string and also contains some related metadata. The term is derived from the [Translate Toolkit](#) and XLIFF.

Të reja në versionin 2.10.

GET `/api/units/`
Returns list of translation units.

Shihni edhe:

Unit object attributes are documented at `GET /api/units/(int:id)/`.

GET `/api/units/(int: id)/`
Ndryshuar në versionin 4.3: The `target` and `source` are now arrays to properly handle plural strings.
Returns information about translation unit.

Parameters

- **id** (*int*) – ID Njësie

Response JSON Object

- **translation** (*string*) – URL of a related translation object
- **source** (*array*) – varg burim

- **previous_source** (*string*) – previous source string used for fuzzy matching
- **target** (*array*) – target string
- **id_hash** (*string*) – unique identifier of the unit
- **content_hash** (*string*) – unique identifier of the source string
- **location** (*string*) – location of the unit in source code
- **context** (*string*) – translation unit context
- **note** (*string*) – translation unit note
- **flags** (*string*) – translation unit flags
- **state** (*int*) – unit state, 0 - not translated, 10 - needs editing, 20 - translated, 30 - approved, 100 - read only
- **fuzzy** (*boolean*) – whether the unit is fuzzy or marked for review
- **translated** (*boolean*) – whether the unit is translated
- **approved** (*boolean*) – whether the translation is approved
- **position** (*int*) – unit position in translation file
- **has_suggestion** (*boolean*) – whether the unit has suggestions
- **has_comment** (*boolean*) – whether the unit has comments
- **has_failing_check** (*boolean*) – whether the unit has failing checks
- **num_words** (*int*) – number of source words
- **priority** (*int*) – translation priority; 100 is default
- **id** (*int*) – unit identifier
- **explanation** (*string*) – String explanation, available on source units, see [Additional info on source strings](#)
- **extra_flags** (*string*) – Additional string flags, available on source units, see [Customizing behavior using flags](#)
- **web_url** (*string*) – URL where the unit can be edited
- **source_unit** (*string*) – Source unit link; see `GET /api/units/(int:id)/`

PATCH /api/units/(int: id) /

Të reja në versionin 4.3.

Performs partial update on translation unit.

Parameters

- **id** (*int*) – ID Njësie

Request JSON Object

- **state** (*int*) – unit state, 0 - not translated, 10 - needs editing, 20 - translated, 30 - approved (need review workflow enabled, see [Shqyrtues enkas](#))
- **target** (*array*) – target string
- **explanation** (*string*) – String explanation, available on source units, see [Additional info on source strings](#)
- **extra_flags** (*string*) – Additional string flags, available on source units, see [Customizing behavior using flags](#)

PUT /api/units/(int: id) /

Të reja në versionin 4.3.

Performs full update on translation unit.

Parameters

- **id** (*int*) – ID Njësie

Request JSON Object

- **state** (*int*) – unit state, 0 - not translated, 10 - needs editing, 20 - translated, 30 - approved (need review workflow enabled, see [Shqyrtues enkas](#))
- **target** (*array*) – target string
- **explanation** (*string*) – String explanation, available on source units, see [Additional info on source strings](#)
- **extra_flags** (*string*) – Additional string flags, available on source units, see [Customizing behavior using flags](#)

DELETE /api/units/ (*int: id*) /

Të reja në versionin 4.3.

Deletes a translation unit.

Parameters

- **id** (*int*) – ID Njësie

1.12.11 Ndryshime

Të reja në versionin 2.10.

GET /api/changes/

Ndryshuar në versionin 4.1: Filtering of changes was introduced in the 4.1 release.

Returns a list of translation changes.

Shihni edhe:

Change object attributes are documented at [GET /api/changes/ \(*int:id*\) /](#).

Query Parameters

- **user** (*string*) – Username of user to filters
- **action** (*int*) – Action to filter, can be used several times
- **timestamp_after** (*timestamp*) – ISO 8601 formatted timestamp to list changes after
- **timestamp_before** (*timestamp*) – ISO 8601 formatted timestamp to list changes before

GET /api/changes/ (*int: id*) /

Returns information about translation change.

Parameters

- **id** (*int*) – Change ID

Response JSON Object

- **unit** (*string*) – URL of a related unit object
- **translation** (*string*) – URL of a related translation object
- **component** (*string*) – URL of a related component object
- **user** (*string*) – URL of a related user object
- **author** (*string*) – URL of a related author object
- **timestamp** (*timestamp*) – vullë kohore e aktit

- **action** (*int*) – numeric identification of action
- **action_name** (*string*) – text description of action
- **target** (*string*) – event changed text or detail
- **id** (*int*) – change identifier

1.12.12 Foto ekrani

Të reja në versionin 2.14.

GET /api/screenshots/

Returns a list of screenshot string information.

Shihni edhe:

Screenshot object attributes are documented at [GET /api/screenshots/\(int:id\)/](#).

GET /api/screenshots/(int: id) /

Returns information about screenshot information.

Parameters

- **id** (*int*) – Screenshot ID

Response JSON Object

- **name** (*string*) – name of a screenshot
- **component** (*string*) – URL of a related component object
- **file_url** (*string*) – URL to download a file; see [GET /api/screenshots/\(int:id\)/file/](#)
- **units** (*array*) – link to associated source string information; see [GET /api/units/\(int:id\)/](#)

GET /api/screenshots/(int: id) /file/

Download the screenshot image.

Parameters

- **id** (*int*) – Screenshot ID

POST /api/screenshots/(int: id) /file/

Replace screenshot image.

Parameters

- **id** (*int*) – Screenshot ID

Form Parameters

- **file image** – Uploaded file

CURL example:

```
curl -X POST \
  -F image=@image.png \
  -H "Authorization: Token TOKEN" \
  http://example.com/api/screenshots/1/file/
```

POST /api/screenshots/(int: id) /units/

Associate source string with screenshot.

Parameters

- **id** (*int*) – Screenshot ID

Form Parameters

- **string unit_id** – ID Njësie

Response JSON Object

- **name** (*string*) – name of a screenshot
- **translation** (*string*) – URL of a related translation object
- **file_url** (*string*) – URL to download a file; see *GET /api/screenshots/(int:id)/file/*
- **units** (*array*) – link to associated source string information; see *GET /api/units/(int:id)/*

DELETE /api/screenshots/(int: id)/units/
int: *unit_id* Remove source string association with screenshot.

Parameters

- **id** (*int*) – Screenshot ID
- **unit_id** – Source string unit ID

POST /api/screenshots/
Creates a new screenshot.

Form Parameters

- **file image** – Uploaded file
- **string name** – Emër fotoje ekrani
- **string project_slug** – Project slug
- **string component_slug** – Component slug
- **string language_code** – Kod gjuhe

Response JSON Object

- **name** (*string*) – name of a screenshot
- **component** (*string*) – URL of a related component object
- **file_url** (*string*) – URL to download a file; see *GET /api/screenshots/(int:id)/file/*
- **units** (*array*) – link to associated source string information; see *GET /api/units/(int:id)/*

PATCH /api/screenshots/(int: id) /
Edit partial information about screenshot.

Parameters

- **id** (*int*) – Screenshot ID

Response JSON Object

- **name** (*string*) – name of a screenshot
- **component** (*string*) – URL of a related component object
- **file_url** (*string*) – URL to download a file; see *GET /api/screenshots/(int:id)/file/*
- **units** (*array*) – link to associated source string information; see *GET /api/units/(int:id)/*

PUT /api/screenshots/(int: id) /
Edit full information about screenshot.

Parameters

- **id** (*int*) – Screenshot ID

Response JSON Object

- **name** (*string*) – name of a screenshot
- **component** (*string*) – URL of a related component object
- **file_url** (*string*) – URL to download a file; see `GET /api/screenshots/(int:id)/file/`
- **units** (*array*) – link to associated source string information; see `GET /api/units/(int:id)/`

DELETE `/api/screenshots/(int: id) /`
Delete screenshot.

Parameters

- **id** (*int*) – Screenshot ID

1.12.13 Shtesa

Të reja në versionin 4.4.1.

GET `/api/addons/`
Returns a list of addons.

Shihni edhe:

Add-on object attributes are documented at `GET /api/addons/(int:id)/`.

GET `/api/addons/(int: id) /`
Returns information about addon information.

Parameters

- **id** (*int*) – Add-on ID

Response JSON Object

- **name** (*string*) – name of an addon
- **component** (*string*) – URL of a related component object
- **configuration** (*object*) – Optional addon configuration

Shihni edhe:

Shtesa

POST `/api/components/(string: project) /`
string: `component/addons/` Creates a new addon.

Parameters

- **project_slug** (*string*) – Project slug
- **component_slug** (*string*) – Component slug

Request JSON Object

- **name** (*string*) – name of an addon
- **configuration** (*object*) – Optional addon configuration

PATCH `/api/addons/(int: id) /`
Edit partial information about addon.

Parameters

- **id** (*int*) – Add-on ID

Response JSON Object

- **configuration** (*object*) – Optional addon configuration

PUT `/api/addons/(int: id) /`
Edit full information about addon.

Parameters

- **id** (*int*) – Add-on ID

Response JSON Object

- **configuration** (*object*) – Optional addon configuration

DELETE `/api/addons/(int: id) /`
Delete addon.

Parameters

- **id** (*int*) – Add-on ID

1.12.14 Lista përbërësish

Të reja në versionin 4.0.

GET `/api/component-lists/`
Returns a list of component lists.

Shihni edhe:

Component list object attributes are documented at `GET /api/component-lists/(str:slug) /`.

GET `/api/component-lists/(str: slug) /`
Returns information about component list.

Parameters

- **slug** (*string*) – Identifikues liste përbërësish

Response JSON Object

- **name** (*string*) – emër i një liste përbërësish
- **slug** (*string*) – identifikues i një liste përbërësish
- **show_dashboard** (*boolean*) – të shfaqet apo jo në një pult
- **components** (*array*) – link to associated components; see `GET /api/components/(string:project)/(string:component) /`
- **auto_assign** (*array*) – automatic assignment rules

PUT `/api/component-lists/(str: slug) /`
Ndryshon parametrat e listës së përbërësve.

Parameters

- **slug** (*string*) – Identifikues liste përbërësish

Request JSON Object

- **name** (*string*) – emër i një liste përbërësish
- **slug** (*string*) – identifikues i një liste përbërësish
- **show_dashboard** (*boolean*) – të shfaqet apo jo në një pult

PATCH `/api/component-lists/(str: slug) /`
Ndryshon parametrat e listës së përbërësve.

Parameters

- **slug** (*string*) – Identifikues liste përbërësish

Request JSON Object

- **name** (*string*) – emër i një liste përbërësish
- **slug** (*string*) – identifikues i një liste përbërësish
- **show_dashboard** (*boolean*) – të shfaqet apo jo në një pult

DELETE /api/component-lists/ (str: slug) /

Fshin listën e përbërësve.

Parameters

- **slug** (*string*) – Identifikues liste përbërësish

POST /api/component-lists/ (str: slug) /components/

Përshoqëroni përbërës me një listë përbërësish.

Parameters

- **slug** (*string*) – Identifikues liste përbërësish

Form Parameters

- **string component_id** – ID Përbërësi

DELETE /api/component-lists/ (str: slug) /components/

str: component_slug Disassociate a component from the component list.

Parameters

- **slug** (*string*) – Identifikues liste përbërësish
- **component_slug** (*string*) – Component slug

1.12.15 Fjalorth

Ndryshuar në versionin 4.5: Glossaries are now stored as regular components, translations and strings, please use respective API instead.

1.12.16 Tasks

Të reja në versionin 4.4.

GET /api/tasks/

Listing of the tasks is currently not available.

GET /api/tasks/ (str: uuid) /

Returns information about a task

Parameters

- **uuid** (*string*) – Task UUID

Response JSON Object

- **completed** (*boolean*) – Whether the task has completed
- **progress** (*int*) – Task progress in percent
- **result** (*object*) – Task result or progress details
- **log** (*string*) – Task log

1.12.17 Metrics

GET `/api/metrics/`
Returns server metrics.

Response JSON Object

- **units** (*int*) – Number of units
- **units_translated** (*int*) – Number of translated units
- **users** (*int*) – Number of users
- **changes** (*int*) – Numër Ndryshimesh
- **projects** (*int*) – Number of projects
- **components** (*int*) – Numër përbërësish
- **translations** (*int*) – Number of translations
- **languages** (*int*) – Number of used languages
- **checks** (*int*) – Number of triggered quality checks
- **configuration_errors** (*int*) – Number of configuration errors
- **suggestions** (*int*) – Number of pending suggestions
- **celery_queues** (*object*) – Lengths of Celery queues, see *Background tasks using Celery*
- **name** (*string*) – Configured server name

1.12.18 Hook-e njoftimesh

Notification hooks allow external applications to notify Weblate that the VCS repository has been updated.

You can use repository endpoints for projects, components and translations to update individual repositories; see `POST /api/projects/(string:project)/repository/` for documentation.

GET `/hooks/update/(string: project) /`
string: *component/* Nxjerrë nga përdorimi që me versionin 2.6: Please use `POST /api/components/(string:project)/(string:component)/repository/` instead which works properly with authentication for ACL limited projects.

Triggers update of a component (pulling from VCS and scanning for translation changes).

GET `/hooks/update/(string: project) /`
Nxjerrë nga përdorimi që me versionin 2.6: Please use `POST /api/projects/(string:project)/repository/` instead which works properly with authentication for ACL limited projects.

Triggers update of all components in a project (pulling from VCS and scanning for translation changes).

POST `/hooks/github/`
Special hook for handling GitHub notifications and automatically updating matching components.

Shënim: GitHub includes direct support for notifying Weblate: enable Weblate service hook in repository settings and set the URL to the URL of your Weblate installation.

Shihni edhe:

Automatically receiving changes from GitHub For instruction on setting up GitHub integration

<https://docs.github.com/en/github/extending-github/about-webhooks> Generic information about GitHub Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST /hooks/gitlab/

Special hook for handling GitLab notifications and automatically updating matching components.

Shihni edhe:

Automatically receiving changes from GitLab For instruction on setting up GitLab integration

<https://docs.gitlab.com/ce/user/project/integrations/webhooks.html> Generic information about GitLab Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST /hooks/bitbucket/

Special hook for handling Bitbucket notifications and automatically updating matching components.

Shihni edhe:

Automatically receiving changes from Bitbucket For instruction on setting up Bitbucket integration

<https://support.atlassian.com/bitbucket-cloud/docs/manage-webhooks/> Generic information about Bitbucket Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST /hooks/pagure/

Të reja në versionin 3.3.

Special hook for handling Pagure notifications and automatically updating matching components.

Shihni edhe:

Automatically receiving changes from Pagure For instruction on setting up Pagure integration

https://docs.pagure.org/pagure/usage/using_webhooks.html Generic information about Pagure Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST /hooks/azure/

Të reja në versionin 3.8.

Special hook for handling Azure Repos notifications and automatically updating matching components.

Shihni edhe:

Automatically receiving changes from Azure Repos For instruction on setting up Azure integration

<https://docs.microsoft.com/en-us/azure/devops/service-hooks/services/webhooks?view=azure-devops> Generic information about Azure Repos Web Hooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST /hooks/gitea/

Të reja në versionin 3.9.

Special hook for handling Gitea Webhook notifications and automatically updating matching components.

Shihni edhe:

Automatically receiving changes from Gitea Repos For instruction on setting up Gitea integration

<https://docs.gitea.io/en-us/webhooks/> Generic information about Gitea Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

POST /hooks/gitee/

Të reja në versionin 3.9.

Special hook for handling Gitee Webhook notifications and automatically updating matching components.

Shihni edhe:

Automatically receiving changes from Gitee Repos For instruction on setting up Gitee integration

<https://gitee.com/help/categories/40> Generic information about Gitee Webhooks

ENABLE_HOOKS For enabling hooks for whole Weblate

1.12.19 Eksporte

Weblate provides various exports to allow you to further process the data.

GET /exports/stats/(string: project) /
string: component/

Query Parameters

- **format** (*string*) – Output format: either json or csv

Nxjerrë nga përdorimi që me versionin 2.6: Please use `GET /api/components/(string:project)/(string:component)/statistics/` and `GET /api/translations/(string:project)/(string:component)/(string:language)/statistics/` instead; it allows access to ACL controlled projects as well.

Retrieves statistics for given component in given format.

Shembull kërkesë:

```
GET /exports/stats/weblate/main/ HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
```

Shembull përgjigjeje:

```
HTTP/1.1 200 OK
Vary: Accept
Content-Type: application/json

[
  {
    "code": "cs",
    "failing": 0,
    "failing_percent": 0.0,
    "fuzzy": 0,
    "fuzzy_percent": 0.0,
    "last_author": "Michal Čihař",
    "last_change": "2012-03-28T15:07:38+00:00",
    "name": "Czech",
    "total": 436,
    "total_words": 15271,
    "translated": 436,
    "translated_percent": 100.0,
    "translated_words": 3201,
    "url": "http://hosted.weblate.org/engage/weblate/cs/",
    "url_translate": "http://hosted.weblate.org/projects/weblate/main/cs/"
  },
  {
    "code": "nl",
    "failing": 21,
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "failing_percent": 4.8,
    "fuzzy": 11,
    "fuzzy_percent": 2.5,
    "last_author": null,
    "last_change": null,
    "name": "Dutch",
    "total": 436,
    "total_words": 15271,
    "translated": 319,
    "translated_percent": 73.2,
    "translated_words": 3201,
    "url": "http://hosted.weblate.org/engage/weblate/nl/",
    "url_translate": "http://hosted.weblate.org/projects/weblate/main/nl/"
  },
  {
    "code": "el",
    "failing": 11,
    "failing_percent": 2.5,
    "fuzzy": 21,
    "fuzzy_percent": 4.8,
    "last_author": null,
    "last_change": null,
    "name": "Greek",
    "total": 436,
    "total_words": 15271,
    "translated": 312,
    "translated_percent": 71.6,
    "translated_words": 3201,
    "url": "http://hosted.weblate.org/engage/weblate/el/",
    "url_translate": "http://hosted.weblate.org/projects/weblate/main/el/"
  }
]

```

1.12.20 Prurje RSS

Changes in translations are exported in RSS feeds.

GET /exports/rss/ (string: project) /
string: component/string: language/ Retrieves RSS feed with recent changes for a translation.

GET /exports/rss/ (string: project) /
string: component/ Retrieves RSS feed with recent changes for a component.

GET /exports/rss/ (string: project) /
 Retrieves RSS feed with recent changes for a project.

GET /exports/rss/language/ (string: language) /
 Retrieves RSS feed with recent changes for a language.

GET /exports/rss/
 Retrieves RSS feed with recent changes for Weblate instance.

Shihni edhe:

[RSS on wikipedia](#)

1.13 Klient Weblate

Të reja në versionin 2.7: There has been full wlc utility support ever since Weblate 2.7. If you are using an older version some incompatibilities with the API might occur.

1.13.1 Instalim

The Weblate Client is shipped separately and includes the Python module. To use the commands below, you need to install *wlc*:

```
pip3 install wlc
```

1.13.2 Përdorim Docker-i

The Weblate Client is also available as a Docker image.

The image is published on Docker Hub: <https://hub.docker.com/r/weblate/wlc>

Installing:

```
docker pull weblate/wlc
```

The Docker container uses Weblate's default settings and connects to the API deployed in localhost. The API URL and API_KEY can be configured through the arguments accepted by Weblate.

The command to launch the container uses the following syntax:

```
docker run --rm weblate/wlc [WLC_ARGS]
```

Shembull:

```
docker run --rm weblate/wlc --url https://hosted.weblate.org/api/ list-projects
```

You might want to pass your *Kartela Formësimi* to the Docker container, the easiest approach is to add your current directory as /home/weblate volume:

```
docker run --volume $PWD:/home/weblate --rm weblate/wlc show
```

1.13.3 Si t'ia fillohet

The wlc configuration is stored in ~/ .config/weblate (see *Kartela Formësimi* for other locations), please create it to match your environment:

```
[weblate]
url = https://hosted.weblate.org/api/

[keys]
https://hosted.weblate.org/api/ = APIKEY
```

You can then invoke commands on the default server:

```
wlc ls
wlc commit sandbox/hello-world
```

Shihni edhe:

Kartela Formësimi

1.13.4 Synopsis

```
wlc [arguments] <command> [options]
```

Commands actually indicate which operation should be performed.

1.13.5 Përshkrim

Weblate Client is a Python library and command-line utility to manage Weblate remotely using *Weblate's REST API*. The command-line utility can be invoked as **wlc** and is built-in on *wlc*.

Argumente

The program accepts the following arguments which define output format or which Weblate instance to use. These must be entered before any command.

--format {csv,json,text,html}
Përcaktoni formatin e përfundimeve.

--url URL
Specify the API URL. Overrides any value found in the configuration file, see *Kartela Formësimi*. The URL should end with /api/, for example `https://hosted.weblate.org/api/`.

--key KEY
Specify the API user key to use. Overrides any value found in the configuration file, see *Kartela Formësimi*. You can find your key in your profile on Weblate.

--config PATH
Overrides the configuration file path, see *Kartela Formësimi*.

--config-section SECTION
Overrides configuration file section in use, see *Kartela Formësimi*.

Urdhra

Janë gati urdhrat vijues:

version
Shtyp versionin e tanishëm.

list-languages
Paraqet gjuhët e përdorura në Weblate.

list-projects
Paraqet projekte në Weblate.

list-components
Paraqet përbërës në Weblate.

list-translations
Paraqet përkthime në Weblate.

show
Shows Weblate object (translation, component or project).

ls
Lists Weblate object (translation, component or project).

commit
Commits changes made in a Weblate object (translation, component or project).

pull

Pulls remote repository changes into Weblate object (translation, component or project).

push

Pushes Weblate object changes into remote repository (translation, component or project).

reset

Të reja në versionin 0.7: Supported since wlc 0.7.

Resets changes in Weblate object to match remote repository (translation, component or project).

cleanup

Të reja në versionin 0.9: Supported since wlc 0.9.

Removes any untracked changes in a Weblate object to match the remote repository (translation, component or project).

repo

Displays repository status for a given Weblate object (translation, component or project).

statistics

Displays detailed statistics for a given Weblate object (translation, component or project).

lock-status

Të reja në versionin 0.5: Supported since wlc 0.5.

Shfaq gjendje kyçjeje.

lock

Të reja në versionin 0.5: Supported since wlc 0.5.

Locks component from further translation in Weblate.

unlock

Të reja në versionin 0.5: Supported since wlc 0.5.

Bën shkyçjen e përkthimit të përbërësit Weblate.

changes

Të reja në versionin 0.7: Supported since wlc 0.7 and Weblate 2.10.

Shfaq ndryshime për një objekt të dhënë.

download

Të reja në versionin 0.7: Supported since wlc 0.7.

Shkarkon një kartelë përkthimi.

--convert

Converts file format, if unspecified no conversion happens on the server and the file is downloaded as is to the repository.

--output

Specifies file to save output in, if left unspecified it is printed to stdout.

upload

Të reja në versionin 0.9: Supported since wlc 0.9.

Ngarkon një kartelë përkthimi.

--overwrite

Mbishkruaj përkthime ekzistuese gjatë ngarkimit.

--input

File from which content is read, if left unspecified it is read from stdin.

Ndihmëz: You can get more detailed information on invoking individual commands by passing `--help`, for example: `wlc ls --help`.

1.13.6 Kartela Formësimi

.weblate, **.weblate.ini**, **weblate.ini** Ndryshuar në versionin 1.6: The files with *.ini* extension are accepted as well.

Per project configuration file

C:\Users\NAME\AppData\weblate.ini Të reja në versionin 1.6.

Kartelë formësimi përdoruesi në Windows.

~/.config/weblate Kartelë formësimi përdoruesi

/etc/xdg/weblate Kartelë formësimi për mbarë sistemin

The program follows the XDG specification, so you can adjust placement of config files by environment variables `XDG_CONFIG_HOME` or `XDG_CONFIG_DIRS`. On Windows APPDATA directory is preferred location for the configuration file.

Following settings can be configured in the `[weblate]` section (you can customize this by `--config-section`):

key

KYÇ API për hyrje në Weblate.

url

API server URL, defaults to `http://127.0.0.1:8000/api/`.

translation

Path to the default translation - component or project.

Kartela e formësimi, është një kartelë INI, për shembull:

```
[weblate]
url = https://hosted.weblate.org/api/
key = APIKEY
translation = weblate/application
```

Additionally API keys can be stored in the `[keys]` section:

```
[keys]
https://hosted.weblate.org/api/ = APIKEY
```

This allows you to store keys in your personal settings, while using the `.weblate` configuration in the VCS repository so that `wlc` knows which server it should talk to.

1.13.7 Shembuj

Shtyp të dhëna versioni aktual të programit:

```
$ wlc version
version: 0.1
```

Paraqit krejt projektet:

```
$ wlc list-projects
name: Hello
slug: hello
url: http://example.com/api/projects/hello/
web: https://weblate.org/
web_url: http://example.com/projects/hello/
```

You can also designate what project `wlc` should work on:

```
$ cat .weblate
[weblate]
url = https://hosted.weblate.org/api/
translation = weblate/application

$ wlc show
branch: main
file_format: po
source_language: en
filemask: weblate/locale/*/LC_MESSAGES/django.po
git_export: https://hosted.weblate.org/git/weblate/application/
license: GPL-3.0+
license_url: https://spdx.org/licenses/GPL-3.0+
name: Application
new_base: weblate/locale/django.pot
project: weblate
repo: git://github.com/WeblateOrg/weblate.git
slug: application
template:
url: https://hosted.weblate.org/api/components/weblate/application/
vcs: git
web_url: https://hosted.weblate.org/projects/weblate/application/
```

With this setup it is easy to commit pending changes in the current project:

```
$ wlc commit
```

1.14 API Python e Weblate-it

1.14.1 Instalim

The Python API is shipped separately, you need to install the *Klient Weblate*: (wlc) to have it.

```
pip install wlc
```

1.14.2 wlc

WeblateException

exception `wlc.WeblateException`

Klasë bazë për krejt përjashtimet.

Weblate

class `wlc.Weblate` (*key=""*, *url=None*, *config=None*)

Parametra

- **key** (*str*) – Kyç përdoruesi
- **url** (*str*) – API server URL, if not specified default is used
- **config** (`wlc.config.WeblateConfig`) – Configuration object, overrides any other parameters.

Access class to the API, define API key and optionally API URL.

get (*path*)

Parametra *path* (*str*) – Shteg kërkesë

Lloj kthimi *object*

Performs a single API GET call.

post (*path*, ***kwargs*)

Parametra *path* (*str*) – Shteg kërkesë

Lloj kthimi *object*

Performs a single API GET call.

1.14.3 wlc.config

WeblateConfig

class `wlc.config.WeblateConfig` (*section*='wlc')

Parametra *section* (*str*) – Ndarje formësimi për t'u përdorur

Configuration file parser following XDG specification.

load (*path*=None)

Parametra *path* (*str*) – Path from which to load configuration.

Loads configuration from a file, if none is specified, it loads from the *wlc* configuration file (`~/.config/wlc`) placed in your XDG configuration path (`/etc/xdg/wlc`).

1.14.4 wlc.main

`wlc.main.main` (*settings*=None, *stdout*=None, *args*=None)

Parametra

- **settings** (*list*) – Settings to override as list of tuples
- **stdout** (*object*) – stdout file object for printing output, uses `sys.stdout` as default
- **args** (*list*) – Command-line arguments to process, uses `sys.args` as default

Main entry point for command-line interface.

`@wlc.main.register_command` (*command*)

Decorator to register *Command* class in main parser used by *main()*.

Command

```
class wlc.main.Command(args, config, stdout=None)  
    Main class for invoking commands.
```

2.1 Udhëzime formësimi

2.1.1 Instalim i Weblate-it

Installing using Docker

With dockerized Weblate deployment you can get your personal Weblate instance up and running in seconds. All of Weblate's dependencies are already included. PostgreSQL is set up as the default database.

Domosdoshmëri hardware

Weblate should run on any contemporary hardware without problems, the following is the minimal configuration required to run Weblate on a single host (Weblate, database and webserver):

- 2 GB RAM
- 2 CPU cores
- 1 GB of storage space

The more memory the better - it is used for caching on all levels (filesystem, database and Weblate).

Many concurrent users increases the amount of needed CPU cores. For hundreds of translation components at least 4 GB of RAM is recommended.

The typical database storage usage is around 300 MB per 1 million hosted words. Storage space needed for cloned repositories varies, but Weblate tries to keep their size minimal by doing shallow clones.

Shënim: Actual requirements for your installation of Weblate vary heavily based on the size of the translations managed in it.

Instalim

The following examples assume you have a working Docker environment, with `docker-compose` installed. Please check the Docker documentation for instructions.

1. Clone the weblate-docker repo:

```
git clone https://github.com/WeblateOrg/docker-compose.git weblate-docker
cd weblate-docker
```

2. Create a `docker-compose.override.yml` file with your settings. See *Ndryshore mjedisi Docker* for full list of environment variables.

```
version: '3'
services:
  weblate:
    ports:
      - 80:8080
    environment:
      WEBLATE_EMAIL_HOST: smtp.example.com
      WEBLATE_EMAIL_HOST_USER: user
      WEBLATE_EMAIL_HOST_PASSWORD: pass
      WEBLATE_SERVER_EMAIL: weblate@example.com
      WEBLATE_DEFAULT_FROM_EMAIL: weblate@example.com
      WEBLATE_SITE_DOMAIN: weblate.example.com
      WEBLATE_ADMIN_PASSWORD: password for the admin user
      WEBLATE_ADMIN_EMAIL: weblate.admin@example.com
```

Shënim: If `WEBLATE_ADMIN_PASSWORD` is not set, the admin user is created with a random password shown on first startup.

The provided example makes Weblate listen on port 80, edit the port mapping in the `docker-compose.override.yml` file to change it.

3. Start Weblate containers:

```
docker-compose up
```

Enjoy your Weblate deployment, it's accessible on port 80 of the `weblate` container.

Ndryshuar në versionin 2.15-2: The setup has changed recently, priorly there was separate web server container, since 2.15-2 the web server is embedded in the Weblate container.

Ndryshuar në versionin 3.7.1-6: In July 2019 (starting with the 3.7.1-6 tag), the containers are not running as a root user. This has changed the exposed port from 80 to 8080.

Shihni edhe:

Invoking management commands

Choosing Docker hub tag

You can use following tags on Docker hub, see <https://hub.docker.com/r/weblate/weblate/tags/> for full list of available ones.

Tag name	Përshkrim	Use case
latest	Weblate stable release, matches latest tagged release	Rolling updates in a production environment
<VERSION>-<PATCH>	Weblate stable release	Well defined deploy in a production environment
edge	Weblate stable release with development changes in the Docker container (for example updated dependencies)	Rolling updates in a staging environment
edge-<DATE>-<SHA>	Weblate stable release with development changes in the Docker container (for example updated dependencies)	Well defined deploy in a staging environment
bleeding	Development version Weblate from Git	Rolling updates to test upcoming Weblate features
bleeding-<DATE>-<SHA>	Development version Weblate from Git	Well defined deploy to test upcoming Weblate features

Every image is tested by our CI before it gets published, so even the *bleeding* version should be quite safe to use.

Docker container with HTTPS support

Please see *Instalim* for generic deployment instructions, this section only mentions differences compared to it.

Using own SSL certificates

Të reja në versionin 3.8-3.

In case you have own SSL certificate you want to use, simply place the files into the Weblate data volume (see *Docker container volumes*):

- `ssl/fullchain.pem` containing the certificate including any needed CA certificates
- `ssl/privkey.pem` containing the private key

Both of these files must be owned by the same user as the one starting the docker container and have file mask set to 600 (readable and writable only by the owning user).

Additionally, Weblate container will now accept SSL connections on port 4443, you will want to include the port forwarding for HTTPS in docker compose override:

```
version: '3'
services:
  weblate:
    ports:
      - 80:8080
      - 443:4443
```

If you already host other sites on the same server, it is likely ports 80 and 443 are used by a reverse proxy, such as NGINX. To pass the HTTPS connection from NGINX to the docker container, you can use the following configuration:

```
server {
    listen 443;
    listen [::]:443;
```

(vazhdon në faqen pasuese)

```

server_name <SITE_URL>;
ssl_certificate /etc/letsencrypt/live/<SITE>/fullchain.pem;
ssl_certificate_key /etc/letsencrypt/live/<SITE>/privkey.pem;

location / {
    proxy_set_header HOST $host;
    proxy_set_header X-Forwarded-Proto https;
    proxy_set_header X-Real-IP $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header X-Forwarded-Host $server_name;
    proxy_pass https://127.0.0.1:<EXPOSED_DOCKER_PORT>;
}
}

```

Replace <SITE_URL>, <SITE> and <EXPOSED_DOCKER_PORT> with actual values from your environment.

Automatic SSL certificates using Let's Encrypt

In case you want to use [Let's Encrypt](#) automatically generated SSL certificates on public installation, you need to add a reverse HTTPS proxy an additional Docker container, [https-portal](#) will be used for that. This is made use of in the `docker-compose-https.yml` file. Then create a `docker-compose-https.override.yml` file with your settings:

```

version: '3'
services:
  weblate:
    environment:
      WEBLATE_EMAIL_HOST: smtp.example.com
      WEBLATE_EMAIL_HOST_USER: user
      WEBLATE_EMAIL_HOST_PASSWORD: pass
      WEBLATE_SITE_DOMAIN: weblate.example.com
      WEBLATE_ADMIN_PASSWORD: password for admin user
  https-portal:
    environment:
      DOMAINS: 'weblate.example.com -> http://weblate:8080'

```

Whenever invoking **docker-compose** you need to pass both files to it, and then do:

```

docker-compose -f docker-compose-https.yml -f docker-compose-https.override.yml
↩️build
docker-compose -f docker-compose-https.yml -f docker-compose-https.override.yml up

```

Upgrading the Docker container

Usually it is good idea to only update the Weblate container and keep the PostgreSQL container at the version you have, as upgrading PostgreSQL is quite painful and in most cases does not bring many benefits.

You can do this by sticking with the existing docker-compose and just pull the latest images and then restart:

```

docker-compose stop
docker-compose pull
docker-compose up

```

The Weblate database should be automatically migrated on first startup, and there should be no need for additional manual actions.

Shënim: Upgrades across 3.0 are not supported by Weblate. If you are on 2.x series and want to upgrade to 3.x, first upgrade to the latest 3.0.1-x (at time of writing this it is the 3.0.1-7) image, which will do the migration and then continue upgrading to newer versions.

You might also want to update the `docker-compose` repository, though it's not needed in most case. Please beware of PostgreSQL version changes in this case as it's not straightforward to upgrade the database, see [GitHub issue](#) for more info.

Admin sign in

After container setup, you can sign in as `admin` user with password provided in `WEBLATE_ADMIN_PASSWORD`, or a random password generated on first start if that was not set.

To reset `admin` password, restart the container with `WEBLATE_ADMIN_PASSWORD` set to new password.

Shihni edhe:

`WEBLATE_ADMIN_PASSWORD`, `WEBLATE_ADMIN_NAME`, `WEBLATE_ADMIN_EMAIL`

Number of processes and memory consumption

The number of worker processes for both uWSGI and Celery is determined automatically based on number of CPUs. This works well for most cloud virtual machines as these typically have few CPUs and good amount of memory.

In case you have a lot of CPU cores and hit out of memory issues, try reducing number of workers:

```
environment:
  WEBLATE_WORKERS: 2
```

You can also fine-tune individual worker categories:

```
environment:
  UWSGI_WORKERS: 4
  CELERY_MAIN_OPTIONS: --concurrency 2
  CELERY_NOTIFY_OPTIONS: --concurrency 1
  CELERY_TRANSLATE_OPTIONS: --concurrency 1
```

Shihni edhe:

`WEBLATE_WORKERS`, `CELERY_MAIN_OPTIONS`, `CELERY_NOTIFY_OPTIONS`,
`CELERY_MEMORY_OPTIONS`, `CELERY_TRANSLATE_OPTIONS`, `CELERY_BACKUP_OPTIONS`,
`CELERY_BEAT_OPTIONS`, `UWSGI_WORKERS`

Scaling horizontally

Të reja në versionin 4.6.

Sinjalizim: This feature is a technology preview.

You can run multiple Weblate containers to scale the service horizontally. The `/app/data` volume has to be shared by all containers, it is recommended to use cluster filesystem such as GlusterFS for this. The `/app/cache` volume should be separate for each container.

Each Weblate container has defined role using `WEBLATE_SERVICE` environment variable. Please follow carefully the documentation as some of the services should be running just once in the cluster and the ordering of the services matters as well.

You can find example setup in the `docker-compose` repo as [docker-compose-split.yml](#).

Ndryshore mjedisi Docker

Many of Weblate's *Formësim* can be set in the Docker container using environment variables:

Rregullime të përgjithshme

WEBLATE_DEBUG

Configures Django debug mode using *DEBUG*.

Example:

```
environment:
  WEBLATE_DEBUG: 1
```

Shihni edhe:

Disable debug mode

WEBLATE_LOGLEVEL

Configures the logging verbosity.

WEBLATE_SITE_TITLE

Changes the site-title shown in the header of all pages.

WEBLATE_SITE_DOMAIN

Configures the site domain. This parameter is required.

Shihni edhe:

Set correct site domain, SITE_DOMAIN

WEBLATE_ADMIN_NAME

WEBLATE_ADMIN_EMAIL

Configures the site-admin's name and e-mail. It is used for both *ADMINS* setting and creating *admin* user (see *WEBLATE_ADMIN_PASSWORD* for more info on that).

Example:

```
environment:
  WEBLATE_ADMIN_NAME: Weblate admin
  WEBLATE_ADMIN_EMAIL: noreply@example.com
```

Shihni edhe:

Admin sign in, Properly configure admins, ADMINS

WEBLATE_ADMIN_PASSWORD

Sets the password for the *admin* user.

- If not set and *admin* user does not exist, it is created with a random password shown on first container startup.
- If not set and *admin* user exists, no action is performed.
- If set the *admin* user is adjusted on every container startup to match *WEBLATE_ADMIN_PASSWORD*, *WEBLATE_ADMIN_NAME* and *WEBLATE_ADMIN_EMAIL*.

Sinjalizim: It might be a security risk to store password in the configuration file. Consider using this variable only for initial setup (or let Weblate generate random password on initial startup) or for password recovery.

Shihni edhe:

Admin sign in, `WEBLATE_ADMIN_PASSWORD`, `WEBLATE_ADMIN_PASSWORD_FILE`, `WEBLATE_ADMIN_NAME`, `WEBLATE_ADMIN_EMAIL`

WEBLATE_ADMIN_PASSWORD_FILE

Sets the path to a file containing the password for the *admin* user.

Shihni edhe:

`WEBLATE_ADMIN_PASSWORD`

WEBLATE_SERVER_EMAIL**WEBLATE_DEFAULT_FROM_EMAIL**

Configures the address for outgoing e-mails.

Shihni edhe:

Formësoni dërgimi email-esh

WEBLATE_CONTACT_FORM

Configures contact form behavior, see *`CONTACT_FORM`*.

WEBLATE_ALLOWED_HOSTS

Configures allowed HTTP hostnames using *`ALLOWED_HOSTS`*.

Defaults to * which allows all hostnames.

Example:

```
environment:
  WEBLATE_ALLOWED_HOSTS: weblate.example.com,example.com
```

Shihni edhe:

`ALLOWED_HOSTS`, `Allowed hosts setup`, `Set correct site domain`

WEBLATE_REGISTRATION_OPEN

Configures whether registrations are open by toggling *`REGISTRATION_OPEN`*.

Example:

```
environment:
  WEBLATE_REGISTRATION_OPEN: 0
```

WEBLATE_REGISTRATION_ALLOW_BACKENDS

Configure which authentication methods can be used to create new account via *`REGISTRATION_ALLOW_BACKENDS`*.

Example:

```
environment:
  WEBLATE_REGISTRATION_OPEN: 0
  WEBLATE_REGISTRATION_ALLOW_BACKENDS: azuread-oauth2,azuread-tenant-
  ↪oauth2
```

WEBLATE_TIME_ZONE

Configures the used time zone in Weblate, see *`TIME_ZONE`*.

Shënim: To change the time zone of the Docker container itself, use the TZ environment variable.

Example:

```
environment:
  WEBLATE_TIME_ZONE: Europe/Prague
```

WEBLATE_ENABLE_HTTPS

Makes Weblate assume it is operated behind a reverse HTTPS proxy, it makes Weblate use HTTPS in e-mail and API links or set secure flags on cookies.

Ndihmëz: Please see [ENABLE_HTTPS](#) documentation for possible caveats.

Shënim: This does not make the Weblate container accept HTTPS connections, you need to configure that as well, see [Docker container with HTTPS support](#) for examples.

Example:

```
environment:
  WEBLATE_ENABLE_HTTPS: 1
```

Shihni edhe:

[ENABLE_HTTPS](#) Set correct site domain, [WEBLATE_SECURE_PROXY_SSL_HEADER](#)

WEBLATE_IP_PROXY_HEADER

Lets Weblate fetch the IP address from any given HTTP header. Use this when using a reverse proxy in front of the Weblate container.

Enables [IP_BEHIND_REVERSE_PROXY](#) and sets [IP_PROXY_HEADER](#).

Shënim: The format must conform to Django's expectations. Django [transforms](#) raw HTTP header names as follows:

- converts all characters to uppercase
- replaces any hyphens with underscores
- prepends HTTP_ prefix

So X-Forwarded-For would be mapped to HTTP_X_FORWARDED_FOR.

Example:

```
environment:
  WEBLATE_IP_PROXY_HEADER: HTTP_X_FORWARDED_FOR
```

WEBLATE_SECURE_PROXY_SSL_HEADER

A tuple representing a HTTP header/value combination that signifies a request is secure. This is needed when Weblate is running behind a reverse proxy doing SSL termination which does not pass standard HTTPS headers.

Example:

```
environment:
  WEBLATE_SECURE_PROXY_SSL_HEADER: HTTP_X_FORWARDED_PROTO,https
```

Shihni edhe:

[SECURE_PROXY_SSL_HEADER](#)

WEBLATE_REQUIRE_LOGIN

Enables [REQUIRE_LOGIN](#) to enforce authentication on whole Weblate.

Example:

```
environment:
  WEBLATE_REQUIRE_LOGIN: 1
```

WEBLATE_LOGIN_REQUIRED_URLS_EXCEPTIONS

WEBLATE_ADD_LOGIN_REQUIRED_URLS_EXCEPTIONS**WEBLATE_REMOVE_LOGIN_REQUIRED_URLS_EXCEPTIONS**

Adds URL exceptions for authentication required for the whole Weblate installation using [*LOGIN_REQUIRED_URLS_EXCEPTIONS*](#).

You can either replace whole settings, or modify default value using ADD and REMOVE variables.

WEBLATE_GOOGLE_ANALYTICS_ID

Configures ID for Google Analytics by changing [*GOOGLE_ANALYTICS_ID*](#).

WEBLATE_GITHUB_USERNAME

Configures GitHub username for GitHub pull-requests by changing [*GITHUB_USERNAME*](#).

Shihni edhe:

[*GitHub*](#)

WEBLATE_GITHUB_TOKEN

Të reja në versionin 4.3.

Configures GitHub personal access token for GitHub pull-requests via API by changing [*GITHUB_TOKEN*](#).

Shihni edhe:

[*GitHub*](#)

WEBLATE_GITLAB_USERNAME

Configures GitLab username for GitLab merge-requests by changing [*GITLAB_USERNAME*](#)

Shihni edhe:

[*GitLab*](#)

WEBLATE_GITLAB_TOKEN

Configures GitLab personal access token for GitLab merge-requests via API by changing [*GITLAB_TOKEN*](#)

Shihni edhe:

[*GitLab*](#)

WEBLATE_PAGURE_USERNAME

Configures Pagure username for Pagure merge-requests by changing [*PAGURE_USERNAME*](#)

Shihni edhe:

[*Pagure*](#)

WEBLATE_PAGURE_TOKEN

Configures Pagure personal access token for Pagure merge-requests via API by changing [*PAGURE_TOKEN*](#)

Shihni edhe:

[*Pagure*](#)

WEBLATE_SIMPLIFY_LANGUAGES

Configures the language simplification policy, see [*SIMPLIFY_LANGUAGES*](#).

WEBLATE_DEFAULT_ACCESS_CONTROL

Configures the default *Kontroll hyrjesh* for new projects, see [*DEFAULT_ACCESS_CONTROL*](#).

WEBLATE_DEFAULT_RESTRICTED_COMPONENT

Configures the default value for *Restricted access* for new components, see [*DEFAULT_RESTRICTED_COMPONENT*](#).

WEBLATE_DEFAULT_TRANSLATION_PROPAGATION

Configures the default value for *Lejo përhapje përkthimesh* for new components, see [*DEFAULT_TRANSLATION_PROPAGATION*](#).

WEBLATE_DEFAULT_COMMITTER_EMAIL

Configures [*DEFAULT_COMMITTER_EMAIL*](#).

WEBLATE_DEFAULT_COMMITER_NAME

Configures *DEFAULT_COMMITER_NAME*.

WEBLATE_DEFAULT_SHARED_TM

Configures *DEFAULT_SHARED_TM*.

WEBLATE_AKISMET_API_KEY

Configures the Akismet API key, see *AKISMET_API_KEY*.

WEBLATE_GPG_IDENTITY

Configures GPG signing of commits, see *WEBLATE_GPG_IDENTITY*.

Shihni edhe:

Signing Git commits with GnuPG

WEBLATE_URL_PREFIX

Configures URL prefix where Weblate is running, see *URL_PREFIX*.

WEBLATE_SILENCED_SYSTEM_CHECKS

Configures checks which you do not want to be displayed, see *SILENCED_SYSTEM_CHECKS*.

WEBLATE_CSP_SCRIPT_SRC**WEBLATE_CSP_IMG_SRC****WEBLATE_CSP_CONNECT_SRC****WEBLATE_CSP_STYLE_SRC****WEBLATE_CSP_FONT_SRC**

Allows to customize Content-Security-Policy HTTP header.

Shihni edhe:

Content security policy, CSP_SCRIPT_SRC, CSP_IMG_SRC, CSP_CONNECT_SRC, CSP_STYLE_SRC, CSP_FONT_SRC

WEBLATE_LICENSE_FILTER

Configures *LICENSE_FILTER*.

WEBLATE_LICENSE_REQUIRED

Configures *LICENSE_REQUIRED*

WEBLATE_WEBSITE_REQUIRED

Configures *WEBSITE_REQUIRED*

WEBLATE_HIDE_VERSION

Configures *HIDE_VERSION*.

WEBLATE_BASIC_LANGUAGES

Configures *BASIC_LANGUAGES*.

WEBLATE_DEFAULT_AUTO_WATCH

Configures *DEFAULT_AUTO_WATCH*.

WEBLATE_RATELIMIT_ATTEMPTS**WEBLATE_RATELIMIT_LOCKOUT****WEBLATE_RATELIMIT_WINDOW**

Të reja në versionin 4.6.

Configures rate limiter.

Ndihmëz: You can set configuration for any rate limiter scopes. To do that add *WEBLATE_* prefix to any of setting described in *Rate limiting*.

Shihni edhe:

Rate limiting, *RATELIMIT_ATTEMPTS*, *RATELIMIT_WINDOW*, *RATELIMIT_LOCKOUT*

WEBLATE_ENABLE_AVATARS

Të reja në versionin 4.6.1.

Configures *ENABLE_AVATARS*.

Rregullime mbi përkthim nga makina

Ndihmëz: Configuring API key for a service automatically configures it in *MT_SERVICES*.

WEBLATE_MT_APERTIUM_APY

Enables *Apertium* machine translation and sets *MT_APERTIUM_APY*

WEBLATE_MT_AWS_REGION**WEBLATE_MT_AWS_ACCESS_KEY_ID****WEBLATE_MT_AWS_SECRET_ACCESS_KEY**

Configures *AWS* machine translation.

```
environment:
  WEBLATE_MT_AWS_REGION: us-east-1
  WEBLATE_MT_AWS_ACCESS_KEY_ID: AKIAIOSFODNN7EXAMPLE
  WEBLATE_MT_AWS_SECRET_ACCESS_KEY: wJalrXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY
```

WEBLATE_MT_DEEPL_KEY

Enables *DeepL* machine translation and sets *MT_DEEPL_KEY*

WEBLATE_MT_DEEPL_API_URL

Configures *DeepL* API version to use, see *MT_DEEPL_API_URL*.

WEBLATE_MT_LIBRETRANSLATE_KEY

Enables *LibreTranslate* machine translation and sets *MT_LIBRETRANSLATE_KEY*

WEBLATE_MT_LIBRETRANSLATE_API_URL

Configures *LibreTranslate* API instance to use, see *MT_LIBRETRANSLATE_API_URL*.

WEBLATE_MT_GOOGLE_KEY

Enables *Google Translate* and sets *MT_GOOGLE_KEY*

WEBLATE_MT_MICROSOFT_COGNITIVE_KEY

Enables *Microsoft Cognitive Services Translator* and sets *MT_MICROSOFT_COGNITIVE_KEY*

WEBLATE_MT_MICROSOFT_ENDPOINT_URL

Sets *MT_MICROSOFT_ENDPOINT_URL*, please note this is supposed to contain domain name only.

WEBLATE_MT_MICROSOFT_REGION

Sets *MT_MICROSOFT_REGION*

WEBLATE_MT_MICROSOFT_BASE_URL

Sets *MT_MICROSOFT_BASE_URL*

WEBLATE_MT_MODERNMT_KEY

Enables *ModernMT* and sets *MT_MODERNMT_KEY*.

WEBLATE_MT_MYMEMORY_ENABLED

Enables *MyMemory* machine translation and sets *MT_MYMEMORY_EMAIL* to *WEBLATE_ADMIN_EMAIL*.

Example:

```
environment:
  WEBLATE_MT_MYMEMORY_ENABLED: 1
```

WEBLATE_MT_GLOSBE_ENABLED

Enables *Glosbe* machine translation.

```
environment:
  WEBLATE_MT_GLOSBE_ENABLED: 1
```

WEBLATE_MT_MICROSOFT_TERMINOLOGY_ENABLED

Enables *Microsoft Terminology Service* machine translation.

```
environment:
  WEBLATE_MT_MICROSOFT_TERMINOLOGY_ENABLED: 1
```

WEBLATE_MT_SAP_BASE_URL

WEBLATE_MT_SAP_SANDBOX_APIKEY

WEBLATE_MT_SAP_USERNAME

WEBLATE_MT_SAP_PASSWORD

WEBLATE_MT_SAP_USE_MT

Configures *SAP Translation Hub* machine translation.

```
environment:
  WEBLATE_MT_SAP_BASE_URL: "https://example.hana.ondemand.com/translationhub/
↪api/v1/"
  WEBLATE_MT_SAP_USERNAME: "user"
  WEBLATE_MT_SAP_PASSWORD: "password"
  WEBLATE_MT_SAP_USE_MT: 1
```

Rregullime për mirëfilltësim

LDAP

WEBLATE_AUTH_LDAP_SERVER_URI

WEBLATE_AUTH_LDAP_USER_DN_TEMPLATE

WEBLATE_AUTH_LDAP_USER_ATTR_MAP

WEBLATE_AUTH_LDAP_BIND_DN

WEBLATE_AUTH_LDAP_BIND_PASSWORD

WEBLATE_AUTH_LDAP_CONNECTION_OPTION_REFERRALS

WEBLATE_AUTH_LDAP_USER_SEARCH

WEBLATE_AUTH_LDAP_USER_SEARCH_FILTER

WEBLATE_AUTH_LDAP_USER_SEARCH_UNION

WEBLATE_AUTH_LDAP_USER_SEARCH_UNION_DELIMITER

LDAP authentication configuration.

Example for direct bind:

```
environment:
  WEBLATE_AUTH_LDAP_SERVER_URI: ldap://ldap.example.org
  WEBLATE_AUTH_LDAP_USER_DN_TEMPLATE: uid=%(user)s,ou=People,dc=example,dc=net
  # map weblate 'full_name' to ldap 'name' and weblate 'email' attribute to
↪'mail' ldap attribute.
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
# another example that can be used with OpenLDAP: 'full_name:cn,email:mail'
WEBLATE_AUTH_LDAP_USER_ATTR_MAP: full_name:name,email:mail
```

Example for search and bind:

```
environment:
  WEBLATE_AUTH_LDAP_SERVER_URI: ldap://ldap.example.org
  WEBLATE_AUTH_LDAP_BIND_DN: CN=ldap,CN=Users,DC=example,DC=com
  WEBLATE_AUTH_LDAP_BIND_PASSWORD: password
  WEBLATE_AUTH_LDAP_USER_ATTR_MAP: full_name:name,email:mail
  WEBLATE_AUTH_LDAP_USER_SEARCH: CN=Users,DC=example,DC=com
```

Example for union search and bind:

```
environment:
  WEBLATE_AUTH_LDAP_SERVER_URI: ldap://ldap.example.org
  WEBLATE_AUTH_LDAP_BIND_DN: CN=ldap,CN=Users,DC=example,DC=com
  WEBLATE_AUTH_LDAP_BIND_PASSWORD: password
  WEBLATE_AUTH_LDAP_USER_ATTR_MAP: full_name:name,email:mail
  WEBLATE_AUTH_LDAP_USER_SEARCH_UNION: ou=users,dc=example,
  ↪dc=com|ou=otherusers,dc=example,dc=com
```

Example with search and bind against Active Directory:

```
environment:
  WEBLATE_AUTH_LDAP_BIND_DN: CN=ldap,CN=Users,DC=example,DC=com
  WEBLATE_AUTH_LDAP_BIND_PASSWORD: password
  WEBLATE_AUTH_LDAP_SERVER_URI: ldap://ldap.example.org
  WEBLATE_AUTH_LDAP_CONNECTION_OPTION_REFERRALS: 0
  WEBLATE_AUTH_LDAP_USER_ATTR_MAP: full_name:name,email:mail
  WEBLATE_AUTH_LDAP_USER_SEARCH: CN=Users,DC=example,DC=com
  WEBLATE_AUTH_LDAP_USER_SEARCH_FILTER: (sAMAccountName=%(user)s)
```

Shihni edhe:*Mirëfilltësim LDAP***GitHub****WEBLATE_SOCIAL_AUTH_GITHUB_KEY****WEBLATE_SOCIAL_AUTH_GITHUB_SECRET**Enables *Mirëfilltësim GitHub*.**Bitbucket****WEBLATE_SOCIAL_AUTH_BITBUCKET_KEY****WEBLATE_SOCIAL_AUTH_BITBUCKET_SECRET**Enables *Mirëfilltësim Bitbucket*.

Facebook

`WEBLATE_SOCIAL_AUTH_FACEBOOK_KEY`

`WEBLATE_SOCIAL_AUTH_FACEBOOK_SECRET`

Enables *Facebook OAuth 2*.

Google

`WEBLATE_SOCIAL_AUTH_GOOGLE_OAUTH2_KEY`

`WEBLATE_SOCIAL_AUTH_GOOGLE_OAUTH2_SECRET`

`WEBLATE_SOCIAL_AUTH_GOOGLE_OAUTH2_WHITELISTED_DOMAINS`

`WEBLATE_SOCIAL_AUTH_GOOGLE_OAUTH2_WHITELISTED_EMAILS`

Enables *Google OAuth 2*.

GitLab

`WEBLATE_SOCIAL_AUTH_GITLAB_KEY`

`WEBLATE_SOCIAL_AUTH_GITLAB_SECRET`

`WEBLATE_SOCIAL_AUTH_GITLAB_API_URL`

Enables *GitLab OAuth 2*.

Azure Active Directory

`WEBLATE_SOCIAL_AUTH_AZUREAD_OAUTH2_KEY`

`WEBLATE_SOCIAL_AUTH_AZUREAD_OAUTH2_SECRET`

Enables Azure Active Directory authentication, see *Microsoft Azure Active Directory*.

Azure Active Directory with Tenant support

`WEBLATE_SOCIAL_AUTH_AZUREAD_TENANT_OAUTH2_KEY`

`WEBLATE_SOCIAL_AUTH_AZUREAD_TENANT_OAUTH2_SECRET`

`WEBLATE_SOCIAL_AUTH_AZUREAD_TENANT_OAUTH2_TENANT_ID`

Enables Azure Active Directory authentication with Tenant support, see *Microsoft Azure Active Directory*.

Keycloak

`WEBLATE_SOCIAL_AUTH_KEYCLOAK_KEY`

`WEBLATE_SOCIAL_AUTH_KEYCLOAK_SECRET`

`WEBLATE_SOCIAL_AUTH_KEYCLOAK_PUBLIC_KEY`

`WEBLATE_SOCIAL_AUTH_KEYCLOAK_ALGORITHM`

`WEBLATE_SOCIAL_AUTH_KEYCLOAK_AUTHORIZATION_URL`

`WEBLATE_SOCIAL_AUTH_KEYCLOAK_ACCESS_TOKEN_URL`

Enables Keycloak authentication, see [documentation](#).

Linux vendors

You can enable authentication using Linux vendors authentication services by setting following variables to any value.

WEBLATE_SOCIAL_AUTH_FEDORA

WEBLATE_SOCIAL_AUTH_OPENSUSE

WEBLATE_SOCIAL_AUTH_UBUNTU

Slack

WEBLATE_SOCIAL_AUTH_SLACK_KEY

SOCIAL_AUTH_SLACK_SECRET

Enables Slack authentication, see *Slack*.

SAML

Self-signed SAML keys are automatically generated on first container startup. In case you want to use own keys, place the certificate and private key in `/app/data/ssl/saml.crt` and `/app/data/ssl/saml.key`.

WEBLATE_SAML_IDP_ENTITY_ID

WEBLATE_SAML_IDP_URL

WEBLATE_SAML_IDP_X509CERT

SAML Identity Provider settings, see *Mirëfilltësim SAML*.

Other authentication settings

WEBLATE_NO_EMAIL_AUTH

Disables e-mail authentication when set to any value.

Ujdisje baze të dhënash PostgreSQL

The database is created by `docker-compose.yml`, so these settings affect both Weblate and PostgreSQL containers.

Shihni edhe:

Ujdisje baze të dhënash për Weblate

POSTGRES_PASSWORD

Fjalëkalim PostgreSQL.

POSTGRES_PASSWORD_FILE

Path to the file containing the PostgreSQL password. Use as an alternative to `POSTGRES_PASSWORD`.

POSTGRES_USER

Emër përdoruesi PostgreSQL.

POSTGRES_DATABASE

Emër baze të dhënash PostgreSQL.

POSTGRES_HOST

PostgreSQL server hostname or IP address. Defaults to `database`.

POSTGRES_PORT

PostgreSQL server port. Defaults to none (uses the default value).

POSTGRES_SSL_MODE

Configure how PostgreSQL handles SSL in connection to the server, for possible choices see [SSL Mode Descriptions](#)

POSTGRES_ALTER_ROLE

Configures name of role to alter during migrations, see *Formësim i Weblate-it që të përdorë PostgreSQL-in*.

Database backup settings

Shihni edhe:

Dumped data for backups

WEBLATE_DATABASE_BACKUP

Configures the daily database dump using `DATABASE_BACKUP`. Defaults to `plain`.

Caching server setup

Using Redis is strongly recommended by Weblate and you have to provide a Redis instance when running Weblate in Docker.

Shihni edhe:

Aktivizoni përdorim fshehtine

REDIS_HOST

The Redis server hostname or IP address. Defaults to `cache`.

REDIS_PORT

The Redis server port. Defaults to `6379`.

REDIS_DB

The Redis database number, defaults to `1`.

REDIS_PASSWORD

The Redis server password, not used by default.

REDIS_TLS

Enables using SSL for Redis connection.

REDIS_VERIFY_SSL

Can be used to disable SSL certificate verification for Redis connection.

Ujdisje shërbyesi email-esh

To make outgoing e-mail work, you need to provide a mail server.

Shembull formësimi TLS-je:

```
environment:
  WEBLATE_EMAIL_HOST: smtp.example.com
  WEBLATE_EMAIL_HOST_USER: user
  WEBLATE_EMAIL_HOST_PASSWORD: pass
```

Shembull formësimi SSL-je:

```
environment:
  WEBLATE_EMAIL_HOST: smtp.example.com
  WEBLATE_EMAIL_PORT: 465
  WEBLATE_EMAIL_HOST_USER: user
  WEBLATE_EMAIL_HOST_PASSWORD: pass
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
WEBLATE_EMAIL_USE_TLS: 0
WEBLATE_EMAIL_USE_SSL: 1
```

Shihni edhe:*Formësim i email-eve që dërgohen***WEBLATE_EMAIL_HOST**

Mail server hostname or IP address.

Shihni edhe:

```
WEBLATE_EMAIL_PORT, WEBLATE_EMAIL_USE_SSL, WEBLATE_EMAIL_USE_TLS,
EMAIL_HOST
```

WEBLATE_EMAIL_PORT

Mail server port, defaults to 25.

Shihni edhe:`EMAIL_PORT`**WEBLATE_EMAIL_HOST_USER**

E-mail authentication user.

Shihni edhe:`EMAIL_HOST_USER`**WEBLATE_EMAIL_HOST_PASSWORD**

E-mail authentication password.

Shihni edhe:`EMAIL_HOST_PASSWORD`**WEBLATE_EMAIL_HOST_PASSWORD_FILE**

Path to the file containing the e-mail authentication password.

Shihni edhe:`WEBLATE_EMAIL_HOST_PASSWORD`**WEBLATE_EMAIL_USE_SSL**

Whether to use an implicit TLS (secure) connection when talking to the SMTP server. In most e-mail documentation, this type of TLS connection is referred to as SSL. It is generally used on port 465. If you are experiencing problems, see the explicit TLS setting `WEBLATE_EMAIL_USE_TLS`.

Shihni edhe:

```
WEBLATE_EMAIL_PORT, WEBLATE_EMAIL_USE_TLS, EMAIL_USE_SSL
```

WEBLATE_EMAIL_USE_TLS

Whether to use a TLS (secure) connection when talking to the SMTP server. This is used for explicit TLS connections, generally on port 587 or 25. If you are experiencing connections that hang, see the implicit TLS setting `WEBLATE_EMAIL_USE_SSL`.

Shihni edhe:

```
WEBLATE_EMAIL_PORT, WEBLATE_EMAIL_USE_SSL, EMAIL_USE_TLS
```

WEBLATE_EMAIL_BACKEND

Configures Django back-end to use for sending e-mails.

Shihni edhe:*Formësoni dërgimi email-esh*, `EMAIL_BACKEND`

Site integration

WEBLATE_GET_HELP_URL

Configures *GET_HELP_URL*.

WEBLATE_STATUS_URL

Configures *STATUS_URL*.

WEBLATE_LEGAL_URL

Configures *LEGAL_URL*.

Error reporting

It is recommended to collect errors from the installation systematically, see *Collecting error reports*.

To enable support for Rollbar, set the following:

ROLLBAR_KEY

Your Rollbar post server access token.

ROLLBAR_ENVIRONMENT

Your Rollbar environment, defaults to `production`.

To enable support for Sentry, set following:

SENTRY_DSN

Your Sentry DSN.

SENTRY_ENVIRONMENT

Your Sentry Environment (optional).

CDN përktimesh

WEBLATE_LOCALIZE_CDN_URL

WEBLATE_LOCALIZE_CDN_PATH

Të reja në versionin 4.2.1.

Configuration for *CDN përktimesh JavaScript*.

The *WEBLATE_LOCALIZE_CDN_PATH* is path within the container. It should be stored on the persistent volume and not in the transient storage.

One of possibilities is storing that inside the Weblate data dir:

```
environment:  
  WEBLATE_LOCALIZE_CDN_URL: https://cdn.example.com/  
  WEBLATE_LOCALIZE_CDN_PATH: /app/data/l10n-cdn
```

Shënim: You are responsible for setting up serving of the files generated by Weblate, it only does stores the files in configured location.

Shihni edhe:

weblate-cdn, *LOCALIZE_CDN_URL*, *LOCALIZE_CDN_PATH*

Changing enabled apps, checks, addons or autofixes

Të reja në versionin 3.8-5.

The built-in configuration of enabled checks, addons or autofixes can be adjusted by the following variables:

WEBLATE_ADD_APPS

WEBLATE_REMOVE_APPS

WEBLATE_ADD_CHECK

WEBLATE_REMOVE_CHECK

WEBLATE_ADD_AUTOFIX

WEBLATE_REMOVE_AUTOFIX

WEBLATE_ADD_ADDONS

WEBLATE_REMOVE_ADDONS

Example:

```
environment:
  WEBLATE_REMOVE_AUTOFIX: weblate.trans.autofixes.whitespace.
  ↪ SameBookendingWhitespace
  WEBLATE_ADD_ADDONS: customize.addons.MyAddon, customize.addons.OtherAddon
```

Shihni edhe:

CHECK_LIST, AUTOFIX_LIST, WEBLATE_ADDONS, INSTALLED_APPS

Container settings

WEBLATE_WORKERS

Të reja në versionin 4.6.1.

Base number of worker processes running in the container. When not set it is determined automatically on container startup based on number of CPU cores available.

It is used to determine *CELERY_MAIN_OPTIONS*, *CELERY_NOTIFY_OPTIONS*, *CELERY_MEMORY_OPTIONS*, *CELERY_TRANSLATE_OPTIONS*, *CELERY_BACKUP_OPTIONS*, *CELERY_BEAT_OPTIONS*, and *UWSGI_WORKERS*. You can use these settings to fine-tune.

CELERY_MAIN_OPTIONS

CELERY_NOTIFY_OPTIONS

CELERY_MEMORY_OPTIONS

CELERY_TRANSLATE_OPTIONS

CELERY_BACKUP_OPTIONS

CELERY_BEAT_OPTIONS

These variables allow you to adjust Celery worker options. It can be useful to adjust concurrency (`--concurrency 16`) or use different pool implementation (`--pool=gevent`).

By default, the number of concurrent workers is based on *WEBLATE_WORKERS*.

Example:

```
environment:
  CELERY_MAIN_OPTIONS: --concurrency 16
```

Shihni edhe:

Celery worker options, Background tasks using Celery

UWSGI_WORKERS

Configure how many uWSGI workers should be executed.

It defaults to [WEBLATE_WORKERS](#).

Example:

```
environment:  
  UWSGI_WORKERS: 32
```

WEBLATE_SERVICE

Defines which services should be executed inside the container. Use this for *Scaling horizontally*.

Following services are defined:

celery-beat Celery task scheduler, only one instance should be running. This container is also responsible for the database structure migrations and it should be started prior others.

celery-backup Celery worker for backups, only one instance should be running.

celery-celery Generic Celery worker.

celery-memory Translation memory Celery worker.

celery-notify Notifications Celery worker.

celery-translate Automatic translation Celery worker.

web Web server.

Docker container volumes

There are two volumes (data and cache) exported by the Weblate container. The other service containers (PostgreSQL or Redis) have their data volumes as well, but those are not covered by this document.

The data volume is used to store Weblate persistent data such as cloned repositories or to customize Weblate installation.

The placement of the Docker volume on host system depends on your Docker configuration, but usually it is stored in `/var/lib/docker/volumes/weblate-docker_weblate-data/_data/` (the path consist of name of your docker-compose directory, container, and volume names). In the container it is mounted as `/app/data`.

The cache volume is mounted as `/app/cache` and is used to store static files. Its content is recreated on container startup and the volume can be mounted using ephemeral filesystem such as *tmpfs*.

When creating the volumes manually, the directories should be owned by UID 1000 as that is user used inside the container.

Shihni edhe:

[Docker volumes documentation](#)

Further configuration customization

You can further customize Weblate installation in the data volume, see *Docker container volumes*.

Custom configuration files

You can additionally override the configuration in `/app/data/settings-override.py` (see [Docker container volumes](#)). This is executed at the end of built-in settings, after all environment settings are loaded, and you can adjust or override them.

Replacing logo and other static files

Të reja në versionin 3.8-5.

The static files coming with Weblate can be overridden by placing into `/app/data/python/customize/static` (see [Docker container volumes](#)). For example creating `/app/data/python/customize/static/favicon.ico` will replace the favicon.

Ndihmëz: The files are copied to the corresponding location upon container startup, so a restart of Weblate is needed after changing the content of the volume.

Alternatively you can also include own module (see [Përshatje e Weblate-it](#)) and add it as separate volume to the Docker container, for example:

```
weblate:
  volumes:
    - weblate-data:/app/data
    - ./weblate_customization/weblate_customization:/app/data/python/weblate_
    ↪customization
  environment:
    WEBLATE_ADD_APPS: weblate_customization
```

Adding own Python modules

Të reja në versionin 3.8-5.

You can place own Python modules in `/app/data/python/` (see [Docker container volumes](#)) and they can be then loaded by Weblate, most likely by using [Custom configuration files](#).

Shihni edhe:

[Përshatje e Weblate-it](#)

Installing on Debian and Ubuntu

Domosdoshmëri hardware

Weblate should run on any contemporary hardware without problems, the following is the minimal configuration required to run Weblate on a single host (Weblate, database and webserver):

- 2 GB RAM
- 2 CPU cores
- 1 GB of storage space

The more memory the better - it is used for caching on all levels (filesystem, database and Weblate).

Many concurrent users increases the amount of needed CPU cores. For hundreds of translation components at least 4 GB of RAM is recommended.

The typical database storage usage is around 300 MB per 1 million hosted words. Storage space needed for cloned repositories varies, but Weblate tries to keep their size minimal by doing shallow clones.

Shënim: Actual requirements for your installation of Weblate vary heavily based on the size of the translations managed in it.

Instalim

System requirements

Install the dependencies needed to build the Python modules (see *Domosdoshmëri software*):

```
apt install \
    libxml2-dev libxslt-dev libfreetype6-dev libjpeg-dev libz-dev libyaml-dev \
    libcairo-dev gir1.2-pango-1.0 libgirepository1.0-dev libacl1-dev libssl-dev \
    build-essential python3-gdbm python3-dev python3-pip python3-virtualenv \
    ↪virtualenv git
```

Install wanted optional dependencies depending on features you intend to use (see *Varësi opsionale*):

```
apt install tesseract-ocr libtesseract-dev liblibleptonica-dev
```

Optionally install software for running production server, see *Running server*, *Ujdisje baze të dhënash për Weblate*, *Background tasks using Celery*. Depending on size of your installation you might want to run these components on dedicated servers.

The local installation instructions:

```
# Web server option 1: NGINX and uWSGI
apt install nginx uwsgi uwsgi-plugin-python3

# Web server option 2: Apache with `mod_wsgi`
apt install apache2 libapache2-mod-wsgi

# Caching backend: Redis
apt install redis-server

# Database server: PostgreSQL
apt install postgresql postgresql-contrib

# SMTP server
apt install exim4
```

Python modules

Ndihmëz: We're using virtualenv to install Weblate in a separate environment from your system. If you are not familiar with it, check virtualenv [User Guide](#).

1. Create the virtualenv for Weblate:

```
virtualenv --python=python3 ~/weblate-env
```

2. Activate the virtualenv for Weblate:

```
. ~/weblate-env/bin/activate
```

3. Install Weblate including all dependencies:

```
pip install Weblate
```

4. Install database driver:

```
pip install psycopg2-binary
```

5. Install wanted optional dependencies depending on features you intend to use (some might require additional system libraries, check *Varësi opsionale*):

```
pip install ruamel.yaml aeidon boto3 zeep chardet tesseractocr
```

Configuring Weblate

Shënim: Following steps assume virtualenv used by Weblate is active (what can be done by `. ~/weblate-env/bin/activate`). In case this is not true, you will have to specify full path to **weblate** command as `~/weblate-env/bin/weblate`.

1. Copy the file `~/weblate-env/lib/python3.7/site-packages/weblate/settings_example.py` to `~/weblate-env/lib/python3.7/site-packages/weblate/settings.py`.
2. Adjust the values in the new `settings.py` file to your liking. You will need to provide at least the database credentials and Django secret key, but you will want more changes for production setup, see *Përshtatje formësimi*.
3. Create the database and its structure for Weblate (the example settings use PostgreSQL, check *Ujdisje baze të dhënash për Weblate* for production ready setup):

```
weblate migrate
```

4. Create the administrator user account and copy the password it outputs to the clipboard, and also save it for later use:

```
weblate createadmin
```

5. Collect static files for web server (see *Running server* and *Serving static files*):

```
weblate collectstatic
```

6. Compress JavaScript and CSS files (optional, see *Compressing client assets*):

```
weblate compress
```

7. Start Celery workers. This is not necessary for development purposes, but strongly recommended otherwise. See *Background tasks using Celery* for more info:

```
~/weblate-env/lib/python3.7/site-packages/weblate/examples/celery start
```

8. Start the development server (see *Running server* for production setup):

```
weblate runserver
```

After installation

Congratulations, your Weblate server is now running and you can start using it.

- You can now access Weblate on `http://localhost:8000/`.
- Login with admin credentials obtained during installation or register with new users.
- You can now run Weblate commands using **weblate** command when Weblate virtualenv is active, see *Management commands*.
- You can stop the test server with Ctrl+C.
- Review potential issues with your installation either on `/manage/performance/` URL or using **weblate check --deploy**, see *Production setup*.

Adding translation

1. Open the admin interface (`http://localhost:8000/create/project/`) and create the project you want to translate. See *Project configuration* for more details.

All you need to specify here is the project name and its website.

2. Create a component which is the real object for translation - it points to the VCS repository, and selects which files to translate. See *Component configuration* for more details.

The important fields here are: Component name, VCS repository address and mask for finding translatable files. Weblate supports a wide range of formats including gettext PO files, Android resource strings, iOS string properties, Java properties or Qt Linguist files, see *Formate të mbuluar kartelash* for more details.

3. Once the above is completed (it can be lengthy process depending on the size of your VCS repository, and number of messages to translate), you can start translating.

Installing on SUSE and openSUSE

Domosdoshmëri hardware

Weblate should run on any contemporary hardware without problems, the following is the minimal configuration required to run Weblate on a single host (Weblate, database and webserver):

- 2 GB RAM
- 2 CPU cores
- 1 GB of storage space

The more memory the better - it is used for caching on all levels (filesystem, database and Weblate).

Many concurrent users increases the amount of needed CPU cores. For hundreds of translation components at least 4 GB of RAM is recommended.

The typical database storage usage is around 300 MB per 1 million hosted words. Storage space needed for cloned repositories varies, but Weblate tries to keep their size minimal by doing shallow clones.

Shënim: Actual requirements for your installation of Weblate vary heavily based on the size of the translations managed in it.

Instalim

System requirements

Install the dependencies needed to build the Python modules (see *Domosdoshmëri software*):

```
zypper install \
    libxslt-devel libxml2-devel freetype-devel libjpeg-devel zlib-devel libyaml-
    ↪devel \
    cairo-devel typelib-1_0-Pango-1_0 gobject-introspection-devel libacl-devel \
    python3-pip python3-virtualenv python3-devel git
```

Install wanted optional dependencies depending on features you intend to use (see *Varësi opsionale*):

```
zypper install tesseract-ocr tesseract-devel leptonica-devel
```

Optionally install software for running production server, see *Running server*, *Ujdisje baze të dhënash për Weblate*, *Background tasks using Celery*. Depending on size of your installation you might want to run these components on dedicated servers.

The local installation instructions:

```
# Web server option 1: NGINX and uWSGI
zypper install nginx uwsgi uwsgi-plugin-python3

# Web server option 2: Apache with ``mod_wsgi``
zypper install apache2 apache2-mod_wsgi

# Caching backend: Redis
zypper install redis-server

# Database server: PostgreSQL
zypper install postgresql postgresql-contrib

# SMTP server
zypper install postfix
```

Python modules

Ndihmëz: We're using virtualenv to install Weblate in a separate environment from your system. If you are not familiar with it, check virtualenv [User Guide](#).

1. Create the virtualenv for Weblate:

```
virtualenv --python=python3 ~/weblate-env
```

2. Activate the virtualenv for Weblate:

```
. ~/weblate-env/bin/activate
```

3. Install Weblate including all dependencies:

```
pip install Weblate
```

4. Install database driver:

```
pip install psycopg2-binary
```


5. Install wanted optional dependencies depending on features you intend to use (some might require additional system libraries, check *Varësi opsionale*):

```
pip install ruamel.yaml aeidon boto3 zeep chardet tesseractocr
```

Configuring Weblate

Shënim: Following steps assume virtualenv used by Weblate is active (what can be done by `. ~/weblate-env/bin/activate`). In case this is not true, you will have to specify full path to **weblate** command as `~/weblate-env/bin/weblate`.

1. Copy the file `~/weblate-env/lib/python3.7/site-packages/weblate/settings_example.py` to `~/weblate-env/lib/python3.7/site-packages/weblate/settings.py`.
2. Adjust the values in the new `settings.py` file to your liking. You will need to provide at least the database credentials and Django secret key, but you will want more changes for production setup, see *Përshtatje formësimi*.
3. Create the database and its structure for Weblate (the example settings use PostgreSQL, check *Ujdisje baze të dhënash për Weblate* for production ready setup):

```
weblate migrate
```

4. Create the administrator user account and copy the password it outputs to the clipboard, and also save it for later use:

```
weblate createadmin
```

5. Collect static files for web server (see *Running server* and *Serving static files*):

```
weblate collectstatic
```

6. Compress JavaScript and CSS files (optional, see *Compressing client assets*):

```
weblate compress
```

7. Start Celery workers. This is not necessary for development purposes, but strongly recommended otherwise. See *Background tasks using Celery* for more info:

```
~/weblate-env/lib/python3.7/site-packages/weblate/examples/celery start
```

8. Start the development server (see *Running server* for production setup):

```
weblate runserver
```

After installation

Congratulations, your Weblate server is now running and you can start using it.

- You can now access Weblate on `http://localhost:8000/`.
- Login with admin credentials obtained during installation or register with new users.
- You can now run Weblate commands using **weblate** command when Weblate virtualenv is active, see *Management commands*.
- You can stop the test server with `Ctrl+C`.

- Review potential issues with your installation either on `/manage/performance/` URL or using `weblate check --deploy`, see *Production setup*.

Adding translation

1. Open the admin interface (`http://localhost:8000/create/project/`) and create the project you want to translate. See *Project configuration* for more details.

All you need to specify here is the project name and its website.

2. Create a component which is the real object for translation - it points to the VCS repository, and selects which files to translate. See *Component configuration* for more details.

The important fields here are: Component name, VCS repository address and mask for finding translatable files. Weblate supports a wide range of formats including gettext PO files, Android resource strings, iOS string properties, Java properties or Qt Linguist files, see *Formate të mbuluar kartelash* for more details.

3. Once the above is completed (it can be lengthy process depending on the size of your VCS repository, and number of messages to translate), you can start translating.

Installing on RedHat, Fedora and CentOS

Domosdoshmëri hardware

Weblate should run on any contemporary hardware without problems, the following is the minimal configuration required to run Weblate on a single host (Weblate, database and webserver):

- 2 GB RAM
- 2 CPU cores
- 1 GB of storage space

The more memory the better - it is used for caching on all levels (filesystem, database and Weblate).

Many concurrent users increases the amount of needed CPU cores. For hundreds of translation components at least 4 GB of RAM is recommended.

The typical database storage usage is around 300 MB per 1 million hosted words. Storage space needed for cloned repositories varies, but Weblate tries to keep their size minimal by doing shallow clones.

Shënim: Actual requirements for your installation of Weblate vary heavily based on the size of the translations managed in it.

Instalim

System requirements

Install the dependencies needed to build the Python modules (see *Domosdoshmëri software*):

```
dnf install \
    libxslt-devel libxml2-devel freetype-devel libjpeg-devel zlib-devel libyaml-
    <del>devel</del> \
    cairo-devel pango-devel gobject-introspection-devel libacl-devel \
    python3-pip python3-virtualenv python3-devel git
```

Install wanted optional dependencies depending on features you intend to use (see *Varësi opsionale*):

```
dnf install tesseract-langpack-eng tesseract-devel leptonica-devel
```

Optionally install software for running production server, see [Running server](#), [Ujdisje baze të dhënash për Weblate](#), [Background tasks using Celery](#). Depending on size of your installation you might want to run these components on dedicated servers.

The local installation instructions:

```
# Web server option 1: NGINX and uWSGI
dnf install nginx uwsgi uwsgi-plugin-python3

# Web server option 2: Apache with ``mod_wsgi``
dnf install apache2 apache2-mod_wsgi

# Caching backend: Redis
dnf install redis

# Database server: PostgreSQL
dnf install postgresql postgresql-contrib

# SMTP server
dnf install postfix
```

Python modules

Ndihmëz: We're using virtualenv to install Weblate in a separate environment from your system. If you are not familiar with it, check virtualenv [User Guide](#).

1. Create the virtualenv for Weblate:

```
virtualenv --python=python3 ~/weblate-env
```

2. Activate the virtualenv for Weblate:

```
. ~/weblate-env/bin/activate
```

3. Install Weblate including all dependencies:

```
pip install Weblate
```

4. Install database driver:

```
pip install psycopg2-binary
```

5. Install wanted optional dependencies depending on features you intend to use (some might require additional system libraries, check [Varësi opsionale](#)):

```
pip install ruamel.yaml aeidon boto3 zeep chardet tesseractocr
```

Configuring Weblate

Shënim: Following steps assume virtualenv used by Weblate is active (what can be done by `. ~/weblate-env/bin/activate`). In case this is not true, you will have to specify full path to **weblate** command as `~/weblate-env/bin/weblate`.

1. Copy the file `~/weblate-env/lib/python3.7/site-packages/weblate/settings_example.py` to `~/weblate-env/lib/python3.7/site-packages/weblate/settings.py`.
2. Adjust the values in the new `settings.py` file to your liking. You will need to provide at least the database credentials and Django secret key, but you will want more changes for production setup, see [Përshtatje formësimi](#).
3. Create the database and its structure for Weblate (the example settings use PostgreSQL, check [Ujdisje baze të dhënash për Weblate](#) for production ready setup):

```
weblate migrate
```

4. Create the administrator user account and copy the password it outputs to the clipboard, and also save it for later use:

```
weblate createadmin
```

5. Collect static files for web server (see [Running server](#) and [Serving static files](#)):

```
weblate collectstatic
```

6. Compress JavaScript and CSS files (optional, see [Compressing client assets](#)):

```
weblate compress
```

7. Start Celery workers. This is not necessary for development purposes, but strongly recommended otherwise. See [Background tasks using Celery](#) for more info:

```
~/weblate-env/lib/python3.7/site-packages/weblate/examples/celery start
```

8. Start the development server (see [Running server](#) for production setup):

```
weblate runserver
```

After installation

Congratulations, your Weblate server is now running and you can start using it.

- You can now access Weblate on `http://localhost:8000/`.
- Login with admin credentials obtained during installation or register with new users.
- You can now run Weblate commands using **weblate** command when Weblate virtualenv is active, see [Management commands](#).
- You can stop the test server with `Ctrl+C`.
- Review potential issues with your installation either on `/manage/performance/` URL or using **weblate check --deploy**, see [Production setup](#).

Adding translation

1. Open the admin interface (<http://localhost:8000/create/project/>) and create the project you want to translate. See [Project configuration](#) for more details.

All you need to specify here is the project name and its website.

2. Create a component which is the real object for translation - it points to the VCS repository, and selects which files to translate. See [Component configuration](#) for more details.

The important fields here are: Component name, VCS repository address and mask for finding translatable files. Weblate supports a wide range of formats including gettext PO files, Android resource strings, iOS string properties, Java properties or Qt Linguist files, see [Formate të mbuluar kartelash](#) for more details.

3. Once the above is completed (it can be lengthy process depending on the size of your VCS repository, and number of messages to translate), you can start translating.

Installing on macOS

Domosdoshmëri hardware

Weblate should run on any contemporary hardware without problems, the following is the minimal configuration required to run Weblate on a single host (Weblate, database and webserver):

- 2 GB RAM
- 2 CPU cores
- 1 GB of storage space

The more memory the better - it is used for caching on all levels (filesystem, database and Weblate).

Many concurrent users increases the amount of needed CPU cores. For hundreds of translation components at least 4 GB of RAM is recommended.

The typical database storage usage is around 300 MB per 1 million hosted words. Storage space needed for cloned repositories varies, but Weblate tries to keep their size minimal by doing shallow clones.

Shënim: Actual requirements for your installation of Weblate vary heavily based on the size of the translations managed in it.

Instalim

System requirements

Install the dependencies needed to build the Python modules (see [Domosdoshmëri software](#)):

```
brew install python pango cairo gobject-introspection libffi glib libyaml
pip3 install virtualenv
```

Make sure pip will be able to find the libffi version provided by homebrew — this will be needed during the installation build step.

```
export PKG_CONFIG_PATH="/usr/local/opt/libffi/lib/pkgconfig"
```

Install wanted optional dependencies depending on features you intend to use (see [Varësi opsionale](#)):

```
brew install tesseract
```

Optionally install software for running production server, see [Running server](#), [Ujdisje baze të dhënash për Weblate](#), [Background tasks using Celery](#). Depending on size of your installation you might want to run these components on dedicated servers.

The local installation instructions:

```
# Web server option 1: NGINX and uWSGI
brew install nginx uwsgi

# Web server option 2: Apache with `mod_wsgi`
brew install httpd

# Caching backend: Redis
brew install redis

# Database server: PostgreSQL
brew install postgresql
```

Python modules

Ndihmëz: We're using virtualenv to install Weblate in a separate environment from your system. If you are not familiar with it, check virtualenv [User Guide](#).

1. Create the virtualenv for Weblate:

```
virtualenv --python=python3 ~/weblate-env
```

2. Activate the virtualenv for Weblate:

```
. ~/weblate-env/bin/activate
```

3. Install Weblate including all dependencies:

```
pip install Weblate
```

4. Install database driver:

```
pip install psycopg2-binary
```

5. Install wanted optional dependencies depending on features you intend to use (some might require additional system libraries, check [Varësi opsionale](#)):

```
pip install ruamel.yaml aedon boto3 zeep chardet tesseract
```

Configuring Weblate

Shënim: Following steps assume virtualenv used by Weblate is active (what can be done by `. ~/weblate-env/bin/activate`). In case this is not true, you will have to specify full path to **weblate** command as `~/weblate-env/bin/weblate`.

1. Copy the file `~/weblate-env/lib/python3.7/site-packages/weblate/settings_example.py` to `~/weblate-env/lib/python3.7/site-packages/weblate/settings.py`.

2. Adjust the values in the new `settings.py` file to your liking. You will need to provide at least the database credentials and Django secret key, but you will want more changes for production setup, see [Përshatje formësimi](#).
3. Create the database and its structure for Weblate (the example settings use PostgreSQL, check [Ujdisje baze të dhënash për Weblate](#) for production ready setup):

```
weblate migrate
```

4. Create the administrator user account and copy the password it outputs to the clipboard, and also save it for later use:

```
weblate createadmin
```

5. Collect static files for web server (see [Running server](#) and [Serving static files](#)):

```
weblate collectstatic
```

6. Compress JavaScript and CSS files (optional, see [Compressing client assets](#)):

```
weblate compress
```

7. Start Celery workers. This is not necessary for development purposes, but strongly recommended otherwise. See [Background tasks using Celery](#) for more info:

```
~/weblate-env/lib/python3.7/site-packages/weblate/examples/celery start
```

8. Start the development server (see [Running server](#) for production setup):

```
weblate runserver
```

After installation

Congratulations, your Weblate server is now running and you can start using it.

- You can now access Weblate on `http://localhost:8000/`.
- Login with admin credentials obtained during installation or register with new users.
- You can now run Weblate commands using **weblate** command when Weblate virtualenv is active, see [Management commands](#).
- You can stop the test server with Ctrl+C.
- Review potential issues with your installation either on `/manage/performance/` URL or using **weblate check --deploy**, see [Production setup](#).

Adding translation

1. Open the admin interface (`http://localhost:8000/create/project/`) and create the project you want to translate. See [Project configuration](#) for more details.

All you need to specify here is the project name and its website.

2. Create a component which is the real object for translation - it points to the VCS repository, and selects which files to translate. See [Component configuration](#) for more details.

The important fields here are: Component name, VCS repository address and mask for finding translatable files. Weblate supports a wide range of formats including gettext PO files, Android resource strings, iOS string properties, Java properties or Qt Linguist files, see [Formate të mbuluar kartelash](#) for more details.

3. Once the above is completed (it can be lengthy process depending on the size of your VCS repository, and number of messages to translate), you can start translating.

Installing from sources

1. Please follow the installation instructions for your system first:

- [Installing on Debian and Ubuntu](#)
- [Installing on SUSE and openSUSE](#)
- [Installing on RedHat, Fedora and CentOS](#)

2. Grab the latest Weblate sources using Git (or download a tarball and unpack that):

```
git clone https://github.com/WeblateOrg/weblate.git weblate-src
```

Alternatively you can use released archives. You can download them from our website <https://weblate.org/>. Those downloads are cryptographically signed, please see [Verifying release signatures](#).

3. Install current Weblate code into the virtualenv:

```
. ~/weblate-env/bin/activate
pip install -e weblate-src
```

4. Copy `weblate/settings_example.py` to `weblate/settings.py`.
5. Adjust the values in the new `settings.py` file to your liking. You will need to provide at least the database credentials and Django secret key, but you will want more changes for production setup, see [Përshtatje formësimi](#).
6. Create the database used by Weblate, see [Ujdisje baze të dhënash për Weblate](#).
7. Build Django tables, static files and initial data (see [Mbushje e bazës së të dhënave](#) and [Serving static files](#)):

```
weblate migrate
weblate collectstatic
weblate compress
weblate compilemessages
```

Shënim: This step should be repeated whenever you update the repository.

Installing on OpenShift

With the OpenShift Weblate template you can get your personal Weblate instance up and running in seconds. All of Weblate's dependencies are already included. PostgreSQL is set up as the default database and persistent volume claims are used.

You can find the template at <https://github.com/WeblateOrg/openshift/>.

Instalim

The following examples assume you have a working OpenShift v3.x environment, with `oc` client tool installed. Please check the OpenShift documentation for instructions.

The `template.yml` is suited for running all components in OpenShift. There is also `template-external-postgresql.yml` which does not start a PostgreSQL server and allows you to configure external PostgreSQL server.

Web Console

Copy the raw content from `template.yml` and import them into your project, then use the `Create` button in the OpenShift web console to create your application. The web console will prompt you for the values for all of the parameters used by the template.

CLI

To upload the Weblate template to your current project's template library, pass the `template.yml` file with the following command:

```
$ oc create -f https://raw.githubusercontent.com/WeblateOrg/openshift/main/
↪template.yml \
  -n <PROJECT>
```

The template is now available for selection using the web console or the CLI.

Parameters

The parameters that you can override are listed in the parameters section of the template. You can list them with the CLI by using the following command and specifying the file to be used:

```
$ oc process --parameters -f https://raw.githubusercontent.com/WeblateOrg/
↪openshift/main/template.yml

# If the template is already uploaded
$ oc process --parameters -n <PROJECT> weblate
```

Provisioning

You can also use the CLI to process templates and use the configuration that is generated to create objects immediately.

```
$ oc process -f https://raw.githubusercontent.com/WeblateOrg/openshift/main/
↪template.yml \
  -p APPLICATION_NAME=weblate \
  -p WEBLATE_VERSION=4.3.1-1 \
  -p WEBLATE_SITE_DOMAIN=weblate.app-openshift.example.com \
  -p POSTGRESQL_IMAGE=docker-registry.default.svc:5000/openshift/postgresql:9.6 \
  -p REDIS_IMAGE=docker-registry.default.svc:5000/openshift/redis:3.2 \
  | oc create -f
```

The Weblate instance should be available after successful migration and deployment at the specified `WEBLATE_SITE_DOMAIN` parameter.

After container setup, you can sign in as `admin` user with password provided in `WEBLATE_ADMIN_PASSWORD`, or a random password generated on first start if that was not set.

To reset `admin` password, restart the container with `WEBLATE_ADMIN_PASSWORD` set to new password in the respective Secret.

Eliminate

```
$ oc delete all -l app=<APPLICATION_NAME>
$ oc delete configmap -l app= <APPLICATION_NAME>
$ oc delete secret -l app=<APPLICATION_NAME>
# ATTENTION! The following command is only optional and will permanently delete
→all of your data.
$ oc delete pvc -l app=<APPLICATION_NAME>

$ oc delete all -l app=weblate \
    && oc delete secret -l app=weblate \
    && oc delete configmap -l app=weblate \
    && oc delete pvc -l app=weblate
```

Formësim

By processing the template a respective ConfigMap will be created and which can be used to customize the Weblate image. The ConfigMap is directly mounted as environment variables and triggers a new deployment every time it is changed. For further configuration options, see *Ndryshore mjedisi Docker* for full list of environment variables.

Installing on Kubernetes

Shënim: This guide is looking for contributors experienced with Kubernetes to cover the setup in more details.

With the Kubernetes Helm chart you can get your personal Weblate instance up and running in seconds. All of Weblate's dependencies are already included. PostgreSQL is set up as the default database and persistent volume claims are used.

You can find the chart at <https://github.com/WeblateOrg/helm/> and it can be displayed at <https://artifacthub.io/packages/helm/weblate/weblate>.

Instalim

```
helm repo add weblate https://helm.weblate.org
helm install my-release weblate/weblate
```

Formësim

For further configuration options, see *Ndryshore mjedisi Docker* for full list of environment variables.

Depending on your setup and experience, choose an appropriate installation method for you:

- *Installing using Docker*, recommended for production setups.
- Virtualenv installation, recommended for production setups:
 - *Installing on Debian and Ubuntu*
 - *Installing on SUSE and openSUSE*
 - *Installing on RedHat, Fedora and CentOS*
 - *Installing on macOS*
- *Installing from sources*, recommended for development.
- *Installing on OpenShift*

- *Installing on Kubernetes*

2.1.2 Domosdoshmëri software

Sistem operativ

Weblate is known to work on Linux, FreeBSD and macOS. Other Unix like systems will most likely work too.

Weblate is not supported on Windows. But it may still work and patches are happily accepted.

Shërbime të tjera

Weblate is using other services for its operation. You will need at least following services running:

- PostgreSQL database server, see *Ujdisje baze të dhënash për Weblate*.
- Redis server for cache and tasks queue, see *Background tasks using Celery*.
- SMTP server for outgoing e-mail, see *Formësim i email-eve që dërgohen*.

Varësi Python

Weblate is written in [Python](#) and supports Python 3.6 or newer. You can install dependencies using pip or from your distribution packages, full list is available in `requirements.txt`.

Varësitë më të rëndësishme:

Django <https://www.djangoproject.com/>

Celery <https://docs.celeryproject.org/>

Translate Toolkit <https://toolkit.translatehouse.org/>

translation-finder <https://github.com/WeblateOrg/translation-finder>

Python Social Auth <https://python-social-auth.readthedocs.io/>

Django REST Framework <https://www.django-rest-framework.org/>

Varësi opsionale

Following modules are necessary for some Weblate features. You can find all of them in `requirements-optional.txt`.

Mercurial (optional for Mercurial repositories support) <https://www.mercurial-scm.org/>

phply (optional for PHP support) <https://github.com/viraptor/phply>

tesseract (optional for screenshots OCR) <https://github.com/sirfz/tesseract>

akismet (optional for suggestion spam protection) <https://github.com/ubernostrum/akismet>

ruamel.yaml (optional for *Kartela YAML*) <https://pypi.org/project/ruamel.yaml/>

Zeep (optional for *Microsoft Terminology Service*) <https://docs.python-zeep.org/>

aeidon (optional for *Kartela titrash*) <https://pypi.org/project/aeidon/>

Database backend dependencies

Weblate supports PostgreSQL, MySQL and MariaDB, see *Ujdisje baze të dhënash për Weblate* and backends documentation for more details.

Domosdoshmëri të tjera sistemi

Varësitë vijuese duhet të instalohen te sistemi:

Git <https://git-scm.com/>

Pango, Cairo and related header files and gir introspection data <https://cairographics.org/>, <https://pango.gnome.org/>, see *Pango dhe Cairo*

git-review (optional for Gerrit support) <https://pypi.org/project/git-review/>

git-svn (optional for Subversion support) <https://git-scm.com/docs/git-svn>

tesseract and its data (optional for screenshots OCR) <https://github.com/tesseract-ocr/tesseract>

licensee (optional for detecting license when creating component) <https://github.com/licensee/licensee>

Build-time dependencies

To build some of the *Varësi Python* you might need to install their dependencies. This depends on how you install them, so please consult individual packages for documentation. You won't need those if using prebuilt *Wheels* while installing using *pip* or when you use distribution packages.

Pango dhe Cairo

Ndryshuar në versionin 3.7.

Weblate uses Pango and Cairo for rendering bitmap widgets (see promotion) and rendering checks (see *Administrim shkronjash*). To properly install Python bindings for those you need to install system libraries first - you need both Cairo and Pango, which in turn need GLib. All those should be installed with development files and GObject introspection data.

2.1.3 Verifying release signatures

Weblate release are cryptographically signed by the releasing developer. Currently this is Michal Čihař. Fingerprint of his PGP key is:

```
63CB 1DF1 EF12 CF2A C0EE 5A32 9C27 B313 42B7 511D
```

and you can get more identification information from <https://keybase.io/nijel>.

You should verify that the signature matches the archive you have downloaded. This way you can be sure that you are using the same code that was released. You should also verify the date of the signature to make sure that you downloaded the latest version.

Each archive is accompanied with *.asc* files which contain the PGP signature for it. Once you have both of them in the same folder, you can verify the signature:

```
$ gpg --verify Weblate-3.5.tar.xz.asc
gpg: assuming signed data in 'Weblate-3.5.tar.xz'
gpg: Signature made Ne 3. března 2019, 16:43:15 CET
gpg:                using RSA key 87E673AF83F6C3A0C344C8C3F4AA229D4D58C245
gpg: Can't check signature: public key not found
```

As you can see GPG complains that it does not know the public key. At this point you should do one of the following steps:

- Përdorni *wkd* për të shkarkuar kyçin:

```
$ gpg --auto-key-locate wkd --locate-keys michal@cihar.com
pub   rsa4096 2009-06-17 [SC]
      63CB1DF1EF12CF2AC0EE5A329C27B31342B7511D
uid           [ultimate] Michal Čihař <michal@cihar.com>
uid           [ultimate] Michal Čihař <nijel@debian.org>
uid           [ultimate] [jpeg image of size 8848]
uid           [ultimate] Michal Čihař (Braiiins) <michal.cihar@braiiins.cz>
sub   rsa4096 2009-06-17 [E]
sub   rsa4096 2015-09-09 [S]
```

- Download the keyring from [Michal's server](#), then import it with:

```
$ gpg --import wmxth3chu9jfxdxywj1skpmhsj311mzm
```

- Download and import the key from one of the key servers:

```
$ gpg --keyserver hkp://pgp.mit.edu --recv-keys 87E673AF83F6C3A0C344C8C3F4AA229D4D58C245
gpg: key 9C27B31342B7511D: "Michal Čihař <michal@cihar.com>" imported
gpg: Total number processed: 1
gpg:          unchanged: 1
```

This will improve the situation a bit - at this point you can verify that the signature from the given key is correct but you still can not trust the name used in the key:

```
$ gpg --verify Weblate-3.5.tar.xz.asc
gpg: assuming signed data in 'Weblate-3.5.tar.xz'
gpg: Signature made Ne 3. března 2019, 16:43:15 CET
gpg:          using RSA key 87E673AF83F6C3A0C344C8C3F4AA229D4D58C245
gpg: Good signature from "Michal Čihař <michal@cihar.com>" [ultimate]
gpg:          aka "Michal Čihař <nijel@debian.org>" [ultimate]
gpg:          aka "[jpeg image of size 8848]" [ultimate]
gpg:          aka "Michal Čihař (Braiiins) <michal.cihar@braiiins.cz>"
↳[ultimate]
gpg: WARNING: This key is not certified with a trusted signature!
gpg:          There is no indication that the signature belongs to the owner.
Primary key fingerprint: 63CB 1DF1 EF12 CF2A C0EE  5A32 9C27 B313 42B7 511D
```

The problem here is that anybody could issue the key with this name. You need to ensure that the key is actually owned by the mentioned person. The GNU Privacy Handbook covers this topic in the chapter [Validating other keys on your public keyring](#). The most reliable method is to meet the developer in person and exchange key fingerprints, however you can also rely on the web of trust. This way you can trust the key transitively through signatures of others, who have met the developer in person.

Once the key is trusted, the warning will not occur:

```
$ gpg --verify Weblate-3.5.tar.xz.asc
gpg: assuming signed data in 'Weblate-3.5.tar.xz'
gpg: Signature made Sun Mar  3 16:43:15 2019 CET
gpg:          using RSA key 87E673AF83F6C3A0C344C8C3F4AA229D4D58C245
gpg: Good signature from "Michal Čihař <michal@cihar.com>" [ultimate]
gpg:          aka "Michal Čihař <nijel@debian.org>" [ultimate]
gpg:          aka "[jpeg image of size 8848]" [ultimate]
gpg:          aka "Michal Čihař (Braiiins) <michal.cihar@braiiins.cz>"
↳[ultimate]
```

Should the signature be invalid (the archive has been changed), you would get a clear error regardless of the fact that the key is trusted or not:

```
$ gpg --verify Weblate-3.5.tar.xz.asc
gpg: Signature made Sun Mar  3 16:43:15 2019 CET
gpg:                using RSA key 87E673AF83F6C3A0C344C8C3F4AA229D4D58C245
gpg: BAD signature from "Michal Čihar <michal@cihar.com>" [ultimate]
```

2.1.4 Leje sistemi kartelash

The Weblate process needs to be able to read and write to the directory where it keeps data - `DATA_DIR`. All files within this directory should be owned and writable by the user running all Weblate processes (typically WSGI and Celery, see *Running server* and *Background tasks using Celery*).

The default configuration places them in the same tree as the Weblate sources, however you might prefer to move these to a better location such as: `/var/lib/weblate`.

Weblate tries to create these directories automatically, but it will fail when it does not have permissions to do so.

You should also take care when running *Management commands*, as they should be ran under the same user as Weblate itself is running, otherwise permissions on some files might be wrong.

In the Docker container, all files in the `/app/data` volume have to be owned by weblate user inside the container (UID 1000).

Shihni edhe:

Serving static files

2.1.5 Ujdisje baze të dhënash për Weblate

It is recommended to run Weblate with a PostgreSQL database server.

Shihni edhe:

Përdorni një mekanizëm të fuqishëm baze të dhënash, Databases, Migrating from other databases to PostgreSQL

PostgreSQL

PostgreSQL is usually the best choice for Django-based sites. It's the reference database used for implementing Django database layer.

Shënim: Weblate uses trigram extension which has to be installed separately in some cases. Look for `postgresql-contrib` or a similarly named package.

Shihni edhe:

PostgreSQL notes

Krijim i një baze të dhënash në PostgreSQL

It is usually a good idea to run Weblate in a separate database, and separate user account:

```
# If PostgreSQL was not installed before, set the main password
sudo -u postgres psql postgres -c "\password postgres"

# Create a database user called "weblate"
sudo -u postgres createuser --superuser --pwprompt weblate

# Create the database "weblate" owned by "weblate"
sudo -u postgres createdb -E UTF8 -O weblate weblate
```

Ndihmëz: If you don't want to make the Weblate user a superuser in PostgreSQL, you can omit that. In that case you will have to perform some of the migration steps manually as a PostgreSQL superuser in schema Weblate will use:

```
CREATE EXTENSION IF NOT EXISTS pg_trgm WITH SCHEMA weblate;
```

Formësim i Weblate-it që të përdorë PostgreSQL-in

The `settings.py` snippet for PostgreSQL:

```
DATABASES = {
    "default": {
        # Database engine
        "ENGINE": "django.db.backends.postgresql",
        # Database name
        "NAME": "weblate",
        # Database user
        "USER": "weblate",
        # Name of role to alter to set parameters in PostgreSQL,
        # use in case role name is different than user used for authentication.
        # "ALTER_ROLE": "weblate",
        # Database password
        "PASSWORD": "password",
        # Set to empty string for localhost
        "HOST": "database.example.com",
        # Set to empty string for default
        "PORT": "",
    }
}
```

The database migration performs `ALTER ROLE` on database role used by Weblate. In most cases the name of the role matches username. In more complex setups the role name is different than username and you will get error about non-existing role during the database migration (`psycopg2.errors.UndefinedObject: role "weblate@hostname" does not exist`). This is known to happen with Azure Database for PostgreSQL, but it's not limited to this environment. Please set `ALTER_ROLE` to change name of the role Weblate should alter during the database migration.

MySQL dhe MariaDB

Ndihmëz: Some Weblate features will perform better with *PostgreSQL*. This includes searching and translation memory, which both utilize full-text features in the database and PostgreSQL implementation is superior.

Weblate can be also used with MySQL or MariaDB, please see [MySQL notes](#) and [MariaDB notes](#) for caveats using Django with those. Because of the limitations it is recommended to use *PostgreSQL* for new installations.

Weblate requires MySQL at least 5.7.8 or MariaDB at least 10.2.7.

Following configuration is recommended for Weblate:

- Use the `utf8mb4` charset to allow representation of higher Unicode planes (for example emojis).
- Configure the server with `innodb_large_prefix` to allow longer indices on text fields.
- Set the isolation level to `READ COMMITTED`.
- The SQL mode should be set to `STRICT_TRANS_TABLES`.

MySQL 8.x, MariaDB 10.5.x or newer have reasonable default configuration so that no server tweaking should be necessary and all what is needed can be configured on the client side.

Below is an example `/etc/my.cnf.d/server.cnf` for a server with 8 GB of RAM. These settings should be sufficient for most installs. MySQL and MariaDB have tunables that will increase the performance of your server that are considered not necessary unless you are planning on having large numbers of concurrent users accessing the system. See the various vendors documentation on those details.

It is absolutely critical to reduce issues when installing that the setting `innodb_file_per_table` is set properly and MySQL/MariaDB restarted before you start your Weblate install.

```
[mysqld]
character-set-server = utf8mb4
character-set-client = utf8mb4
collation-server = utf8mb4_unicode_ci

datadir=/var/lib/mysql

log-error=/var/log/mariadb/mariadb.log

innodb_large_prefix=1
innodb_file_format=Barracuda
innodb_file_per_table=1
innodb_buffer_pool_size=2G
sql_mode=STRICT_TRANS_TABLES
```

Ndihmëz: In case you are getting `#1071 - Specified key was too long; max key length is 767 bytes error`, please update your configuration to include the `innodb` settings above and restart your install.

Ndihmëz: In case you are getting `#2006 - MySQL server has gone away error`, configuring `CONN_MAX_AGE` might help.

Configuring Weblate to use MySQL/MariaDB

The `settings.py` snippet for MySQL and MariaDB:

```
DATABASES = {
    "default": {
        # Database engine
        "ENGINE": "django.db.backends.mysql",
        # Database name
        "NAME": "weblate",
        # Database user
        "USER": "weblate",
        # Database password
        "PASSWORD": "password",
        # Set to empty string for localhost
        "HOST": "127.0.0.1",
        # Set to empty string for default
        "PORT": "3306",
        # In case you wish to use additional
        # connection options
        "OPTIONS": {},
    }
}
```

You should also create the `weblate` user account in MySQL or MariaDB before you begin the install. Use the commands below to achieve that:


```
GRANT ALL ON weblate.* to 'weblate'@'localhost' IDENTIFIED BY 'password';
FLUSH PRIVILEGES;
```

2.1.6 Formësimet e tjera

Formësimi i email-eve që dërgohen

Weblate sends out e-mails on various occasions - for account activation and on various notifications configured by users. For this it needs access to an SMTP server.

The mail server setup is configured using these settings: `EMAIL_HOST`, `EMAIL_HOST_PASSWORD`, `EMAIL_USE_TLS`, `EMAIL_USE_SSL`, `EMAIL_HOST_USER` and `EMAIL_PORT`. Their names are quite self-explanatory, but you can find more info in the Django documentation.

Ndihmëz: In case you get error about not supported authentication (for example SMTP AUTH extension not supported by server), it is most likely caused by using insecure connection and server refuses to authenticate this way. Try enabling `EMAIL_USE_TLS` in such case.

Shihni edhe:

Not receiving e-mails from Weblate, Configuring outgoing e-mail in Docker container

Running behind reverse proxy

Several features in Weblate rely on being able to get client IP address. This includes *Rate limiting*, *Spam protection* or *Auditim regjistri*.

In default configuration Weblate parses IP address from `REMOTE_ADDR` which is set by the WSGI handler.

In case you are running a reverse proxy, this field will most likely contain its address. You need to configure Weblate to trust additional HTTP headers and parse the IP address from these. This can not be enabled by default as it would allow IP address spoofing for installations not using a reverse proxy. Enabling `IP_BEHIND_REVERSE_PROXY` might be enough for the most usual setups, but you might need to adjust `IP_PROXY_HEADER` and `IP_PROXY_OFFSET` as well.

Shihni edhe:

Spam protection, Rate limiting, Auditim regjistri, IP_BEHIND_REVERSE_PROXY, IP_PROXY_HEADER, IP_PROXY_OFFSET, SECURE_PROXY_SSL_HEADER

Ndërmjetës HTTP

Weblate does execute VCS commands and those accept proxy configuration from environment. The recommended approach is to define proxy settings in `settings.py`:

```
import os

os.environ["http_proxy"] = "http://proxy.example.com:8080"
os.environ["HTTPS_PROXY"] = "http://proxy.example.com:8080"
```

Shihni edhe:

Proxy Environment Variables

2.1.7 Përshtatje formësimi

Shihni edhe:

Sample configuration

Copy `weblate/settings_example.py` to `weblate/settings.py` and adjust it to match your setup. You will probably want to adjust the following options: `ADMINS`

List of site administrators to receive notifications when something goes wrong, for example notifications on failed merges, or Django errors.

Shihni edhe:

`ADMINS`

`ALLOWED_HOSTS`

You need to set this to list the hosts your site is supposed to serve. For example:

```
ALLOWED_HOSTS = ["demo.weblate.org"]
```

Ndryshe, mund të përdorni shenjë të gjithëpushtetshme:

```
ALLOWED_HOSTS = ["*"]
```

Shihni edhe:

`ALLOWED_HOSTS`, `WEBLATE_ALLOWED_HOSTS`, *Allowed hosts setup*

`SESSION_ENGINE`

Configure how your sessions will be stored. In case you keep the default database backend engine, you should schedule: **weblate clearsessions** to remove stale session data from the database.

If you are using Redis as cache (see *Aktivizoni përdorim fshehtine*) it is recommended to use it for sessions as well:

```
SESSION_ENGINE = "django.contrib.sessions.backends.cache"
```

Shihni edhe:

Configuring the session engine, `SESSION_ENGINE`

`DATABASES`

Connectivity to database server, please check Django's documentation for more details.

Shihni edhe:

Ujdisje baze të dhënash për Weblate, `DATABASES`, *Databases*

`DEBUG`

Disable this for any production server. With debug mode enabled, Django will show backtraces in case of error to users, when you disable it, errors will be sent per e-mail to `ADMINS` (see above).

Debug mode also slows down Weblate, as Django stores much more info internally in this case.

Shihni edhe:

`DEBUG`

`DEFAULT_FROM_EMAIL`

E-mail sender address for outgoing e-mail, for example registration e-mails.

Shihni edhe:

`DEFAULT_FROM_EMAIL`

`SECRET_KEY`

Key used by Django to sign some info in cookies, see [Django secret key](#) for more info.

Shihni edhe:

`SECRET_KEY`

`SERVER_EMAIL`

E-mail used as sender address for sending e-mails to the administrator, for example notifications on failed merges.

Shihni edhe:

`SERVER_EMAIL`

2.1.8 Mbushje e bazës së të dhënave

After your configuration is ready, you can run `weblate migrate` to create the database structure. Now you should be able to create translation projects using the admin interface.

In case you want to run an installation non interactively, you can use `weblate migrate --noinput`, and then create an admin user using `createadmin` command.


Once you are done, you should also check the *Performance report* in the admin interface, which will give you hints of potential non optimal configuration on your site.

Shihni edhe:

Formësim, Listë privilegjesh

2.1.9 Production setup

For a production setup you should carry out adjustments described in the following sections. The most critical settings will trigger a warning, which is indicated by an exclamation mark in the top bar if signed in as a superuser:



It is also recommended to inspect checks triggered by Django (though you might not need to fix all of them):

```
weblate check --deploy
```

You can also review the very same checklist from the *Ndërfaqe administrimi*.

Shihni edhe:

[Deployment checklist](#)

Disable debug mode

Disable Django's debug mode (*DEBUG*) by:

```
DEBUG = False
```

With debug mode on, Django stores all executed queries and shows users backtraces of errors, which is not desired in a production setup.

Shihni edhe:

Përshatje formësimi

Properly configure admins

Set the correct admin addresses to the *ADMINS* setting to defining who will receive e-mails in case something goes wrong on the server, for example:

```
ADMINS = (("Your Name", "your_email@example.com"),)
```

Shihni edhe:

Përshatje formësimi

Set correct site domain

Adjust site name and domain in the admin interface, otherwise links in RSS or registration e-mails will not work. This is configured using *SITE_DOMAIN* which should contain site domain name.

Ndryshuar në versionin 4.2: Prior to the 4.2 release the Django sites framework was used instead, please see [The “sites” framework](#).

Shihni edhe:

Allowed hosts setup, Formësoni si duhet HTTPS-në SITE_DOMAIN, WEBLATE_SITE_DOMAIN, ENABLE_HTTPS

Formësoni si duhet HTTPS-në

It is strongly recommended to run Weblate using the encrypted HTTPS protocol. After enabling it, you should set *ENABLE_HTTPS* in the settings:

```
ENABLE_HTTPS = True
```

Ndihmëz: You might want to set up HSTS as well, see [SSL/HTTPS](#) for more details.

Shihni edhe:

ENABLE_HTTPS, Allowed hosts setup, Set correct site domain

Set properly `SECURE_HSTS_SECONDS`

If your site is served over SSL, you have to consider setting a value for `SECURE_HSTS_SECONDS` in the `settings.py` to enable HTTP Strict Transport Security. By default it's set to 0 as shown below.

```
SECURE_HSTS_SECONDS = 0
```

If set to a non-zero integer value, the `django.middleware.security.SecurityMiddleware` sets the HTTP Strict Transport Security header on all responses that do not already have it.

Sinjalizim: Setting this incorrectly can irreversibly (for some time) break your site. Read the [HTTP Strict Transport Security](#) documentation first.

Përdorni një mekanizëm të fuqishëm baze të dhënash

- Please use PostgreSQL for a production environment, see *Ujdisje baze të dhënash për Weblate* for more info.
- Use adjacent location for running the database server, otherwise the networking performance or reliability might ruin your Weblate experience.
- Check the database server performance or tweak its configuration, for example using [PGTune](#).

Shihni edhe:

Ujdisje baze të dhënash për Weblate, Migrating from other databases to PostgreSQL, Përshtatje formësimi, Databases

Aktivizoni përdorim fshehtine

If possible, use Redis from Django by adjusting the `CACHES` configuration variable, for example:

```
CACHES = {
    "default": {
        "BACKEND": "django_redis.cache.RedisCache",
        "LOCATION": "redis://127.0.0.1:6379/0",
        # If redis is running on same host as Weblate, you might
        # want to use unix sockets instead:
        # 'LOCATION': 'unix:///var/run/redis/redis.sock?db=0',
        "OPTIONS": {
            "CLIENT_CLASS": "django_redis.client.DefaultClient",
            "PARSER_CLASS": "redis.connection.HiredisParser",
        },
    },
}
```

Ndihmëz: In case you change Redis settings for the cache, you might need to adjust them for Celery as well, see *Background tasks using Celery*.

Shihni edhe:

Avatar caching, Django's cache framework

Avatar caching

In addition to caching of Django, Weblate performs caching of avatars. It is recommended to use a separate, file-backed cache for this purpose:

```
CACHES = {
    "default": {
        # Default caching backend setup, see above
        "BACKEND": "django_redis.cache.RedisCache",
        "LOCATION": "unix:///var/run/redis/redis.sock?db=0",
        "OPTIONS": {
            "CLIENT_CLASS": "django_redis.client.DefaultClient",
            "PARSER_CLASS": "redis.connection.HiredisParser",
        },
    },
    "avatar": {
        "BACKEND": "django.core.cache.backends.filebased.FileBasedCache",
        "LOCATION": os.path.join(DATA_DIR, "avatar-cache"),
        "TIMEOUT": 604800,
        "OPTIONS": {
            "MAX_ENTRIES": 1000,
        },
    },
}
```

Shihni edhe:

`ENABLE_AVATARS`, `AVATAR_URL_PREFIX`, *Avatars*, *Aktivizoni përdorim fshehtine*, Django's cache framework

Formësoni dërgimi email-esh

Weblate needs to send out e-mails on several occasions, and these e-mails should have a correct sender address, please configure `SERVER_EMAIL` and `DEFAULT_FROM_EMAIL` to match your environment, for example:

```
SERVER_EMAIL = "admin@example.org"
DEFAULT_FROM_EMAIL = "weblate@example.org"
```

Shënim: To disable sending e-mails by Weblate set `EMAIL_BACKEND` to `django.core.mail.backends.dummy.EmailBackend`.

This will disable *all* e-mail delivery including registration or password reset e-mails.

Shihni edhe:

Përshatje formësimi, *Formësim i email-eve që dërgohen*, `EMAIL_BACKEND`, `DEFAULT_FROM_EMAIL`, `SERVER_EMAIL`

Allowed hosts setup

Django requires `ALLOWED_HOSTS` to hold a list of domain names your site is allowed to serve, leaving it empty will block any requests.

In case this is not configured to match your HTTP server, you will get errors like Invalid HTTP_HOST header: '1.1.1.1'. You may need to add '1.1.1.1' to `ALLOWED_HOSTS`.

Ndihmëz: On Docker container, this is available as `WEBLATE_ALLOWED_HOSTS`.

Shihni edhe:

`ALLOWED_HOSTS`, `WEBLATE_ALLOWED_HOSTS`, *Set correct site domain*

Django secret key

The `SECRET_KEY` setting is used by Django to sign cookies, and you should really generate your own value rather than using the one from the example setup.

You can generate a new key using `weblate/examples/generate-secret-key` shipped with Weblate.

Shihni edhe:

`SECRET_KEY`

Home directory

Ndryshuar në versionin 2.1: This is no longer required, Weblate now stores all its data in `DATA_DIR`.

The home directory for the user running Weblate should exist and be writable by this user. This is especially needed if you want to use SSH to access private repositories, but Git might need to access this directory as well (depending on the Git version you use).

You can change the directory used by Weblate in `settings.py`, for example to set it to configuration directory under the Weblate tree:

```
os.environ["HOME"] = os.path.join(BASE_DIR, "configuration")
```

Shënim: On Linux, and other UNIX like systems, the path to user's home directory is defined in `/etc/passwd`. Many distributions default to a non-writable directory for users used for serving web content (such as `apache`, `www-data` or `wwwrun`), so you either have to run Weblate under a different user, or change this setting.

Shihni edhe:

Hyrje në depo

Template loading

It is recommended to use a cached template loader for Django. It caches parsed templates and avoids the need to do parsing with every single request. You can configure it using the following snippet (the `loaders` setting is important here):

```
TEMPLATES = [
    {
        "BACKEND": "django.template.backends.django.DjangoTemplates",
        "DIRS": [
            os.path.join(BASE_DIR, "templates"),
        ],
        "OPTIONS": {
            "context_processors": [
                "django.contrib.auth.context_processors.auth",
                "django.template.context_processors.debug",
                "django.template.context_processors.i18n",
                "django.template.context_processors.request",
                "django.template.context_processors.csrf",
                "django.contrib.messages.context_processors.messages",
                "weblate.trans.context_processors.weblate_context",
            ],
            "loaders": [
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

        (
            "django.template.loaders.cached.Loader",
            [
                "django.template.loaders.filesystem.Loader",
                "django.template.loaders.app_directories.Loader",
            ],
        ),
    ],
},
]

```

Shihni edhe:`django.template.loaders.cached.Loader`**Xhirim aktesh mirëmbajtjeje**

For optimal performance, it is good idea to run some maintenance tasks in the background. This is now automatically done by *Background tasks using Celery* and covers following tasks:

- Configuration health check (hourly).
- Committing pending changes (hourly), see *Lazy commits* and *commit_pending*.
- Updating component alerts (daily).
- Update remote branches (nightly), see *AUTO_UPDATE*.
- Translation memory backup to JSON (daily), see *dump_memory*.
- Fulltext and database maintenance tasks (daily and weekly tasks), see *cleanuptrans*.

Ndryshuar në versionin 3.2: Since version 3.2, the default way of executing these tasks is using Celery and Weblate already comes with proper configuration, see *Background tasks using Celery*.

Vendore dhe kodim sistemi

The system locales should be configured to UTF-8 capable ones. On most Linux distributions this is the default setting. In case it is not the case on your system, please change locales to UTF-8 variant.

For example by editing `/etc/default/locale` and setting there `LANG="C.UTF-8"`.

In some cases the individual services have separate configuration for locales. This varies between distribution and web servers, so check documentation of your web server packages for that.

Apache on Ubuntu uses `/etc/apache2/envvars`:

```
export LANG='en_US.UTF-8'
export LC_ALL='en_US.UTF-8'
```

Apache on CentOS uses `/etc/sysconfig/httpd` (or `/opt/rh/httpd24/root/etc/sysconfig/httpd`):

```
LANG='en_US.UTF-8'
```


Using custom certificate authority

Weblate does verify SSL certificates during HTTP requests. In case you are using custom certificate authority which is not trusted in default bundles, you will have to add its certificate as trusted.

The preferred approach is to do this at system level, please check your distro documentation for more details (for example on debian this can be done by placing the CA certificate into `/usr/local/share/ca-certificates/` and running `update-ca-certificates`).

Once this is done, system tools will trust the certificate and this includes Git.

For Python code, you will need to configure requests to use system CA bundle instead of the one shipped with it. This can be achieved by placing following snippet to `settings.py` (the path is Debian specific):

```
import os

os.environ["REQUESTS_CA_BUNDLE"] = "/etc/ssl/certs/ca-certificates.crt"
```

Compressing client assets

Weblate comes with a bunch of JavaScript and CSS files. For performance reasons it is good to compress them before sending to a client. In default configuration this is done on the fly at cost of little overhead. On big installations, it is recommended to enable offline compression mode. This needs to be done in the configuration and the compression has to be triggered on every Weblate upgrade.

The configuration switch is simple by enabling `django.conf.settings.COMPRESS_OFFLINE` and configuring `django.conf.settings.COMPRESS_OFFLINE_CONTEXT` (the latter is already included in the example configuration):

```
COMPRESS_OFFLINE = True
```

On each deploy you need to compress the files to match current version:

```
weblate compress
```

Ndihmëz: The official Docker image has this feature already enabled.

Shihni edhe:

[Common Deployment Scenarios](#), [Serving static files](#)

2.1.10 Running server

Ndihmëz: In case you are not experienced with services described below, you might want to try [Installing using Docker](#).

You will need several services to run Weblate, the recommended setup consists of:

- Database server (see [Ujdisje baze të dhënash për Weblate](#))
- Cache server (see [Aktivizimi përdorim fshehtine](#))
- Frontend web server for static files and SSL termination (see [Serving static files](#))
- WSGI server for dynamic content (see [Sample configuration for NGINX and uWSGI](#))
- Celery for executing background tasks (see [Background tasks using Celery](#))

Shënim: There are some dependencies between the services, for example cache and database should be running when starting up Celery or uwsgi processes.

In most cases, you will run all services on single (virtual) server, but in case your installation is heavily loaded, you can split up the services. The only limitation on this is that Celery and Wsgi servers need access to `DATA_DIR`.

Shënim: The WSGI process has to be executed under the same user the Celery process, otherwise files in the `DATA_DIR` will be stored with mixed ownership, leading to runtime issues.

See also *Leje sistemi kartelash* and *Background tasks using Celery*.

Running web server

Running Weblate is not different from running any other Django based program. Django is usually executed as uWSGI or fcgi (see examples for different web servers below).

For testing purposes, you can use the built-in web server in Django:

```
weblate runserver
```

Sinjalizim: DO NOT USE THIS SERVER IN A PRODUCTION SETTING. It has not gone through security audits or performance tests. See also Django documentation on `runserver`.

Ndihmëz: The Django built-in server serves static files only with `DEBUG` enabled as it is intended for development only. For production use, please see wsgi setups in *Sample configuration for NGINX and uWSGI*, *Sample configuration for Apache*, *Sample configuration for Apache and Gunicorn*, and *Serving static files*.

Serving static files

Ndryshuar në versionin 2.4: Prior to version 2.4, Weblate didn't properly use the Django static files framework and the setup was more complex.

Django needs to collect its static files in a single directory. To do so, execute `weblate collectstatic --noinput`. This will copy the static files into a directory specified by the `STATIC_ROOT` setting (this defaults to a `static` directory inside `DATA_DIR`).

It is recommended to serve static files directly from your web server, you should use that for the following paths:

/static/ Serves static files for Weblate and the admin interface (from defined by `STATIC_ROOT`).

/media/ Used for user media uploads (e.g. screenshots).

/favicon.ico Should be rewritten to rewrite a rule to serve `/static/favicon.ico`.

Shihni edhe:

Sample configuration for NGINX and uWSGI, *Sample configuration for Apache*, *Sample configuration for Apache and Gunicorn*, *Compressing client assets*, *Deploying Django*, *Deploying static files*

Content security policy

The default Weblate configuration enables `weblate.middleware.SecurityMiddleware` middleware which sets security related HTTP headers like `Content-Security-Policy` or `X-XSS-Protection`. These are by default set up to work with Weblate and its configuration, but this might need customization for your environment.

Shihni edhe:

`CSP_SCRIPT_SRC`, `CSP_IMG_SRC`, `CSP_CONNECT_SRC`, `CSP_STYLE_SRC`, `CSP_FONT_SRC`

Sample configuration for NGINX and uWSGI

To run production webserver, use the wsgi wrapper installed with Weblate (in virtual env case it is installed as `~/weblate-env/lib/python3.7/site-packages/weblate/wsgi.py`). Don't forget to set the Python search path to your virtualenv as well (for example using `virtualenv = /home/user/weblate-env` in uWSGI).

The following configuration runs Weblate as uWSGI under the NGINX webserver.

Configuration for NGINX (also available as `weblate/examples/weblate.nginx.conf`):

```
# This example assumes Weblate is installed in virtualenv in /home/weblate/weblate-
# and DATA_DIR is set to /home/weblate/data, please adjust paths to match your
server {
    listen 80;
    server_name weblate;
    # Not used
    root /var/www/html;

    location ~ ^/favicon.ico$ {
        # DATA_DIR/static/favicon.ico
        alias /home/weblate/data/static/favicon.ico;
        expires 30d;
    }

    location /static/ {
        # DATA_DIR/static/
        alias /home/weblate/data/static/;
        expires 30d;
    }

    location /media/ {
        # DATA_DIR/media/
        alias /home/weblate/data/media/;
        expires 30d;
    }

    location / {
        include uwsgi_params;
        # Needed for long running operations in admin interface
        uwsgi_read_timeout 3600;
        # Adjust based to uwsgi configuration:
        uwsgi_pass unix:///run/uwsgi/app/weblate/socket;
        # uwsgi_pass 127.0.0.1:8080;
    }
}
```

Configuration for uWSGI (also available as `weblate/examples/weblate.uwsgi.ini`):

```

# This example assumes Weblate is installed in virtualenv in /home/weblate/weblate-
↪env
# and DATA_DIR is set to /home/weblate/data, please adjust paths to match your
↪setup.
[uwsgi]
plugins      = python3
master       = true
protocol     = uwsgi
socket       = 127.0.0.1:8080
wsgi-file    = /home/weblate/weblate-env/lib/python3.9/site-packages/weblate/wsgi.
↪py

# Add path to Weblate checkout if you did not install
# Weblate by pip
# python-path = /path/to/weblate

# In case you're using virtualenv uncomment this:
virtualenv = /home/weblate/weblate-env

# Needed for OAuth/OpenID
buffer-size  = 8192

# Reload when consuming too much of memory
reload-on-rss = 250

# Increase number of workers for heavily loaded sites
workers      = 8

# Enable threads for Sentry error submission
enable-threads = true

# Child processes do not need file descriptors
close-on-exec = true

# Avoid default 0000 umask
umask = 0022

# Run as weblate user
uid = weblate
gid = weblate

# Enable harakiri mode (kill requests after some time)
# harakiri = 3600
# harakiri-verbose = true

# Enable uWSGI stats server
# stats = :1717
# stats-http = true

# Do not log some errors caused by client disconnects
ignore-sigpipe = true
ignore-write-errors = true
disable-write-exception = true

```

Shihni edhe:

How to use Django with uWSGI

Sample configuration for Apache

It is recommended to use prefork MPM when using WSGI with Weblate.

The following configuration runs Weblate as WSGI, you need to have enabled `mod_wsgi` (available as `weblate/examples/apache.conf`):

```
#
# VirtualHost for Weblate
#
# This example assumes Weblate is installed in virtualenv in /home/weblate/weblate-
# ↪env
# and DATA_DIR is set to /home/weblate/data, please adjust paths to match your_
# ↪setup.
#
<VirtualHost *:80>
    ServerAdmin admin@weblate.example.org
    ServerName weblate.example.org

    # DATA_DIR/static/favicon.ico
    Alias /favicon.ico /home/weblate/data/static/favicon.ico

    # DATA_DIR/static/
    Alias /static/ /home/weblate/data/static/
    <Directory /home/weblate/data/static/>
        Require all granted
    </Directory>

    # DATA_DIR/media/
    Alias /media/ /home/weblate/data/media/
    <Directory /home/weblate/data/media/>
        Require all granted
    </Directory>

    # Path to your Weblate virtualenv
    WSGIDaemonProcess weblate python-home=/home/weblate/weblate-env user=weblate
    WSGIProcessGroup weblate
    WSGIApplicationGroup %{GLOBAL}

    WSGIScriptAlias / /home/weblate/weblate-env/lib/python3.7/site-packages/
    ↪weblate/wsgi.py process-group=weblate request-timeout=600
    WSGIPassAuthorization On

    <Directory /home/weblate/weblate-env/lib/python3.7/site-packages/weblate/>
        <Files wsgi.py>
            Require all granted
        </Files>
    </Directory>
</VirtualHost>
```

Shënim: Weblate requires Python 3, so please make sure you are running Python 3 variant of the `modwsgi`. Usually it is available as a separate package, for example `libapache2-mod-wsgi-py3`.

Shihni edhe:

Vendore dhe kodim sistemi, How to use Django with Apache and `mod_wsgi`

Sample configuration for Apache and Gunicorn

The following configuration runs Weblate in Gunicorn and Apache 2.4 (available as `weblate/examples/apache.gunicorn.conf`):

```
#
# VirtualHost for Weblate using gunicorn on localhost:8000
#
# This example assumes Weblate is installed in virtualenv in /home/weblate/weblate-
# ↪env
# and DATA_DIR is set to /home/weblate/data, please adjust paths to match your_
# ↪setup.
#
<VirtualHost *:443>
    ServerAdmin admin@weblate.example.org
    ServerName weblate.example.org

    # DATA_DIR/static/favicon.ico
    Alias /favicon.ico /home/weblate/data/static/favicon.ico

    # DATA_DIR/static/
    Alias /static/ /home/weblate/data/static/
    <Directory /home/weblate/data/static/>
        Require all granted
    </Directory>

    # DATA_DIR/media/
    Alias /media/ /home/weblate/data/media/
    <Directory /home/weblate/data/media/>
        Require all granted
    </Directory>

    SSLEngine on
    SSLCertificateFile /etc/apache2/ssl/https_cert.cert
    SSLCertificateKeyFile /etc/apache2/ssl/https_key.pem
    SSLProxyEngine On

    ProxyPass /favicon.ico !
    ProxyPass /static/ !
    ProxyPass /media/ !

    ProxyPass / http://localhost:8000/
    ProxyPassReverse / http://localhost:8000/
    ProxyPreserveHost On
</VirtualHost>
```

Shihni edhe:

How to use Django with Gunicorn

Running Weblate under path

Të reja në versionin 1.3.

It is recommended to use prefork MPM when using WSGI with Weblate.

A sample Apache configuration to serve Weblate under `/weblate`. Again using `mod_wsgi` (also available as `weblate/examples/apache-path.conf`):

```
#
# VirtualHost for Weblate, running under /weblate path
#
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
# This example assumes Weblate is installed in virtualenv in /home/weblate/weblate-
↪env
# and DATA_DIR is set to /home/weblate/data, please adjust paths to match your_
↪setup.
#
<VirtualHost *:80>
    ServerAdmin admin@weblate.example.org
    ServerName weblate.example.org

    # DATA_DIR/static/favicon.ico
    Alias /weblate/favicon.ico /home/weblate/data/static/favicon.ico

    # DATA_DIR/static/
    Alias /weblate/static/ /home/weblate/data/static/
    <Directory /home/weblate/data/static/>
        Require all granted
    </Directory>

    # DATA_DIR/media/
    Alias /weblate/media/ /home/weblate/data/media/
    <Directory /home/weblate/data/media/>
        Require all granted
    </Directory>

    # Path to your Weblate virtualenv
    WSGIDaemonProcess weblate python-home=/home/weblate/weblate-env user=weblate
    WSGIProcessGroup weblate
    WSGIApplicationGroup %{GLOBAL}

    WSGIScriptAlias /weblate /home/weblate/weblate-env/lib/python3.7/site-packages/
↪weblate/wsgi.py process-group=weblate request-timeout=600
    WSGIPassAuthorization On

    <Directory /home/weblate/weblate-env/lib/python3.7/site-packages/weblate/>
        <Files wsgi.py>
            Require all granted
        </Files>
    </Directory>
</VirtualHost>
```

Additionally, you will have to adjust `weblate/settings.py`:

```
URL_PREFIX = "/weblate"
```

2.1.11 Background tasks using Celery

Të reja në versionin 3.2.

Weblate uses Celery to process background tasks. A typical setup using Redis as a backend looks like this:

```
CELERY_TASK_ALWAYS_EAGER = False
CELERY_BROKER_URL = "redis://localhost:6379"
CELERY_RESULT_BACKEND = CELERY_BROKER_URL
```

Shihni edhe:

[Redis broker configuration in Celery](#)

For development, you might want to use eager configuration, which does process all tasks in place, but this will have performance impact on Weblate:

```
CELERY_TASK_ALWAYS_EAGER = True
CELERY_BROKER_URL = "memory://"
CELERY_TASK_EAGER_PROPAGATES = True
```

You should also start the Celery worker to process the tasks and start scheduled tasks, this can be done directly on the command line (which is mostly useful when debugging or developing):

```
./weblate/examples/celery start
./weblate/examples/celery stop
```

Shënim: The Celery process has to be executed under the same user as the WSGI process, otherwise files in the `DATA_DIR` will be stored with mixed ownership, leading to runtime issues.

See also *Leje sistemi kartelash* and *Running server*.

Running Celery as system service

Most likely you will want to run Celery as a daemon and that is covered by [Daemonization](#). For the most common Linux setup using systemd, you can use the example files shipped in the `examples` folder listed below.

Systemd unit to be placed as `/etc/systemd/system/celery-weblate.service`:

```
[Unit]
Description=Celery Service (Weblate)
After=network.target

[Service]
Type=forking
User=weblate
Group=weblate
EnvironmentFile=/etc/default/celery-weblate
WorkingDirectory=/home/weblate
RuntimeDirectory=celery
RuntimeDirectoryPreserve=restart
LogsDirectory=celery
ExecStart=/bin/sh -c '${CELERY_BIN} multi start ${CELERYD_NODES} \
  -A ${CELERY_APP} --pidfile=${CELERYD_PID_FILE} \
  --logfile=${CELERYD_LOG_FILE} --loglevel=${CELERYD_LOG_LEVEL} ${CELERYD_OPTS}'
ExecStop=/bin/sh -c '${CELERY_BIN} multi stopwait ${CELERYD_NODES} \
  --pidfile=${CELERYD_PID_FILE}'
ExecReload=/bin/sh -c '${CELERY_BIN} multi restart ${CELERYD_NODES} \
  -A ${CELERY_APP} --pidfile=${CELERYD_PID_FILE} \
  --logfile=${CELERYD_LOG_FILE} --loglevel=${CELERYD_LOG_LEVEL} ${CELERYD_OPTS}'

[Install]
WantedBy=multi-user.target
```

Environment configuration to be placed as `/etc/default/celery-weblate`:

```
# Name of nodes to start
CELERYD_NODES="celery notify memory backup translate"

# Absolute or relative path to the 'celery' command:
CELERY_BIN="/home/weblate/weblate-env/bin/celery"

# App instance to use
# comment out this line if you don't use an app
CELERY_APP="weblate.utils"
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
# Extra command-line arguments to the worker,
# increase concurrency if you get weblate.E019
CELERYD_OPTS="--beat:celery --queues:celery=celery --prefetch-multiplier:celery=4 \
--queues:notify=notify --prefetch-multiplier:notify=10 \
--queues:memory=memory --prefetch-multiplier:memory=10 \
--queues:translate=translate --prefetch-multiplier:translate=4 \
--concurrency:backup=1 --queues:backup=backup --prefetch-multiplier:backup=2"

# Logging configuration
# - %n will be replaced with the first part of the nodename.
# - %I will be replaced with the current child process index
# and is important when using the prefork pool to avoid race conditions.
CELERYD_PID_FILE="/run/celery/weblate-%n.pid"
CELERYD_LOG_FILE="/var/log/celery/weblate-%n%I.log"
CELERYD_LOG_LEVEL="INFO"

# Internal Weblate variable to indicate we're running inside Celery
CELERY_WORKER_RUNNING="1"
```

Additional configuration to rotate Celery logs using **logrotate** to be placed as `/etc/logrotate.d/celery`:

```
/var/log/celery/*.log {
    weekly
    missingok
    rotate 12
    compress
    notifempty
}
```

Periodic tasks using Celery beat

Weblate comes with built-in setup for scheduled tasks. You can however define additional tasks in `settings.py`, for example see *Lazy commits*.

The tasks are supposed to be executed by Celery beats daemon. In case it is not working properly, it might not be running or its database was corrupted. Check the Celery startup logs in such case to figure out root cause.

Monitoring Celery status

You can use `celery_queues` to see current length of Celery task queues. In case the queue will get too long, you will also get configuration error in the admin interface.

Sinjalizim: The Celery errors are by default only logged into Celery log and are not visible to user. In case you want to have overview on such failures, it is recommended to configure *Collecting error reports*.

Shihni edhe:

Configuration and defaults, Workers Guide, Daemonization, Monitoring and Management Guide, `celery_queues`

2.1.12 Monitoring Weblate

Weblate provides the `/healthz/` URL to be used in simple health checks, for example using Kubernetes. The Docker container has built-in health check using this URL.

For monitoring metrics of Weblate you can use `GET /api/metrics/` API endpoint.

Shihni edhe:

[Weblate plugin for Munin](#)

2.1.13 Collecting error reports

Weblate, as any other software, can fail. In order to collect useful failure states we recommend to use third party services to collect such information. This is especially useful in case of failing Celery tasks, which would otherwise only report error to the logs and you won't get notified on them. Weblate has support for the following services:

Sentry

Weblate has built-in support for [Sentry](#). To use it, it's enough to set `SENTRY_DSN` in the `settings.py`:

```
SENTRY_DSN = "https://id@your.sentry.example.com/"
```

Rollbar

Weblate has built-in support for [Rollbar](#). To use it, it's enough to follow instructions for [Rollbar notifier for Python](#).

In short, you need to adjust `settings.py`:

```
# Add rollbar as last middleware:
MIDDLEWARE = [
    # ... other middleware classes ...
    "rollbar.contrib.django.middleware.RollbarNotifierMiddleware",
]

# Configure client access
ROLLBAR = {
    "access_token": "POST_SERVER_ITEM_ACCESS_TOKEN",
    "client_token": "POST_CLIENT_ITEM_ACCESS_TOKEN",
    "environment": "development" if DEBUG else "production",
    "branch": "main",
    "root": "/absolute/path/to/code/root",
}
```

Everything else is integrated automatically, you will now collect both server and client side errors.

2.1.14 Migrating Weblate to another server

Migrating Weblate to another server should be pretty easy, however it stores data in few locations which you should migrate carefully. The best approach is to stop Weblate for the migration.

Migrim baze të dhënash

Depending on your database backend, you might have several options to migrate the database. The most straightforward one is to dump the database on one server and import it on the new one. Alternatively you can use replication in case your database supports it.

The best approach is to use database native tools, as they are usually the most effective (e.g. **mysqldump** or **pg_dump**). If you want to migrate between different databases, the only option might be to use Django management to dump and import the database:

```
# Export current data
weblate dumpdata > /tmp/weblate.dump
# Import dump
weblate loaddata /tmp/weblate.dump
```

Migrating VCS repositories

The VCS repositories stored under `DATA_DIR` need to be migrated as well. You can simply copy them or use **rsync** to do the migration more effectively.

Shënime të Tjera

Don't forget to move other services Weblate might have been using like Redis, Cron jobs or custom authentication backends.

2.2 Sendësrtime Weblate

Weblate can be easily installed in your cloud. Please find detailed guide for your platform:

- *Installing using Docker*
- *Installing on OpenShift*
- *Installing on Kubernetes*

2.2.1 Third-party deployments for Weblate

Shënim: Following deployments are not developed or supported by Weblate team. Parts of the setup might vary from what is described in this documentation.

Bitnami Weblate stack

Bitnami provides a Weblate stack for many platforms at <<https://bitnami.com/stack/weblate>>. The setup will be adjusted during installation, see <<https://bitnami.com/stack/weblate/README.txt>> for more documentation.

Weblate Cloudron Package

Cloudron is a platform for self-hosting web applications. Weblate installed with Cloudron will be automatically kept up-to-date. The package is maintained by the Cloudron team at their [Weblate package repo](#).



Weblate në YunoHost

The self-hosting project [YunoHost](#) provides a package for Weblate. Once you have your YunoHost installation, you may install Weblate as any other application. It will provide you with a fully working stack with backup and restoration, but you may still have to edit your settings file for specific usages.

You may use your administration interface, or this button (it will bring you to your server):



It also is possible to use the commandline interface:

```
yunohost app install https://github.com/YunoHost-Apps/weblate_ynh
```

2.3 Upgrading Weblate

2.3.1 Docker image upgrades

The official Docker image (see [Installing using Docker](#)) has all upgrade steps integrated. There are no manual step besides pulling latest version.

2.3.2 Generic upgrade instructions

Before upgrading, please check the current *Domosdoshmëri software* as they might have changed. Once all requirements are installed or updated, please adjust your `settings.py` to match changes in the configuration (consult `settings_example.py` for correct values).

Always check [Version specific instructions](#) before upgrade. In case you are skipping some versions, please follow instructions for all versions you are skipping in the upgrade. Sometimes it's better to upgrade to some intermediate version to ensure a smooth migration. Upgrading across multiple releases should work, but is not as well tested as single version upgrades.

Shënim: It is recommended to perform a full database backup prior to upgrade so that you can roll back the database in case upgrade fails, see [Kopjeruajtje dhe zhvendosje e Weblate](#).

1. Stop wsgi and Celery processes. The upgrade can perform incompatible changes in the database, so it is always safer to avoid old processes running while upgrading.
2. Upgrade Weblate code.

For pip installs it can be achieved by:

```
pip install -U Weblate
```

With Git checkout you need to fetch new source code and update your installation:

```
cd weblate-src
git pull
# Update Weblate inside your virtualenv
. ~/weblate-env/bin/pip install -e .
# Install dependencies directly when not using virtualenv
pip install --upgrade -r requirements.txt
```

3. Upgrade configuration file, refer to `settings_example.py` or *Version specific instructions* for needed steps.

4. Upgrade database structure:

```
weblate migrate --noinput
```

5. Collect updated static files (see *Running server* and *Serving static files*):

```
weblate collectstatic --noinput
```

6. Compress JavaScript and CSS files (optional, see *Compressing client assets*):

```
weblate compress
```

7. If you are running version from Git, you should also regenerate locale files every time you are upgrading. You can do this by invoking:

```
weblate compilemessages
```

8. Verify that your setup is sane (see also *Production setup*):

```
weblate check --deploy
```

9. Restart Celery worker (see *Background tasks using Celery*).

2.3.3 Version specific instructions

Upgrade from 2.x

If you are upgrading from 2.x release, always first upgrade to 3.0.1 and then continue upgrading in the 3.x series. Upgrades skipping this step are not supported and will break.

Shihni edhe:

Upgrade from 2.20 to 3.0 in [Weblate 3.0 documentation](#)

Upgrade from 3.x

If you are upgrading from 3.x release, always first upgrade to 4.0.4 or 4.1.1 and then continue upgrading in the 4.x series. Upgrades skipping this step are not supported and will break.

Shihni edhe:

Upgrade from 3.11 to 4.0 in [Weblate 4.0 documentation](#)

Upgrade from 4.0 to 4.1

Please follow *Generic upgrade instructions* in order to perform update.

Notable configuration or dependencies changes:

- There are several changes in `settings_example.py`, most notable middleware changes, please adjust your settings accordingly.
- There are new file formats, you might want to include them in case you modified the `WEBLATE_FORMATS`.
- There are new quality checks, you might want to include them in case you modified the `CHECK_LIST`.
- There is change in `DEFAULT_THROTTLE_CLASSES` setting to allow reporting of rate limiting in the API.
- There are some new and updated requirements.
- There is a change in `INSTALLED_APPS`.
- The `MT_DEEPL_API_VERSION` setting has been removed in Version 4.7. The *DeepL* machine translation now uses the new `MT_DEEPL_API_URL` instead. You might need to adjust `MT_DEEPL_API_URL` to match your subscription.

Shihni edhe:

Generic upgrade instructions

Upgrade from 4.1 to 4.2

Please follow *Generic upgrade instructions* in order to perform update.

Notable configuration or dependencies changes:

- Upgrade from 3.x releases is not longer supported, please upgrade to 4.0 or 4.1 first.
- There are some new and updated requirements.
- There are several changes in `settings_example.py`, most notable new middleware and changed application ordering.
- The keys for JSON based formats no longer include leading dot. The strings are adjusted during the database migration, but external components might need adjustment in case you rely on keys in exports or API.
- The Celery configuration was changed to no longer use `memory` queue. Please adjust your startup scripts and `CELERY_TASK_ROUTES` setting.
- The Weblate domain is now configured in the settings, see `SITE_DOMAIN` (or `WEBLATE_SITE_DOMAIN`). You will have to configure it before running Weblate.
- The username and email fields on user database now should be case insensitive unique. It was mistakenly not enforced with PostgreSQL.

Shihni edhe:

Generic upgrade instructions

Upgrade from 4.2 to 4.3

Please follow *Generic upgrade instructions* in order to perform update.

Notable configuration or dependencies changes:

- There are some changes in quality checks, you might want to include them in case you modified the `CHECK_LIST`.
- The source language attribute was moved from project to a component what is exposed in the API. You will need to update *Klient Weblate* in case you are using it.
- The database migration to 4.3 might take long depending on number of strings you are translating (expect around one hour of migration time per 100,000 source strings).
- There is a change in `INSTALLED_APPS`.
- There is a new setting `SESSION_COOKIE_AGE_AUTHENTICATED` which complements `SESSION_COOKIE_AGE`.
- In case you were using **hub** or **lab** to integrate with GitHub or GitLab, you will need to reconfigure this, see *GITHUB_CREDENTIALS* and *GITLAB_CREDENTIALS*.

Ndryshuar në versionin 4.3.1:

- The Celery configuration was changed to add memory queue. Please adjust your startup scripts and `CELERY_TASK_ROUTES` setting.

Ndryshuar në versionin 4.3.2:

- The `post_update` method of addons now takes extra `skip_push` parameter.

Shihni edhe:

Generic upgrade instructions

Upgrade from 4.3 to 4.4

Please follow *Generic upgrade instructions* in order to perform update.

Notable configuration or dependencies changes:

- There is a change in `INSTALLED_APPS`, `weblate.configuration` has to be added there.
- Django 3.1 is now required.
- In case you are using MySQL or MariaDB, the minimal required versions have increased, see *MySQL dhe MariaDB*.

Ndryshuar në versionin 4.4.1:

- *Monolingual gettext* now uses both `msgid` and `msgctxt` when present. This will change identification of translation strings in such files breaking links to Weblate extended data such as screenshots or review states. Please make sure you commit pending changes in such files prior upgrading and it is recommended to force loading of affected component using *loadpo*.
- Increased minimal required version of translate-toolkit to address several file format issues.

Shihni edhe:

Generic upgrade instructions

Upgrade from 4.4 to 4.5

Please follow *Generic upgrade instructions* in order to perform update.

Notable configuration or dependencies changes:

- The migration might take considerable time if you had big glossaries.
- Glossaries are now stored as regular components.
- The glossary API is removed, use regular translation API to access glossaries.
- There is a change in `INSTALLED_APPS` - `weblate.metrics` should be added.

Ndryshuar në versionin 4.5.1:

- There is a new dependency on the *pyahocorasick* module.

Shihni edhe:

Generic upgrade instructions

Upgrade from 4.5 to 4.6

Please follow *Generic upgrade instructions* in order to perform update.

Notable configuration or dependencies changes:

- There are new file formats, you might want to include them in case you modified the `WEBLATE_FORMATS`.
- API for creating components now automatically uses *URL të brendshme Weblate*, see `POST /api/projects/(string:project)/components/`.
- There is a change in dependencies and `PASSWORD_HASHERS` to prefer Argon2 for passwords hashing.

Shihni edhe:

Generic upgrade instructions

Upgrade from 4.6 to 4.7

Please follow *Generic upgrade instructions* in order to perform update.

Notable configuration or dependencies changes:

- There are several changes in `settings_example.py`, most notable middleware changes (`MIDDLEWARE`), please adjust your settings accordingly.
- The *DeepL* machine translation now has a generic `MT_DEEPL_API_URL` setting to adapt to different subscription models more flexibly. The `MT_DEEPL_API_VERSION` setting is no longer used.
- Django 3.2 is now required.

Shihni edhe:

Generic upgrade instructions

2.3.4 Upgrading from Python 2 to Python 3

Weblate no longer supports Python older than 3.5. In case you are still running on older version, please perform migration to Python 3 first on existing version and upgrade later. See [Upgrading from Python 2 to Python 3](#) in the Weblate 3.11.1 documentation.

2.3.5 Migrating from other databases to PostgreSQL

If you are running Weblate on other database than PostgreSQL, you should consider migrating to PostgreSQL as Weblate performs best with it. The following steps will guide you in migrating your data between the databases. Please remember to stop both web and Celery servers prior to the migration, otherwise you might end up with inconsistent data.

Krijim i një baze të dhënash në PostgreSQL

It is usually a good idea to run Weblate in a separate database, and separate user account:

```
# If PostgreSQL was not installed before, set the main password
sudo -u postgres psql postgres -c "\password postgres"

# Create a database user called "weblate"
sudo -u postgres createuser -D -P weblate

# Create the database "weblate" owned by "weblate"
sudo -u postgres createdb -E UTF8 -O weblate weblate
```

Migrating using Django JSON dumps

The simplest approach for migration is to utilize Django JSON dumps. This works well for smaller installations. On bigger sites you might want to use pgloader instead, see [Migrating to PostgreSQL using pgloader](#).

1. Add PostgreSQL as additional database connection to the `settings.py`:

```
DATABASES = {
    "default": {
        # Database engine
        "ENGINE": "django.db.backends.mysql",
        # Database name
        "NAME": "weblate",
        # Database user
        "USER": "weblate",
        # Database password
        "PASSWORD": "password",
        # Set to empty string for localhost
        "HOST": "database.example.com",
        # Set to empty string for default
        "PORT": "",
        # Additional database options
        "OPTIONS": {
            # In case of using an older MySQL server, which has MyISAM as a
            # default storage
            # 'init_command': 'SET storage_engine=INNODB',
            # Uncomment for MySQL older than 5.7:
            # 'init_command': "SET sql_mode='STRICT_TRANS_TABLES'",
            # If your server supports it, see the Unicode issues above
            "charset": "utf8mb4",
            # Change connection timeout in case you get MySQL gone away error:
            "connect_timeout": 28800,
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    },
  },
  "postgresql": {
    # Database engine
    "ENGINE": "django.db.backends.postgresql",
    # Database name
    "NAME": "weblate",
    # Database user
    "USER": "weblate",
    # Database password
    "PASSWORD": "password",
    # Set to empty string for localhost
    "HOST": "database.example.com",
    # Set to empty string for default
    "PORT": "",
  },
}

```

2. Run migrations and drop any data inserted into the tables:

```

weblate migrate --database=postgresql
weblate sqlflush --database=postgresql | weblate dbshell --database=postgresql

```

3. Dump legacy database and import to PostgreSQL

```

weblate dumpdata --all --output weblate.json
weblate loaddata weblate.json --database=postgresql

```

4. Adjust `DATABASES` to use just PostgreSQL database as default, remove legacy connection.

Weblate should be now ready to run from the PostgreSQL database.

Migrating to PostgreSQL using pgloader

The `pgloader` is a generic migration tool to migrate data to PostgreSQL. You can use it to migrate Weblate database.

1. Adjust your `settings.py` to use PostgreSQL as a database.
2. Migrate the schema in the PostgreSQL database:

```

weblate migrate
weblate sqlflush | weblate dbshell

```

3. Run the `pgloader` to transfer the data. The following script can be used to migrate the database, but you might want to learn more about `pgloader` to understand what it does and tweak it to match your setup:

```

LOAD DATABASE
FROM      mysql://weblate:password@localhost/weblate
INTO      postgresql://weblate:password@localhost/weblate

WITH include no drop, truncate, create no tables, create no indexes, no_
↳foreign keys, disable triggers, reset sequences, data only

ALTER SCHEMA 'weblate' RENAME TO 'public'
;

```

2.3.6 Migrating from Pootle

As Weblate was originally written as replacement from Pootle, it is supported to migrate user accounts from Pootle. You can dump the users from Pootle and import them using *importusers*.

2.4 Kopjeruajtje dhe zhvendosje e Weblate

2.4.1 Kopjeruajtje e automatizuar duke përdorur BorgBackup

Të reja në versionin 3.9.

Weblate has built-in support for creating service backups using [BorgBackup](#). Borg creates space-effective encrypted backups which can be safely stored in the cloud. The backups can be controlled in the management interface from the *Backups* tab.

Ndryshuar në versionin 4.4.1: Both PostgreSQL and MySQL/MariaDB databases are included in the automated backups.

The backups using Borg are incremental and Weblate is configured to keep following backups:

- Daily backups for 14 days back
- Weekly backups for 8 weeks back
- Monthly backups for 6 months back

[Dashboard](#)
[Projects](#)
[Languages](#)
[Checks](#)

[Manage](#) / Backups

Backup process triggered

[Weblate status](#)
[Backups](#)
[Translation memory](#)
[Performance report](#)
[SSH keys](#)
[Alerts](#)
[Repositories](#)
[Users](#)
[Appearance](#)

[Tools](#)
[Billing](#)

Backup service: /tmp/tmptsi6wr4cweblate

Backup service credentials Aug. 21, 2021

Backup repository /tmp/tmptsi6wr4cweblate

Passphrase g615nhIzuZmp\$(8DuCg^d)nBp52hGOVuvWDQKKAZnc5HtD4gGj
 The passphrase is used to encrypt the backups and is necessary to restore them.

SSH key [Download private key](#)
 The private key is needed to access the remote backup repository.

Deleted the oldest backups Aug. 21, 2021

Backup performed Aug. 21, 2021

Repository initialization Aug. 21, 2021

[Turn off](#)
[Perform backup](#)
[Delete](#)

Activate support package ⓘ

The support packages include priority e-mail support, or cloud backups of your Weblate installation.

Activation token
 Please enter the activation token obtained when making the subscription.

[Activate](#)
[Purchase support package](#)

Add backup service ⓘ

Backup repository URL
 Use /path/to/repo for local backups or user@host:/path/to/repo for remote SSH backups.

[Add](#)

Powered by Weblate 4.8
 [About Weblate](#)
[Legal](#)
[Contact](#)
[Documentation](#)
[Donate to Weblate](#)

Kyç fshehtëzimesh Borg

BorgBackup creates encrypted backups and you wouldn't be able to restore them without the passphrase. The passphrase is generated when adding a new backup service and you should copy it and keep it in a secure place.

If you are using *Weblate provisioned backup storage*, please backup your private SSH key too, as it's used to access your backups.

Shihni edhe:

`borg init`

2.4.2 Weblate provisioned backup storage

The easiest way of backing up your Weblate instance is purchasing the [backup service at weblate.org](https://weblate.org/support/#backup). This is how you get it running:

1. Purchase the *Backup service* on <https://weblate.org/support/#backup>.
2. Enter the obtained key in the management interface, see *Integrating support*.
3. Weblate connects to the cloud service and obtains access info for the backups.
4. Turn on the new backup configuration from the *Backups* tab.
5. Backup your Borg credentials to be able to restore the backups, see *Kyç fshehtëzimesh Borg*.

Ndihmëz: The manual step of turning everything on is there for your safety. Without your consent no data is sent to the backup repository obtained through the registration process.

2.4.3 Using custom backup storage

You can also use your own storage for the backups. SSH can be used to store backups in the remote destination, the target server needs to have **BorgBackup** installed.

Shihni edhe:

[General](#) in the Borg documentation

Sistem kartelash vendor

It is recommended to specify the absolute path for the local backup, for example `/path/to/backup`. The directory has to be writable by the user running Weblate (see *Leje sistemi kartelash*). If it doesn't exist, Weblate attempts to create it but needs the appropriate permissions to do so.

Ndihmëz: When running Weblate in Docker, please ensure the backup location is exposed as a volume from the Weblate container. Otherwise the backups will be discarded by Docker upon restarting the container it is in.

One option is to place backups into an existing volume, for example `/app/data/borgbackup`. This is an existing volume in the container.

You can also add a new container for the backups in the Docker Compose file for example by using `/borgbackup`:

```
services:
  weblate:
    volumes:
      - /home/weblate/data:/app/data
      - /home/weblate/borgbackup:/borgbackup
```

The directory where backups will be stored have to be owned by UID 1000, otherwise Weblate won't be able to write the backups there.

Kopjeruajtje të largëta

For creating remote backups, you will have to install [BorgBackup](#) onto another server that's accessible for your Weblate deployment via SSH using the Weblate SSH key:

1. Prepare a server where your backups will be stored.
2. Install the SSH server on it (you will get it by default with most Linux distributions).
3. Install [BorgBackup](#) on that server; most Linux distributions have packages available (see [Installation](#)).
4. Choose an existing user or create a new user that will be used for backing up.
5. Add Weblate SSH key to the user so that Weblate can SSH to the server without a password (see [Kryë SSH Weblate-i](#)).
6. Configure the backup location in Weblate as `user@host:/path/to/backups`.

Ndihmëz: [Weblate provisioned backup storage](#) provides you automated remote backups without any effort.

Shihni edhe:

[Kryë SSH Weblate-i](#)

2.4.4 Rikthim prej BorgBackup

1. Restore access to your backup repository and prepare your backup passphrase.
2. List all the backups on the server using `borg list REPOSITORY`.
3. Restore the desired backup to the current directory using `borg extract REPOSITORY::ARCHIVE`.
4. Restore the database from the SQL dump placed in the backup directory in the Weblate data dir (see [Dumped data for backups](#)).
5. Copy the Weblate configuration (`backups/settings.py`, see [Dumped data for backups](#)) to the correct location, see [Përshtatje formësimi](#).

When using Docker container, the settings file is already included in the container and you should restore the original environment variables. The `environment.yml` file might help you with this (see [Dumped data for backups](#)).

6. Copy the whole restored data dir to the location configured by `DATA_DIR`.

When using Docker container place the data into the data volume, see [Docker container volumes](#).

Please make sure the files have correct ownership and permissions, see [Leje sistemi kartelash](#).

The Borg session might look like this:

```
$ borg list /tmp/xxx
Enter passphrase for key /tmp/xxx:
2019-09-26T14:56:08          Thu, 2019-09-26 14:56:08
→ [de0e0f13643635d5090e9896bdaceb92a023050749ad3f3350e788f1a65576a5]
$ borg extract /tmp/xxx::2019-09-26T14:56:08
Enter passphrase for key /tmp/xxx:
```

Shihni edhe:

[borg list](#), [borg extract](#)

2.4.5 Kopjeruajtje dorazi

Depending on what you want to save, back up the type of data Weblate stores in each respective place.

Ndihmëz: If you are doing the manual backups, you might want to silence Weblate's warning about a lack of backups by adding `weblate.I028` to `SILENCED_SYSTEM_CHECKS` in `settings.py` or `WEBLATE_SILENCED_SYSTEM_CHECKS` for Docker.

```
SILENCED_SYSTEM_CHECKS.append("weblate.I028")
```

Bazë të dhënash

The actual storage location depends on your database setup.

Ndihmëz: The database is the most important storage. Set up regular backups of your database. Without the database, all the translations are gone.

Native database backup

The recommended approach is to save a dump of the database using database-native tools such as `pg_dump` or `mysqldump`. It usually performs better than Django backup, and it restores complete tables with all their data.

You can restore this backup in a newer Weblate release, it will perform all the necessary migrations when running in `migrate`. Please consult *Upgrading Weblate* on more detailed info on how to upgrade between versions.

Django database backup

Alternatively, you can back up your database using Django's `dumpdata` command. That way the backup is database agnostic and can be used in case you want to change the database backend.

Prior to restoring the database you need to be running exactly the same Weblate version the backup was made on. This is necessary as the database structure does change between releases and you would end up corrupting the data in some way. After installing the same version, run all database migrations using `migrate`.

Afterwards some entries will already be created in the database and you will have them in the database backup as well. The recommended approach is to delete such entries manually using the management shell (see *Invoking management commands*):

```
weblate shell
>>> from weblate.auth.models import User
>>> User.objects.get(username='anonymous').delete()
```

Kartela

If you have enough backup space, simply back up the whole `DATA_DIR`. This is a safe bet even if it includes some files you don't want. The following sections describe what you should back up and what you can skip in detail.

Dumped data for backups

Ndryshuar në versionin 4.7: The environment dump was added as `environment.yml` to help in restoring in the Docker environments.

Stored in `DATA_DIR/backups`.

Weblate dumps various data here, and you can include these files for more complete backups. The files are updated daily (requires a running Celery beats server, see [Background tasks using Celery](#)). Currently, this includes:

- Weblate settings as `settings.py` (there is also expanded version in `settings-expanded.py`).
- PostgreSQL database backup as `database.sql`.
- Environment dump as `environment.yml`.

The database backups are saved as plain text by default, but they can also be compressed or entirely skipped using `DATABASE_BACKUP`.

To restore the database backup load it using database tools, for example:

```
psql --file=database.sql weblate
```

Depo nën kontroll versionesh

Stored in `DATA_DIR/vcs`.

The version control repositories contain a copy of your upstream repositories with Weblate changes. If you have [Push on commit](#) enabled for all your translation components, all Weblate changes are included upstream. No need to back up the repositories on the Weblate side as they can be cloned again from the upstream location(s) with no data loss.

Kyçe SSH dhe GPG

Stored in `DATA_DIR/ssh` and `DATA_DIR/home`.

If you are using SSH or GPG keys generated by Weblate, you should back up these locations. Otherwise you will lose the private keys and you will have to regenerate new ones.

Kartela të ngarkuara nga përdoruesi

Stored in `DATA_DIR/media`.

You should back up all user uploaded files (e.g. [Visual context for strings](#)).

Akte Celery

The Celery task queue might contain some info, but is usually not needed for a backup. At most you will lose updates not yet been processed to translation memory. It is recommended to perform the fulltext or repository update upon restoration anyhow, so there is no problem in losing these.

Shihni edhe:

[Background tasks using Celery](#)

Rresht urdhrash për kopjeruajtje dorazi

Using a cron job, you can set up a Bash command to be executed on a daily basis, for example:

```
$ XZ_OPT="-9" tar -Jcf ~/backup/weblate-backup-$(date -u +%Y-%m-%d_%H%M%S).xz_
↪backups vcs ssh home media fonts secret
```

The string between the quotes after `XZ_OPT` allows you to choose your xz options, for instance the amount of memory used for compression; see <https://linux.die.net/man/1/xz>

You can adjust the list of folders and files to your needs. To avoid saving the translation memory (in backups folder), you can use:

```
$ XZ_OPT="-9" tar -Jcf ~/backup/weblate-backup-$(date -u +%Y-%m-%d_%H%M%S).xz_
↪backups/database.sql backups/settings.py vcs ssh home media fonts secret
```

2.4.6 Rikthim kopjeruajtje të bërë dorazi

1. Restore all data you have backed up.
2. Update all repositories using *updategit*.

```
weblate updategit --all
```

2.4.7 Zhvendosje e një instalimi Weblate

Relocate your installation to a different system by following the backing up and restoration instructions above.

Shihni edhe:

Upgrading from Python 2 to Python 3, Migrating from other databases to PostgreSQL

2.5 Mirëfilltësim

2.5.1 Regjistrim përdoruesi

The default setup for Weblate is to use python-social-auth, a form on the website to handle registration of new users. After confirming their e-mail a new user can contribute or authenticate by using one of the third party services.

You can also turn off registration of new users using *REGISTRATION_OPEN*.

The authentication attempts are subject to *Rate limiting*.

2.5.2 Authentication backends

The built-in solution of Django is used for authentication, including various social options to do so. Using it means you can import the user database of other Django-based projects (see *Migrating from Pootle*).

Django can additionally be set up to authenticate against other means too.

Shihni edhe:

Rregullime për mirëfilltësim describes how to configure authentication in the official Docker image.

2.5.3 Mirëfilltësim me rrjete shoqërore

Thanks to [Welcome to Python Social Auth's documentation!](#), Weblate support authentication using many third party services such as GitLab, Ubuntu, Fedora, etc.

Please check their documentation for generic configuration instructions in [Django Framework](#).

Shënim: By default, Weblate relies on third-party authentication services to provide a validated e-mail address. If some of the services you want to use don't support this, please enforce e-mail validation on the Weblate side by configuring `FORCE_EMAIL_VALIDATION` for them. For example:

```
SOCIAL_AUTH_OPENSUSE_FORCE_EMAIL_VALIDATION = True
```

Shihni edhe:

[Pipeline](#)

Enabling individual backends is quite easy, it's just a matter of adding an entry to the `AUTHENTICATION_BACKENDS` setting and possibly adding keys needed for a given authentication method. Please note that some backends do not provide user e-mail by default, you have to request it explicitly, otherwise Weblate will not be able to properly credit contributions users make.

Ndihmëz: Most of the authentication backends require HTTPS. Once HTTPS is enabled in your web server please configure Weblate to report it properly using `ENABLE_HTTPS`, or by `WEBLATE_ENABLE_HTTPS` in the Docker container.

Shihni edhe:

[Python Social Auth backend](#)

Mirëfilltësim OpenID

For OpenID-based services it's usually just a matter of enabling them. The following section enables OpenID authentication for OpenSUSE, Fedora and Ubuntu:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.email.EmailAuth",
    "social_core.backends.suse.OpenSUSEOpenId",
    "social_core.backends.ubuntu.UbuntuOpenId",
    "social_core.backends.fedora.FedoraOpenId",
    "weblate.accounts.auth.WeblateUserBackend",
)
```

Shihni edhe:

[OpenID](#)

Mirëfilltësim GitHub

You need to register an OAuth application on GitHub and then tell Weblate all its secrets:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.github.GithubOAuth2",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Social auth backends setup
SOCIAL_AUTH_GITHUB_KEY = "GitHub Client ID"
SOCIAL_AUTH_GITHUB_SECRET = "GitHub Client Secret"
SOCIAL_AUTH_GITHUB_SCOPE = ["user:email"]
```

The GitHub should be configured to have callback URL as `https://example.com/accounts/complete/github/`.

Shënim: Weblate provided callback URL during the authentication includes configured domain. In case you get errors about URL mismatch, you might want to fix this, see [Set correct site domain](#).

Shihni edhe:

GitHub

Mirëfilltësim Bitbucket

You need to register an application on Bitbucket and then tell Weblate all its secrets:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.bitbucket.BitbucketOAuth",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Social auth backends setup
SOCIAL_AUTH_BITBUCKET_KEY = "Bitbucket Client ID"
SOCIAL_AUTH_BITBUCKET_SECRET = "Bitbucket Client Secret"
SOCIAL_AUTH_BITBUCKET_VERIFIED_EMAILS_ONLY = True
```

Shënim: Weblate provided callback URL during the authentication includes configured domain. In case you get errors about URL mismatch, you might want to fix this, see [Set correct site domain](#).

Shihni edhe:

Bitbucket

Google OAuth 2

To use Google OAuth 2, you need to register an application on <<https://console.developers.google.com/>> and enable the Google+ API.

The redirect URL is `https://WEBLATE_SERVER/accounts/complete/google-oauth2/`

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.google.GoogleOAuth2",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Social auth backends setup
SOCIAL_AUTH_GOOGLE_OAUTH2_KEY = "Client ID"
SOCIAL_AUTH_GOOGLE_OAUTH2_SECRET = "Client secret"
```

Shënim: Weblate provided callback URL during the authentication includes configured domain. In case you get errors about URL mismatch, you might want to fix this, see [Set correct site domain](#).

Shihni edhe:

[Google](#)

Facebook OAuth 2

As per usual with OAuth 2 services, you need to register your application with Facebook. Once this is done, you can set up Weblate to use it:

The redirect URL is `https://WEBLATE_SERVER/accounts/complete/facebook/`

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.facebook.FacebookOAuth2",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Social auth backends setup
SOCIAL_AUTH_FACEBOOK_KEY = "key"
SOCIAL_AUTH_FACEBOOK_SECRET = "secret"
SOCIAL_AUTH_FACEBOOK_SCOPE = ["email", "public_profile"]
```

Shënim: Weblate provided callback URL during the authentication includes configured domain. In case you get errors about URL mismatch, you might want to fix this, see [Set correct site domain](#).

Shihni edhe:

[Facebook](#)

GitLab OAuth 2

For using GitLab OAuth 2, you need to register an application on <<https://gitlab.com/profile/applications>>.

The redirect URL is `https://WEBLATE_SERVER/accounts/complete/gitlab/` and ensure you mark the `read_user` scope.

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.gitlab.GitLabOAuth2",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Social auth backends setup
SOCIAL_AUTH_GITLAB_KEY = "Application ID"
SOCIAL_AUTH_GITLAB_SECRET = "Secret"
SOCIAL_AUTH_GITLAB_SCOPE = ["read_user"]

# If you are using your own GitLab
# SOCIAL_AUTH_GITLAB_API_URL = 'https://gitlab.example.com/'
```

Shënim: Weblate provided callback URL during the authentication includes configured domain. In case you get errors about URL mismatch, you might want to fix this, see *Set correct site domain*.

Shihni edhe:

GitLab

Microsoft Azure Active Directory

Weblate can be configured to use common or specific tenants for authentication.

The redirect URL is `https://WEBLATE_SERVER/accounts/complete/azuread-oauth2/` for common and `https://WEBLATE_SERVER/accounts/complete/azuread-tenant-oauth2/` for tenant-specific authentication.

```
# Azure AD common

# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.azuread.AzureADOAuth2",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# OAuth2 keys
SOCIAL_AUTH_AZUREAD_OAUTH2_KEY = ""
SOCIAL_AUTH_AZUREAD_OAUTH2_SECRET = ""
```

```
# Azure AD Tenant

# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.azuread_tenant.AzureADTenantOAuth2",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# OAuth2 keys
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
SOCIAL_AUTH_AZUREAD_TENANT_OAUTH2_KEY = ""
SOCIAL_AUTH_AZUREAD_TENANT_OAUTH2_SECRET = ""
# Tenant ID
SOCIAL_AUTH_AZUREAD_TENANT_OAUTH2_TENANT_ID = ""
```

Shënim: Weblate provided callback URL during the authentication includes configured domain. In case you get errors about URL mismatch, you might want to fix this, see [Set correct site domain](#).

Shihni edhe:

Microsoft Azure Active Directory

Slack

For using Slack OAuth 2, you need to register an application on <https://api.slack.com/apps>.

The redirect URL is `https://WEBLATE_SERVER/accounts/complete/slack/`.

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.slack.SlackOAuth2",
    "social_core.backends.email.EmailAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Social auth backends setup
SOCIAL_AUTH_SLACK_KEY = ""
SOCIAL_AUTH_SLACK_SECRET = ""
```

Shënim: Weblate provided callback URL during the authentication includes configured domain. In case you get errors about URL mismatch, you might want to fix this, see [Set correct site domain](#).

Shihni edhe:

Slack

Overriding authentication method names and icons

You can override the authentication method display name and icon using settings as `SOCIAL_AUTH_<NAME>_IMAGE` and `SOCIAL_AUTH_<NAME>_TITLE`. For example overriding naming for Auth0 would look like:

```
SOCIAL_AUTH_AUTH0_IMAGE = "custom.svg"
SOCIAL_AUTH_AUTH0_TITLE = "Custom auth"
```

Çaktivizim mirëfilltësimesh me fjalëkalim

E-mail and password authentication can be turned off by removing `social_core.backends.email.EmailAuth` from `AUTHENTICATION_BACKENDS`. Always keep `weblate.accounts.auth.WeblateUserBackend` there, it is needed for core Weblate functionality.

Ndihmëz: You can still use password authentication for the admin interface, for users you manually create there. Just navigate to `/admin/`.

For example authentication using only the openSUSE Open ID provider can be achieved using the following:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.suse.OpenSUSEOpenId",
    "weblate.accounts.auth.WeblateUserBackend",
)
```

2.5.4 Mirëfilltësim me fjalëkalim

The default `settings.py` comes with a reasonable set of `AUTH_PASSWORD_VALIDATORS`:

- Fjalëkalimet s'mund të jetë shumë të ngjashëm me të tjera të dhëna personale tuajat.
- Fjalëkalimet duhet të përmbajnë të paktën 10 shenja.
- Fjalëkalimet s'mund të jenë fjalëkalim i përdorur rëndom.
- Fjalëkalimet s'mund të jenë tërësisht numerikë.
- Fjalëkalimet s'mund të përbëhen nga një shenjë e vetme ose nga vetëm një hapësirë.
- Fjalëkalimet s'mund të përputhen me një fjalëkalim që keni përdorur në të kaluarën.

You can customize this setting to match your password policy.

Additionally you can also install `django-zxcvbn-password` which gives quite realistic estimates of password difficulty and allows rejecting passwords below a certain threshold.

2.5.5 Mirëfilltësim SAML

Të reja në versionin 4.1.1.

Please follow the Python Social Auth instructions for configuration. Notable differences:

- Weblate supports single IDP which has to be called `weblate` in `SOCIAL_AUTH_SAML_ENABLED_IDPS`.
- The SAML XML metadata URL is `/accounts/metadata/saml/`.
- Following settings are automatically filled in: `SOCIAL_AUTH_SAML_SP_ENTITY_ID`, `SOCIAL_AUTH_SAML_TECHNICAL_CONTACT`, `SOCIAL_AUTH_SAML_SUPPORT_CONTACT`

Formësim shembull:

```
# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.email.EmailAuth",
    "social_core.backends.saml.SAMLAuth",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Social auth backends setup
SOCIAL_AUTH_SAML_SP_ENTITY_ID = f"https://{SITE_DOMAIN}/accounts/metadata/saml/"
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

SOCIAL_AUTH_SAML_SP_PUBLIC_CERT = "-----BEGIN CERTIFICATE-----"
SOCIAL_AUTH_SAML_SP_PRIVATE_KEY = "-----BEGIN PRIVATE KEY-----"
SOCIAL_AUTH_SAML_ENABLED_IDPS = {
    "weblate": {
        "entity_id": "https://idp.testshib.org/idp/shibboleth",
        "url": "https://idp.testshib.org/idp/profile/SAML2/Redirect/SSO",
        "x509cert": "MIIEDjCCAvagAwIBAgIBADA ... 8Bbn1+ev0peYzxFyF5sQA==",
        "attr_name": "full_name",
        "attr_username": "username",
        "attr_email": "email",
    }
}
SOCIAL_AUTH_SAML_ORG_INFO = {
    "en-US": {
        "name": "example",
        "displayname": "Example Inc.",
        "url": "http://example.com"
    }
}
SOCIAL_AUTH_SAML_TECHNICAL_CONTACT = {
    "givenName": "Tech Gal",
    "emailAddress": "technical@example.com"
}
SOCIAL_AUTH_SAML_SUPPORT_CONTACT = {
    "givenName": "Support Guy",
    "emailAddress": "support@example.com"
}

```

The default configuration extracts user details from following attributes, configure your IDP to provide them:

Attribute	SAML URI reference
Emër i plotë	urn:oid:2.5.4.3
First name	urn:oid:2.5.4.42
Last name	urn:oid:2.5.4.4
Email	urn:oid:0.9.2342.19200300.100.1.3
Emër përdoruesi	urn:oid:0.9.2342.19200300.100.1.1

Ndihmëz: The example above and the Docker image define an IDP labelled `weblate`. You might need to configure this string as *Relay* in your IDP.

Shihni edhe:

Configuring SAML in Docker, [SAML](#)

2.5.6 Mirëfilltësim LDAP

LDAP authentication can be best achieved using the *django-auth-ldap* package. You can install it via usual means:

```

# Using PyPI
pip install django-auth-ldap>=1.3.0

# Using apt-get
apt-get install python-django-auth-ldap

```

Ndihmëz: This package is included in the Docker container, see *Installing using Docker*.

Shënim: There are some incompatibilities in the Python LDAP 3.1.0 module, which might prevent you from using that version. If you get error `AttributeError: <module> object has no attribute <_trace_level>`, downgrading python-ldap to 3.0.0 might help.

Once you have the package installed, you can hook it into the Django authentication:

```
# Add LDAP backed, keep Django one if you want to be able to sign in
# even without LDAP for admin account
AUTHENTICATION_BACKENDS = (
    "django_auth_ldap.backend.LDAPBackend",
    "weblate.accounts.auth.WeblateUserBackend",
)

# LDAP server address
AUTH_LDAP_SERVER_URI = "ldaps://ldap.example.net"

# DN to use for authentication
AUTH_LDAP_USER_DN_TEMPLATE = "cn=%(user)s,o=Example"
# Depending on your LDAP server, you might use a different DN
# like:
# AUTH_LDAP_USER_DN_TEMPLATE = 'ou=users,dc=example,dc=com'

# List of attributes to import from LDAP upon sign in
# Weblate stores full name of the user in the full_name attribute
AUTH_LDAP_USER_ATTR_MAP = {
    "full_name": "name",
    # Use the following if your LDAP server does not have full name
    # Weblate will merge them later
    # 'first_name': 'givenName',
    # 'last_name': 'sn',
    # Email is required for Weblate (used in VCS commits)
    "email": "mail",
}

# Hide the registration form
REGISTRATION_OPEN = False
```

Shënim: You should remove `'social_core.backends.email.EmailAuth'` from the `AUTHENTICATION_BACKENDS` setting, otherwise users will be able to set their password in Weblate, and authenticate using that. Keeping `'weblate.accounts.auth.WeblateUserBackend'` is still needed in order to make permissions and facilitate anonymous users. It will also allow you to sign in using a local admin account, if you have created it (e.g. by using `createadmin`).

Using bind password

If you can not use direct bind for authentication, you will need to use search, and provide a user to bind for the search. For example:

```
import ldap
from django_auth_ldap.config import LDAPSearch

AUTH_LDAP_BIND_DN = ""
AUTH_LDAP_BIND_PASSWORD = ""
AUTH_LDAP_USER_SEARCH = LDAPSearch(
    "ou=users,dc=example,dc=com", ldap.SCOPE_SUBTREE, "(uid=%(user)s)"
)
```

Integrim me Active Directory

```
import ldap
from django_auth_ldap.config import LDAPSearch, NestedActiveDirectoryGroupType

AUTH_LDAP_BIND_DN = "CN=ldap,CN=Users,DC=example,DC=com"
AUTH_LDAP_BIND_PASSWORD = "password"

# User and group search objects and types
AUTH_LDAP_USER_SEARCH = LDAPSearch(
    "CN=Users,DC=example,DC=com", ldap.SCOPE_SUBTREE, "(sAMAccountName=%(user)s)"
)

# Make selected group a superuser in Weblate
AUTH_LDAP_USER_FLAGS_BY_GROUP = {
    # is_superuser means user has all permissions
    "is_superuser": "CN=weblate_AdminUsers,OU=Groups,DC=example,DC=com",
}

# Map groups from AD to Weblate
AUTH_LDAP_GROUP_SEARCH = LDAPSearch(
    "OU=Groups,DC=example,DC=com", ldap.SCOPE_SUBTREE, "(objectClass=group)"
)
AUTH_LDAP_GROUP_TYPE = NestedActiveDirectoryGroupType()
AUTH_LDAP_FIND_GROUP_PERMS = True

# Optionally enable group mirroring from LDAP to Weblate
# AUTH_LDAP_MIRROR_GROUPS = True
```

Shihni edhe:

Django Authentication Using LDAP, Authentication

2.5.7 Mirëfilltësim CAS

CAS authentication can be achieved using a package such as *django-cas-ng*.

Step one is disclosing the e-mail field of the user via CAS. This has to be configured on the CAS server itself, and requires you run at least CAS v2 since CAS v1 doesn't support attributes at all.

Step two is updating Weblate to use your CAS server and attributes.

To install *django-cas-ng*:

```
pip install django-cas-ng
```

Once you have the package installed you can hook it up to the Django authentication system by modifying the settings.py file:

```
# Add CAS backed, keep the Django one if you want to be able to sign in
# even without LDAP for the admin account
AUTHENTICATION_BACKENDS = (
    "django_cas_ng.backends.CASBackend",
    "weblate.accounts.auth.WeblateUserBackend",
)

# CAS server address
CAS_SERVER_URL = "https://cas.example.net/cas/"

# Add django_cas_ng somewhere in the list of INSTALLED_APPS
INSTALLED_APPS = (... , "django_cas_ng")
```

Finally, a signal can be used to map the e-mail field to the user object. For this to work you have to import the signal from the *django-cas-ng* package and connect your code with this signal. Doing this in settings file can cause problems, therefore it's suggested to put it:

- In your app config's `django.apps.AppConfig.ready()` method
- In the project's `urls.py` file (when no models exist)

```
from django_cas_ng.signals import cas_user_authenticated
from django.dispatch import receiver

@receiver(cas_user_authenticated)
def update_user_email_address(sender, user=None, attributes=None, **kwargs):
    # If your CAS server does not always include the email attribute
    # you can wrap the next two lines of code in a try/catch block.
    user.email = attributes["email"]
    user.save()
```

Shihni edhe:

Django CAS NG

2.5.8 Configuring third party Django authentication

Generally any Django authentication plugin should work with Weblate. Just follow the instructions for the plugin, just remember to keep the Weblate user backend installed.

Shihni edhe:

Mirëfilltësim LDAP, Mirëfilltësim CAS

Typically the installation will consist of adding an authentication backend to `AUTHENTICATION_BACKENDS` and installing an authentication app (if there is any) into `INSTALLED_APPS`:

```
AUTHENTICATION_BACKENDS = (
    # Add authentication backend here
    "weblate.accounts.auth.WeblateUserBackend",
)

INSTALLED_APPS += (
    # Install authentication app here
)
```

2.6 Kontroll hyrjesh

Weblate comes with a fine-grained privilege system to assign user permissions for the whole instance, or in a limited scope.

Ndryshuar në versionin 3.0: Before Weblate 3.0, the privilege system was based on Django privilege system only, but is specifically built for Weblate now. If using anything older, please consult the documentation for the specific version you are using.

2.6.1 Simple access control

If you are not administrating the whole Weblate installation and just have access to manage certain projects (like on [Hosted Weblate](#)), your access control management options are limited to following settings. If you don't need any complex setup, those are sufficient for you.

Kontroll hyrjesh te projekti

Shënim: This feature is unavailable for the projects running Libre plan on Hosted Weblate.

You can limit user's access to individual projects by selecting a different *Access control* setting. Available options are:


Publik Publicly visible, translatable for all logged-in users.

I mbrojtur Publicly visible, but translatable only for selected users.

Privat Visible and translatable only for selected users.

Vetjake *User management* features will be disabled; by default all users are forbidden to performed any actions on the project. You will have to set up all the permissions using *Custom access control*.

Access control can be changed in the *Access* tab of the configuration (*Manage* ↓ *Settings*) of each respective project.



The default value can be changed by `DEFAULT_ACCESS_CONTROL`.

Shënim: Even for *Private* projects, some info about your project will be exposed: statistics and language summary for the whole instance will include counts for all projects despite the access control setting. Your project name and other information can't be revealed through this.

Shënim: The actual set of permissions available for users by default in *Public*, *Protected*, and *Private* projects can be redefined by Weblate instance administrator using *custom settings*.

Sinjalizim: By turning on *Custom* access control, Weblate will remove all *special groups* it has created for a selected project. If you are doing this without admin permission for the whole Weblate instance, you will instantly lose your access to manage the project.

Shihni edhe:

Kontroll hyrjesh

Managing per-project access control

Users with the *Manage project access* privilege (see *Listë privilegjesh*) can manage users in projects with non-*Custom* access control. They can assign users to one of the following groups.

For *Public*, *Protected* and *Private* projects:

Administrim Includes all permissions available for the project.

Review (only if *review workflow* is turned on) Can approve translations during review.

For *Protected* and *Private* projects only:

Përktheni Can translate the project and upload translations made offline.

Burime Can edit source strings (if allowed in the *project settings*) and source string info.

Gjuhë Can manage translated languages (add or remove translations).

Fjalorth Can manage glossary (add or remove entries, also upload).

Kujtesë Can manage translation memory.

Foto ekrani Can manage screenshots (add or remove them, and associate them to source strings).

VCS Can manage VCS and access the exported repository.

Faturim Can access billing info and settings (see *Faturim*).

Unfortunately, it's not possible to change this predefined set of groups for now. Also this way it's not possible to give just some additional permissions to all users.

Shënim: For non-*Custom* access control an instance of each group described above is actually defined for each project. The actual name of those groups will be `Project@Group`, also displayed in the Django admin interface this way. Although they can't be edited from Weblate user-interface.

Users

Username	Full name	E-mail	Last login	Administration	Billing	Glossary	Languages	Memory	Screenshots	Sources	Translate	VCS
testuser	Weblate Test	weblate@example.org	31 seconds ago	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Once all its permissions are removed, the user will be removed from the project.

Add a user

User to add

Please type in an existing Weblate account name or e-mail address.

Add

Block user

User to block

Please type in an existing Weblate account name or e-mail address.

Block duration

Block user until I unblock them

Block

Invite new user

E-mail

Username

Username may only contain letters, numbers or the following characters: @ . + - _

Full name

Invite

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

These features are available on the *Access control* page, which can be accessed from the project's menu *Manage* ↓ *Users*.

New user invitation

Also, besides adding an existing user to the project, it is possible to invite new ones. Any new user will be created immediately, but the account will remain inactive until signing in with a link in the invitation sent via an e-mail. It is not required to have any site-wide privileges in order to do so, access management permission on the project's scope (e.g. a membership in the *Administration* group) would be sufficient.

Ndihmëz: If the invited user missed the validity of the invitation, they can set their password using invited e-mail address in the password reset form as the account is created already.

Të reja në versionin 3.11: It is possible to resend the e-mail for user invitations (invalidating any previously sent invitation).

The same kind of invitations are available site-wide from the *management interface* on the *Users* tab.

Blocking users

Të reja në versionin 4.7.

In case some users behave badly in your project, you have an option to block them from contributing. The blocked user still will be able to see the project if he has permissions for that, but he won't be able to contribute.

Per-project permission management

You can set your projects to *Protected* or *Private*, and [manage users](#) per-project in the Weblate user interface.

By default this prevents Weblate from granting access provided by *Users* and *Viewers default groups* due to these groups' own configuration. This doesn't prevent you from granting permissions to those projects site-wide by altering default groups, creating a new one, or creating additional custom settings for individual component as described in [Custom access control](#) below.

One of the main benefits of managing permissions through the Weblate user interface is that you can delegate it to other users without giving them the superuser privilege. In order to do so, add them to the *Administration* group of the project.

2.6.2 Custom access control

Shënim: This feature is unavailable for the projects running Libre plan on Hosted Weblate.

The permission system is based on groups and roles, where roles define a set of permissions, and groups link them to users and translations, see [Users, roles, groups, and permissions](#) for more details.

The most powerful features of the Weblate's access control system for now are available only through the [Django admin interface](#). You can use it to manage permissions of any project. You don't necessarily have to switch it to [Custom access control](#) to utilize it. However you must have superuser privileges in order to use it.

If you are not interested in details of implementation, and just want to create a simple-enough configuration based on the defaults, or don't have a site-wide access to the whole Weblate installation (like on [Hosted Weblate](#)), please refer to the [Simple access control](#) section.

Ujdisje të rëndomta

This section contains an overview of some common configurations you may be interested in.

Site-wide permission management

To manage permissions for a whole instance at once, add users to appropriate [default groups](#):

- *Users* (this is done by default by the [automatic group assignment](#)).
- *Reviewers* (if you are using [review workflow](#) with dedicated reviewers).
- *Managers* (if you want to delegate most of the management operations to somebody else).

You should keep all projects configured as *Public* (see [Kontroll hyrjesh te projekti](#)), otherwise the site-wide permissions provided by membership in the *Users* and *Reviewers* groups won't have any effect.

You may also grant some additional permissions of your choice to the default groups. For example, you may want to give a permission to manage screenshots to all the *Users*.

You can define some new custom groups as well. If you want to keep managing your permissions site-wide for these groups, choose an appropriate value for the *Project selection* (e.g. *All projects* or *All public projects*).

Custom permissions for languages, components or projects

You can create your own dedicated groups to manage permissions for distinct objects such as languages, components, and projects. Although these groups can only grant additional privileges, you can't revoke any permission granted by site-wide or per-project groups by adding another custom group.

Example:

If you want (for whatever reason) to allow translation to a specific language (lets say *Czech*) only to a closed set of reliable translators while keeping translations to other languages public, you will have to:

1. Remove the permission to translate *Czech* from all the users. In the default configuration this can be done by altering the *Users default group*.

Tabela 1: Group *Users*

Përzgjedhje gjuhe	<i>As defined</i>
Gjuhë	All but <i>Czech</i>

2. Add a dedicated group for *Czech* translators.

Tabela 2: Group *Czech translators*

Role	<i>Power users</i>
Përzgjedhje projekti	<i>All public projects</i>
Përzgjedhje gjuhe	<i>As defined</i>
Gjuhë	<i>Czech</i>

3. Add users you wish to give the permissions to into this group.

As you can see, permissions management this way is powerful, but can be quite a tedious job. You can't delegate it to another user, unless granting superuser permissions.

Users, roles, groups, and permissions


The authentication models consist of several objects:

Leje Individual permission defined by Weblate. Permissions cannot be assigned to users. This can only be done through assignment of roles.

Rol A role defines a set of permissions. This allows reuse of these sets in several places, making the administration easier.

Përdorues User can belong to several groups.

Grup Group connect roles, users, and authentication objects (projects, languages, and component lists).



Shënim: A group can have no roles assigned to it, in that case access to browse the project by anyone is assumed (see below).

Access for browse to a project

A user has to be a member of a group linked to the project, or any component inside that project. Having membership is enough, no specific permissions are needed to browse the project (this is used in the default *Viewers* group, see *Listë grupesh*).

Access for browse to a component

A user can access unrestricted components once able to access the components' project (and will have all the permissions the user was granted for the project). With *Restricted access* turned on, access to the component requires explicit permissions for the component (or a component list the component is in).

Scope of groups

The scope of the permission assigned by the roles in the groups are applied by the following rules:

- If the group specifies any *Component list*, all the permissions given to members of that group are granted for all the components in the component lists attached to the group, and an access with no additional permissions is granted for all the projects these components are in. *Components* and *Projects* are ignored.
- If the group specifies any *Components*, all the permissions given to the members of that group are granted for all the components attached to the group, and an access with no additional permissions is granted for all the projects these components are in. *Projects* are ignored.
- Otherwise, if the group specifies any *Projects*, either by directly listing them or by having *Projects selection* set to a value like *All public projects*, all those permissions are applied to all the projects, which effectively grants the same permissions to access all the projects *unrestricted components*.
- The restrictions imposed by a group's *Languages* are applied separately, when it's verified if a user has an access to perform certain actions. Namely, it's applied only to actions directly related to the translation process itself like reviewing, saving translations, adding suggestions, etc.

Ndihmëz: Use *Language selection* or *Project selection* to automate inclusion of all languages or projects.

Example:

Let's say there is a project `foo` with the components: `foo/bar` and `foo/baz` and the following group:

Tabela 3: Group *Spanish Admin-Reviewers*

Role	<i>Review Strings, Manage repository</i>
Përbërës	<code>foo/bar</code>
Gjuhë	<i>Spanish</i>

Members of that group will have following permissions (assuming the default role settings):

- General (browsing) access to the whole project `foo` including both components in it: `foo/bar` and `foo/baz`.
- Review strings in `foo/bar` Spanish translation (not elsewhere).
- Manage VCS for the whole `foo/bar` repository e.g. commit pending changes made by translators for all languages.

Caktim i automatizuar grupesh

On the bottom of the *Group* editing page in the *Django admin interface*, you can specify *Automatic group assignments*, which is a list of regular expressions used to automatically assign newly created users to a group based on their e-mail addresses. This assignment only happens upon account creation.

The most common use-case for the feature is to assign all new users to some default group. In order to do so, you will probably want to keep the default value (`^.*$`) in the regular expression field. Another use-case for this option might be to give some additional privileges to employees of your company by default. Assuming all of them use corporate e-mail addresses on your domain, this can be accomplished with an expression like `^.*@mycompany.com`.

Shënim: Automatic group assignment to *Users* and *Viewers* is always recreated when upgrading from one Weblate version to another. If you want to turn it off, set the regular expression to `^$` (which won't match anything).

Shënim: As for now, there is no way to bulk-add already existing users to some group via the user interface. For that, you may resort to using the *REST API*.

Role dhe grupe parazgjedhje

After installation, a default set of groups is created (see *Listë grupesh*).

These roles and groups are created upon installation. The built-in roles are always kept up to date by the database migration when upgrading. You can't actually change them, please define a new role if you want to define your own set of permissions.

Listë privilegjesh

Faturim (shihni *Faturim*) View billing info [*Administration, Billing*]

Ndryshime Download changes [*Administration*]

Komente Post comment [*Administration, Edit source, Power user, Review strings, Translate*]

Të fshijë komentin [*Administrim*]

Përbërës Të përpunojë rregullime përbërësi [*Administrim*]

Lock component, preventing translations [*Administration*]

Fjalorth Add glossary entry [*Administration, Manage glossary, Power user*]

Edit glossary entry [*Administration, Manage glossary, Power user*]

Delete glossary entry [*Administration, Manage glossary, Power user*]

Upload glossary entries [*Administration, Manage glossary, Power user*]

Sugjerime të automatizuara Use automatic suggestions [*Administration, Edit source, Power user, Review strings, Translate*]

Kujtesë përkthimesh Edit translation memory [*Administration, Manage translation memory*]

Delete translation memory [*Administration, Manage translation memory*]

Projekte Të përpunojë rregullime projekti [*Administrim*]

Të administrojë hyrje te projekti [*Administrim*]

Raportime Të shkarkojë raporte [*Administrim*]

Foto ekрани Add screenshot [*Administration, Manage screenshots*]

Edit screenshot [*Administration, Manage screenshots*]

Delete screenshot [*Administration, Manage screenshots*]

Vargjet e burimit Edit additional string info [*Administration, Edit source*]

Vargje Add new string [*Administration*]

Remove a string [*Administration*]

Dismiss failing check [*Administration, Edit source, Power user, Review strings, Translate*]

Edit strings [*Administration, Edit source, Power user, Review strings, Translate*]

Review strings [*Administration, Review strings*]

Edit string when suggestions are enforced [*Administration, Review strings*]

Edit source strings [*Administration, Edit source, Power user*]

Sugjerime Accept suggestion [*Administration, Edit source, Power user, Review strings, Translate*]

Add suggestion [*Administration, Edit source, Add suggestion, Power user, Review strings, Translate*]

Delete suggestion [*Administration, Power user*]

Vote on suggestion [*Administration, Edit source, Power user, Review strings, Translate*]

Përkthime Add language for translation [*Administration, Power user, Manage languages*]

Perform automatic translation [*Administration, Manage languages*]

Delete existing translation [*Administration, Manage languages*]

Add several languages for translation [*Administration, Manage languages*]

Ngarkime Define author of uploaded translation [*Administration*]

Overwrite existing strings with upload [*Administration, Edit source, Power user, Review strings, Translate*]

Upload translations [*Administration, Edit source, Power user, Review strings, Translate*]

VCS Access the internal repository [*Administration, Access repository, Power user, Manage repository*]

Commit changes to the internal repository [*Administration, Manage repository*]

Push change from the internal repository [*Administration, Manage repository*]

Reset changes in the internal repository [*Administration, Manage repository*]

View upstream repository location [*Administration, Access repository, Power user, Manage repository*]

Update the internal repository [*Administration, Manage repository*]

Privilegje në mbarë sajtin Të përdorë ndërfaqe administrimi

Të shtojë projekte të rinj

Të shtojë përkufizime gjuhësh

Të administrojë përkufizime gjuhësh

Të administrojë grupe

Të administrojë përdorues

Të administrojë role

Të administrojë lajmërimet

Të administrojë kujtesë përkthimesh

Të administrojë listë përbërësish

Shënim: Site-wide privileges are not granted to any default role. These are powerful and quite close to superuser status. Most of them affect all projects in your Weblate installation.

Listë grupesh

The following groups are created upon installation (or after executing *setupgroups*) and you are free to modify them. The migration will, however, re-create them if you delete or rename them.

Vizitorë Defines permissions for non-authenticated users.

This group only contains anonymous users (see *ANONYMOUS_USER_NAME*).

You can remove roles from this group to limit permissions for non-authenticated users.

Default roles: *Add suggestion, Access repository*

Parës This role ensures visibility of public projects for all users. By default, all users are members of this group.

By default, *automatic group assignment* makes all new accounts members of this group when they join.

Role parazgjedhje: asnjë

Përdorues Grup parazgjedhje për krejt përdoruesit.

By default, *automatic group assignment* makes all new accounts members of this group when they join.

Role parazgjedhje: *Përdorues i regjur*

Shqyrtues Group for reviewers (see *Rrjedha pune përkthimi*).

Role parazgjedhje: *Të shqyrtojë vargje*

Managers Grup për përgjegjësit.

Role parazgjedhje: *Administrim*

Sinjalizim: Never remove the predefined Weblate groups and users as this can lead to unexpected problems! If you have no use for them, you can removing all their privileges instead.

2.6.3 Additional access restrictions

If you want to use your Weblate installation in a less public manner, i.e. allow new users on an invitational basis only, it can be done by configuring Weblate in such a way that only known users have an access to it. In order to do so, you can set `REGISTRATION_OPEN` to `False` to prevent registrations of any new users, and set `REQUIRE_LOGIN` to `/*` to require logging-in to access all the site pages. This is basically the way to lock your Weblate installation.

Ndihmëz: You can use built-in *invitations* to add new users.

2.7 Projekte përkthimi

2.7.1 Translation organization

Weblate organizes translatable VCS content of project/components into a tree-like structure.

- The bottom level object is *Project configuration*, which should hold all translations belonging together (for example translation of an application in several versions and/or accompanying documentation).
- On the level above, *Component configuration*, which is actually the component to translate, you define the VCS repository to use, and the mask of files to translate.
- Above *Component configuration* there are individual translations, handled automatically by Weblate as translation files (which match *File mask* defined in *Component configuration*) appear in the VCS repository.

Weblate supports a wide range of translation formats (both bilingual and monolingual ones) supported by Translate Toolkit, see *Formate të mbuluar kartelash*.

Shënim: You can share cloned VCS repositories using *URL të brendshme Weblate*. Using this feature is highly recommended when you have many components sharing the same VCS. It improves performance and decreases required disk space.

2.7.2 Adding translation projects and components

Ndryshuar në versionin 3.2: An interface for adding projects and components is included, and you no longer have to use *Ndërfaqe përgjegjësi Django*.

Ndryshuar në versionin 3.4: The process of adding components is now multi staged, with automated discovery of most parameters.

Based on your permissions, new translation projects and components can be created. It is always permitted for users with the *Add new projects* permission, and if your instance uses billing (e.g. like <https://hosted.weblate.org/> see *Faturim*), you can also create those based on your plans allowance from the user account that manages billing.

You can view your current billing plan on a separate page:

[Dashboard](#)
[Projects](#)
[Languages](#)
[Checks](#)

[Your profile](#) / [Billing](#)

Billing plan	
Current plan	Basic plan (Active)
Monthly price	19 EUR
Yearly price	199 EUR
Strings limit	Used 0 <div></div>
Languages limit	Used 0 <div></div>
Last invoice	2021-08-20 - 2021-08-22
Projects limit	Used 0 of 1 <div></div>
Projects	No projects currently assigned! Add new translation project
Terminate billing plan	

Invoices		
Invoice period	Invoice amount	Download invoice
08/20/2021 - 08/22/2021	19.0 EUR	Not available

Powered by Weblate 4.8
 [About Weblate](#)
[Legal](#)
[Contact](#)
[Documentation](#)
[Donate to Weblate](#)

The project creation can be initiated from there, or using the menu in the navigation bar, filling in basic info about the translation project to complete addition of it:

[Dashboard](#)
[Projects](#)
[Languages](#)
[Checks](#)

[Create project](#)

Add new translation project

Project name

WeblateOrg

Display name

URL slug

weblateorg

Name used in URLs and filenames.

Project website

https://weblate.org/

Main website of translated project.

Translation instructions

https://weblate.org/contribute/

You can use Markdown and mention users by @username.


Billing

Weblate Test (Basic plan)

Save

Powered by Weblate 4.8
 [About Weblate](#)
[Legal](#)
[Contact](#)
[Documentation](#)
[Donate to Weblate](#)

After creating the project, you are taken directly to the project page:



Creating a new translation component can be initiated via a single click there. The process of creating a component is multi-staged and automatically detects most translation parameters. There are several approaches to creating component:

Prej kontrolli versionesh Creates component from remote version control repository.

Prej përbërësi ekzistues Creates additional component to existing one by choosing different files.

Degë shitesë Creates additional component to existing one, just for different branch.

Ngarkoni kartela përkthimesh Upload translation files to Weblate in case you do not have version control or do not want to integrate it with Weblate. You can later update the content using the web interface or [Weblate's REST API](#).

Përktheni dokument Upload single document or translation file and translate that.

Nisjani nga hiçi Create blank translation project and add strings manually.

Once you have existing translation components, you can also easily add new ones for additional files or branches using same repository.

First you need to fill in name and repository location:

Weblate
 Dashboard Projects Languages Checks

Create component

From version control
 Upload translations files
 Translate document
 Start from scratch

Create a new translation component from remote version control system repository.

Component name ⓘ

Display name

URL slug ⓘ

Name used in URLs and filenames.

☐ Use as a glossary ⓘ

Project ⓘ

Source language ⓘ

Language used for source strings in all components

Version control system ⓘ

Version control system to use to access your repository with translations.

Source code repository ⓘ

URL of a repository, use weblate://project/component for sharing with other component.

Repository branch ⓘ

Repository branch to translate

Continue

Powered by Weblate 4.8
 About Weblate
 Legal
 Contact
 Documentation
 Donate to Weblate

On the next page, you are presented with a list of discovered translatable resources:

Weblate
 Dashboard Projects Languages Checks

Create component

Add new translation component ⓘ

Choose translation files to import ⓘ

- ☐ Specify configuration manually
- ☐ File format **Android String Resource**, Filemask **app/src/main/res/values-*/strings.xml**
- ☐ File format **gettext PO file**, Filemask **weblate/langdata/locale/*/LC_MESSAGES/django.po**
- ☐ File format **gettext PO file**, Filemask **weblate/locale/*/LC_MESSAGES/django.po**
- ☐ File format **gettext PO file**, Filemask **weblate/locale/*/LC_MESSAGES/djangojs.po**

Continue

Powered by Weblate 4.8
 About Weblate
 Legal
 Contact
 Documentation
 Donate to Weblate

As a last step, you review the translation component info and fill in optional details:

Web

late

Dashboard

Projects ▾

Languages ▾

Checks ▾

+

▾

▾

...

Create component

Add new translation component

Project ⓘ

WebplateOrg ▾

Component name ⓘ

Language names

Display name

URL slug ⓘ

language-names

Name used in URLs and filenames.

Version control system ⓘ

Git ▾

Version control system to use to access your repository containing translations. You can also choose additional integration with third party providers to submit merge requests.

Source code repository ⓘ

https://github.com/WebplateOrg/demo.git

URL of a repository, use weblate://project/component to share it with other component.

Repository branch ⓘ

Repository branch to translate

Repository push URL ⓘ

URL of a push repository, pushing is turned off if empty.

Push branch ⓘ

Branch for pushing changes, leave empty to use repository branch

Repository browser ⓘ

https://github.com/WebplateOrg/demo/blob/{{branch}}/{{filename}}#L{{line}}

Link to repository browser, use {{branch}} for branch, {{filename}} and {{line}} as filename and line placeholders. You might want to strip leading directory by using {{filename|parentdir}}.

File format ⓘ

gettext PO file ▾

Filemask ⓘ

weblate/langdata/locale/*/LC_MESSAGES/django.po

Path of files to translate relative to repository root, use * instead of language code, for example: po/*.po or locale/*/LC_MESSAGES/django.po.

Monolingual base language file ⓘ

Filename of translation base file, containing all strings and their source; it is recommended for monolingual translation formats.

☒ Edit base file ⓘ

Whether users will be able to edit the base file for monolingual translations.

Intermediate language file ⓘ

Filename of intermediate translation file. In most cases this is a translation file provided by developers and is used when creating actual source strings.

Template for new translations ⓘ

weblate/langdata/locale/django.pot

Filename of file used for creating new translations. For gettext choose .pot file.

Translation license ⓘ

GNU General Public License v3.0 or later ▾

Adding new translation ⓘ

Create new language file ▾

How to handle requests for creating new translations.

Language code style ⓘ

Default based on the file format ▾

Customize language code used to generate the filename for translations created by Weblate.

Language filter ⓘ

^(cs|he|hu)\$

Regular expression used to filter translation files when scanning for filemask.

Source language ⓘ

English ▾

Language used for source strings in all components

☐ Use as a glossary ⓘ

You will be able to edit more options in the component settings after creating it.

Save

Shihni edhe:

Ndërfaqe përgjegjësi Django, Project configuration, Component configuration

2.7.3 Project configuration

Create a translation project and then add a new component for translation in it. The project is like a shelf, in which real translations are stacked. All components in the same project share suggestions and their dictionary; the translations are also automatically propagated through all components in a single project (unless turned off in the component configuration), see *Kujtesë Përkthimesh*.

Shihni edhe:

/devel/integration

These basic attributes set up and inform translators of a project:

Emër projekti

Verbose project name, used to display the project name.

Identifikues URL-je

Project name suitable for URLs.

Sajt projekti

URL where translators can find more info about the project.

This is a required parameter unless turned off by *WEBSITE_REQUIRED*.

Udhëzime përkthimi

URL to more site with more detailed instructions for translators.

Caktoni krye «Language-Team»

Whether Weblate should manage the Language-Team header (this is a *GNU gettext* only feature right now).

Përdor kujtesë përkthimesh të përbashkët

Whether to use shared translation memory, see *Kujtesë përkthimesh e përbashkët* for more details.

Default value is determined by *DEFAULT_SHARED_TM*.

Kontribuoni te kujtesë përkthimesh të përbashkët

Whether to contribute to shared translation memory, see *Kujtesë përkthimesh e përbashkët* for more details.

Default value is determined by `DEFAULT_SHARED_TM`.

Kontroll hyrjesh

Configure per project access control, see *Kontroll hyrjesh te projekti* for more details.

Default value can be changed by `DEFAULT_ACCESS_CONTROL`.

Aktivizoni shqyrtime

Enable review workflow for translations, see *Shqyrtues enkas*.

Aktivizo shqyrtime burimi

Enable review workflow for source strings, see *Shqyrtim vargjes burim*.

Shihni edhe:

report-source, *Komente*

Aktivizoni hook-e

Whether unauthenticated *Hook-e njoftimesh* are to be used for this repository.

Shihni edhe:

Kartelë gjuhe ndërmjetëse, *Quality gateway for the source strings*, *Formate dygjuhësh dhe njëgjuhësh*, *Language definitions*

Aliase gjuhe

Define language codes mapping when importing translations into Weblate. Use this when language codes are inconsistent in your repositories and you want to get a consistent view in Weblate or in case you want to use non-standard naming of your translation files.

The typical use case might be mapping American English to English: `en_US:en`

Multiple mappings to be separated by comma: `en_GB:en,en_US:en`

Using non standard code: `ia_FOO:ia`

Ndihmëz: The language codes are mapped when matching the translation files and the matches are case sensitive, so make sure you use the source language codes in same form as used in the filenames.

Shihni edhe:

Parsing language codes

2.7.4 Component configuration

A component is a grouping of something for translation. You enter a VCS repository location and file mask for which files you want translated, and Weblate automatically fetches from this VCS, and finds all matching translatable files.

Shihni edhe:

/devel/integration

You can find some examples of typical configurations in the *Formate të mbuluar kartelash*.

Shënim: It is recommended to keep translation components to a reasonable size - split the translation by anything that makes sense in your case (individual apps or addons, book chapters or websites).

Weblate easily handles translations with 10000s of strings, but it is harder to split work and coordinate among translators with such large translation components.

Should the language definition for a translation be missing, an empty definition is created and named as «cs_CZ (generated)». You should adjust the definition and report this back to the Weblate authors, so that the missing languages can be included in next release.

The component contains all important parameters for working with the VCS, and for getting translations out of it:

Emër përbërësi

Verbose component name, used to display the component name.

Component slug

Component name suitable for URLs.

Component project

Project configuration where the component belongs.

Sistem kontrolli versionesh

VCS to use, see *Integrim kontrolli versioni* for details.

Shihni edhe:

Pushing changes from Weblate

Depo kodi burim

VCS repository used to pull changes.

Shihni edhe:

See *Hyrje në depo* for more details on specifying URLs.

Ndihmëz: This can either be a real VCS URL or `weblate://project/component` indicating that the repository should be shared with another component. See *URL të brendshme Weblate* for more details.

URL push-i për depon

Repository URL used for pushing. This setting is used only for *Git* and *Mercurial* and push support is turned off for these when this is empty.

Shihni edhe:

See *Hyrje në depo* for more details on how to specify a repository URL and *Pushing changes from Weblate* for more details on pushing changes from Weblate.

Shfletues depoje

URL of repository browser used to display source files (location of used messages). When empty, no such links will be generated. You can use *Template markup*.

For example on GitHub, use something like: `https://github.com/WeblateOrg/hello/blob/{{branch}}/{{filename}}#L{{line}}`

In case your paths are relative to different folder (path contains `..`), you might want to strip leading directory by `parentdir` filter (see *Template markup*): `https://github.com/WeblateOrg/hello/blob/{{branch}}/{{filename|parentdir}}#L{{line}}`

URL depoje të eksportuar

URL where changes made by Weblate are exported. This is important when *Përkthim në vazhdimësi* is not used, or when there is a need to manually merge changes. You can use *Git exporter* to automate this for Git repositories.

Degë depoje

Which branch to checkout from the VCS, and where to look for translations.

Degë push

Branch for pushing changes, leave empty to use *Degë depoje*.

Shënim: This is currently only supported for Git, GitLab and GitHub, it is ignored for other VCS integrations.

Shihni edhe:

Pushing changes from Weblate

File mask

Mask of files to translate, including path. It should include one «*» replacing language code (see *Language definitions* for info on how this is processed). In case your repository contains more than one translation file (e.g. more gettext domains), you need to create a component for each of them.

For example `po/*.po` or `locale/*/LC_MESSAGES/django.po`.

In case your filename contains special characters such as `[]`, these need to be escaped as `[]` or `[]`.

Shihni edhe:

Formate dygjuhësh dhe njëgjuhësh, What does mean «There are more files for the single language (en)»?

Kartelë njëgjuhëshe gjuhe bazë

Base file containing string definitions for *Përbërës njëgjuhësh*.

Shihni edhe:

Formate dygjuhësh dhe njëgjuhësh, *What does mean «There are more files for the single language (en)»?*

Përpunoni kartelën bazë

Whether to allow editing the base file for *Përbërës njëgjuhësh*.

Kartelë gjuhe ndërmjetëse

Intermediate language file for *Përbërës njëgjuhësh*. In most cases this is a translation file provided by developers and is used when creating actual source strings.

When set, the source strings are based on this file, but all other languages are based on *Kartelë njëgjuhëshe gjuhe bazë*. In case the string is not translated into the source language, translating to other languages is prohibited. This provides *Quality gateway for the source strings*.

Shihni edhe:

Quality gateway for the source strings, *Formate dygjuhësh dhe njëgjuhësh*, *What does mean «There are more files for the single language (en)»?*

Gjedhe për përkthime të reja

Base file used to generate new translations, e.g. .pot file with gettext.

Ndihmëz: In many monolingual formats Weblate starts with blank file by default. Use this in case you want to have all strings present with empty value when creating new translation.

Shihni edhe:

adding-translation, *Shtim përkthimesh të reja*, *Shtim përkthimi të ri*, *Formate dygjuhësh dhe njëgjuhësh*, *What does mean «There are more files for the single language (en)»?*

Format kartelash

Translation file format, see also *Formate të mbuluar kartelash*.

Adresë njoftimi të metash në vargje burim

Email address used for reporting upstream bugs. This address will also receive notification about any source string comments made in Weblate.

Lejo përhapje përkthimesh

You can turn off propagation of translations to this component from other components within same project. This really depends on what you are translating, sometimes it's desirable to have make use of a translation more than once.

It's usually a good idea to turn this off for monolingual translations, unless you are using the same IDs across the whole project.

Default value can be changed by `DEFAULT_TRANSLATION_PROPAGATION`.

Shihni edhe:

Keeping translations same across components

Enable suggestions

Whether translation suggestions are accepted for this component.

Votim sugjerimesh

Turns on vote casting for suggestions, see *Votim sugjerimesh*.

Vetëprano sugjerime

Automatically accept voted suggestions, see *Votim sugjerimesh*.

Flamuj përkthimi

Customization of quality checks and other Weblate behavior, see *Customizing behavior using flags*.

Kontrolle me detyrim

List of checks which can not be ignored, see *Enforcing checks*.

Shënim: Enforcing the check does not automatically enable it, you still should enabled it using *Customizing behavior using flags* in *Flamuj përkthimi* or *Additional info on source strings*.

Licencë përkthimi

License of the translation (does not need to be the same as the source code license).

Marrëveshje kontribuesi

Marrëveshje përdoruesi që duhet miratuar përpara se një përdorues të mund të përkthejë këtë përbërës.

Shtim përkthimi të ri

How to handle requests for creation of new languages. Available options:

Lidhuni me mirëmbajtësit User can select desired language and the project maintainers will receive a notification about this. It is up to them to add (or not) the language to the repository.

Shpjë te URL udhëzimesh përkthimi User is presented a link to page which describes process of starting new translations. Use this in case more formal process is desired (for example forming a team of people before starting actual translation).

Krijoni kartelë gjuhe të re User can select language and Weblate automatically creates the file for it and translation can begin.

Çaktivizo shtim përkthimesh të reja There will be no option for user to start new translation.

Ndihmëz: The project admins can add new translations even if it is disabled here when it is possible (either *Gjedhe për përkthime të reja* or the file format supports starting from an empty file).

Shihni edhe:

adding-translation, *Shtim përkthimesh të reja*

Administroni vargje

Të reja në versionin 4.5.

Configures whether users in Weblate will be allowed to add new strings and remove existing ones. Adjust this to match your localization workflow - how the new strings are supposed to be introduced.

For bilingual formats, the strings are typically extracted from the source code (for example by using `xgettext`) and adding new strings in Weblate should be disabled (they would be discarded next time you update the translation files). In Weblate you can manage strings for every translation and it does not enforce the strings in all translations to be consistent.

For monolingual formats, the strings are managed only on source language and are automatically added or removed in the translations. The strings appear in the translation files once they are translated.

Shihni edhe:

Formate dygjuhësh dhe njëgjuhësh, adding-new-strings, `POST /api/translations/(string:project)/(string:component)/(string:language)/units/`

Stil kodi gjuhe

Përshtatni kod gjuhe të përdorur për të prodhuar emrin e kartelës për përkthime të krijuar nga Weblate.

Shihni edhe:

Shtim përkthimesh të reja, *Kod gjuhe*, *Parsing language codes*

Stil përzierjeje

You can configure how updates from the upstream repository are handled. This might not be supported for some VCSs. See [Merge or rebase](#) for more details.

Default value can be changed by `DEFAULT_MERGE_STYLE`.

Commit, add, delete, merge and addon messages

Message used when committing a translation, see [Template markup](#).

Default value can be changed by `DEFAULT_ADD_MESSAGE`, `DEFAULT_ADDON_MESSAGE`, `DEFAULT_COMMIT_MESSAGE`, `DEFAULT_DELETE_MESSAGE`, `DEFAULT_MERGE_MESSAGE`.

Push on commit

Whether committed changes should be automatically pushed to the upstream repository. When enabled, the push is initiated once Weblate commits changes to its underlying repository (see [Lazy commits](#)). To actually enable pushing [Repository push URL](#) has to be configured as well.

Moshë ndryshimesh për depozitim

Sets how old (in hours) changes have to be before they are committed by background task or the `commit_pending` management command. All changes in a component are committed once there is at least one change older than this period.

Default value can be changed by `COMMIT_PENDING_HOURS`.

Ndihmëz: There are other situations where pending changes might be committed, see [Lazy commits](#).

Kyçe, në rast gabimesh

Locks the component (and linked components, see [URL të brendshme Weblate](#)) upon the first failed push or merge into its upstream repository, or pull from it. This avoids adding another conflicts, which would have to be resolved manually.

The component will be automatically unlocked once there are no repository errors left.

Gjuhë burimi

Language used for source strings. Change this if you are translating from something else than English.

Ndihmëz: In case you are translating bilingual files from English, but want to be able to do fixes in the English translation as well, choose *English (Developer)* as a source language to avoid conflict between the name of the source language and the existing translation.

For monolingual translations, you can use intermediate translation in this case, see [Kartelë gjuhe ndërmjetëse](#).

Filtër gjuhësh

Regular expression used to filter the translation when scanning for filemask. It can be used to limit the list of languages managed by Weblate.

Shënim: You need to list language codes as they appear in the filename.

Some examples of filtering:

Filter description	Shprehje e rregullt
Selected languages only	<code>^(cs de es)\$</code>
Exclude languages	<code>^(?! (it fr)\$) .+\$</code>
Filter two letter codes only	<code>^[.]+\$</code>
Exclude non language files	<code>^(?! (blank)\$) .+\$</code>
Include all files (default)	<code>^[^.] +\$</code>

Shprehje e rregullt variantesh

Regular expression used to determine the variants of a string, see variants.

Shënim: Most of the fields can be edited by project owners or managers, in the Weblate interface.

Shihni edhe:

Does Weblate support other VCSes than Git and Mercurial?, alerts

Përparësi

Përbërësit me përparësi më të lartë u ofrohen të parat përkthyesve.

Restricted access

By default the component is visible to anybody who has access to the project, even if the person can not perform any changes in the component. This makes it easier to keep translation consistency within the project.

Restricting access at a component, or component-list level takes over access permission to a component, regardless of project-level permissions. You will have to grant access to it explicitly. This can be done through granting access to a new user group and putting users in it, or using the default *custom* or *private* access control groups.

The default value can be changed in `DEFAULT_RESTRICTED_COMPONENT`.

Ndihmëz: This applies to project admins as well — please make sure you will not loose access to the component after toggling the status.

Ndaje te projekte

You can choose additional projects where the component will be visible. Useful for shared libraries which you use in several projects.

Shënim: Sharing a component doesn't change its access control. It only makes it visible when browsing other projects. Users still need access to the actual component to browse or translate it.

Përdore si fjalorth

Të reja në versionin 4.5.

Allows using this component as a glossary. You can configure how it will be listed using *Ngjyrë fjalorthi*.

The glossary will be accessible in all projects defined by *Ndaje te projekte*.

It is recommended to enable *Administroni vargje* on glossaries in order to allow adding new words to them.

Shihni edhe:

Fjalorth

Ngjyrë fjalorthi

Display color for a glossary used when showing word matches.

2.7.5 Template markup

Weblate uses simple markup language in several places where text rendering is needed. It is based on [The Django template language](#), so it can be quite powerful.

Currently it is used in:

- Commit message formatting, see *Component configuration*
- **Several addons**
 - *Pikasje përbërësish*
 - *Prodhues statistikash*
 - *Executing scripts from add-on*

There following variables are available in the component templates:

```
{{ language_code }} Kod gjuhe
{{ language_name }} Emër gjuhe
{{ component_name }} Emër përbërësi
{{ component_slug }} Component slug
{{ project_name }} Emër projekti
{{ project_slug }} Project slug
{{ url }} Translation URL
{{ filename }} Emër karteletë përkthimi
{{ stats }} Translation stats, this has further attributes, examples below.
{{ stats.all }} Total strings count
{{ stats.fuzzy }} Count of strings needing review
```

`{{ stats.fuzzy_percent }}` Percent of strings needing review
`{{ stats.translated }}` Translated strings count
`{{ stats.translated_percent }}` Translated strings percent
`{{ stats.allchecks }}` Number of strings with failing checks
`{{ stats.allchecks_percent }}` Percent of strings with failing checks
`{{ author }}` Author of current commit, available only in the commit scope.
`{{ addon_name }}` Name of currently executed addon, available only in the addon commit message.

The following variables are available in the repository browser or editor templates:

`{{branch}}` current branch

`{{line}}` line in file

`{{filename}}` filename, you can also strip leading parts using the `parentdir` filter, for example
`{{filename|parentdir}}`

You can combine them with filters:

```
{{ component|title }}
```

You can use conditions:

```
{% if stats.translated_percent > 80 %}Well translated!{% endif %}
```

There is additional tag available for replacing characters:

```
{% replace component "-" " " %}
```

You can combine it with filters:

```
{% replace component|capfirst "-" " " %}
```

There are also additional filter to manipulate with filenames:

```

Directory of a file: {{ filename|dirname }}
File without extension: {{ filename|striptext }}
File in parent dir: {{ filename|parentdir }}
It can be used multiple times: {{ filename|parentdir|parentdir }}
  
```

...and other Django template features.

2.7.6 Importing speed

Fetching VCS repository and importing translations to Weblate can be a lengthy process, depending on size of your translations. Here are some tips:

Optimize configuration

The default configuration is useful for testing and debugging Weblate, while for a production setup, you should do some adjustments. Many of them have quite a big impact on performance. Please check [Production setup](#) for more details, especially:

- Configure Celery for executing background tasks (see [Background tasks using Celery](#))
- *Aktivizoni përdorim fshehtine*
- *Përdorni një mekanizëm të fuqishëm baze të dhënash*
- *Disable debug mode*

Check resource limits

If you are importing huge translations or repositories, you might be hit by resource limitations of your server.

- Check the amount of free memory, having translation files cached by the operating system will greatly improve performance.
- Disk operations might be bottleneck if there is a lot of strings to process—the disk is pushed by both Weblate and the database.
- Additional CPU cores might help improve performance of background tasks (see *Background tasks using Celery*).

Disable unneeded checks

Some quality checks can be quite expensive, and if not needed, can save you some time during import if omitted. See *CHECK_LIST* for info on configuration.

2.7.7 Automatic creation of components

In case your project has dozen of translation files (e.g. for different gettext domains, or parts of Android apps), you might want to import them automatically. This can either be achieved from the command line by using *import_project* or *import_json*, or by installing the *Pikasje përbërësish* addon.

To use the addon, you first need to create a component for one translation file (choose the one that is the least likely to be renamed or removed in future), and install the addon on this component.

For the management commands, you need to create a project which will contain all components and then run *import_project* or *import_json*.

Shihni edhe:

Management commands, Pikasje përbërësish

2.8 Language definitions

To present different translations properly, info about language name, text direction, plural definitions and language code is needed.

2.8.1 Parsing language codes

While parsing translations, Weblate attempts to map language code (usually the ISO 639-1 one) to any existing language object.

You can further adjust this mapping at project level by *Alias gjuhe*.

If no exact match can be found, an attempt will be made to best fit it into an existing language. Following steps are tried:

- Case insensitive lookups.
- Normalizing underscores and dashes.
- Looking up built-in language aliases.
- Looking up by language name.
- Ignoring the default country code for a given language—choosing *cs* instead of *cs_CZ*.

Should that also fail, a new language definition will be created using the defaults (left to right text direction, one plural). The automatically created language with code `xx_XX` will be named as `xx_XX` (*generated*). You might want to change this in the admin interface later, (see [Changing language definitions](#)) and report it to the issue tracker (see [Dhënie ndihmese te Weblate](#)), so that the proper definition can be added to the upcoming Weblate release.

Ndihmëz: In case you see something unwanted as a language, you might want to adjust [Filtër gjuhësh](#) to ignore such file when parsing translations.

Shihni edhe:

[Kod gjuhe](#), [Shtim përkthimesh të reja](#)

2.8.2 Changing language definitions

You can change language definitions in the languages interface (`/languages/` URL).

While editing, make sure all fields are correct (especially plurals and text direction), otherwise translators will be unable to properly edit those translations.

2.8.3 Built-in language definitions

Definitions for about 600 languages are included in Weblate and the list is extended in every release. Whenever Weblate is upgraded (more specifically whenever **weblate migrate** is executed, see [Generic upgrade instructions](#)) the database of languages is updated to include all language definitions shipped in Weblate.

This feature can be disabled using `UPDATE_LANGUAGES`. You can also enforce updating the database to match Weblate built-in data using `setuplang`.

Shihni edhe:

[Extending built-in language definitions](#)

2.8.4 Ambiguous language codes and macrolanguages

In many cases it is not a good idea to use macro language code for a translation. The typical problematic case might be Kurdish language, which might be written in Arabic or Latin script, depending on actual variant. To get correct behavior in Weblate, it is recommended to use individual language codes only and avoid macro languages.

Shihni edhe:

[Macrolanguages definition](#), [List of macrolanguages](#)

2.8.5 Language definitions

Each language consists of following fields:

Kod gjuhe

Code identifying the language. Weblate prefers two letter codes as defined by [ISO 639-1](#), but uses [ISO 639-2](#) or [ISO 639-3](#) codes for languages that do not have two letter code. It can also support extended codes as defined by [BCP 47](#).

Shihni edhe:

Parsing language codes, Shtim përkthimesh të reja

Emër gjuhe

Visible name of the language. The language names included in Weblate are also being localized depending on user interface language.

Drejtimit teksti

Determines whether language is written right to left or left to right. This property is autodetected correctly for most of the languages.

Plural number

Number of plurals used in the language.

Formulë shumësi

Gettext compatible plural formula used to determine which plural form is used for given count.

Shihni edhe:

Shumësa, GNU gettext utilities: Plural forms, Language Plural Rules by the Unicode Consortium

2.8.6 Shtim përkthimesh të reja

Ndryshuar në versionin 2.18: In versions prior to 2.18 the behaviour of adding new translations was file format specific.

Weblate can automatically start new translation for all of the file formats.

Some formats expect to start with an empty file and only translated strings to be included (for example *Burime vargjeshe Android*), while others expect to have all keys present (for example *GNU gettext*). In some situations this really doesn't depend on the format, but rather on the framework you use to handle the translation (for example with *Kartela JSON*).

When you specify *Gjedhe për përkthime të reja* in *Component configuration*, Weblate will use this file to start new translations. Any exiting translations will be removed from the file when doing so.

When *Gjedhe për përkthime të reja* is empty and the file format supports it, an empty file is created where new strings will be added once they are translated.

The *Stil kodi gjuhe* allows you to customize language code used in generated filenames:

Parazgjedhje e bazuar te formati i kartelave Dependent on file format, for most of them POSIX is used.

Në stil POSIX, me përdorim të nënvijës si ndarës Typically used by gettext and related tools, produces language codes like `pt_BR`.

Në stil POSIX, me përdorim të nënvijës si ndarës, përfshi kod vendi POSIX style language code including the country code even when not necessary (for example `cs_CZ`).

Në stil BCP, me përdorim të vijës në mes si ndarës Typically used on web platforms, produces language codes like `pt-BR`.

Në stil BCP, me përdorim të vijës në mes si ndarës, përfshi kod vendi BCP style language code including the country code even when not necessary (for example `cs-CZ`).

Në stil Android Only used in Android apps, produces language codes like `pt-rBR`.

Në stil Java Used by Java—mostly BCP with legacy codes for Chinese.

Additionally, any mappings defined in *Aliase gjuhe* are applied in reverse.

Shënim: Weblate recognizes any of these when parsing translation files, the above settings only influences how new files are created.

Shihni edhe:

Kod gjuhe, Parsing language codes

2.9 Përkthim në vazhdimësi


There is infrastructure in place so that your translation closely follows development. This way translators can work on translations the entire time, instead of working through huge amount of new text just prior to release.

Shihni edhe:

`/dev/integration` describes basic ways to integrate your development with Weblate.

This is the process:

1. Developers make changes and push them to the VCS repository.
2. Optionally the translation files are updated (this depends on the file format, see *Why does Weblate still show old translation strings when I've updated the template?*).
3. Weblate pulls changes from the VCS repository, see *Përditësim deposh*.
4. Once Weblate detects changes in translations, translators are notified based on their subscription settings.
5. Translators submit translations using the Weblate web interface, or upload offline changes.
6. Once the translators are finished, Weblate commits the changes to the local repository (see *Lazy commits*) and pushes them back if it has permissions to do so (see *Pushing changes from Weblate*).



2.9.1 Përditësim deposh

You should set up some way of updating backend repositories from their source.

- Use *Hook-e njoftimesh* to integrate with most of common code hosting services:
 - *Automatically receiving changes from GitHub*
 - *Automatically receiving changes from GitLab*
 - *Automatically receiving changes from Bitbucket*
 - *Automatically receiving changes from Pagure*
 - *Automatically receiving changes from Azure Repos*
- Manually trigger update either in the repository management or using *Weblate's REST API* or *Klient Weblate*
- Enable `AUTO_UPDATE` to automatically update all components on your Weblate instance
- Execute `updategit` (with selection of project or `--all` to update all)

Whenever Weblate updates the repository, the post-update addons will be triggered, see *Shtesa*.

Shmangie përplasjesh përzierjeje

The merge conflicts from Weblate arise when same file was changed both in Weblate and outside it. There are two approaches to deal with that - avoid edits outside Weblate or integrate Weblate into your updating process, so that it flushes changes prior to updating the files outside Weblate.

The first approach is easy with monolingual files - you can add new strings within Weblate and leave whole editing of the files there. For bilingual files, there is usually some kind of message extraction process to generate translatable files from the source code. In some cases this can be split into two parts - one for the extraction generates template (for example gettext POT is generated using **xgettext**) and then further process merges it into actual translations (the gettext PO files are updated using **msgmerge**). You can perform the second step within Weblate and it will make sure that all pending changes are included prior to this operation.

The second approach can be achieved by using *Weblate's REST API* to force Weblate to push all pending changes and lock the translation while you are doing changes on your side.

The script for doing updates can look like this:

```
# Lock Weblate translation
wlc lock
# Push changes from Weblate to upstream repository
wlc push
# Pull changes from upstream repository to your local copy
git pull
# Update translation files, this example is for Django
./manage.py makemessages --keep-pot -a
git commit -m 'Locale updates' -- locale
# Push changes to upstream repository
git push
# Tell Weblate to pull changes (not needed if Weblate follows your repo
# automatically)
wlc pull
# Unlock translations
wlc unlock
```

If you have multiple components sharing same repository, you need to lock them all separately:

```
wlc lock foo/bar
wlc lock foo/baz
wlc lock foo/baj
```

Shënim: The example uses *Klient Weblate*, which needs configuration (API keys) to be able to control Weblate remotely. You can also achieve this using any HTTP client instead of wlc, e.g. curl, see *Weblate's REST API*.

Shihni edhe:

Klient Weblate

Automatically receiving changes from GitHub

Weblate comes with native support for GitHub.

If you are using Hosted Weblate, the recommended approach is to install the *Weblate app*, that way you will get the correct setup without having to set much up. It can also be used for pushing changes back.

To receive notifications on every push to a GitHub repository, add the Weblate Webhook in the repository settings (*Webhooks*) as shown on the image below:

The screenshot shows the GitHub interface for configuring a webhook. The repository is 'WeblateOrg / hello'. The left sidebar contains links: Options, Collaborators & teams, Branches, Webhooks (selected), Integrations & services, Deploy keys, and Alerts. The main content area is titled 'Webhooks / Add webhook'. It includes a description of webhooks, a 'Payload URL' field with the value 'https://hosted.weblate.org/hooks/github/', a 'Content type' dropdown set to 'application/x-www-form-urlencoded', and a 'Secret' field. Below these is a checkbox for 'Disable SSL verification'. The 'Which events would you like to trigger this webhook?' section has three radio buttons: 'Just the push event.' (selected), 'Send me everything.', and 'Let me select individual events.'. At the bottom, there is a checked 'Active' checkbox and a green 'Add webhook' button.

For the payload URL, append `/hooks/github/` to your Weblate URL, for example for the Hosted Weblate service, this is `https://hosted.weblate.org/hooks/github/`.


You can leave other values at default settings (Weblate can handle both content types and consumes just the *push* event).

Shihni edhe:

POST /hooks/github/, Accessing repositories from Hosted Weblate

Automatically receiving changes from Bitbucket

Weblate has support for Bitbucket webhooks, add a webhook which triggers upon repository push, with destination to `/hooks/bitbucket/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/bitbucket/`).

**Shihni edhe:**

POST /hooks/bitbucket/, Accessing repositories from Hosted Weblate

Automatically receiving changes from GitLab

Weblate has support for GitLab hooks, add a project webhook with destination to `/hooks/gitlab/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/gitlab/`).


Shihni edhe:

POST /hooks/gitlab/, Accessing repositories from Hosted Weblate

Automatically receiving changes from Pagure

Të reja në versionin 3.3.

Weblate has support for Pagure hooks, add a webhook with destination to `/hooks/pagure/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/pagure/`). This can be done in *Activate Web-hooks* under *Project options*:



The screenshot shows the Weblate web interface. At the top, there's a header with the 'fedora PAGURE' logo, 'Browse' and 'Create' links, and a user profile icon. Below the header, the project name 'nijel-test' is displayed, followed by buttons for 'New Issue', 'Open PR', 'Fork', and 'Clone'. A navigation bar includes links for 'Source', 'Issues' (0), 'Pull Requests' (0), 'Stats', and 'Settings' (which is highlighted).

The 'Settings' page has a sidebar on the left with a list of settings categories: Project Settings, Project Details, Default Branch, Private Web Hook Key, API Keys, Project Options (selected), Public Notifications, Users & Groups, Deploy Keys, Hooks, Priorities, Roadmap, Close Status, Custom Issue Fields, Reports, Tags, Quick Replies, Regenerate Repos, Give Project, and Delete Project.

The main content area is titled 'Project Options' and contains several checkboxes and a text input field:

- ☐ Activate always merge
- ☐ Activate disable non fast-forward merges
- ☐ Activate Enforce signed-off commits in pull-request
- ☒ Activate fedmsg notifications
- ☒ Activate Issue tracker
- ☐ Activate Issue tracker read only
- ☐ Activate Issues default to private
- Activate Minimum score to merge pull-request:
- ☐ Activate notify on commit flag
- ☐ Activate notify on pull-request flag
- ☐ Activate Only assignee can merge pull-request
- ☐ Activate open metadata access to all
- ☐ Activate project documentation
- ☐ Activate pull request access only
- ☒ Activate pull requests
- ☒ Activate stomp notifications

Below these options, there's a section for 'Activate Web-hooks' with a text input field containing 'https://hosted.weblate.org/hooks/pagure/'. Below the input field are two buttons: 'Update' and 'Test web-hook'.

At the bottom, there's a section titled 'Learn more about' with a list of links:

- Flags
- Tracker read-only
- Pull-request access only
- Roadmap on Issue page
- fedmsg notifications

Shihni edhe:

POST /hooks/pagure/, Accessing repositories from Hosted Weblate

Automatically receiving changes from Azure Repos

Të reja në versionin 3.8.

Weblate has support for Azure Repos web hooks, add a webhook for *Code pushed* event with destination to `/hooks/azure/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/azure/`). This can be done in *Service hooks* under *Project settings*.

Shihni edhe:

Web hooks in Azure DevOps manual, *POST /hooks/azure/, Accessing repositories from Hosted Weblate*

Automatically receiving changes from Gitea Repos

Të reja në versionin 3.9.

Weblate has support for Gitea webhooks, add a *Gitea Webhook* for *Push events* event with destination to `/hooks/gitea/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/gitea/`). This can be done in *Webhooks* under repository *Settings*.

Shihni edhe:

Webhooks in Gitea manual, *POST /hooks/gitea/*, *Accessing repositories from Hosted Weblate*

Automatically receiving changes from Gitee Repos

Të reja në versionin 3.9.

Weblate has support for Gitee webhooks, add a *WebHook* for *Push* event with destination to `/hooks/gitee/` URL on your Weblate installation (for example `https://hosted.weblate.org/hooks/gitee/`). This can be done in *WebHooks* under repository *Management*.

Shihni edhe:

Webhooks in Gitee manual, *POST /hooks/gitee/*, *Accessing repositories from Hosted Weblate*

Përditësim i automatizuar i përnatshëm i depove

Weblate automatically fetches remote repositories nightly to improve performance when merging changes later. You can optionally turn this into doing nightly merges as well, by enabling *AUTO_UPDATE*.

2.9.2 Pushing changes from Weblate

Each translation component can have a push URL set up (see *URL push-i për depon*), and in that case Weblate will be able to push change to the remote repository. Weblate can be also be configured to automatically push changes on every commit (this is default, see *Push on commit*). If you do not want changes to be pushed automatically, you can do that manually under *Repository maintenance* or using API via *wlc push*.

The push options differ based on the *Integrim kontrolli versioni* used, more details are found in that chapter.

In case you do not want direct pushes by Weblate, there is support for *GitHub*, *GitLab*, *Pagure* pull requests or *Gerrit* reviews, you can activate these by choosing *GitHub*, *GitLab*, *Gerrit* or *Pagure* as *Sistem kontrolli versionesh* in *Component configuration*.

Overall, following options are available with Git, GitHub and GitLab:

Ujdisje e dëshiruar	<i>Sistem kontrolli versionesh</i>	<i>URL push-i për depon</i>	<i>Degë push</i>
No push	<i>Git</i>	<i>empty</i>	<i>empty</i>
Push directly	<i>Git</i>	URL SSH	<i>empty</i>
Push to separate branch	<i>Git</i>	URL SSH	Emër dege
GitHub pull request from fork	<i>GitHub</i>	<i>empty</i>	<i>empty</i>
GitHub pull request from branch	<i>GitHub</i>	URL SSH ¹	Emër dege
GitLab merge request from fork	<i>GitLab</i>	<i>empty</i>	<i>empty</i>
GitLab merge request from branch	<i>GitLab</i>	URL SSH ^{Page 65, 1}	Emër dege
Pagure merge request from fork	<i>Pagure</i>	<i>empty</i>	<i>empty</i>
Pagure merge request from branch	<i>Pagure</i>	URL SSH ^{Page 65, 1}	Emër dege

¹ Can be empty in case *Depo kodi burim* supports pushing.

Shënim: You can also enable automatic pushing of changes after Weblate commits, this can be done in [Push on commit](#).

Shihni edhe:

See [Hyrje në depo](#) for setting up SSH keys, and [Lazy commits](#) for info about when Weblate decides to commit changes.

Degë të mbrojtura

If you are using Weblate on protected branch, you can configure it to use pull requests and perform actual review on the translations (what might be problematic for languages you do not know). An alternative approach is to waive this limitation for the Weblate push user.

For example on GitHub this can be done in the repository configuration:

☒ **Require pull request reviews before merging**

When enabled, all commits must be made to a non-protected branch and submitted via a pull request with the required number of approving reviews and no changes requested before it can be merged into a branch that matches this rule.

Required approving reviews: 1 ▾

☐ **Dismiss stale pull request approvals when new commits are pushed**

New reviewable commits pushed to a matching branch will dismiss pull request review approvals.

☐ **Require review from Code Owners**

Require an approved review in pull requests including files with a designated code owner.

☒ **Restrict who can dismiss pull request reviews**

Specify people or teams allowed to dismiss pull request reviews.

🔍 Search for people or teams

People and teams that can dismiss reviews.



Organization and repository administrators

These members can always dismiss.



weblate

Weblate push user



2.9.3 Merge or rebase

By default, Weblate merges the upstream repository into its own. This is the safest way in case you also access the underlying repository by other means. In case you don't need this, you can enable rebasing of changes on upstream, which will produce a history with fewer merge commits.

Shënim: Rebasing can cause you trouble in case of complicated merges, so carefully consider whether or not you want to enable them.

2.9.4 Ndërveprim me të tjerët

Weblate makes it easy to interact with others using its API.

Shihni edhe:

Weblate's REST API

2.9.5 Lazy commits

The behaviour of Weblate is to group commits from the same author into one commit if possible. This greatly reduces the number of commits, however you might need to explicitly tell it to do the commits in case you want to get the VCS repository in sync, e.g. for merge (this is by default allowed for the *Managers* group, see *Listë privilegjesh*).

The changes in this mode are committed once any of the following conditions are fulfilled:

- Somebody else changes an already changed string.
- A merge from upstream occurs.
- An explicit commit is requested.
- Change is older than period defined as *Moshë ndryshimesh për depozitim* on *Component configuration*.

Ndihmëz: Commits are created for every component. So in case you have many components you will still see lot of commits. You might utilize *Kryej «squash» për depozitime Git* addon in that case.

If you want to commit changes more frequently and without checking of age, you can schedule a regular task to perform a commit:

```
CELERY_BEAT_SCHEDULE = {
    # Unconditionally commit all changes every 2 minutes
    "commit": {
        "task": "weblate.trans.tasks.commit_pending",
        # Ommiting hours will honor per component settings,
        # otherwise components with no changes older than this
        # won't be committed
        "kwargs": {"hours": 0},
        # How frequently to execute the job in seconds
        "schedule": 120,
    }
}
```

2.9.6 Processing repository with scripts

The way to customize how Weblate interacts with the repository is *Shtesa*. Consult *Executing scripts from add-on* for info on how to execute external scripts through addons.

2.9.7 Keeping translations same across components

Once you have multiple translation components, you might want to ensure that the same strings have same translation. This can be achieved at several levels.

Përhapje përkthimesh

With *Lejo përhapje përkthimesh* enabled (what is the default, see *Component configuration*), all new translations are automatically done in all components with matching strings. Such translations are properly credited to currently translating user in all components.

Shënim: The translation propagation requires the key to be match for monolingual translation formats, so keep that in mind when creating translation keys.

Consistency check

The *Jo i njëtrajtshëm* check fires whenever the strings are different. You can utilize this to review such differences manually and choose the right translation.

Përkthim i automatizuar

Automatic translation based on different components can be way to synchronize the translations across components. You can either trigger it manually (see *Përkthim i automatizuar*) or make it run automatically on repository update using addon (see *Përkthim i automatizuar*).

2.10 Licencim përkthimesh

You can specify which license translations are contributed under. This is especially important to do if translations are open to the public, to stipulate what they can be used for.

You should specify *Component configuration* license info. You should avoid requiring a contributor license agreement, though it is possible.

2.10.1 Të dhëna licence

Upon specifying license info (license name and URL), this info is shown in the translation info section of the respective *Component configuration*.

Usually this is best place to post licensing info if no explicit consent is required. If your project or translation is not libre you most probably need prior consent.

2.10.2 Marrëveshje kontribuesi

If you specify a contributor license agreement, only users who have agreed to it will be able to contribute. This is a clearly visible step when accessing the translation:

Webplate Dashboard Projects Languages Checks

WebplateOrg / Language names translated 95%

Contribution to this translation requires you to agree with a contributor agreement. [View contributor agreement](#)

Translations Info Alerts Search Insights Files Tools Manage Share Watching

Language	Translated	Untranslated	Untranslated words	Checks	Suggestions	Comments
Czech GPL-3.0	✓					
Hebrew GPL-3.0	✓					
Hungarian GPL-3.0	81%	4	5			
English GPL-3.0	✓					

[Start new translation](#)

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

The entered text is formatted into paragraphs and external links can be included. HTML markup can not be used.

2.10.3 Licenca përdoruesi

Any user can review all translation licenses of all public projects on the instance from their profile:

Webplate Dashboard Projects Languages Checks

Your profile

Languages Preferences Notifications Account Profile Licenses Audit log API access

Licenses

Please pay attention to the licensing info, as this specifies how translations can be used.

By registering you agree to use your name and e-mail in the commits, and provide your contribution under the license defined by each localization project.

You have agreed to the following as a contributor:

- [WebplateOrg/Language names](#)

Licenses for individual translations

GNU General Public License v3.0 or later

[WebplateOrg/Djangojs](#) [WebplateOrg/Django](#) [WebplateOrg/WebplateOrg](#) [WebplateOrg/Language names](#)

MIT License

[WebplateOrg/Android](#)

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

2.11 Procesi i përkthimit

2.11.1 Votim sugjerimesh

Everyone can add suggestions by default, to be accepted by signed in users. Suggestion voting can be used to make use of a string when more than one signed-in user agrees, by setting up the *Component configuration* with *Suggestion voting* to turn on voting, and *Autoaccept suggestions* to set a threshold for accepted suggestions (this includes a vote from the user making the suggestion if it is cast).


Shënim: Once automatic acceptance is set up, normal users lose the privilege to directly save translations or accept suggestions. This can be overridden with the *Edit string when suggestions are enforced permission*.

You can combine these with *access control* into one of the following setups:

- Users suggest and vote for suggestions and a limited group controls what is accepted. - Turn on voting. - Turn off automatic acceptance. - Don't let users save translations.
- Users suggest and vote for suggestions with automatic acceptance once the defined number of them agree. - Turn on voting. - Set the desired number of votes for automatic acceptance.
- Optional voting for suggestions. (Can optionally be used by users when they are unsure about a translation by making multiple suggestions.) - Only turn on voting.

2.11.2 Additional info on source strings

Enhance the translation process by adding additional info to the strings including explanations, string priorities, check flags and visual context. Some of that info may be extracted from the translation files and some may be added by editing the additional string info:



Access this directly from the translation interface by clicking the «Edit» icon next to *Screenshot context* or *Flags*.

Webplate

Dashboard

Projects

Languages

Checks

WebplateOrg

Django

Czech

Translate

translated 96%

11 / 26

All strings

Position and priority

Zen

Translation

Explanation

Help text for automatic translation tool

English

Automatic translation via machine translation uses active machine translation engines to get the best possible translations and applies them in this project.

Czech

Automatický překlad prostřednictvím strojového překladu používá aktivní enginy strojového překladu pro získání nejlepších možných překladů a použije je na tento projekt.

Needs editing

Save

Suggest

Skip

Nearby strings

Comments

Automatic suggestions

Other languages

History

Context	English	Czech
	Files	Soubory
	Automatic translation	Automatický překlad
	Add new translation string	Add new translation string
	Translation status	Stav překladu
	%(count)s word	%(count)s slovo
	Other components	Další součásti
	Translation file	Soubor s překladem
	Download	Stáhnout
	Browse all translation changes	Procházet všechny změny v překladu.
	Automatic translation takes existing translations in this project and applies them to the current component. It can be used to push translations to a different branch, to fix inconsistent translations or to translate a new component using translation memory.	Automatický překlad použije stávající překlady v projektu na tuto součást. Může být užitečný pro sloučení překladů z jiné větve, opravu nekonzistentních překladů nebo překlad nové součásti pomocí překladové paměti.
	Automatic translation via machine translation uses active machine translation engines to get the best possible translations and applies them in this project.	Automatický překlad prostřednictvím strojového překladu používá aktivní enginy strojového překladu pro získání nejlepších možných překladů a použije je na tento projekt.
	You can add new translation string here, it will automatically appear in all translations.	Zde můžete přidat nový řetězec k překladu, automaticky se objeví ve všech jazycích.
	The uploaded file will be merged with the current translation. In case you want to overwrite already translated strings, don't forget to enable it.	Nahráný soubor bude sloučen se stávajícími překlady. Pokud chcete přepsat již přeložené řetězce, nezapomeňte to povolit.
	The uploaded file will be merged with the current translation.	Nahráný soubor bude sloučen se stávajícími překlady.
	The fulltext search might not work properly as the fulltext index for this translation is not yet up to date.	Fulltextové vyhledávání nemusí fungovat správně, protože fulltextový index pro tento překlad ještě není plně zpracován.
	Review	Kontrola
	Review translations touched by other users.	Zkontrolovat překlady od ostatních uživatelů.
	Start review	Začít kontrolu
	Percent	Procenta
	Total	Celkem
	Failing check	Neúspěšných kontrol
	Last activity	Poslední aktivita
	Last change	Poslední změna
	Last author	Poslední autor
Question for a mathematics-based CAPTCHA, the %s is an arithmetic problem	What is %s?	Kolik to je?
	The string uses three dots (...) instead of an ellipsis character (...)	

Glossary

English

Czech

machine

strojový

weblate.org

translation

překlad

weblate.org

project

projekt

weblate.org

Add term to glossary

String information

Screenshot context

No screenshot currently associated.

Add screenshot

Explanation

Help text for automatic translation tool

Labels

No labels currently set.

Flags

No flags currently set.

Source string location

weblate/templates/translation.html:212

String age

5 seconds ago

Source string age

6 seconds ago

Translation file

weblate/locale/cs/LC_MESSAGES/django.po, string 11

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

266

Kapitulli 2. Dokumentime përgjegjësi

Strings prioritization

Të reja në versionin 2.0.

String priority can be changed to offer higher priority strings for translation earlier by using the `priority` flag.

Ndihmëz: This can be used to order the flow of translation in a logical manner.

Shihni edhe:

Kontrolle cilësie

Flamuj përkthimi

Të reja në versionin 2.4.

Ndryshuar në versionin 3.3: Previously called *Quality checks flags*, it no longer configures only checks.

The default set of translation flags is determined by the translation *Component configuration* and the translation file. However, you might want to use it to customize this per source string.

Shihni edhe:

Kontrolle cilësie, Customizing behavior using flags

Shpjegim

Ndryshuar në versionin 4.1: In previous versions this has been called *Extra context*.

Use the explanation to clarify scope or usage of the translation. You can use Markdown to include links and other markup.

Visual context for strings

Të reja në versionin 2.9.

You can upload a screenshot showing a given source string in use within your program. This helps translators understand where it is used, and how it should be translated.

The uploaded screenshot is shown in the translation context sidebar:

Webate

Dashboard

Projects

Languages

Checks

WebateOrg / Django / Czech / Translate

translated 96%

<<

<

11 / 26

>

>>

All strings

Position and priority

Translation

Explanation

Help text for automatic translation tool

English

Automatic translation via machine translation uses active machine translation engines to get the best possible translations and applies them in this project.

Czech

Automatický překlad prostřednictvím strojového překladu používá aktivní enginy strojového překladu pro získání nejlepších možných překladů a použije je na tento projekt.

Needs editing

169/1570 · 157

Save

Suggest

Skip

Nearby strings 26

Comments

Automatic suggestions

Other languages 4

History

Translation memory

Search

Translation	Source	Origin	Similarity	
Automatický překlad prostřednictvím strojového překladu používá aktivní enginy strojového překladu pro získání nejlepších možných překladů a použije je na tento projekt.	Automatic translation via machine translation uses active machine translation engines to get the best possible translations and applies them in this project.	Webate Translation Memory (Project: weblateorg/django) Webate Translation Memory (Shared: weblateorg/django) Webate (WebateOrg/Django)	100%	<div>Copy</div> <div>Copy and save</div>

Glossary

English

Czech

machine translation

strojový překlad

project

projekt

Add term to glossary

String information

Screenshot context

Add screenshot

Explanation

Help text for automatic translation tool

Labels

No labels currently set.

Flags

No flags currently set.

Source string location

weblate/templates/translation.html:212

String age

13 seconds ago

Source string age

14 seconds ago

Translation file

weblate/locale/cs/LC_MESSAGES/django.po, string 11

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

In addition to *Additional info on source strings*, screenshots have a separate management interface under the *Tools* menu. Upload screenshots, assign them to source strings manually, or use optical character recognition to do so.

Once a screenshot is uploaded, this interface handles management and source string association:

268

Kapitulli 2. Dokumentime përgjegjësi

Webate

Dashboard

Projects

Languages

Checks

WebateOrg / Django / Screenshots / Automatic translation

Screenshot has been uploaded, you can now assign it to source strings.

Assigned source strings

English	Location	Assigned screenshots	Actions
No matching strings found.			
Screenshot is shown to add visual context for all listed source strings.			

Assign source strings

English	Location	Assigned screenshots	Actions
No matching strings found.			

Source string search

Search

Automatically recognize

Image

Source string

Hello, world! [⚠]

One
Orangutan has %d banana. [⚠]

Other
Orangutan has %d bananas. [⚠]

Try Weblate at <http://demo.weblate.org/>! [⚠]

Thank you for using Weblate.

Screenshot is shown to add visual context for all listed source strings.

Edit screenshot

Screenshot name

Automatic translation

Image

Currently: [screenshots/screenshot.png](#)

Change:

Choose File

No file chosen

Upload JPEG or PNG images up to 2000x2000 pixels.

Save

Screenshot details

Created	now
Uploaded by	testuser
Language	English

Delete screenshot

Deleting screenshot will remove it from all associated source strings.

Delete

2.12 Checks and fixups

2.12.1 Custom automatic fixups

You can also implement your own automatic fixup in addition to the standard ones and include them in `AUTOFIX_LIST`.

The automatic fixes are powerful, but can also cause damage; be careful when writing one.

For example, the following automatic fixup would replace every occurrence of the string `foo` in a translation with `bar`:

```
#
# Copyright © 2012 - 2021 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <https://www.gnu.org/licenses/>.
#

from django.utils.translation import gettext_lazy as _

from weblate.trans.autofixes.base import AutoFix

class ReplaceFooWithBar(AutoFix):
    """Replace foo with bar."""

    name = _("Foobar")

    def fix_single_target(self, target, source, unit):
        if "foo" in target:
            return target.replace("foo", "bar"), True
        return target, False
```

To install custom checks, provide a fully-qualified path to the Python class in the `AUTOFIX_LIST`, see *Custom quality checks, addons and auto-fixes*.

2.12.2 Customizing behavior using flags

You can fine-tune the behavior of Weblate (mostly checks) for each source string (in source strings review, see *Additional info on source strings*) or in the *Component configuration (Flamuj përktimi)*. Some file formats also allow to specify flags directly in the format (see *Formate të mbuluar kartelash*).

The flags are comma-separated, the parameters are separated with colon. You can use quotes to include whitespace or special chars in the string. For example:

```
placeholders:"special:value":"other value", regex:.*
```

Here is a list of flags currently accepted:

rst-text Treat a text as an reStructuredText document, affects *Përkthim i pandryshuar*.

dos-eol Uses DOS end-of-line markers instead of Unix ones (`\r\n` instead of `\n`).

read-only The string is read-only and should not be edited in Weblate, see *Vargje vetëm për lexim*.

priority:N Priority of the string. Higher priority strings are presented first for translation. The default priority is 100, the higher priority a string has, the earlier it is offered for translation.

max-length:N Limit the maximal length for a string to N characters, see *Gjatësi maksimum e përkthimit*.

xml-text Treat text as XML document, affects *Sintaksë XML* and *Markup XML*.

font-family:NAME Define font-family for rendering checks, see *Administrim shkronjash*.

font-weight:WEIGHT Define font-weight for rendering checks, see *Administrim shkronjash*.

font-size:SIZE Define font-size for rendering checks, see *Administrim shkronjash*.

font-spacing:SPACING Define letter spacing for rendering checks, see *Administrim shkronjash*.

placeholders:NAME:NAME2:... Placeholder strings expected in translation, see *Vendmbajtëse*.

replacements:FROM:TO:FROM2:TO2... Replacements to perform when checking resulting text parameters (for example in *Madhësi maksimum e përkthimit* or *Gjatësi maksimum e përkthimit*). The typical use case for this is to expand placeables to ensure that the text fits even with long values, for example: `replacements:%s:"John Doe"`.

variants:SOURCE Mark this string as a variant of string with matching source. See variants.

regex:REGEX Shprehje e rregullt kundrejt të cilës duhen kërkuar përpunime te kartela përkthimi, shihni *Shprehje e rregullt*.

forbidden Indicates forbidden translation in a glossary, see *Forbidden translations*.

strict-same Make «Unchanged translation» avoid using built-in words blacklist, see *Përkthim i pandryshuar*.

check-glossary Enable the *S'ndjek fjalorthin* quality check.

angularjs-format Enable the *Varg ndërshtënie AngularJS* quality check.

c-format Enable the *Format C* quality check.

c-sharp-format Enable the *Format C#* quality check.

es-format Enable the *ECMAScript template literals* quality check.

i18next-interpolation Enable the *Ndërshtënie i18next* quality check.

java-format Enable the *Format Java* quality check.

java-messageformat Enable the *Java MessageFormat* quality check.

javascript-format Enable the *Format JavaScript* quality check.

lua-format Enable the *Format Lua* quality check.

object-pascal-format Enable the *Object Pascal format* quality check.

percent-placeholders Enable the *Vendmbajtëse përqindjeje* quality check.

perl-format Enable the *Format Perl* quality check.

php-format Enable the *Format PHP* quality check.

python-brace-format Enable the *Format kllapash Python* quality check.

python-format Enable the *Format Python* quality check.

qt-format Enable the *Format Qt* quality check.

qt-plural-format Enable the *Format shumësi Qt* quality check.

ruby-format Enable the *Format Ruby* quality check.

scheme-format Enable the *Format Schema* quality check.

vue-format Enable the *Formatim i18n Vue* quality check.

md-text Treat text as a Markdown document. Enable *Lidhje Markdown*, *Referenca Markdown*, and *Sintaksë Markdown* quality checks.

safe-html Enable the *HTML jo e parrezik* quality check.

url The string should consist of only a URL. Enable the *URL* quality check.

ignore-bbcode Skip the *Markup BBCode* quality check.

ignore-duplicate Skip the *Fjalë të njëpasnjëshme të përsëdytura* quality check.

ignore-check-glossary Skip the *S'ndjek fjalorthin* quality check.

ignore-double-space Skip the *Hapësirë dyshe* quality check.

ignore-angularjs-format Skip the *Varg ndërshtënie AngularJS* quality check.

ignore-c-format Skip the *Format C* quality check.

ignore-c-sharp-format Skip the *Format C#* quality check.

ignore-es-format Skip the *ECMAScript template literals* quality check.

ignore-i18next-interpolation Skip the *Ndërshtënie i18next* quality check.

ignore-java-format Skip the *Format Java* quality check.

ignore-java-messageformat Skip the *Java MessageFormat* quality check.

ignore-javascript-format Skip the *Format JavaScript* quality check.

ignore-lua-format Skip the *Format Lua* quality check.

ignore-object-pascal-format Skip the *Object Pascal format* quality check.

ignore-percent-placeholders Skip the *Vendmbajtëse përqindjeje* quality check.

ignore-perl-format Skip the *Format Perl* quality check.

ignore-php-format Skip the *Format PHP* quality check.

ignore-python-brace-format Skip the *Format kllapash Python* quality check.

ignore-python-format Skip the *Format Python* quality check.

ignore-qt-format Skip the *Format Qt* quality check.

ignore-qt-plural-format Skip the *Format shumësi Qt* quality check.

ignore-ruby-format Skip the *Format Ruby* quality check.

ignore-scheme-format Skip the *Format Schema* quality check.

ignore-vue-format Skip the *Formatim i18n Vue* quality check.

ignore-translated Skip the *Është përkthyer* quality check.

ignore-inconsistent Skip the *Jo i njëtrajtshëm* quality check.

ignore-kashida Skip the *Është përdorur shkronjë Kashida* quality check.

ignore-md-link Skip the *Lidhje Markdown* quality check.

ignore-md-reflink Skip the *Referenca Markdown* quality check.

ignore-md-syntax Skip the *Sintaksë Markdown* quality check.

ignore-max-length Skip the *Gjatësi maksimum e përkthimit* quality check.

ignore-max-size Skip the *Madhësi maksimum e përkthimit* quality check.

ignore-escaped-newline Skip the *Mospërputhje n* quality check.

ignore-end-colon Skip the *Mospërputhje dy pikash* quality check.

ignore-end-ellipsis Skip the *Mospërputhje tre pikash* quality check.

ignore-end-exclamation Skip the *Mospërputhje pikëçuditjesh* quality check.

ignore-end-stop Skip the *Mospërputhje pike* quality check.

ignore-end-question Skip the *Mospërputhje pikëpyetjesh* quality check.

ignore-end-semicolon Skip the *Mospërputhje pikëpresjesh* quality check.

ignore-newline-count Skip the *Mospërputhje ndërprerjesh rreshti* quality check.

ignore-plurals Skip the *Mungon shumës* quality check.

ignore-placeholders Skip the *Vendmbajtëse* quality check.

ignore-punctuation-spacing Skip the *Hapësirë pikësimi* quality check.

ignore-regex Skip the *Shprehje e rregullt* quality check.

ignore-same-plurals Skip the *Shumës i njëjtë* quality check.

ignore-begin-newline Skip the *Shenjë rresht i ri në fillim* quality check.

ignore-begin-space Skip the *Hapësira fillimi* quality check.

ignore-end-newline Skip the *Shenjë rresht i ri në fund* quality check.

ignore-end-space Skip the *Hapësirë në fund* quality check.

ignore-same Skip the *Përkthim i pandryshuar* quality check.

ignore-safe-html Skip the *HTML jo e parrezik* quality check.

ignore-url Skip the *URL* quality check.

ignore-xml-tags Skip the *Markup XML* quality check.

ignore-xml-invalid Skip the *Sintaksë XML* quality check.

ignore-zero-width-space Skip the *Hapësirë me gjerësi zero* quality check.

ignore-ellipsis Skip the *Tre pika* quality check.

ignore-long-untranslated Skip the *I papërkthyer prej kohësh* quality check.

ignore-multiple-failures Skip the *Dështime të shumta kontrollesh* quality check.

ignore-unnamed-format Skip the *Ndryshore të shumta të paemërtuara* quality check.

ignore-optional-plural Skip the *Pa forma shumësi* quality check.

Shënim: Generally the rule is named `ignore-*` for any check, using its identifier, so you can use this even for your custom checks.

These flags are understood both in *Component configuration* settings, per source string settings and in the translation file itself (for example in GNU gettext).

2.12.3 Enforcing checks

Të reja në versionin 3.11.

You can configure a list of checks which can not be ignored by setting *Kontrolle me detyrim* in *Component configuration*. Each listed check can not be ignored in the user interface and any string failing this check is marked as *Needs editing* (see *Translation states*).

2.12.4 Administrim shkronjash

Të reja në versionin 3.7.

Ndihmëz: Fonts uploaded into Weblate are used purely for purposes of the *Madhësi maksimum e përkthimit* check, they do not have an effect in Weblate user interface.

The *Madhësi maksimum e përkthimit* check used to calculate dimensions of the rendered text needs font to be loaded into Weblate and selected using a translation flag (see *Customizing behavior using flags*).

Weblate font management tool in *Fonts* under the *Manage* menu of your translation project provides interface to upload and manage fonts. TrueType or OpenType fonts can be uploaded, set up font-groups and use those in the check.

The font-groups allow you to define different fonts for different languages, which is typically needed for non-latin languages:

Font group

Name	default-font
Default font	Source Sans 3 Bold
Japanese	language override Droid Sans Fallback Regular Remove
Korean	language override Droid Sans Fallback Regular Remove
Delete	

Add language override

Language

Font

Save

Edit font group

Font group name

Identifier you will use in checks to select this font group. Avoid whitespaces and special characters.


Default font

Default font is used unless per language override matches.

Save

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

The font-groups are identified by name, which can not contain whitespace or special characters, so that it can be easily used in the check definition:

 Weblate Dashboard Projects Languages Checks

WeblateOrg / Fonts

Font groups Fonts

Group name	Default font	Language overrides	
default-font	Source Sans 3 Bold	Japanese: Droid Sans Fallback Regular Korean: Droid Sans Fallback Regular	Edit

Add font group

Font group name

Identifier you will use in checks to select this font group. Avoid whitespaces and special characters.


Default font

Default font is used unless per language override matches.


Save

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

Font-family and style is automatically recognized after uploading them:


 Weblate Dashboard Projects Languages Checks

WeblateOrg / Fonts / Droid Sans Fallback Regular

Font	
Font family	Droid Sans Fallback
Font style	Regular
File size	3939852
Created	now
Uploaded by	 testuser
Used in groups	
Delete	

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

You can have a number of fonts loaded into Weblate:



To use the fonts for checking the string length, pass it the appropriate flags (see *Customizing behavior using flags*). You will probably need the following ones:

max-size:500 Përcakton gjerësinë maksimum.

font-family:ubuntu Defines font group to use by specifying its identifier.

font-size:22 Përcakton madhësi shkronjash.

2.12.5 Si të shkruani kontrollet tuaja

A wide range of quality checks are built-in, (see *Kontrolle cilësie*), though they might not cover everything you want to check. The list of performed checks can be adjusted using *CHECK_LIST*, and you can also add custom checks.

1. Subclass the *weblate.checks.Check*
2. Caktoni ndoca attribute.
3. Implement either the *check* (if you want to deal with plurals in your code) or the *check_single* method (which does it for you).

Disa shembuj:

To install custom checks, provide a fully-qualified path to the Python class in the *CHECK_LIST*, see *Custom quality checks, addons and auto-fixes*.

Checking translation text does not contain «foo»

This is a pretty simple check which just checks whether the translation is missing the string «foo».

```
#
# Copyright © 2012 - 2021 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <https://www.gnu.org/licenses/>.
#
"""Simple quality check example."""

from django.utils.translation import gettext_lazy as _

from weblate.checks.base import TargetCheck

class FooCheck(TargetCheck):

    # Used as identifier for check, should be unique
    # Has to be shorter than 50 characters
    check_id = "foo"

    # Short name used to display failing check
    name = _("Foo check")

    # Description for failing check
    description = _("Your translation is foo")

    # Real check code
    def check_single(self, source, target, unit):
        return "foo" in target
```

Checking that Czech translation text plurals differ

Check using language info to verify the two plural forms in Czech language are not same.

```
#
# Copyright © 2012 - 2021 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <https://www.gnu.org/licenses/>.
#
"""Quality check example for Czech plurals."""

from django.utils.translation import gettext_lazy as _

from weblate.checks.base import TargetCheck
```

(vazhdon në faqen pasuese)


```
class PluralCzechCheck(TargetCheck):

    # Used as identifier for check, should be unique
    # Has to be shorter than 50 characters
    check_id = "foo"

    # Short name used to display failing check
    name = _("Foo check")

    # Description for failing check
    description = _("Your translation is foo")

    # Real check code
    def check_target_unit(self, sources, targets, unit):
        if self.is_language(unit, ("cs",)):
            return targets[1] == targets[2]
        return False

    def check_single(self, source, target, unit):
        """We don't check target strings here."""
        return False
```

2.13 Përkthim nga makina

Built-in support for several machine translation services and can be turned on by the administrator using `MT_SERVICES` for each one. They come subject to their terms of use, so ensure you are allowed to use them how you want.

The source language can be configured at *Project configuration*.

2.13.1 amaGama

Special installation of *tmserver* run by the authors of Virtaal.

Turn on this service by adding `weblate.machinery.tmserver.AmagamaTranslation` to `MT_SERVICES`.

Shihni edhe:

Installing amaGama, Amagama, amaGama Translation Memory

2.13.2 Apertium

A libre software machine translation platform providing translations to a limited set of languages.

The recommended way to use Apertium is to run your own Apertium-APy server.

Turn on this service by adding `weblate.machinery.apertium.ApertiumAPYTranslation` to `MT_SERVICES` and set `MT_APERTIUM_APY`.

Shihni edhe:

`MT_APERTIUM_APY`, Apertium website, Apertium APy documentation

2.13.3 AWS

Të reja në versionin 3.1.

Amazon Translate is a neural machine translation service for translating text to and from English across a breadth of supported languages.

1. Turn on this service by adding `weblate.machinery.aws.AWSTranslation` to `MT_SERVICES`.
2. Install the `boto3` module.
3. Configure Weblate.

Shihni edhe:

`MT_AWS_REGION`, `MT_AWS_ACCESS_KEY_ID`, `MT_AWS_SECRET_ACCESS_KEY` [Amazon Translate Documentation](#)

2.13.4 Baidu API machine translation

Të reja në versionin 3.2.

Machine translation service provided by Baidu.

This service uses an API and you need to obtain an ID and API key from Baidu to use it.

Turn on this service by adding `weblate.machinery.baidu.BaiduTranslation` to `MT_SERVICES` and set `MT_BAIDU_ID` and `MT_BAIDU_SECRET`.

Shihni edhe:

`MT_BAIDU_ID`, `MT_BAIDU_SECRET` [Baidu Translate API](#)

2.13.5 DeepL

Të reja në versionin 2.20.

DeepL is paid service providing good machine translation for a few languages. You need to purchase *DeepL API* subscription or you can use legacy *DeepL Pro (classic)* plan.

Turn on this service by adding `weblate.machinery.deepl.DeepLTranslation` to `MT_SERVICES` and set `MT_DEEPL_KEY`.

Ndihmëz: In case you have subscription for CAT tools, you are supposed to use «v1 API» instead of default «v2» used by Weblate (it is not really an API version in this case). In case you are on a free instead of a paid plan, you have to use `https://api-free.deepl.com/` instead of `https://api.deepl.com/` You can adjust both parameters by `MT_DEEPL_API_URL`.

Shihni edhe:

`MT_DEEPL_KEY`, `MT_DEEPL_API_URL`, [DeepL website](#), [DeepL pricing](#), [DeepL API documentation](#)

2.13.6 LibreTranslate

Të reja në versionin 4.7.1.

LibreTranslate is a free and open-source service for machine translations. The public instance requires an API key, but LibreTranslate can be self-hosted and there are several mirrors available to use the API for free.

Turn on this service by adding `weblate.machinery.libretranslate.LibreTranslateTranslation` to `MT_SERVICES` and set `MT_LIBRETRANSLATE_API_URL`. If your instance requires an API key, you must also set `MT_LIBRETRANSLATE_KEY`.

Shihni edhe:

`MT_LIBRETRANSLATE_KEY`, `MT_LIBRETRANSLATE_API_URL`, LibreTranslate website, LibreTranslate repository, LibreTranslate mirrors

2.13.7 Glosbe

Free dictionary and translation memory for almost every living language.

The API is gratis to use, but subject to the used data source license. There is a limit of calls that may be done from one IP in a set period of time, to prevent abuse.

Turn on this service by adding `weblate.machinery.glosbe.GlosbeTranslation` to `MT_SERVICES`.

Shihni edhe:

Glosbe website

2.13.8 Google Translate

Machine translation service provided by Google.

This service uses the Google Translation API, and you need to obtain an API key and turn on billing in the Google API console.

To turn on this service, add `weblate.machinery.google.GoogleTranslation` to `MT_SERVICES` and set `MT_GOOGLE_KEY`.

Shihni edhe:

`MT_GOOGLE_KEY`, Google translate documentation

2.13.9 Google Translate API V3 (Advanced)

Machine translation service provided by Google Cloud services.

This service differs from the former one in how it authenticates. To enable service, add `weblate.machinery.googlev3.GoogleV3Translation` to `MT_SERVICES` and set

- `MT_GOOGLE_CREDENTIALS`
- `MT_GOOGLE_PROJECT`

If *location* fails, you may also need to specify `MT_GOOGLE_LOCATION`.

Shihni edhe:

`MT_GOOGLE_CREDENTIALS`, `MT_GOOGLE_PROJECT`, `MT_GOOGLE_LOCATION` Google translate documentation

2.13.10 Microsoft Cognitive Services Translator

Të reja në versionin 2.10.

Machine translation service provided by Microsoft in Azure portal as a one of Cognitive Services.

Weblate implements Translator API V3.

To enable this service, add `weblate.machinery.microsoft.MicrosoftCognitiveTranslation` to `MT_SERVICES` and set `MT_MICROSOFT_COGNITIVE_KEY`.

Translator Text API V2

The key you use with Translator API V2 can be used with API 3.

Translator Text API V3

You need to register at Azure portal and use the key you obtain there. With new Azure keys, you also need to set `MT_MICROSOFT_REGION` to locale of your service.

Shihni edhe:

`MT_MICROSOFT_COGNITIVE_KEY`, `MT_MICROSOFT_REGION`, Cognitive Services - Text Translation API, Microsoft Azure Portal

2.13.11 Microsoft Terminology Service

Të reja në versionin 2.19.

The Microsoft Terminology Service API allows you to programmatically access the terminology, definitions and user interface (UI) strings available in the Language Portal through a web service.

Turn this service on by adding `weblate.machinery.microsoftterminology.MicrosoftTerminologyService` to `MT_SERVICES`.

Shihni edhe:

Microsoft Terminology Service API

2.13.12 ModernMT

Të reja në versionin 4.2.

Turn this service on by adding `weblate.machinery.modernmt.ModernMTTranslation` to `MT_SERVICES` and configure `MT_MODERNMT_KEY`.

Shihni edhe:

ModernMT API, `MT_MODERNMT_KEY`, `MT_MODERNMT_URL`

2.13.13 MyMemory

Huge translation memory with machine translation.

Free, anonymous usage is currently limited to 100 requests/day, or to 1000 requests/day when you provide a contact e-mail address in `MT_MYMEMORY_EMAIL`. You can also ask them for more.

Turn on this service by adding `weblate.machinery.mymemory.MyMemoryTranslation` to `MT_SERVICES` and set `MT_MYMEMORY_EMAIL`.

Shihni edhe:

`MT_MYMEMORY_EMAIL`, `MT_MYMEMORY_USER`, `MT_MYMEMORY_KEY`, [MyMemory website](#)

2.13.14 NetEase Sight API machine translation

Të reja në versionin 3.3.

Machine translation service provided by NetEase.

This service uses an API, and you need to obtain key and secret from NetEase.

Turn on this service by adding `weblate.machinery.youdao.NeteaseSightTranslation` to `MT_SERVICES` and set `MT_NETEASE_KEY` and `MT_NETEASE_SECRET`.

Shihni edhe:

`MT_NETEASE_KEY`, `MT_NETEASE_SECRET` [NetEase Sight Translation Platform](#)

2.13.15 tmserver

You can run your own translation memory server by using the one bundled with Translate-toolkit and let Weblate talk to it. You can also use it with an amaGama server, which is an enhanced version of tmserver.

1. First you will want to import some data to the translation memory:
2. Turn on this service by adding `weblate.machinery.tmserver.TMServerTranslation` to `MT_SERVICES`.

```
build_tmdb -d /var/lib/tm/db -s en -t cs locale/cs/LC_MESSAGES/django.po
build_tmdb -d /var/lib/tm/db -s en -t de locale/de/LC_MESSAGES/django.po
build_tmdb -d /var/lib/tm/db -s en -t fr locale/fr/LC_MESSAGES/django.po
```

3. Start tmserver to listen to your requests:

```
tmserver -d /var/lib/tm/db
```

4. Configure Weblate to talk to it:

```
MT_TMSERVER = "http://localhost:8888/tmserver/"
```

Shihni edhe:

`MT_TMSERVER`, [tmserver](#) [Installing amaGama](#), [Amagama](#), [Amagama Translation Memory](#)

2.13.16 Yandex Translate

Machine translation service provided by Yandex.

This service uses a Translation API, and you need to obtain an API key from Yandex.

Turn on this service by adding `weblate.machinery.yandex.YandexTranslation` to `MT_SERVICES`, and set `MT_YANDEX_KEY`.

Shihni edhe:

`MT_YANDEX_KEY`, Yandex Translate API, Powered by Yandex.Translate

2.13.17 Youdao Zhiyun API machine translation

Të reja në versionin 3.2.

Machine translation service provided by Youdao.

This service uses an API, and you need to obtain an ID and an API key from Youdao.

Turn on this service by adding `weblate.machinery.youdao.YoudaoTranslation` to `MT_SERVICES` and set `MT_YOUDAO_ID` and `MT_YOUDAO_SECRET`.

Shihni edhe:

`MT_YOUDAO_ID`, `MT_YOUDAO_SECRET` Youdao Zhiyun Natural Language Translation Service

2.13.18 Weblate

Weblate can be the source of machine translations as well. It is based on the Woosh fulltext engine, and provides both exact and inexact matches.

Turn on these services by adding `weblate.machinery.weblatetm.WeblateTranslation` to `MT_SERVICES`.

2.13.19 Weblate Translation Memory

Të reja në versionin 2.20.

The *Kujtesë Përkthimesh* can be used as a source for machine translation suggestions as well.

Turn on these services by adding `weblate.memory.machine.WeblateMemory` to the `MT_SERVICES`. This service is turned on by default.

2.13.20 SAP Translation Hub

Machine translation service provided by SAP.

You need to have a SAP account (and the SAP Translation Hub enabled in the SAP Cloud Platform) to use this service.

Turn on this service by adding `weblate.machinery.saptranslationhub.SAPTranslationHub` to `MT_SERVICES` and set the appropriate access to either the sandbox or the production API.

Shënim: To access the Sandbox API, you need to set `MT_SAP_BASE_URL` and `MT_SAP_SANDBOX_APIKEY`.

To access the productive API, you need to set `MT_SAP_BASE_URL`, `MT_SAP_USERNAME` and `MT_SAP_PASSWORD`.

Shihni edhe:

`MT_SAP_BASE_URL`, `MT_SAP_SANDBOX_APIKEY`, `MT_SAP_USERNAME`, `MT_SAP_PASSWORD`,
`MT_SAP_USE_MT` SAP Translation Hub API

2.13.21 Custom machine translation

You can also implement your own machine translation services using a few lines of Python code. This example implements machine translation in a fixed list of languages using dictionary Python module:

```
#
# Copyright © 2012 - 2021 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <https://www.gnu.org/licenses/>.
#
"""Machine translation example."""

import dictionary

from weblate.machinery.base import MachineTranslation

class SampleTranslation(MachineTranslation):
    """Sample machine translation interface."""

    name = "Sample"

    def download_languages(self):
        """Return list of languages your machine translation supports."""
        return {"cs"}

    def download_translations(
        self,
        source,
        language,
        text: str,
        unit,
        user,
        search: bool,
        threshold: int = 75,
    ):
        """Return tuple with translations."""
        for t in dictionary.translate(text):
            yield {"text": t, "quality": 100, "service": self.name, "source": text}
```


You can list your own class in `MT_SERVICES` and Weblate will start using that.


2.14 Shtesa

Të reja në versionin 2.19.

Add-ons provide ways to customize and automate the translation workflow. Admins can add and manage add-ons from the *Manage* ↓ *Add-ons* menu of each respective translation component.

Ndihmëz: You can also configure add-ons using [API](#), [DEFAULT_ADDONS](#), or [install_addon](#).



Dashboard
Projects ▾
Languages ▾
Checks ▾
⚙️
+
🌐
...


WebOrg / Language names / Add-ons

Installed add-ons


There are no add-ons currently installed.

Available add-ons


Automatic translation ⓘ

Automatically translates strings using machine translation or other components.


Install


Add missing languages ⓘ

Ensures a consistent set of languages is used for all components within a project.

project wide


Install


Component discovery ⓘ

Automatically adds or removes project components based on file changes in the version control system.


repository wide

Install


Bulk edit ⓘ


Bulk edit flags, labels, or states of strings.

Install


Statistics generator ⓘ


Generates a file containing detailed info about the translation status.

Install


Pseudolocale generation ⓘ


Generates a translation by adding prefix and suffix to source strings automatically.

Install


Contributors in comment ⓘ


Updates the comment part of the PO file header to include contributor names and years of contributions.

Install


Customize gettext output ⓘ


Allows customization of gettext output behavior, for example line wrapping.

Install


Generate MO files ⓘ


Automatically generates a MO file for every changed PO file.

Install


Update PO files to match POT (msgmerge) ⓘ

Updates all PO files (as configured by "Filemask") to match the POT file (as configured by "Template for new translations") using msgmerge.


Install


Squash Git commits ⓘ

Squash Git commits prior to pushing changes.

repository wide


Install


Stale comment removal ⓘ

Set a timeframe for removal of comments.

project wide

Install


Stale suggestion removal ⓘ

Set a timeframe for removal of suggestions.

project wide

Install

Some add-ons will ask for additional configuration during installation.

2.14.1 Built-in add-ons

Përkthim i automatizuar

Të reja në versionin 3.9.

Add-on ID weblate.autotranslate.autotranslate

Formësim

mode	Mënyrë përkthim i automatizuar	
filter_type	Filtër kërkimi	
auto_source	Burim përkthimesh të automatizuara	
component	Përbërës	Aktivizoni kontribut te kujtesë e përbashkët përkthimesh për projektin, që të mund të hyni te përbërës të tjerë.
engines	Motorë përkthimi nga makina	
threshold	Prag vlerësimi	

Events triggering add-on component update, daily

Përkthen automatikisht vargje duke përdorur përkthim nga makina ose nga përbërës të tjerë.

It is triggered:

- When new strings appear in a component.
- Once in a month for every component, this can be configured using `BACKGROUND_TASKS`.

Shihni edhe:

Përkthim i automatizuar, Keeping translations same across components

CDN përkthimesh JavaScript

Të reja në versionin 4.2.

Add-on ID weblate.cdn.cdnjs

Formësim

threshold	Prag përkthimi	Prag për përfshirje përkthimesh.
css_selector	Përzgjedhës CSS	Përzgjedhës CSS për të pikasur elementë të përkthyeshem.
cookie_name	Emër për cookie-n e gjuhës	Emër për cookie-n e cila depoziton parapëlqim gjuhe.
files	Përfto vargje prej kartelash HTML	Listë e emrave të kartelave në depon e tanishme ose URL-ra të largëta që duhen kontrolluar për vargje të përkthyeshem.

Events triggering add-on daily, repository post-commit, repository post-update

Boton përkthime te një rrjet shpërndarjeje lënde për përdorim në përkthime JavaScript-i ose HTML-je.

Can be used to localize static HTML pages, or to load localization in the JavaScript code.

Generates a unique URL for your component you can include in HTML pages to localize them. See weblate-cdn for more details.

Shihni edhe:

cdn-addon-config, weblate-cdn, cdn-addon-extract, cdn-addon-html

Hiqni vargje të zbrazët

Të reja në versionin 4.4.

Add-on ID `weblate.cleanup.blank`

Formësim *This add-on has no configuration.*

Events triggering add-on repository post-commit, repository post-update

Heq nga kartelat e përkthimit vargje pa përkthim.

Use this to not have any empty strings in translation files (for example if your localization library displays them as missing instead of falling back to the source string).

Shihni edhe:

Does Weblate update translation files besides translations?

Spastro kartela përkthimi

Add-on ID `weblate.cleanup.generic`

Formësim *This add-on has no configuration.*

Events triggering add-on repository pre-commit, repository post-update

Përditësoni krejt kartelat e përkthimit që të përputhen me kartelën bazë njëgjuhëshe. Për shumicën e formateve të kartelave, kjo do të thotë heqje zërash të ndenjtur përkthimi, që s'janë më të pranishëm te kartela bazë.

Shihni edhe:

Does Weblate update translation files besides translations?

Add missing languages

Add-on ID `weblate.consistency.languages`

Formësim *This add-on has no configuration.*

Events triggering add-on daily, repository post-add

Siguron përdorimin e një grupi të qëndrueshëm gjuhë për krejt përbërësit brenda një projekti.

Missing languages are checked once every 24 hours, and when new languages are added in Weblate.

Unlike most others, this add-on affects the whole project.

Ndihmëz: Auto-translate the newly added strings with *Përkthim i automatizuar*.

Pikasje përbërësish

Add-on ID `weblate.discovery.discovery`

Formësim

match	Shprehje e rregullt kundrejt të cilës duhen kërkuar përputhje të kartela përkthimi	
file_format	Format kartelash	
name_template	Përshtatni emrin e përbërësit	
base_file_format	Përcaktoni emër kartele bazë njëgjuhëse	Për kartela përkthimi dygjuhëshe, lëreni të zbrazët.
new_base_file_format	Përcaktoni kartelën bazë për përkthime të reja	Emër kartele i kartelës së përdorur për krijim përkthimesh të reja. Për gettext zgjidhni kartelë .pot.
language_regex	Filtër njëgjuhësh	Shprehje e rregullt kundrejt të cilës të filtrohen kartela përkthimi, kur skanohet për filemask.
copy_addon	Klono shtesa prej përbërësit kryesor të të reja të sapokrijuara	
remove	Hiq përbërës për kartela që s'ekzistojnë	
confirm	Ripohoj se përputhjet më sipër duken të sakta	

Events triggering add-on repository post-update

Shton ose heq automatikisht përbërës projekti, bazuar te ndryshime kartelash nën sistem kontrolli versionesh.

Triggered each time the VCS is updated, and otherwise similar to the `import_project` management command. This way you can track multiple translation components within one VCS.

The matching is done using regular expressions enabling complex configuration, but some knowledge is required to do so. Some examples for common use cases can be found in the add-on help section.

Once you hit *Save*, a preview of matching components will be presented, from where you can check whether the configuration actually matches your needs:

Weblate

Dashboard

Projects

Languages

Checks

+

WebOrg

Language names

Add-ons

Component discovery

Configure add-on

Please review and confirm the matched components.

Component	Matched files
The following components would be created	
Djangojs	<div>weblate/locale/cs/LC_MESSAGES/djangojs.po (cs)</div> <div>weblate/locale/he/LC_MESSAGES/djangojs.po (he)</div> <div>weblate/locale/hu/LC_MESSAGES/djangojs.po (hu)</div>
Django	<div>weblate/locale/he/LC_MESSAGES/django.po (he)</div> <div>weblate/locale/hu/LC_MESSAGES/django.po (hu)</div> <div>weblate/locale/cs/LC_MESSAGES/django.po (cs)</div>

☐ I confirm the above matches look correct

Regular expression to match translation files against

weblate/locale/(?P<language>[^\s]*)/LC_MESSAGES/(?P<component>[^\s]*)\.po

File format

gettext PO file

Customize the component name

{{ component|title }}

Define the monolingual base filename

Leave empty for bilingual translation files.

Define the base file for new translations

weblate/locale/{{ component }}.pot

Filename of file used for creating new translations. For gettext choose .pot file.

Language filter

^(cs|he|hu)\$

Regular expression to filter translation files against when scanning for filemask.

☒ Clone addons from the main component to the newly created ones

☐ Remove components for inexistant files

The regular expression to match translation files has to contain two named groups to match component and language, some examples:

Regular expression	Example matched files	Description
(?P<language>[^\s]*)/(?P<component>[^\s]*)\.po	cs/application.po cs/website.po de/application.po de/website.po	One folder per language containing translation files for components.
locale/(?P<language>[^\s]*)/LC_MESSAGES/(?P<component>[^\s]*)\.po	locale/cs/LC_MESSAGES/application.po locale/cs/LC_MESSAGES/website.po locale/de/LC_MESSAGES/application.po locale/de/LC_MESSAGES/website.po	Usual structure for storing gettext PO files.
src/locale/(?P<component>[^\s]*)\. (?P<language>[^\s]*)\.po	src/locale/application.cs.po src/locale/website.cs.po src/locale/application.de.po src/locale/website.de.po	Using both component and language name within filename.
locale/(?P<language>[^\s]*)/(?P<component>[^\s]*)/(?P=language)\.po	locale/cs/application/cs.po locale/cs/website/cs.po locale/de/application/de.po locale/de/website/de.po	Using language in both path and filename.
res/values-(?P<language>[^\s]*)/strings-(?P<component>[^\s]*)\.xml	res/values-cs/strings-about.xml res/values-cs/strings-help.xml res/values-de/strings-about.xml res/values-de/strings-help.xml	Android resource strings, split into several files.

You can use Django template markup in both component name and the monolingual base filename, for example:

{{ component }}

Component filename match

{{ component|title }}

Component filename with upper case first letter

Save

Ndihmëz: Component discovery add-on uses *URL të brendshme Weblate*. It's a convenient way to share VCS setup between multiple components. Linked components use the local repository of the main component set up by filling `weblate://project/main-component` into the *Depo kodi burim* field (in *Manage* ↓ *Settings* ↓ *Version control system*) of each respective component. This saves time with configuration and system resources too.

Shihni edhe:

Template markup

Përpunim në masë

Të reja në versionin 3.11.

Add-on ID `weblate.flags.bulk`

Formësim

q	Kërkesë	
state	Gjendje për t'u caktuar	
add_flags	Flamurka përkthimi për shtim	
remove_flags	Flamurka përkthimi për heqje	
add_labels	Etiketa për shtim	
remove_labels	Etiketa për heqje	

Events triggering add-on component update

Përpunim në masë vargjesh shenjash, etiketash ose gjendjesh.

Automate labeling by starting out with the search query `NOT has:label` and add labels till all strings have all required labels. Other automated operations for Weblate metadata can also be done.

Shembuj:

Tabela 4: Label new strings automatically

Search query	<code>NOT has:label</code>
Etiketa për shtim	<code>recent</code>

Tabela 5: Marking all Kartela tejtëdhënash shitoreje aplikacionesh changelog entries read-only

Search query	<code>language:en AND key:changelogs/</code>
Flamurka përkthimi për shtim	<code>read-only</code>

Shihni edhe:

Përpunim në masë, Customizing behavior using flags, labels

Vëru shenjë përkthimeve të pandryshuara si “Lyp përditësim”

Të reja në versionin 3.1.

Add-on ID `weblate.flags.same_edit`

Formësim *This add-on has no configuration.*

Events triggering add-on `unit post-create`

Kurdo që importohet një varg i ri i përkthyeshem nga VCS-ja dhe përputhet me vargun burim, në Weblate i vihet shenjë si një që ka nevojë të përpunohet. Kjo është veçanërisht e dobishme për formate kartelash që përfshijnë vargje burim për vargjet e papërkthyer.

Ndihmëz: You might also want to tighten the *Përkthim i pandryshuar* check by adding `strict-same` flag to *Flamuj përkthimi*.

Shihni edhe:

Translation states

Vëru shenjë vargjeve të reja burim si “Lyp përditësim”

Add-on ID `weblate.flags.source_edit`

Formësim *This add-on has no configuration.*

Events triggering add-on `unit post-create`

Kurdo që importohet një varg i ri i burim nga VCS-ja, në Weblate i vihet shenjë si “Lyp përpunim”. Në këtë mënyrë mund të filtroni lehtësisht dhe përpunoni vargje burim shkruar nga zhvilluesit.

Shihni edhe:

Translation states

Vëru shenjë përkthimeve të reja si “Lyp përditësim”

Add-on ID `weblate.flags.target_edit`

Formësim *This add-on has no configuration.*

Events triggering add-on `unit post-create`

Kurdo që importohet një varg i ri i përkthyeshem nga VCS-ja, në Weblate i vihet shenjë si “Lyp përpunim”. Në këtë mënyrë mund të filtroni lehtësisht dhe përpunoni vargje të përkthyeshem krijuar nga zhvilluesit.

Shihni edhe:

Translation states

Prodhues statistikash

Add-on ID `weblate.generate.generate`

Formësim

<code>filename</code>	Emër i kartelës së prodhuar	
<code>template</code>	Lëndë e kartelës së prodhuar	

Events triggering add-on `repository pre-commit`

Prodhon një kartelë që përmban të dhëna të hollësishme rreth gjendjes së përkthimit.

You can use a Django template in both filename and content, see [Template markup](#) for a detailed markup description.

For example generating a summary file for each translation:

Emër i kartelës së prodhuar `locale/{{ language_code }}.json`

Lëndë

```
{
  "language": "{{ language_code }}",
  "strings": "{{ stats.all }}",
  "translated": "{{ stats.translated }}",
  "last_changed": "{{ stats.last_changed }}",
  "last_author": "{{ stats.last_author }}"
}
```

Shihni edhe:

[Template markup](#)

Prodhim pseudovendoreje

Add-on ID `weblate.generate.pseudolocale`

Formësim

source	Vargjet e burimit	
target	Përkthimi i synuar	
prefix	Parashtesë vargjesh	
suffix	Prapashtesë vargjesh	

Events triggering add-on component update, daily

Prodhon një përkthim duke shtuar automatikisht parashtesë dhe prapashtesë te vargjet burim.

Pseudolocales are useful to find strings that are not prepared for localization. This is done by altering all translatable source strings to make it easy to spot unaltered strings when running the application in the pseudolocale language.

Finding strings whose localized counterparts might not fit the layout is also possible.

Ndihmëz: You can use real languages for testing, but there are dedicated pseudolocales available in Weblate - `en_XA` and `ar_XB`.

Ndihmëz: You can use this add-on to start translation to a new locale of an existing language or similar language. Once you add the translation to the component, follow to the add-on. *Example:* If you have `fr` and want to start `fr_CA` translation, simply set `fr` as the source, `fr_CA` as the target, and leave the prefix and suffix blank.

Uninstall the add-on once you have the new translation filled to prevent Weblate from changing the translations made after the copying.

Kontribues në koment

Add-on ID `weblate.gettext.authors`

Formësim *This add-on has no configuration.*

Events triggering add-on `repository pre-commit`

Përditëson pjesën e komentit të kryet e kartelës PO, për të përfshirë emrat e kontribuesve dhe vite kontributi.

The PO file header will look like this:

```
# Michal Čihař <michal@cihar.com>, 2012, 2018, 2019, 2020.  
# Pavel Borecki <pavel@example.com>, 2018, 2019.  
# Filip Hron <filip@example.com>, 2018, 2019.  
# anonymous <noreply@weblate.org>, 2019.
```

Përditësoni ndryshoren ALL_LINGUAS te kartela «configure»

Add-on ID `weblate.gettext.configure`

Formësim *This add-on has no configuration.*

Events triggering add-on `repository post-add, daily`

Updates the ALL_LINGUAS variable in `configure`, `configure.in` or any `configure.ac` files, when a new translation is added.

Përshtatni përfundimin e gettext-it

Add-on ID `weblate.gettext.customize`

Formësim

width	Mbështjellje rreshtash të gjatë	Si parazgjedhje, gettext-i i mbështjell rreshtat kur mbërrihet në 77 shenja dhe rreshta të rinj. Me parametrin <code>--no-wrap</code> , mbështjellja kryhet vetëm në rreshta të rinj.
-------	---------------------------------	---

Events triggering add-on `store post-load`

Lejon përshtatje të llojit të përfundimeve nga gettext-i, për shembull, mbështjellje rreshtash.

Ofron mundësitë vijuese:

- Mbështjell rreshtat pas 77 shenjash dhe në rreshta të rinj
- Mbështjell rreshtat vetëm në rreshta të rinj
- Pa mbështjellje rreshtash

Shënim: By default gettext wraps lines at 77 characters and at newlines. With the `--no-wrap` parameter, wrapping is only done at newlines.

Përditëso kartelën LINGUAS

Add-on ID `weblate.gettext.linguas`

Formësim *This add-on has no configuration.*

Events triggering add-on repository post-add, daily

Përditëson kartelën LINGUAS kur shtohet një përkthim i ri.

Prodho kartela MO

Add-on ID `weblate.gettext.mo`

Formësim

path	Shteg për te kartela MO e prodhuar	Nëse s'është përcaktuar, do të përdoret vendndodhja e kartelës PO.
------	------------------------------------	--

Events triggering add-on repository pre-commit

Prodhon automatikisht një kartelë MO për çdo kartelë PO të ndryshuar.

The location of the generated MO file can be customized and the field for it uses *Template markup*.

Përditësoni kartela PO, që të përputhen me POT (msgmerge)

Add-on ID `weblate.gettext.msgmerge`

Formësim

previous	Mba msgid të mëparshëm të vargjeve të përkthyer	
no_location	Hiq vendndodhje vargjes të përkthyer	
fuzzy	Përdor përputhje të turbullt	

Events triggering add-on repository post-update

Updates all PO files (as configured by *File mask*) to match the POT file (as configured by *Gjedhe për përkthime të reja*) using **msgmerge**.

Triggered whenever new changes are pulled from the upstream repository. Most msgmerge command-line options can be set up through the add-on configuration.

Shihni edhe:

Does Weblate update translation files besides translations?

Kryej «squash» për depozitime Git

Add-on ID `weblate.git.squash`

Formësim

squash	Commit squashing	
append	Appends trailers to squashed commit message	Rreshtat mbyllës janë rreshta që duken të ngjashëm me krye RFC 822 email-esh, në fund të pjesës që ndryshe do të ishte në formë të lirë, te një mesazh depozitimi, bie fjala, “Me bashkëautorësinë e: ...”.
commit	Commit message	This commit message will be used instead of the combined commit messages from the squashed commits.

Events triggering add-on repository post-commit

Kryej «squash» për depozitime Git, përpara kryerjes së push-it për ndryshimet.

Git commits can be squashed prior to pushing changes in one of the following modes:

Të reja në versionin 3.4.

- Krejt depozitimet në një të tilli
- Për gjuhë
- Për kartelë

Të reja në versionin 3.5.

- Për autor

Mesazhet origjinale të depozitimeve mbahen, por autorësia humb, veç në qoftë përzgjedhur *Për autor*, ose mesazhi i depozitimit është përshtatur për ta përmbajtur atë.

Të reja në versionin 4.1.

The original commit messages can optionally be overridden with a custom commit message.

Trailers (commit lines like `Co-authored-by: ...`) can optionally be removed from the original commit messages and appended to the end of the squashed commit message. This also generates proper `Co-authored-by: credit` for every translator.

Përshtatni përfundim JSON-i

Add-on ID `weblate.json.customize`

Formësim

<code>sort_keys</code>	Rendit kyçe JSON	
<code>indent</code>	Hapësirë kryeradhe JSON	

Events triggering add-on store post-load

Lejon përshtatje të sjelljes së JSON-it për përfundimet, për shembull, lidhur me shmangie kryeradhe ose renditje.

Formaton kartelën e vetive Java

Add-on ID `weblate.properties.sort`

Formësim *This add-on has no configuration.*

Events triggering add-on repository pre-commit

Rendit kartelën e vetive Java.

Heqje komentesh të vjetruar

Të reja në versionin 3.7.

Add-on ID `weblate.removal.comments`

Formësim

age	Ditë për t'u mbajtur	
-----	----------------------	--

Events triggering add-on daily

Caktoni kohë për heqje komentesh.

This can be useful to remove old comments which might have become outdated. Use with care as comments getting old does not mean they have lost their importance.

Heqje sugjerimesh të vjetruar

Të reja në versionin 3.7.

Add-on ID `weblate.removal.suggestions`

Formësim

age	Ditë për t'u mbajtur	
votes	Prag votimi	Prag për heqje. Kjo fushë s'do të ketë efekt kur votimi është i çaktivizuar.

Events triggering add-on daily

Caktoni kohë për heqje sugjerimesh.

Can be very useful in connection with suggestion voting (see [Peer review](#)) to remove suggestions which don't receive enough positive votes in a given timeframe.

Përditësoni kartela RESX

Të reja në versionin 3.9.

Add-on ID `weblate.resx.update`

Formësim *This add-on has no configuration.*

Events triggering add-on repository post-update

Përditëso krejt kartelat e përkthimit për t'i përputhur me kartelën bazë njëgjueshe të upstream-it. Kartelat e papërdorura hiqen, dhe të reja shtohen si kopje të vargjeve burim.

Ndihmëz: Use *Spastro kartela përkthimi* if you only want to remove stale translation keys.

Shihni edhe:

Does Weblate update translation files besides translations?

Përshtatni përfundim YAML

Të reja në versionin 3.10.2.

Add-on ID `weblate.yaml.customize`

Formësim

<code>indent</code>	Hapësirë kryeradhe YAML	
<code>width</code>	Mbështjellje rreshtash të gjatë	
<code>line_break</code>	Ndërprerje rreshtash	

Events triggering add-on `store post-load`

Lejon përshtatje të sjelljes së YAML-it për përfundimet, për shembull, lidhur me gjatësi rreshti ose rreshta të rinj.

2.14.2 Customizing list of add-ons

The list of add-ons is configured by `WEBLATE_ADDONS`. To add another add-on, simply include the absolute class name in this setting.

2.14.3 Writing add-on

You can write your own add-ons too, create a subclass of `weblate.addons.base.BaseAddon` to define the addon metadata, and then implement a callback to do the processing.

Shihni edhe:

Developing addons

2.14.4 Executing scripts from add-on

Add-ons can also be used to execute external scripts. This used to be integrated in Weblate, but now you have to write some code to wrap your script with an add-on.

```
#
# Copyright © 2012 - 2021 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <https://www.gnu.org/licenses/>.
#
"""Example pre commit script."""
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

from django.utils.translation import gettext_lazy as _

from weblate.addons.events import EVENT_PRE_COMMIT
from weblate.addons.scripts import BaseScriptAddon

class ExamplePreAddon(BaseScriptAddon):
    # Event used to trigger the script
    events = (EVENT_PRE_COMMIT,)
    # Name of the addon, has to be unique
    name = "weblate.example.pre"
    # Verbose name and long description
    verbose = _("Execute script before commit")
    description = _("This addon executes a script.")

    # Script to execute
    script = "/bin/true"
    # File to add in commit (for pre commit event)
    # does not have to be set
    add_file = "po/{{ language_code }}.po"

```

For installation instructions see *Custom quality checks, addons and auto-fixes*.

The script is executed with the current directory set to the root of the VCS repository for any given component.

Additionally, the following environment variables are available:

WL_VCS

Sistem kontrolli versionesh i përdorur.

WL_REPO

Upstream repository URL.

WL_PATH

Shteg absolut për te depo VCS.

WL_BRANCH

Të reja në versionin 2.11.

Repository branch configured in the current component.

WL_FILEMASK

Filemask for current component.

WL_TEMPLATE

Filename of template for monolingual translations (can be empty).

WL_NEW_BASE

Të reja në versionin 2.14.

Filename of the file used for creating new translations (can be empty).

WL_FILE_FORMAT

File format used in current component.

WL_LANGUAGE

Language of currently processed translation (not available for component-level hooks).

WL_PREVIOUS_HEAD

Previous HEAD after update (only available after running the post-update hook).

WL_COMPONENT_SLUG

Të reja në versionin 3.9.

Identifikues përbërësi i përdorur për të ndërtuar URL-në.

WL_PROJECT_SLUG

Të reja në versionin 3.9.

Identifikues projekti i përdorur për të ndërtuar URL-në.

WL_COMPONENT_NAME

Të reja në versionin 3.9.

Emër përbërësi.

WL_PROJECT_NAME

Të reja në versionin 3.9.

Emër projekti.

WL_COMPONENT_URL

Të reja në versionin 3.9.

URL përbërësi.

WL_ENGAGE_URL

Të reja në versionin 3.9.

Project engage URL.

Shihni edhe:

Component configuration

Post-update repository processing

Can be used to update translation files when the VCS upstream source changes. To achieve this, please remember Weblate only sees files committed to the VCS, so you need to commit changes as a part of the script.

For example with Gulp you can do it using following code:

```
#!/bin/sh
gulp --gulpfile gulp-i18n-extract.js
git commit -m 'Update source strings' src/languages/en.lang.json
```

Pre-commit processing of translations

Use the commit script to automatically change a translation before it is committed to the repository.

It is passed as a single parameter consisting of the filename of a current translation.

2.15 Kujtesë Përkthimesh

Të reja në versionin 2.20.

Weblate comes with a built-in translation memory consisting of the following:

- Manually imported translation memory (see *User interface*).
- Automatically stored translations performed in Weblate (depending on *Translation memory scopes*).
- Automatically imported past translations.

Content in the translation memory can be applied one of two ways:

- Manually, *Sugjerime të automatizuara* view while translating.
- Automatically, by translating strings using *Përkthim i automatizuar*, or *Përkthim i automatizuar* addon.

For installation tips, see *Weblate Translation Memory*, which is turned on by default.

2.15.1 Translation memory scopes

Të reja në versionin 3.2: In earlier versions translation memory could be only loaded from a file corresponding to the current imported translation memory scope.

The translation memory scopes are there to allow both privacy and sharing of translations, to suit the desired behavior.

Imported translation memory

Importing arbitrary translation memory data using the `import_memory` command makes memory content available to all users and projects.

Per user translation memory

Stores all user translations automatically in the personal translation memory of each respective user.

Per project translation memory

All translations within a project are automatically stored in a project translation memory only available for this project.

Kujtesë përkthimesh e përbashkët

All translation within projects with shared translation memory turned on are stored in a shared translation memory available to all projects.

Please consider carefully whether to turn this feature on for shared Weblate installations, as it can have severe implications:

- The translations can be used by anybody else.
- This might lead to disclosing secret information.

2.15.2 Managing translation memory

User interface

Të reja në versionin 3.2.

In the basic user interface you can manage per user and per project translation memories. It can be used to download, wipe or import translation memory.

Ndihmëz: Translation memory in JSON can be imported into Weblate, TMX is provided for interoperability with other tools.

Shihni edhe:

Weblate Translation Memory Schema

testuser / Translation memory

Translation memory status ⓘ

Number of your entries	0	Download as JSON	Download as TMX	Delete
Total number of entries	0			

Import translation memory

File

No file chosen

You can upload a TMX or JSON file.

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

Ndërfaqe administrimi

There are several management commands to manipulate the translation memory content. These operate on the translation memory as whole, unfiltered by scopes (unless requested by parameters):

dump_memory Exports the memory into JSON

import_memory Imports TMX or JSON files into the translation memory

2.16 Formësim

All settings are stored in `settings.py` (as is usual for Django).

Shënim: After changing any of these settings, you need to restart Weblate - both WSGI and Celery processes.

In case it is run as `mod_wsgi`, you need to restart Apache to reload the configuration.

Shihni edhe:

Please also check [Django's documentation](#) for parameters configuring Django itself.

2.16.1 AKISMET_API_KEY

Weblate can use Akismet to check incoming anonymous suggestions for spam. Visit akismet.com to purchase an API key and associate it with a site.

2.16.2 ANONYMOUS_USER_NAME

Emër përdoruesi për përdorues që nuk kanë bërë hyrjen.

Shihni edhe:

Kontroll hyrjesh

2.16.3 AUDITLOG_EXPIRY

Të reja në versionin 3.6.

How many days Weblate should keep audit logs, which contain info about account activity.

180 ditë, si parazgjedhje..

2.16.4 AUTH_LOCK_ATTEMPTS

Të reja në versionin 2.14.

Maximum number of failed authentication attempts before rate limiting is applied.

This is currently applied in the following locations:

- Logins. Deletes the account password, preventing the user from signing in without requesting a new password.
- Password resets. Prevents new e-mails from being sent, avoiding spamming users with too many password reset attempts.

10, si parazgjedhje.

Shihni edhe:

Rate limiting,

2.16.5 AUTO_UPDATE

Të reja në versionin 3.2.

Ndryshuar në versionin 3.11: The original on/off option was changed to differentiate which strings are accepted.

Updates all repositories on a daily basis.

Ndihmëz: Useful if you are not using *Hook-e njoftimesh* to update Weblate repositories automatically.

Shënim: On/off options exist in addition to string selection for backward compatibility.

Mundësitë janë:

"none" Pa përditësime të përditshme.

"remote" also False Vetëm përditësime të largëta.

"full" also True Update remotes and merge working copy.

Shënim: This requires that *Background tasks using Celery* is working, and will take effect after it is restarted.

2.16.6 AVATAR_URL_PREFIX

Prefix for constructing avatar URLs as: `${AVATAR_URL_PREFIX}/avatar/${MAIL_HASH}?${PARAMS}`. The following services are known to work:

Gravatar (default), as per <https://gravatar.com/> `AVATAR_URL_PREFIX` = `'https://www.gravatar.com/'`

Libravatar, sipas <https://www.libravatar.org/> `AVATAR_URL_PREFIX` = `'https://www.libravatar.org/'`

Shihni edhe:

Avatar caching, `ENABLE_AVATARS`, `Avatars`

2.16.7 AUTH_TOKEN_VALID

Të reja në versionin 2.14.

How long the authentication token and temporary password from password reset e-mails is valid for. Set in number of seconds, defaulting to 172800 (2 days).

2.16.8 AUTH_PASSWORD_DAYS

Të reja në versionin 2.15.

How many days using the same password should be allowed.

Shënim: Password changes made prior to Weblate 2.15 will not be accounted for in this policy.

180 ditë, si parazgjedhje..

2.16.9 AUTOFIX_LIST

List of automatic fixes to apply when saving a string.

Shënim: Provide a fully-qualified path to the Python class that implementing the autofixer interface.

Ndreqje të mundshme:

`weblate.trans.autofixes.whitespace.SameBookendingWhitespace` Matches whitespace at the start and end of the string to the source.

`weblate.trans.autofixes.chars.ReplaceTrailingDotsWithEllipsis` Replaces trailing dots (...) if the source string has a corresponding ellipsis (...).

`weblate.trans.autofixes.chars.RemoveZeroSpace` Removes zero-width space characters if the source does not contain any.

`weblate.trans.autofixes.chars.RemoveControlChars` Removes control characters if the source does not contain any.

`weblate.trans.autofixes.html.BleachHTML` Removes unsafe HTML markup from strings flagged as `safe-html` (see *HTML jo e parrezik*).

You can select which ones to use:

```
AUTOFIX_LIST = (  
    "weblate.trans.autofixes.whitespace.SameBookendingWhitespace",  
    "weblate.trans.autofixes.chars.ReplaceTrailingDotsWithEllipsis",  
)
```

Shihni edhe:

Automatic fixups, Custom automatic fixups

2.16.10 BACKGROUND_TASKS

Të reja në versionin 4.5.2.

Defines how often lengthy maintenance tasks should be triggered for a component.

Right now this controls:

- *Përkthim i automatizuar* addon
- *Checks and fixups* recalculation

Possible choices:

- monthly (this is the default)
- weekly
- daily
- never

Shënim: Increasing the frequency is not recommended when Weblate contains thousands of components.

2.16.11 BASE_DIR

Base directory where Weblate sources are located. Used to derive several other paths by default:

- *DATA_DIR*

Default value: Top level directory of Weblate sources.

2.16.12 BASIC_LANGUAGES

Të reja në versionin 4.4.

List of languages to offer users for starting new translation. When not specified built-in list is used which includes all commonly used languages, but without country specific variants.

This only limits non privileged users to add unwanted languages. The project admins are still presented with full selection of languages defined in Weblate.

Shënim: This does not define new languages for Weblate, it only filters existing ones in the database.

Example:

```
BASIC_LANGUAGES = {"cs", "it", "ja", "en"}
```

Shihni edhe:

Language definitions

2.16.13 CSP_SCRIPT_SRC, CSP_IMG_SRC, CSP_CONNECT_SRC, CSP_STYLE_SRC, CSP_FONT_SRC

Customize Content-Security-Policy header for Weblate. The header is automatically generated based on enabled integrations with third-party services (Matomo, Google Analytics, Sentry, ...).

All these default to empty list.

Example:

```
# Enable Cloudflare Javascript optimizations
CSP_SCRIPT_SRC = ["ajax.cloudflare.com"]
```

Shihni edhe:

Content security policy, Content Security Policy (CSP)

2.16.14 CHECK_LIST

List of quality checks to perform on a translation.

Shënim: Provide a fully-qualified path to the Python class implementing the check interface.

Adjust the list of checks to include ones relevant to you.

All built-in *Kontrolle cilësie* are turned on by default, from where you can change these settings. By default they are commented out in *Sample configuration* so that default values are used. New checks then carried out for each new Weblate version.

Mund të çaktivizoni krejt kontrollet:

```
CHECK_LIST = ()
```

Mund të aktivizoni vetë, pak prej tyre:

```
CHECK_LIST = (
    "weblate.checks.chars.BeginNewlineCheck",
    "weblate.checks.chars.EndNewlineCheck",
    "weblate.checks.chars.MaxLengthCheck",
)
```

Shënim: Changing this setting only affects newly changed translations, existing checks will still be stored in the database. To also apply changes to the stored translations, run *updatechecks*.

Shihni edhe:

Kontrolle cilësie, Customizing behavior using flags

2.16.15 COMMENT_CLEANUP_DAYS

Të reja në versionin 3.6.

Delete comments after a given number of days. Defaults to `None`, meaning no deletion at all.

2.16.16 COMMIT_PENDING_HOURS

Të reja në versionin 2.10.

Number of hours between committing pending changes by way of the background task.

Shihni edhe:

Component configuration, Moshë ndryshimesh për depozitim, Xhirim aktesh mirëmbajtjeje, commit_pending

2.16.17 CONTACT_FORM

Të reja në versionin 4.6.

Configures how e-mail from the contact form is being sent. Choose a configuration that matches your mail server configuration.

"reply-to" The sender is used in as *Reply-To*, this is the default behaviour.

"from" The sender is used in as *From*. Your mail server needs to allow sending such e-mails.

2.16.18 DATA_DIR

The folder Weblate stores all data in. It contains links to VCS repositories, a fulltext index and various configuration files for external tools.

Zakonisht ekzistojnë nëndrejtoritë vijuese:

home Home directory used for invoking scripts.

ssh Kyçe dhe formësim SSH-je.

static Default location for static Django files, specified by `STATIC_ROOT`. See *Serving static files*.

The Docker container uses a separate volume for this, see *Docker container volumes*.

media Default location for Django media files, specified by `MEDIA_ROOT`. Contains uploaded screenshots, see *Visual context for strings*.

vcs Version control repositories for translations.

backups Daily backup data, please check *Dumped data for backups* for details.

celery Celery scheduler data, see *Background tasks using Celery*.

fonts: User-uploaded fonts, see *Administrim shkronjash*.

Shënim: This directory has to be writable by Weblate. Running it as uWSGI means the `www-data` user should have write access to it.

The easiest way to achieve this is to make the user the owner of the directory:

```
sudo chown www-data:www-data -R $DATA_DIR
```

`$BASE_DIR/data`, si parazgjedhje.

Shihni edhe:

BASE_DIR, Leje sistemi kartelash, Kopjeruajtje dhe zhvendosje e Weblate

2.16.19 DATABASE_BACKUP

Të reja në versionin 3.1.

Whether the database backups should be stored as plain text, compressed or skipped. The authorized values are:

- "plain"
- "compressed"
- "none"

Shihni edhe:

Kopjeruajtje dhe zhvendosje e Weblate

2.16.20 DEFAULT_ACCESS_CONTROL

Të reja në versionin 3.3.

The default access control setting for new projects:

0 *Public*

1 *Protected*

100 *Private*

200 *Custom*

Use *Custom* if you are managing ACL manually, which means not relying on the internal Weblate management.

Shihni edhe:

Kontroll hyrjesh te projekti, Kontroll hyrjesh

2.16.21 DEFAULT_AUTO_WATCH

Të reja në versionin 4.5.

Configures whether *Automatically watch projects on contribution* should be turned on for new users. Defaults to `True`.

Shihni edhe:

Njoftime

2.16.22 DEFAULT_RESTRICTED_COMPONENT

Të reja në versionin 4.1.

Vlera parazgjedhje për kufizim përbërësish.

Shihni edhe:

Restricted access, Scope of groups

2.16.23 DEFAULT_ADD_MESSAGE, DEFAULT_COMMIT_MESSAGE, DEFAULT_MERGE_MESSAGE

DEFAULT_ADDON_MESSAGE, DEFAULT_DELETE_MESSAGE,

Default commit messages for different operations, please check *Component configuration* for details.

Shihni edhe:

Template markup, Component configuration, Commit, add, delete, merge and addon messages

2.16.24 DEFAULT_ADDONS

Default addons to install on every created component.

Shënim: This setting affects only newly created components.

Shembull:

```
DEFAULT_ADDONS = {
    # Add-on with no parameters
    "weblate.flags.target_edit": {},
    # Add-on with parameters
    "weblate.autotranslate.autotranslate": {
        "mode": "suggest",
        "filter_type": "todo",
        "auto_source": "mt",
        "component": "",
        "engines": ["weblate-translation-memory"],
        "threshold": "80",
    },
}
```

Shihni edhe:

install_addon, Shtesa, WEBLATE_ADDONS

2.16.25 DEFAULT_COMMITER_EMAIL

Të reja në versionin 2.4.

Committer e-mail address defaulting to noreply@weblate.org.

Shihni edhe:

DEFAULT_COMMITER_NAME

2.16.26 DEFAULT_COMMITER_NAME

Të reja në versionin 2.4.

Committer name defaulting to Weblate.

Shihni edhe:

DEFAULT_COMMITER_EMAIL

2.16.27 DEFAULT_LANGUAGE

Të reja në versionin 4.3.2.

Default source language to use for example in *Gjuhë burimi*.

Defaults to *en*. The matching language object needs to exist in the database.

Shihni edhe:

Language definitions, Gjuhë burimi

2.16.28 DEFAULT_MERGE_STYLE

Të reja në versionin 3.4.

Merge style for any new components.

- *rebase* - default
- *merge*

Shihni edhe:

Component configuration, Stil përzierjeje

2.16.29 DEFAULT_SHARED_TM

Të reja në versionin 3.2.

Configures default value of *Përdor kujtesë përkthimesh të përbashkët* and *Kontribuoni te kujtesë përkthimesh të përbashkët*.

2.16.30 DEFAULT_TRANSLATION_PROPAGATION

Të reja në versionin 2.5.

Default setting for translation propagation, defaults to `True`.

Shihni edhe:

Component configuration, Lejo përhapje përkthimesh

2.16.31 DEFAULT_PULL_MESSAGE

Title for new pull requests, defaulting to 'Update from Weblate'.

2.16.32 ENABLE_AVATARS

Whether to turn on Gravatar-based avatars for users. By default this is on.

Avatars are fetched and cached on the server, lowering the risk of leaking private info, speeding up the user experience.

Shihni edhe:

Avatar caching, AVATAR_URL_PREFIX, Avatars

2.16.33 ENABLE_HOOKS

Whether to enable anonymous remote hooks.

Shihni edhe:

Hook-e njoftimesh

2.16.34 ENABLE_HTTPS

Whether to send links to Weblate as HTTPS or HTTP. This setting affects sent e-mails and generated absolute URLs.

In the default configuration this is also used for several Django settings related to HTTPS - it enables secure cookies, toggles HSTS or enables redirection to HTTPS URL.

The HTTPS redirection might be problematic in some cases and you might hit issue with infinite redirection in case you are using a reverse proxy doing SSL termination which does not correctly pass protocol headers to Django. Please tweak your reverse proxy configuration to emit `X-Forwarded-Proto` or `Forwarded` headers or configure `SECURE_PROXY_SSL_HEADER` to let Django correctly detect the SSL status.

Shihni edhe:

`SESSION_COOKIE_SECURE,` `CSRF_COOKIE_SECURE,` `SECURE_SSL_REDIRECT,`
`SECURE_PROXY_SSL_HEADER` *Set correct site domain*

2.16.35 ENABLE_SHARING

Turn on/off the *Share* menu so users can share translation progress on social networks.

2.16.36 GET_HELP_URL

Të reja në versionin 4.5.2.

URL where support for your Weblate instance can be found.

2.16.37 GITLAB_CREDENTIALS

Të reja në versionin 4.3.

List for credentials for GitLab servers.

Ndihmëz: Use this in case you want Weblate to interact with more of them, for single GitLab endpoint stick with `GITLAB_USERNAME` and `GITLAB_TOKEN`.

```
GITLAB_CREDENTIALS = {
    "gitlab.com": {
        "username": "weblate",
        "token": "your-api-token",
    },
    "gitlab.example.com": {
        "username": "weblate",
        "token": "another-api-token",
    },
}
```

2.16.38 GITLAB_USERNAME

GitLab username used to send merge requests for translation updates.

Shihni edhe:

GITLAB_CREDENTIALS, *GitLab*

2.16.39 GITLAB_TOKEN

Të reja në versionin 4.3.

GitLab personal access token used to make API calls for translation updates.

Shihni edhe:

GITLAB_CREDENTIALS, *GitLab*, GitLab: Personal access token

2.16.40 GITHUB_CREDENTIALS

Të reja në versionin 4.3.

List for credentials for GitHub servers.

Ndihmëz: Use this in case you want Weblate to interact with more of them, for single GitHub endpoint stick with *GITHUB_USERNAME* and *GITHUB_TOKEN*.

```
GITHUB_CREDENTIALS = {
  "api.github.com": {
    "username": "weblate",
    "token": "your-api-token",
  },
  "github.example.com": {
    "username": "weblate",
    "token": "another-api-token",
  },
}
```

2.16.41 GITHUB_USERNAME

GitHub username used to send pull requests for translation updates.

Shihni edhe:

GITHUB_CREDENTIALS, *GitHub*

2.16.42 GITHUB_TOKEN

Të reja në versionin 4.3.

GitHub personal access token used to make API calls to send pull requests for translation updates.

Shihni edhe:

GITHUB_CREDENTIALS, *GitHub*, Creating a GitHub personal access token

2.16.43 GOOGLE_ANALYTICS_ID

Google Analytics ID to turn on monitoring of Weblate using Google Analytics.

2.16.44 HIDE_REPO_CREDENTIALS

Hide repository credentials from the web interface. In case you have repository URL with user and password, Weblate will hide it when related info is shown to users.

For example instead of `https://user:password@git.example.com/repo.git` it will show just `https://git.example.com/repo.git`. It tries to clean up VCS error messages too in a similar manner.

Shënim: Kjo është e aktivizuar, si parazgjedhje.

2.16.45 HIDE_VERSION

Të reja në versionin 4.3.1.

Hides version information from unauthenticated users. This also makes all documentation links point to latest version instead of the documentation matching currently installed version.

Hiding version is recommended security practice in some corporations, but it doesn't prevent attacker to figure out version by probing the behavior.

Shënim: Kjo është e çaktivizuar, si parazgjedhje.

2.16.46 IP_BEHIND_REVERSE_PROXY

Të reja në versionin 2.14.

Indicates whether Weblate is running behind a reverse proxy.

If set to `True`, Weblate gets IP address from a header defined by `IP_PROXY_HEADER`.

Sinjalizim: Ensure you are actually using a reverse proxy and that it sets this header, otherwise users will be able to fake the IP address.

Shënim: Kjo s'është e aktivizuar, si parazgjedhje.

Shihni edhe:

Running behind reverse proxy, Rate limiting, IP_PROXY_HEADER, IP_PROXY_OFFSET

2.16.47 IP_PROXY_HEADER

Të reja në versionin 2.14.

Indicates which header Weblate should obtain the IP address from when `IP_BEHIND_REVERSE_PROXY` is turned on.

Defaults to `HTTP_X_FORWARDED_FOR`.

Shihni edhe:

Running behind reverse proxy, *Rate limiting*, `SECURE_PROXY_SSL_HEADER`, `IP_BEHIND_REVERSE_PROXY`, `IP_PROXY_OFFSET`

2.16.48 IP_PROXY_OFFSET

Të reja në versionin 2.14.

Indicates which part of `IP_PROXY_HEADER` is used as client IP address.

Depending on your setup, this header might consist of several IP addresses, (for example `X-Forwarded-For: a, b, client-ip`) and you can configure which address from the header is used as client IP address here.

Sinjalizim: Setting this affects the security of your installation, you should only configure it to use trusted proxies for determining IP address.

0, si parazgjedhje.

Shihni edhe:

Running behind reverse proxy, *Rate limiting*, `SECURE_PROXY_SSL_HEADER`, `IP_BEHIND_REVERSE_PROXY`, `IP_PROXY_HEADER`

2.16.49 LEGAL_URL

Të reja në versionin 3.5.

URL where your Weblate instance shows its legal documents.

Ndihmëz: Useful if you host your legal documents outside Weblate for embedding them inside Weblate, please check *Ligjore* for details.

Shembull:

```
LEGAL_URL = "https://weblate.org/terms/"
```

2.16.50 LICENSE_EXTRA

Additional licenses to include in the license choices.

Shënim: Each license definition should be tuple of its short name, a long name and an URL.

Për shembull:

```

LICENSE_EXTRA = [
    (
        "AGPL-3.0",
        "GNU Affero General Public License v3.0",
        "https://www.gnu.org/licenses/agpl-3.0-standalone.html",
    ),
]

```

2.16.51 LICENSE_FILTER

Ndryshuar në versionin 4.3: Setting this to blank value now disables license alert.

Filter list of licenses to show. This also disables the license alert when set to empty.

Shënim: This filter uses the short license names.

Për shembull:

```

LICENSE_FILTER = {"AGPL-3.0", "GPL-3.0-or-later"}

```

Following disables the license alert:

```

LICENSE_FILTER = set()

```

Shihni edhe:

alerts

2.16.52 LICENSE_REQUIRED

Defines whether the license attribute in *Component configuration* is required.

Shënim: This is off by default.

2.16.53 LIMIT_TRANSLATION_LENGTH_BY_SOURCE_LENGTH

Whether the length of a given translation should be limited. The restriction is the length of the source string * 10 characters.

Ndihmëz: Set this to `False` to allow longer translations (up to 10.000 characters) irrespective of source string length.

Shënim: `True`, si parazgjedhje.

2.16.54 LOCALIZE_CDN_URL and LOCALIZE_CDN_PATH

These settings configure the *CDN përthimesh JavaScript* addon. *LOCALIZE_CDN_URL* defines root URL where the localization CDN is available and *LOCALIZE_CDN_PATH* defines path where Weblate should store generated files which will be served at the *LOCALIZE_CDN_URL*.

Ndihmëz: On Hosted Weblate, this uses `https://weblate-cdn.com/`.

Shihni edhe:

CDN përthimesh JavaScript

2.16.55 LOGIN_REQUIRED_URLS

A list of URLs you want to require logging into. (Besides the standard rules built into Weblate).

Ndihmëz: This allows you to password protect a whole installation using:

```
LOGIN_REQUIRED_URLS = (r"/(.*)$",)
REST_FRAMEWORK["DEFAULT_PERMISSION_CLASSES"] = [
    "rest_framework.permissions.IsAuthenticated"
]
```

Ndihmëz: It is desirable to lock down API access as well, as shown in the above example.

Shihni edhe:

REQUIRE_LOGIN

2.16.56 LOGIN_REQUIRED_URLS_EXCEPTIONS

List of exceptions for *LOGIN_REQUIRED_URLS*. If not specified, users are allowed to access the sign in page.

Some of exceptions you might want to include:

```
LOGIN_REQUIRED_URLS_EXCEPTIONS = (
    r"/accounts/(.*)$", # Required for sign in
    r"/static/(.*)$", # Required for development mode
    r"/widgets/(.*)$", # Allowing public access to widgets
    r"/data/(.*)$", # Allowing public access to data exports
    r"/hooks/(.*)$", # Allowing public access to notification hooks
    r"/api/(.*)$", # Allowing access to API
    r"/js/i18n/$", # JavaScript localization
)
```

2.16.57 MATOMO_SITE_ID

ID of a site in Matomo (formerly Piwik) you want to track.

Shënim: This integration does not support the Matomo Tag Manager.

Shihni edhe:

MATOMO_URL

2.16.58 MATOMO_URL

Full URL (including trailing slash) of a Matomo (formerly Piwik) installation you want to use to track Weblate use. Please check <<https://matomo.org/>> for more details.

Ndihmëz: This integration does not support the Matomo Tag Manager.

Për shembull:

```
MATOMO_SITE_ID = 1
MATOMO_URL = "https://example.matomo.cloud/"
```

Shihni edhe:

MATOMO_SITE_ID

2.16.59 MT_SERVICES

Ndryshuar në versionin 3.0: The setting was renamed from MACHINE_TRANSLATION_SERVICES to MT_SERVICES to be consistent with other machine translation settings.

List of enabled machine translation services to use.

Shënim: Many of the services need additional configuration like API keys, please check their documentation *Përkthim nga makina* for more details.

Ndihmëz: When using Docker container, this configuration is automatically generated based on provided API keys, see *Rregullime mbi përkthim nga makina*.

```
MT_SERVICES = (
    "weblate.machinery.apertium.ApertiumAPYTranslation",
    "weblate.machinery.deepl.DeepLTranslation",
    "weblate.machinery.glosbe.GlosbeTranslation",
    "weblate.machinery.google.GoogleTranslation",
    "weblate.machinery.libretranslate.LibreTranslateTranslation",
    "weblate.machinery.microsoft.MicrosoftCognitiveTranslation",
    "weblate.machinery.microsoftterminology.MicrosoftTerminologyService",
    "weblate.machinery.mymemory.MyMemoryTranslation",
    "weblate.machinery.tmserver.AmagamaTranslation",
    "weblate.machinery.tmserver.TMServerTranslation",
    "weblate.machinery.yandex.YandexTranslation",
    "weblate.machinery.weblatetm.WeblateTranslation",
    "weblate.machinery.saptranslationhub.SAPTranslationHub",
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
"weblate.memory.machine.WeblateMemory",  
)
```

Shihni edhe:

Përkthim nga makina, Sugjerime të automatizuara

2.16.60 MT_APERTIUM_APY

URL of the Apertium-APy server, <https://wiki.apertium.org/wiki/Apertium-apy>

Shihni edhe:

Apertium, Përkthim nga makina, Sugjerime të automatizuara

2.16.61 MT_AWS_ACCESS_KEY_ID

Access key ID for Amazon Translate.

Shihni edhe:

AWS, Përkthim nga makina, Sugjerime të automatizuara

2.16.62 MT_AWS_SECRET_ACCESS_KEY

Kyç API i fshehtë për në Amazon Translate.

Shihni edhe:

AWS, Përkthim nga makina, Sugjerime të automatizuara

2.16.63 MT_AWS_REGION

Emër rajoni për t'u përdorur për Amazon Translate.

Shihni edhe:

AWS, Përkthim nga makina, Sugjerime të automatizuara

2.16.64 MT_Baidu_ID

Client ID for the Baidu Zhiyun API, you can register at <https://api.fanyi.baidu.com/api/trans/product/index>

Shihni edhe:

Baidu API machine translation, Përkthim nga makina, Sugjerime të automatizuara

2.16.65 MT_Baidu_SECRET

Client secret for the Baidu Zhiyun API, you can register at <https://api.fanyi.baidu.com/api/trans/product/index>

Shihni edhe:

Baidu API machine translation, Përkthim nga makina, Sugjerime të automatizuara

2.16.66 MT_DEEPL_API_URL

Ndryshuar në versionin 4.7: The full API URL is now configured to allow using the free plan. Before, it was only possible to configure the API version using MT_DEEPL_API_VERSION.

API URL to use with the DeepL service. At the time of writing, there is the v1 API as well as a free and a paid version of the v2 API.

`https://api.deepl.com/v2/` (default in Weblate) Is meant for API usage on the paid plan, and the subscription is usage-based.

`https://api-free.deepl.com/v2/` Is meant for API usage on the free plan, and the subscription is usage-based.

`https://api.deepl.com/v1/` Is meant for CAT tools and is usable with a per-user subscription.

Previously Weblate was classified as a CAT tool by DeepL, so it was supposed to use the v1 API, but now is supposed to use the v2 API. Therefore it defaults to v2, and you can change it to v1 in case you have an existing CAT subscription and want Weblate to use that.

The easiest way to find out which one to use is to open an URL like the following in your browser:

https://api.deepl.com/v2/translate?text=Hello&target_lang=FR&auth_key=XXX

Replace the XXX with your auth_key. If you receive a JSON object which contains «Bonjour», you have the correct URL; if not, try the other three.

Shihni edhe:

DeepL, Përkthim nga makina, Sugjerime të automatizuara

2.16.67 MT_DEEPL_KEY

API key for the DeepL API, you can register at <https://www.deepl.com/pro.html>

Shihni edhe:

DeepL, Përkthim nga makina, Sugjerime të automatizuara

2.16.68 MT_LIBRETRANSLATE_API_URL

Të reja në versionin 4.7.1.

API URL for the LibreTranslate instance to use.

`https://libretranslate.com/` (official public instance) Requires an API key to use outside of the website.

Mirrors are documented on the LibreTranslate GitHub repository, some of which can be used without authentication:

<https://github.com/LibreTranslate/LibreTranslate#user-content-mirrors>

Shihni edhe:

LibreTranslate, Përkthim nga makina, Sugjerime të automatizuara

2.16.69 MT_LIBRETRANSLATE_KEY

Të reja në versionin 4.7.1.

API key for the LibreTranslate instance specified in `MT_LIBRETRANSLATE_API_URL`.

Shihni edhe:

LibreTranslate, Përkthim nga makina, Sugjerime të automatizuara

2.16.70 MT_GOOGLE_KEY

API key for Google Translate API v2, you can register at <https://cloud.google.com/translate/docs>

Shihni edhe:

Google Translate, Përkthim nga makina, Sugjerime të automatizuara

2.16.71 MT_GOOGLE_CREDENTIALS

API v3 JSON credentials file obtained in the Google cloud console. Please provide a full OS path. Credentials are per service-account affiliated with certain project. Please check <https://cloud.google.com/docs/authentication/getting-started> for more details.

2.16.72 MT_GOOGLE_PROJECT

Google Cloud API v3 project id with activated translation service and billing activated. Please check <https://cloud.google.com/appengine/docs/standard/nodejs/building-app/creating-project> for more details

2.16.73 MT_GOOGLE_LOCATION

API v3 Google Cloud App Engine may be specific to a location. Change accordingly if the default `global` fallback does not work for you.

Please check <https://cloud.google.com/appengine/docs/locations> for more details

Shihni edhe:

Google Translate API V3 (Advanced)

2.16.74 MT_MICROSOFT_BASE_URL

Region base URL domain as defined in the «Base URLs» section.

Defaults to `api.cognitive.microsofttranslator.com` for Azure Global.

For Azure China, please use `api.translator.azure.cn`.

2.16.75 MT_MICROSOFT_COGNITIVE_KEY

Client key for the Microsoft Cognitive Services Translator API.

Shihni edhe:

Microsoft Cognitive Services Translator, Përkthim nga makina, Sugjerime të automatizuara, Cognitive Services - Text Translation API, Microsoft Azure Portal

2.16.76 MT_MICROSOFT_REGION

Region prefix as defined in the «Authenticating with a Multi-service resource» section.

2.16.77 MT_MICROSOFT_ENDPOINT_URL

Region endpoint URL domain for access token as defined in the «Authenticating with an access token» section.

Defaults to `api.cognitive.microsoft.com` for Azure Global.

For Azure China, please use your endpoint from the Azure Portal.

2.16.78 MT_MODERNMT_KEY

Kyç API për motorin e përkthimit nga makina ModernMT.

Shihni edhe:

ModernMT MT_MODERNMT_URL

2.16.79 MT_MODERNMT_URL

URL of ModernMT. It defaults to `https://api.modernmt.com/` for the cloud service.

Shihni edhe:

ModernMT MT_MODERNMT_KEY

2.16.80 MT_MYMEMORY_EMAIL

MyMemory identification e-mail address. It permits 1000 requests per day.

Shihni edhe:

MyMemory, Përkthim nga makina, Sugjerime të automatizuara, MyMemory: API technical specifications

2.16.81 MT_MYMEMORY_KEY

MyMemory access key for private translation memory, use it with `MT_MYMEMORY_USER`.

Shihni edhe:

MyMemory, Përkthim nga makina, Sugjerime të automatizuara, MyMemory: API key generator

2.16.82 MT_MYMEMORY_USER

MyMemory user ID for private translation memory, use it with `MT_MYMEMORY_KEY`.

Shihni edhe:

MyMemory, Përkthim nga makina, Sugjerime të automatizuara, MyMemory: API key generator

2.16.83 MT_NETEASE_KEY

App key for NetEase Sight API, you can register at <https://sight.youdao.com/>

Shihni edhe:

NetEase Sight API machine translation, Përkthim nga makina, Sugjerime të automatizuara

2.16.84 MT_NETEASE_SECRET

App secret for the NetEase Sight API, you can register at <https://sight.youdao.com/>

Shihni edhe:

NetEase Sight API machine translation, Përkthim nga makina, Sugjerime të automatizuara

2.16.85 MT_TMSERVER

URL-ja ku xhiron shërbyesi i kujtesës së përkthimeve.

Shihni edhe:

tmserver, Përkthim nga makina, Sugjerime të automatizuara, tmserver

2.16.86 MT_YANDEX_KEY

API key for the Yandex Translate API, you can register at <https://yandex.com/dev/translate/>

Shihni edhe:

Yandex Translate, Përkthim nga makina, Sugjerime të automatizuara

2.16.87 MT_YOUDAO_ID

Client ID for the Youdao Zhiyun API, you can register at <https://ai.youdao.com/product-fanyi-text.s>.

Shihni edhe:

Youdao Zhiyun API machine translation, Përkthim nga makina, Sugjerime të automatizuara

2.16.88 MT_YOUDAO_SECRET

Client secret for the Youdao Zhiyun API, you can register at <https://ai.youdao.com/product-fanyi-text.s>.

Shihni edhe:

Youdao Zhiyun API machine translation, Përkthim nga makina, Sugjerime të automatizuara

2.16.89 MT_SAP_BASE_URL

API URL to the SAP Translation Hub service.

Shihni edhe:

SAP Translation Hub, Përkthim nga makina, Sugjerime të automatizuara

2.16.90 MT_SAP_SANDBOX_APIKEY

API key for sandbox API usage

Shihni edhe:

SAP Translation Hub, Përkthim nga makina, Sugjerime të automatizuara

2.16.91 MT_SAP_USERNAME

Emri juaj i përdoruesit SAP

Shihni edhe:

SAP Translation Hub, Përkthim nga makina, Sugjerime të automatizuara

2.16.92 MT_SAP_PASSWORD

Fjalëkalimi juaj SAP

Shihni edhe:

SAP Translation Hub, Përkthim nga makina, Sugjerime të automatizuara

2.16.93 MT_SAP_USE_MT

Whether to also use machine translation services, in addition to the term database. Possible values: True or False

Shihni edhe:

SAP Translation Hub, Përkthim nga makina, Sugjerime të automatizuara

2.16.94 NEARBY_MESSAGES

How many strings to show around the currently translated string. This is just a default value, users can adjust this in *Profil përdoruesi*.

2.16.95 DEFAULT_PAGE_LIMIT

Të reja në versionin 4.7.

Default number of elements to display when pagination is active.

2.16.96 PAGURE_CREDENTIALS

Të reja në versionin 4.3.2.

List for credentials for Pagure servers.

Ndihmëz: Use this in case you want Weblate to interact with more of them, for single Pagure endpoint stick with *PAGURE_USERNAME* and *PAGURE_TOKEN*.

```
PAGURE_CREDENTIALS = {
    "pagure.io": {
        "username": "weblate",
        "token": "your-api-token",
    },
    "pagure.example.com": {
        "username": "weblate",
        "token": "another-api-token",
    },
}
```

2.16.97 PAGURE_USERNAME

Të reja në versionin 4.3.2.

Pagure username used to send merge requests for translation updates.

Shihni edhe:

PAGURE_CREDENTIALS, *Pagure*

2.16.98 PAGURE_TOKEN

Të reja në versionin 4.3.2.

Pagure personal access token used to make API calls for translation updates.

Shihni edhe:

PAGURE_CREDENTIALS, *Pagure*, *Pagure API*

2.16.99 RATELIMIT_ATTEMPTS

Të reja në versionin 3.2.

Maximum number of authentication attempts before rate limiting is applied.

5, si parazgjedhje.

Shihni edhe:

Rate limiting, *RATELIMIT_WINDOW*, *RATELIMIT_LOCKOUT*

2.16.100 RATELIMIT_WINDOW

Të reja në versionin 3.2.

How long authentication is accepted after rate limiting applies.

An amount of seconds defaulting to 300 (5 minutes).

Shihni edhe:

Rate limiting, `RATELIMIT_ATTEMPTS`, `RATELIMIT_LOCKOUT`

2.16.101 RATELIMIT_LOCKOUT

Të reja në versionin 3.2.

How long authentication is locked after rate limiting applies.

An amount of seconds defaulting to 600 (10 minutes).

Shihni edhe:

Rate limiting, `RATELIMIT_ATTEMPTS`, `RATELIMIT_WINDOW`

2.16.102 REGISTRATION_ALLOW_BACKENDS

Të reja në versionin 4.1.

List of authentication backends to allow registration from. This only limits new registrations, users can still authenticate and add authentication using all configured authentication backends.

It is recommended to keep `REGISTRATION_OPEN` enabled while limiting registration backends, otherwise users will be able to register, but Weblate will not show links to register in the user interface.

Shembull:

```
REGISTRATION_ALLOW_BACKENDS = ["azuread-oauth2", "azuread-tenant-oauth2"]
```

Ndihmëz: The backend names match names used in URL for authentication.

Shihni edhe:

`REGISTRATION_OPEN`, *Mirëfilltësim*

2.16.103 REGISTRATION_CAPTCHA

A value of either `True` or `False` indicating whether registration of new accounts is protected by CAPTCHA. This setting is optional, and a default of `True` will be assumed if it is not supplied.

If turned on, a CAPTCHA is added to all pages where a users enters their e-mail address:

- Regjistrim llogarie të re.
- Rimarrje fjalëkalimesh.
- Shtim email-i te një llogari.
- Formular kontaktesh për përdorues që s'kanë bërë hyrjen.

2.16.104 REGISTRATION_EMAIL_MATCH

Të reja në versionin 2.17.

Allows you to filter which e-mail addresses can register.

Defaults to `.*`, which allows any e-mail address to be registered.

You can use it to restrict registration to a single e-mail domain:

```
REGISTRATION_EMAIL_MATCH = r"^.*@weblate\.org$"
```

2.16.105 REGISTRATION_OPEN

Whether registration of new accounts is currently permitted. This optional setting can remain the default `True`, or changed to `False`.

This setting affects built-in authentication by e-mail address or through the Python Social Auth (you can whitelist certain back-ends using [REGISTRATION_ALLOW_BACKENDS](#)).

Shënim: If using third-party authentication methods such as [Mirëfilltësim LDAP](#), it just hides the registration form, but new users might still be able to sign in and create accounts.

Shihni edhe:

[REGISTRATION_ALLOW_BACKENDS](#), [REGISTRATION_EMAIL_MATCH](#), [Mirëfilltësim](#)

2.16.106 REPOSITORY_ALERT_THRESHOLD

Të reja në versionin 4.0.2.

Threshold for triggering an alert for outdated repositories, or ones that contain too many changes. Defaults to 25.

Shihni edhe:

[alerts](#)

2.16.107 REQUIRE_LOGIN

Të reja në versionin 4.1.

This enables [LOGIN_REQUIRED_URLS](#) and configures REST framework to require authentication for all API endpoints.

Shënim: This is implemented in the [Sample configuration](#). For Docker, use [WEBLATE_REQUIRE_LOGIN](#).

2.16.108 SENTRY_DSN

Të reja në versionin 3.9.

Sentry DSN to use for *Collecting error reports*.

Shihni edhe:

Django integration for Sentry

2.16.109 SESSION_COOKIE_AGE_AUTHENTICATED

Të reja në versionin 4.3.

Set session expiry for authenticated users. This complements `SESSION_COOKIE_AGE` which is used for unauthenticated users.

Shihni edhe:

`SESSION_COOKIE_AGE`

2.16.110 SIMPLIFY_LANGUAGES

Use simple language codes for default language/country combinations. For example an `fr_FR` translation will use the `fr` language code. This is usually the desired behavior, as it simplifies listing languages for these default combinations.

Turn this off if you want to different translations for each variant.

2.16.111 SITE_DOMAIN

Configures site domain. This is necessary to produce correct absolute links in many scopes (for example activation e-mails, notifications or RSS feeds).

In case Weblate is running on non-standard port, include it here as well.

Shembuj:

```
# Production site with domain name
SITE_DOMAIN = "weblate.example.com"

# Local development with IP address and port
SITE_DOMAIN = "127.0.0.1:8000"
```

Shënim: This setting should only contain the domain name. For configuring protocol, (enabling and enforcing HTTPS) use `ENABLE_HTTPS` and for changing URL, use `URL_PREFIX`.

Ndihmëz: On a Docker container, the site domain is configured through `WEBLATE_ALLOWED_HOSTS`.

Shihni edhe:

Set correct site domain, Allowed hosts setup, Formësoni si duhet HTTPS-në `WEBLATE_SITE_DOMAIN`, `ENABLE_HTTPS`

2.16.112 SITE_TITLE

Site title to be used for the website and sent e-mails.

2.16.113 SPECIAL_CHARS

Additional characters to include in the visual keyboard, *Tastierë pamore*.

Vlera parazgjedhje është:

```
SPECIAL_CHARS = ("\t", "\n", "\u00a0", "...")
```

2.16.114 SINGLE_PROJECT

Të reja në versionin 3.8.

Redirects users directly to a project or component instead of showing the dashboard. You can either set it to `True` and in this case it only works in case there is actually only single project in Weblate. Alternatively set the project slug, and it will redirect unconditionally to this project.

Ndryshuar në versionin 3.11: The setting now also accepts a project slug, to force displaying that single project.

Shembull:

```
SINGLE_PROJECT = "test"
```

2.16.115 STATUS_URL

The URL where your Weblate instance reports its status.

2.16.116 SUGGESTION_CLEANUP_DAYS

Të reja në versionin 3.2.1.

Automatically deletes suggestions after a given number of days. Defaults to `None`, meaning no deletions.

2.16.117 UPDATE_LANGUAGES

Të reja në versionin 4.3.2.

Controls whether languages database should be updated when running database migration and is enabled by default. This setting has no effect on invocation of *setuplang*.

Shihni edhe:

Built-in language definitions

2.16.118 URL_PREFIX

This setting allows you to run Weblate under some path (otherwise it relies on being run from the webserver root).

Shënim: To use this setting, you also need to configure your server to strip this prefix. For example with WSGI, this can be achieved by setting `WSGIScriptAlias`.

Ndihmëz: Prefiksi duhet të fillojë me një `/`.

Shembull:

```
URL_PREFIX = "/translations"
```

Shënim: This setting does not work with Django's built-in server, you would have to adjust `urls.py` to contain this prefix.

2.16.119 VCS_BACKENDS

Configuration of available VCS backends.

Shënim: Weblate tries to use all supported back-ends you have the tools for.

Ndihmëz: You can limit choices or add custom VCS back-ends by using this.

```
VCS_BACKENDS = ("weblate.vcs.git.GitRepository",)
```

Shihni edhe:

Integrim kontrolli versioni

2.16.120 VCS_CLONE_DEPTH

Të reja në versionin 3.10.2.

Configures how deep cloning of repositories Weblate should do.

Shënim: Currently this is only supported in *Git*. By default Weblate does shallow clones of the repositories to make cloning faster and save disk space. Depending on your usage (for example when using custom *Shtesa*), you might want to increase the depth or turn off shallow clones completely by setting this to 0.

Ndihmëz: In case you get `fatal: protocol error: expected old/new/ref, got 'shallow <commit hash>'` error when pushing from Weblate, turn off shallow clones completely by setting:

```
VCS_CLONE_DEPTH = 0
```

2.16.121 WEBLATE_ADDONS

List of addons available for use. To use them, they have to be enabled for a given translation component. By default this includes all built-in addons, when extending the list you will probably want to keep existing ones enabled, for example:

```
WEBLATE_ADDONS = (  
    # Built-in addons  
    "weblate.addons.gettext.GenerateMoAddon",  
    "weblate.addons.gettext.UpdateLinguasAddon",  
    "weblate.addons.gettext.UpdateConfigureAddon",  
    "weblate.addons.gettext.MsgmergeAddon",  
    "weblate.addons.gettext.GettextCustomizeAddon",  
    "weblate.addons.gettext.GettextAuthorComments",  
    "weblate.addons.cleanup.CleanupAddon",  
    "weblate.addons.consistency.LanguangeConsistencyAddon",  
    "weblate.addons.discovery.DiscoveryAddon",  
    "weblate.addons.flags.SourceEditAddon",  
    "weblate.addons.flags.TargetEditAddon",  
    "weblate.addons.flags.SameEditAddon",  
    "weblate.addons.flags.BulkEditAddon",  
    "weblate.addons.generate.GenerateFileAddon",  
    "weblate.addons.json.JSONCustomizeAddon",  
    "weblate.addons.properties.PropertiesSortAddon",  
    "weblate.addons.git.GitSquashAddon",  
    "weblate.addons.removal.RemoveComments",  
    "weblate.addons.removal.RemoveSuggestions",  
    "weblate.addons.resx.ResxUpdateAddon",  
    "weblate.addons.autotranslate.AutoTranslateAddon",  
    "weblate.addons.yaml.YAMLCustomizeAddon",  
    "weblate.addons.cdn.CDNJSAddon",  
    # Add-on you want to include  
    "weblate.addons.example.ExampleAddon",  
)
```

Shënim: Removing the addon from the list does not uninstall it from the components. Weblate will crash in that case. Please uninstall addon from all components prior to removing it from this list.

Shihni edhe:

Shtesa, DEFAULT_ADDONS

2.16.122 WEBLATE_EXPORTERS

Të reja në versionin 4.2.

List of a available exporters offering downloading translations or glossaries in various file formats.

Shihni edhe:

Formate të mbuluar kartelash

2.16.123 WEBLATE_FORMATS

Të reja në versionin 3.0.

Listë formatesh kartelash që mund të përdoren.

Shënim: The default list already has the common formats.

Shihni edhe:

Formate të mbuluar kartelash

2.16.124 WEBLATE_GPG_IDENTITY

Të reja në versionin 3.1.

Identity used by Weblate to sign Git commits, for example:

```
WEBLATE_GPG_IDENTITY = "Weblate <weblate@example.com>"
```

The Weblate GPG keyring is searched for a matching key (home/.gnupg under *DATA_DIR*). If not found, a key is generated, please check *Signing Git commits with GnuPG* for more details.

Shihni edhe:

Signing Git commits with GnuPG

2.16.125 WEBSITE_REQUIRED

Defines whether *Sajt projekti* has to be specified when creating a project. Turned on by default as that suits public server setups.

2.17 Sample configuration

The following example is shipped as `weblate/settings_example.py` with Weblate:

```
#
# Copyright © 2012 - 2021 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <https://www.gnu.org/licenses/>.
#

import os
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

import platform
from logging.handlers import SysLogHandler

# Title of site to use
SITE_TITLE = "Weblate"

# Site domain
SITE_DOMAIN = ""

# Whether site uses https
ENABLE_HTTPS = False

#
# Django settings for Weblate project.
#

DEBUG = True

ADMINS = (
    # ("Your Name", "your_email@example.com"),
)

MANAGERS = ADMINS

DATABASES = {
    "default": {
        # Use "postgresql" or "mysql".
        "ENGINE": "django.db.backends.postgresql",
        # Database name.
        "NAME": "weblate",
        # Database user.
        "USER": "weblate",
        # Name of role to alter to set parameters in PostgreSQL,
        # use in case role name is different than user used for authentication.
        # "ALTER_ROLE": "weblate",
        # Database password.
        "PASSWORD": "",
        # Set to empty string for localhost.
        "HOST": "127.0.0.1",
        # Set to empty string for default.
        "PORT": "",
        # Customizations for databases.
        "OPTIONS": {
            # In case of using an older MySQL server,
            # which has MyISAM as a default storage
            # "init_command": "SET storage_engine=INNODB",
            # Uncomment for MySQL older than 5.7:
            # "init_command": "SET sql_mode='STRICT_TRANS_TABLES'",
            # Set emoji capable charset for MySQL:
            # "charset": "utf8mb4",
            # Change connection timeout in case you get MySQL gone away error:
            # "connect_timeout": 28800,
        },
    },
}

BASE_DIR = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))

# Data directory
DATA_DIR = os.path.join(BASE_DIR, "data")

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

# Local time zone for this installation. Choices can be found here:
# http://en.wikipedia.org/wiki/List_of_tz_zones_by_name
# although not all choices may be available on all operating systems.
# In a Windows environment this must be set to your system time zone.
TIME_ZONE = "UTC"

# Language code for this installation. All choices can be found here:
# http://www.i18nguy.com/unicode/language-identifiers.html
LANGUAGE_CODE = "en-us"

LANGUAGES = (
    ("ar", "العربية"),
    ("az", "Azərbaycan"),
    ("be", "Беларуская"),
    ("be@latin", "Biełaruskaja"),
    ("bg", "Български"),
    ("br", "Brezhoneg"),
    ("ca", "Català"),
    ("cs", "Čeština"),
    ("da", "Dansk"),
    ("de", "Deutsch"),
    ("en", "English"),
    ("el", "Ελληνικά"),
    ("en-gb", "English (United Kingdom)"),
    ("es", "Español"),
    ("fi", "Suomi"),
    ("fr", "Français"),
    ("gl", "Galego"),
    ("he", "עברית"),
    ("hu", "Magyar"),
    ("hr", "Hrvatski"),
    ("id", "Indonesia"),
    ("is", "Íslenska"),
    ("it", "Italiano"),
    ("ja", "日本語"),
    ("kab", "Taqbaylit"),
    ("kk", "Қазақ тілі"),
    ("ko", "한국어"),
    ("nb", "Norsk bokmål"),
    ("nl", "Nederlands"),
    ("pl", "Polski"),
    ("pt", "Português"),
    ("pt-br", "Português brasileiro"),
    ("ro", "Română"),
    ("ru", "Русский"),
    ("sk", "Slovenčina"),
    ("sl", "Slovenščina"),
    ("sq", "Shqip"),
    ("sr", "Српски"),
    ("sr-latn", "Srpski"),
    ("sv", "Svenska"),
    ("th", "ไทย"),
    ("tr", "Türkçe"),
    ("uk", "Українська"),
    ("zh-hans", "简体中文"),
    ("zh-hant", "繁體中文"),
)

SITE_ID = 1

# If you set this to False, Django will make some optimizations so as not

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

# to load the internationalization machinery.
USE_I18N = True

# If you set this to False, Django will not format dates, numbers and
# calendars according to the current locale.
USE_L10N = True

# If you set this to False, Django will not use timezone-aware datetimes.
USE_TZ = True

# Type of automatic primary key, introduced in Django 3.2
DEFAULT_AUTO_FIELD = "django.db.models.AutoField"

# URL prefix to use, please see documentation for more details
URL_PREFIX = ""

# Absolute filesystem path to the directory that will hold user-uploaded files.
MEDIA_ROOT = os.path.join(DATA_DIR, "media")

# URL that handles the media served from MEDIA_ROOT. Make sure to use a
# trailing slash.
MEDIA_URL = f"{URL_PREFIX}/media/"

# Absolute path to the directory static files should be collected to.
# Don't put anything in this directory yourself; store your static files
# in apps' "static/" subdirectories and in STATICFILES_DIRS.
STATIC_ROOT = os.path.join(DATA_DIR, "static")

# URL prefix for static files.
STATIC_URL = f"{URL_PREFIX}/static/"

# Additional locations of static files
STATICFILES_DIRS = (
    # Put strings here, like "/home/html/static" or "C:/www/django/static".
    # Always use forward slashes, even on Windows.
    # Don't forget to use absolute paths, not relative paths.
)

# List of finder classes that know how to find static files in
# various locations.
STATICFILES_FINDERS = (
    "django.contrib.staticfiles.finders.FileSystemFinder",
    "django.contrib.staticfiles.finders.AppDirectoriesFinder",
    "compressor.finders.CompressorFinder",
)

# Make this unique, and don't share it with anybody.
# You can generate it using weblate/examples/generate-secret-key
SECRET_KEY = ""

_TEMPLATE_LOADERS = [
    "django.template.loaders.filesystem.Loader",
    "django.template.loaders.app_directories.Loader",
]
if not DEBUG:
    _TEMPLATE_LOADERS = [("django.template.loaders.cached.Loader", _TEMPLATE_
↪LOADERS)]
TEMPLATES = [
    {
        "BACKEND": "django.template.backends.django.DjangoTemplates",
        "OPTIONS": {

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

        "context_processors": [
            "django.contrib.auth.context_processors.auth",
            "django.template.context_processors.debug",
            "django.template.context_processors.i18n",
            "django.template.context_processors.request",
            "django.template.context_processors.csrf",
            "django.contrib.messages.context_processors.messages",
            "weblate.trans.context_processors.weblate_context",
        ],
        "loaders": _TEMPLATE_LOADERS,
    },
}
]

# GitHub username and token for sending pull requests.
# Please see the documentation for more details.
GITHUB_USERNAME = None
GITHUB_TOKEN = None

# GitLab username and token for sending merge requests.
# Please see the documentation for more details.
GITLAB_USERNAME = None
GITLAB_TOKEN = None

# Authentication configuration
AUTHENTICATION_BACKENDS = (
    "social_core.backends.email.EmailAuth",
    # "social_core.backends.google.GoogleOAuth2",
    # "social_core.backends.github.GithubOAuth2",
    # "social_core.backends.bitbucket.BitbucketOAuth",
    # "social_core.backends.suse.OpenSUSEOpenId",
    # "social_core.backends.ubuntu.UbuntuOpenId",
    # "social_core.backends.fedora.FedoraOpenId",
    # "social_core.backends.facebook.FacebookOAuth2",
    "weblate.accounts.auth.WeblateUserBackend",
)

# Custom user model
AUTH_USER_MODEL = "weblate_auth.User"

# Social auth backends setup
SOCIAL_AUTH_GITHUB_KEY = ""
SOCIAL_AUTH_GITHUB_SECRET = ""
SOCIAL_AUTH_GITHUB_SCOPE = ["user:email"]

SOCIAL_AUTH_BITBUCKET_KEY = ""
SOCIAL_AUTH_BITBUCKET_SECRET = ""
SOCIAL_AUTH_BITBUCKET_VERIFIED_EMAILS_ONLY = True

SOCIAL_AUTH_FACEBOOK_KEY = ""
SOCIAL_AUTH_FACEBOOK_SECRET = ""
SOCIAL_AUTH_FACEBOOK_SCOPE = ["email", "public_profile"]
SOCIAL_AUTH_FACEBOOK_PROFILE_EXTRA_PARAMS = {"fields": "id,name,email"}

SOCIAL_AUTH_GOOGLE_OAUTH2_KEY = ""
SOCIAL_AUTH_GOOGLE_OAUTH2_SECRET = ""

# Social auth settings
SOCIAL_AUTH_PIPELINE = (
    "social_core.pipeline.social_auth.social_details",

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    "social_core.pipeline.social_auth.social_uid",
    "social_core.pipeline.social_auth.auth_allowed",
    "social_core.pipeline.social_auth.social_user",
    "weblate.accounts.pipeline.store_params",
    "weblate.accounts.pipeline.verify_open",
    "social_core.pipeline.user.get_username",
    "weblate.accounts.pipeline.require_email",
    "social_core.pipeline.mail.mail_validation",
    "weblate.accounts.pipeline.revoke_mail_code",
    "weblate.accounts.pipeline.ensure_valid",
    "weblate.accounts.pipeline.remove_account",
    "social_core.pipeline.social_auth.associate_by_email",
    "weblate.accounts.pipeline.reauthenticate",
    "weblate.accounts.pipeline.verify_username",
    "social_core.pipeline.user.create_user",
    "social_core.pipeline.social_auth.associate_user",
    "social_core.pipeline.social_auth.load_extra_data",
    "weblate.accounts.pipeline.cleanup_next",
    "weblate.accounts.pipeline.user_full_name",
    "weblate.accounts.pipeline.store_email",
    "weblate.accounts.pipeline.notify_connect",
    "weblate.accounts.pipeline.password_reset",
)
SOCIAL_AUTH_DISCONNECT_PIPELINE = (
    "social_core.pipeline.disconnect.allowed_to_disconnect",
    "social_core.pipeline.disconnect.get_entries",
    "social_core.pipeline.disconnect.revoke_tokens",
    "weblate.accounts.pipeline.cycle_session",
    "weblate.accounts.pipeline.adjust_primary_mail",
    "weblate.accounts.pipeline.notify_disconnect",
    "social_core.pipeline.disconnect.disconnect",
    "weblate.accounts.pipeline.cleanup_next",
)

# Custom authentication strategy
SOCIAL_AUTH_STRATEGY = "weblate.accounts.strategy.WeblateStrategy"

# Raise exceptions so that we can handle them later
SOCIAL_AUTH_RAISE_EXCEPTIONS = True

SOCIAL_AUTH_EMAIL_VALIDATION_FUNCTION = "weblate.accounts.pipeline.send_validation"
SOCIAL_AUTH_EMAIL_VALIDATION_URL = f"{URL_PREFIX}/accounts/email-sent/"
SOCIAL_AUTH_LOGIN_ERROR_URL = f"{URL_PREFIX}/accounts/login/"
SOCIAL_AUTH_EMAIL_FORM_URL = f"{URL_PREFIX}/accounts/email/"
SOCIAL_AUTH_NEW_ASSOCIATION_REDIRECT_URL = f"{URL_PREFIX}/accounts/profile/#account
↪"
SOCIAL_AUTH_PROTECTED_USER_FIELDS = ("email",)
SOCIAL_AUTH_SLUGIFY_USERNAMES = True
SOCIAL_AUTH_SLUGIFY_FUNCTION = "weblate.accounts.pipeline.slugify_username"

# Password validation configuration
AUTH_PASSWORD_VALIDATORS = [
    {
        "NAME": "django.contrib.auth.password_validation.
↪UserAttributeSimilarityValidator" # noqa: E501, pylint: disable=line-too-long
    },
    {
        "NAME": "django.contrib.auth.password_validation.MinimumLengthValidator",
        "OPTIONS": {"min_length": 10},
    },
    {"NAME": "django.contrib.auth.password_validation.CommonPasswordValidator"},

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

{ "NAME": "django.contrib.auth.password_validation.NumericPasswordValidator"},
{ "NAME": "weblate.accounts.password_validation.CharsPasswordValidator"},
{ "NAME": "weblate.accounts.password_validation.PastPasswordsValidator"},
# Optional password strength validation by django-zxcvbn-password
# {
#     "NAME": "zxcvbn_password.ZXCVBNValidator",
#     "OPTIONS": {
#         "min_score": 3,
#         "user_attributes": ("username", "email", "full_name")
#     }
# },
]

# Password hashing (prefer Argon)
PASSWORD_HASHERS = [
    "django.contrib.auth.hashers.Argon2PasswordHasher",
    "django.contrib.auth.hashers.PBKDF2PasswordHasher",
    "django.contrib.auth.hashers.PBKDF2SHA1PasswordHasher",
    "django.contrib.auth.hashers.BCryptSHA256PasswordHasher",
]

# Allow new user registrations
REGISTRATION_OPEN = True

# Shortcut for login required setting
REQUIRE_LOGIN = False

# Middleware
MIDDLEWARE = [
    "weblate.middleware.RedirectMiddleware",
    "weblate.middleware.ProxyMiddleware",
    "django.middleware.security.SecurityMiddleware",
    "django.contrib.sessions.middleware.SessionMiddleware",
    "django.middleware.csrf.CsrfViewMiddleware",
    "weblate.accounts.middleware.AuthenticationMiddleware",
    "django.contrib.messages.middleware.MessageMiddleware",
    "django.middleware.clickjacking.XFrameOptionsMiddleware",
    "social_django.middleware.SocialAuthExceptionMiddleware",
    "weblate.accounts.middleware.RequireLoginMiddleware",
    "weblate.api.middleware.ThrottlingMiddleware",
    "weblate.middleware.SecurityMiddleware",
    "weblate.wladmin.middleware.ManageMiddleware",
]

ROOT_URLCONF = "weblate.urls"

# Django and Weblate apps
INSTALLED_APPS = [
    # Weblate apps on top to override Django locales and templates
    "weblate.addons",
    "weblate.auth",
    "weblate.checks",
    "weblate.formats",
    "weblate.glossary",
    "weblate.machinery",
    "weblate.trans",
    "weblate.lang",
    "weblate_language_data",
    "weblate.memory",
    "weblate.screenshots",
    "weblate.fonts",

```

(vazhdon në faqen pasuese)

```

    "weblate.accounts",
    "weblate.configuration",
    "weblate.utils",
    "weblate.vcs",
    "weblate.wladmin",
    "weblate.metrics",
    "weblate",
    # Optional: Git exporter
    "weblate.gitexport",
    # Standard Django modules
    "django.contrib.auth",
    "django.contrib.contenttypes",
    "django.contrib.sessions",
    "django.contrib.messages",
    "django.contrib.staticfiles",
    "django.contrib.admin.apps.SimpleAdminConfig",
    "django.contrib.admindocs",
    "django.contrib.sitemaps",
    "django.contrib.humanize",
    # Third party Django modules
    "social_django",
    "crispy_forms",
    "compressor",
    "rest_framework",
    "rest_framework.authtoken",
    "django_filters",
]

# Custom exception reporter to include some details
DEFAULT_EXCEPTION_REPORTER_FILTER = "weblate.trans.debug.
↳ WeblateExceptionReporterFilter"

# Default logging of Weblate messages
# - to syslog in production (if available)
# - otherwise to console
# - you can also choose "logfile" to log into separate file
#   after configuring it below

# Detect if we can connect to syslog
HAVE_SYSLOG = False
if platform.system() != "Windows":
    try:
        handler = SysLogHandler(address="/dev/log", facility=SysLogHandler.LOG_
↳ LOCAL2)
        handler.close()
        HAVE_SYSLOG = True
    except OSError:
        HAVE_SYSLOG = False

if DEBUG or not HAVE_SYSLOG:
    DEFAULT_LOG = "console"
else:
    DEFAULT_LOG = "syslog"
DEFAULT_LOGLEVEL = "DEBUG" if DEBUG else "INFO"

# A sample logging configuration. The only tangible logging
# performed by this configuration is to send an email to
# the site admins on every HTTP 500 error when DEBUG=False.
# See http://docs.djangoproject.com/en/stable/topics/logging for
# more details on how to customize your logging configuration.
LOGGING = {

```

(vazhduar nga faqja e mëparshme)

```

"version": 1,
"disable_existing_loggers": True,
"filters": {"require_debug_false": {"()": "django.utils.log.RequireDebugFalse"}
↪},
"formatters": {
    "syslog": {"format": "weblate[%(process)d]: %(levelname)s %(message)s"},
    "simple": {"format": "[% (asctime)s: %(levelname)s/%(process)s] %(message)s
↪"},
    "logfile": {"format": "%(asctime)s %(levelname)s %(message)s"},
    "django.server": {
        "()": "django.utils.log.ServerFormatter",
        "format": "[% (server_time)s] %(message)s",
    },
},
"handlers": {
    "mail_admins": {
        "level": "ERROR",
        "filters": ["require_debug_false"],
        "class": "django.utils.log.AdminEmailHandler",
        "include_html": True,
    },
    "console": {
        "level": "DEBUG",
        "class": "logging.StreamHandler",
        "formatter": "simple",
    },
    "django.server": {
        "level": "INFO",
        "class": "logging.StreamHandler",
        "formatter": "django.server",
    },
    "syslog": {
        "level": "DEBUG",
        "class": "logging.handlers.SysLogHandler",
        "formatter": "syslog",
        "address": "/dev/log",
        "facility": SysLogHandler.LOG_LOCAL2,
    },
    # Logging to a file
    # "logfile": {
    #     "level": "DEBUG",
    #     "class": "logging.handlers.RotatingFileHandler",
    #     "filename": "/var/log/weblate/weblate.log",
    #     "maxBytes": 100000,
    #     "backupCount": 3,
    #     "formatter": "logfile",
    # },
},
"loggers": {
    "django.request": {
        "handlers": ["mail_admins", DEFAULT_LOG],
        "level": "ERROR",
        "propagate": True,
    },
    "django.server": {
        "handlers": ["django.server"],
        "level": "INFO",
        "propagate": False,
    },
    # Logging database queries
    # "django.db.backends": {

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

#     "handlers": [DEFAULT_LOG],
#     "level": "DEBUG",
# },
"weblate": {"handlers": [DEFAULT_LOG], "level": DEFAULT_LOGLEVEL},
# Logging VCS operations
"weblate.vcs": {"handlers": [DEFAULT_LOG], "level": DEFAULT_LOGLEVEL},
# Python Social Auth
"social": {"handlers": [DEFAULT_LOG], "level": DEFAULT_LOGLEVEL},
# Django Authentication Using LDAP
"django_auth_ldap": {"handlers": [DEFAULT_LOG], "level": DEFAULT_LOGLEVEL},
# SAML IdP
"djangosaml2idp": {"handlers": [DEFAULT_LOG], "level": DEFAULT_LOGLEVEL},
},
}

# Remove syslog setup if it's not present
if not HAVE_SYSLOG:
    del LOGGING["handlers"]["syslog"]

# List of machine translations
MT_SERVICES = (
    #     "weblate.machinery.apertium.ApertiumAPYTranslation",
    #     "weblate.machinery.baidu.BaiduTranslation",
    #     "weblate.machinery.deepl.DeepLTranslation",
    #     "weblate.machinery.glosbe.GlosbeTranslation",
    #     "weblate.machinery.google.GoogleTranslation",
    #     "weblate.machinery.googlev3.GoogleV3Translation",
    #     "weblate.machinery.libretranslate.LibreTranslateTranslation",
    #     "weblate.machinery.microsoft.MicrosoftCognitiveTranslation",
    #     "weblate.machinery.microsoftterminology.MicrosoftTerminologyService",
    #     "weblate.machinery.modernmt.ModernMTTranslation",
    #     "weblate.machinery.mymemory.MyMemoryTranslation",
    #     "weblate.machinery.netease.NeteaseSightTranslation",
    #     "weblate.machinery.tmserver.AmagamaTranslation",
    #     "weblate.machinery.tmserver.TMServerTranslation",
    #     "weblate.machinery.yandex.YandexTranslation",
    #     "weblate.machinery.saptranslationhub.SAPTranslationHub",
    #     "weblate.machinery.youdao.YoudaoTranslation",
    "weblate.machinery.weblatetm.WeblateTranslation",
    "weblate.memory.machine.WeblateMemory",
)

# Machine translation API keys

# URL of the Apertium APY server
MT_APERTIUM_APY = None

# DeepL API key
MT_DEEPL_KEY = None

# LibreTranslate
MT_LIBRETRANSLATE_API_URL = None
MT_LIBRETRANSLATE_KEY = None

# Microsoft Cognitive Services Translator API, register at
# https://portal.azure.com/
MT_MICROSOFT_COGNITIVE_KEY = None
MT_MICROSOFT_REGION = None

# ModernMT
MT_MODERNMT_KEY = None

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

# MyMemory identification email, see
# https://mymemory.translated.net/doc/spec.php
MT_MYMEMORY_EMAIL = None

# Optional MyMemory credentials to access private translation memory
MT_MYMEMORY_USER = None
MT_MYMEMORY_KEY = None

# Google API key for Google Translate API v2
MT_GOOGLE_KEY = None

# Google Translate API3 credentials and project id
MT_GOOGLE_CREDENTIALS = None
MT_GOOGLE_PROJECT = None

# Baidu app key and secret
MT_Baidu_ID = None
MT_Baidu_SECRET = None

# Youdao Zhiyun app key and secret
MT_YOUDAO_ID = None
MT_YOUDAO_SECRET = None

# Netease Sight (Jianwai) app key and secret
MT_NETEASE_KEY = None
MT_NETEASE_SECRET = None

# API key for Yandex Translate API
MT_YANDEX_KEY = None

# tmserver URL
MT_TMSERVER = None

# SAP Translation Hub
MT_SAP_BASE_URL = None
MT_SAP_SANDBOX_APIKEY = None
MT_SAP_USERNAME = None
MT_SAP_PASSWORD = None
MT_SAP_USE_MT = True

# Use HTTPS when creating redirect URLs for social authentication, see
# documentation for more details:
# https://python-social-auth-docs.readthedocs.io/en/latest/configuration/settings.
# ↪html#processing-redirects-and-urlopen
SOCIAL_AUTH_REDIRECT_IS_HTTPS = ENABLE_HTTPS

# Make CSRF cookie HttpOnly, see documentation for more details:
# https://docs.djangoproject.com/en/1.11/ref/settings/#csrf-cookie-httponly
CSRF_COOKIE_HTTPONLY = True
CSRF_COOKIE_SECURE = ENABLE_HTTPS
# Store CSRF token in session
CSRF_USE_SESSIONS = True
# Customize CSRF failure view
CSRF_FAILURE_VIEW = "weblate.trans.views.error.csrf_failure"
SESSION_COOKIE_SECURE = ENABLE_HTTPS
SESSION_COOKIE_HTTPONLY = True
# SSL redirect
SECURE_SSL_REDIRECT = ENABLE_HTTPS
# Sent referrrrer only for same origin links
SECURE_REFERRER_POLICY = "same-origin"

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

# SSL redirect URL exemption list
SECURE_REDIRECT_EXEMPT = (r"healthz/$",) # Allowing HTTP access to health check
# Session cookie age (in seconds)
SESSION_COOKIE_AGE = 1000
SESSION_COOKIE_AGE_AUTHENTICATED = 1209600
SESSION_COOKIE_SAMESITE = "Lax"
# Increase allowed upload size
DATA_UPLOAD_MAX_MEMORY_SIZE = 50000000

# Apply session cookie settings to language cookie as well
LANGUAGE_COOKIE_SECURE = SESSION_COOKIE_SECURE
LANGUAGE_COOKIE_HTTPONLY = SESSION_COOKIE_HTTPONLY
LANGUAGE_COOKIE_AGE = SESSION_COOKIE_AGE_AUTHENTICATED * 10
LANGUAGE_COOKIE_SAMESITE = SESSION_COOKIE_SAMESITE

# Some security headers
SECURE_BROWSER_XSS_FILTER = True
X_FRAME_OPTIONS = "DENY"
SECURE_CONTENT_TYPE_NOSNIFF = True

# Optionally enable HSTS
SECURE_HSTS_SECONDS = 31536000 if ENABLE_HTTPS else 0
SECURE_HSTS_PRELOAD = ENABLE_HTTPS
SECURE_HSTS_INCLUDE_SUBDOMAINS = ENABLE_HTTPS

# HTTPS detection behind reverse proxy
SECURE_PROXY_SSL_HEADER = None

# URL of login
LOGIN_URL = f"{URL_PREFIX}/accounts/login/"

# URL of logout
LOGOUT_URL = f"{URL_PREFIX}/accounts/logout/"

# Default location for login
LOGIN_REDIRECT_URL = f"{URL_PREFIX}/"

# Anonymous user name
ANONYMOUS_USER_NAME = "anonymous"

# Reverse proxy settings
IP_PROXY_HEADER = "HTTP_X_FORWARDED_FOR"
IP_BEHIND_REVERSE_PROXY = False
IP_PROXY_OFFSET = 0

# Sending HTML in mails
EMAIL_SEND_HTML = True

# Subject of emails includes site title
EMAIL_SUBJECT_PREFIX = f"[{SITE_TITLE}] "

# Enable remote hooks
ENABLE_HOOKS = True

# By default the length of a given translation is limited to the length of
# the source string * 10 characters. Set this option to False to allow longer
# translations (up to 10.000 characters)
LIMIT_TRANSLATION_LENGTH_BY_SOURCE_LENGTH = True

# Use simple language codes for default language/country combinations
SIMPLIFY_LANGUAGES = True

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

# Render forms using bootstrap
CRISPY_TEMPLATE_PACK = "bootstrap3"

# List of quality checks
# CHECK_LIST = (
#     "weblate.checks.same.SameCheck",
#     "weblate.checks.chars.BeginNewlineCheck",
#     "weblate.checks.chars.EndNewlineCheck",
#     "weblate.checks.chars.BeginSpaceCheck",
#     "weblate.checks.chars.EndSpaceCheck",
#     "weblate.checks.chars.DoubleSpaceCheck",
#     "weblate.checks.chars.EndStopCheck",
#     "weblate.checks.chars.EndColonCheck",
#     "weblate.checks.chars.EndQuestionCheck",
#     "weblate.checks.chars.EndExclamationCheck",
#     "weblate.checks.chars.EndEllipsisCheck",
#     "weblate.checks.chars.EndSemicolonCheck",
#     "weblate.checks.chars.MaxLengthCheck",
#     "weblate.checks.chars.KashidaCheck",
#     "weblate.checks.chars.PunctuationSpacingCheck",
#     "weblate.checks.format.PythonFormatCheck",
#     "weblate.checks.format.PythonBraceFormatCheck",
#     "weblate.checks.format.PHPFormatCheck",
#     "weblate.checks.format.CFormatCheck",
#     "weblate.checks.format.PperlFormatCheck",
#     "weblate.checks.format.JavaScriptFormatCheck",
#     "weblate.checks.format.LuaFormatCheck",
#     "weblate.checks.format.ObjectPascalFormatCheck",
#     "weblate.checks.format.SchemeFormatCheck",
#     "weblate.checks.format.CSharpFormatCheck",
#     "weblate.checks.format.JavaFormatCheck",
#     "weblate.checks.format.JavaMessageFormatCheck",
#     "weblate.checks.format.PercentPlaceholdersCheck",
#     "weblate.checks.format.VueFormattingCheck",
#     "weblate.checks.format.I18NextInterpolationCheck",
#     "weblate.checks.format.ESTemplateLiteralsCheck",
#     "weblate.checks.angularjs.AngularJSInterpolationCheck",
#     "weblate.checks.qt.QtFormatCheck",
#     "weblate.checks.qt.QtPluralCheck",
#     "weblate.checks.ruby.RubyFormatCheck",
#     "weblate.checks.consistency.PluralsCheck",
#     "weblate.checks.consistency.SamePluralsCheck",
#     "weblate.checks.consistency.ConsistencyCheck",
#     "weblate.checks.consistency.TranslatedCheck",
#     "weblate.checks.chars.EscapedNewlineCountingCheck",
#     "weblate.checks.chars.NewLineCountCheck",
#     "weblate.checks.markup.BBCodeCheck",
#     "weblate.checks.chars.ZeroWidthSpaceCheck",
#     "weblate.checks.render.MaxSizeCheck",
#     "weblate.checks.markup.XMLValidityCheck",
#     "weblate.checks.markup.XMLTagsCheck",
#     "weblate.checks.markup.MarkdownRefLinkCheck",
#     "weblate.checks.markup.MarkdownLinkCheck",
#     "weblate.checks.markup.MarkdownSyntaxCheck",
#     "weblate.checks.markup.URLCheck",
#     "weblate.checks.markup.SafeHTMLCheck",
#     "weblate.checks.placeholders.PlaceholderCheck",
#     "weblate.checks.placeholders.RegexCheck",
#     "weblate.checks.duplicate.DuplicateCheck",
#     "weblate.checks.source.OptionalPluralCheck",

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

# "weblate.checks.source.EllipsisCheck",
# "weblate.checks.source.MultipleFailingCheck",
# "weblate.checks.source.LongUntranslatedCheck",
# "weblate.checks.format.MultipleUnnamedFormatsCheck",
# "weblate.checks.glossary.GlossaryCheck",
# )

# List of automatic fixups
# AUTOFIX_LIST = (
#     "weblate.trans.autofixes.whitespace.SameBookendingWhitespace",
#     "weblate.trans.autofixes.chars.ReplaceTrailingDotsWithEllipsis",
#     "weblate.trans.autofixes.chars.RemoveZeroSpace",
#     "weblate.trans.autofixes.chars.RemoveControlChars",
# )

# List of enabled addons
# WEBLATE_ADDONS = (
#     "weblate.addons.gettext.GenerateMoAddon",
#     "weblate.addons.gettext.UpdateLinguasAddon",
#     "weblate.addons.gettext.UpdateConfigureAddon",
#     "weblate.addons.gettext.MsgmergeAddon",
#     "weblate.addons.gettext.GettextCustomizeAddon",
#     "weblate.addons.gettext.GettextAuthorComments",
#     "weblate.addons.cleanup.CleanupAddon",
#     "weblate.addons.cleanup.RemoveBlankAddon",
#     "weblate.addons.consistency.LanguaugeConsistencyAddon",
#     "weblate.addons.discovery.DiscoveryAddon",
#     "weblate.addons.autotranslate.AutoTranslateAddon",
#     "weblate.addons.flags.SourceEditAddon",
#     "weblate.addons.flags.TargetEditAddon",
#     "weblate.addons.flags.SameEditAddon",
#     "weblate.addons.flags.BulkEditAddon",
#     "weblate.addons.generate.GenerateFileAddon",
#     "weblate.addons.generate.PseudolocaleAddon",
#     "weblate.addons.json.JSONCustomizeAddon",
#     "weblate.addons.properties.PropertiesSortAddon",
#     "weblate.addons.git.GitSquashAddon",
#     "weblate.addons.removal.RemoveComments",
#     "weblate.addons.removal.RemoveSuggestions",
#     "weblate.addons.resx.ResxUpdateAddon",
#     "weblate.addons.yaml.YAMLCustomizeAddon",
#     "weblate.addons.cdn.CDNJSAddon",
# )

# E-mail address that error messages come from.
SERVER_EMAIL = "noreply@example.com"

# Default email address to use for various automated correspondence from
# the site managers. Used for registration emails.
DEFAULT_FROM_EMAIL = "noreply@example.com"

# List of URLs your site is supposed to serve
ALLOWED_HOSTS = ["*"]

# Configuration for caching
CACHES = {
    "default": {
        "BACKEND": "django_redis.cache.RedisCache",
        "LOCATION": "redis://127.0.0.1:6379/1",
        # If redis is running on same host as Weblate, you might
        # want to use unix sockets instead:

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

    # "LOCATION": "unix:///var/run/redis/redis.sock?db=1",
    "OPTIONS": {
        "CLIENT_CLASS": "django_redis.client.DefaultClient",
        "PARSER_CLASS": "redis.connection.HiredisParser",
        # If you set password here, adjust CELERY_BROKER_URL as well
        "PASSWORD": None,
        "CONNECTION_POOL_KWARGS": {},
    },
    "KEY_PREFIX": "weblate",
},
"avatar": {
    "BACKEND": "django.core.cache.backends.filebased.FileBasedCache",
    "LOCATION": os.path.join(DATA_DIR, "avatar-cache"),
    "TIMEOUT": 86400,
    "OPTIONS": {"MAX_ENTRIES": 1000},
},
}

# Store sessions in cache
SESSION_ENGINE = "django.contrib.sessions.backends.cache"
# Store messages in session
MESSAGE_STORAGE = "django.contrib.messages.storage.session.SessionStorage"

# REST framework settings for API
REST_FRAMEWORK = {
    # Use Django's standard `django.contrib.auth` permissions,
    # or allow read-only access for unauthenticated users.
    "DEFAULT_PERMISSION_CLASSES": [
        # Require authentication for login required sites
        "rest_framework.permissions.IsAuthenticated"
        if REQUIRE_LOGIN
        else "rest_framework.permissions.IsAuthenticatedOrReadOnly"
    ],
    "DEFAULT_AUTHENTICATION_CLASSES": (
        "rest_framework.authentication.TokenAuthentication",
        "weblate.api.authentication.BearerAuthentication",
        "rest_framework.authentication.SessionAuthentication",
    ),
    "DEFAULT_THROTTLE_CLASSES": (
        "weblate.api.throttling.UserRateThrottle",
        "weblate.api.throttling.AnonRateThrottle",
    ),
    "DEFAULT_THROTTLE_RATES": {"anon": "100/day", "user": "5000/hour"},
    "DEFAULT_PAGINATION_CLASS": ("rest_framework.pagination.PageNumberPagination"),
    "PAGE_SIZE": 20,
    "VIEW_DESCRIPTION_FUNCTION": "weblate.api.views.get_view_description",
    "UNAUTHENTICATED_USER": "weblate.auth.models.get_anonymous",
}

# Fonts CDN URL
FONTS_CDN_URL = None

# Django compressor offline mode
COMPRESS_OFFLINE = False
COMPRESS_OFFLINE_CONTEXT = [
    {"fonts_cdn_url": FONTS_CDN_URL, "STATIC_URL": STATIC_URL, "LANGUAGE_BIDI": ↪
↪ True},
    {"fonts_cdn_url": FONTS_CDN_URL, "STATIC_URL": STATIC_URL, "LANGUAGE_BIDI": ↪
↪ False},
]

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```

# Require login for all URLs
if REQUIRE_LOGIN:
    LOGIN_REQUIRED_URLS = (r"/(.*)$",)

# In such case you will want to include some of the exceptions
# LOGIN_REQUIRED_URLS_EXCEPTIONS = (
#     rf"{URL_PREFIX}/accounts/(.*)$", # Required for login
#     rf"{URL_PREFIX}/admin/login/(.*)$", # Required for admin login
#     rf"{URL_PREFIX}/static/(.*)$", # Required for development mode
#     rf"{URL_PREFIX}/widgets/(.*)$", # Allowing public access to widgets
#     rf"{URL_PREFIX}/data/(.*)$", # Allowing public access to data exports
#     rf"{URL_PREFIX}/hooks/(.*)$", # Allowing public access to notification hooks
#     rf"{URL_PREFIX}/healthz/$", # Allowing public access to health check
#     rf"{URL_PREFIX}/api/(.*)$", # Allowing access to API
#     rf"{URL_PREFIX}/js/i18n/$", # JavaScript localization
#     rf"{URL_PREFIX}/contact/$", # Optional for contact form
#     rf"{URL_PREFIX}/legal/(.*)$", # Optional for legal app
# )

# Silence some of the Django system checks
SILENCED_SYSTEM_CHECKS = [
    # We have modified django.contrib.auth.middleware.AuthenticationMiddleware
    # as weblate.accounts.middleware.AuthenticationMiddleware
    "admin.E408"
]

# Celery worker configuration for testing
# CELERY_TASK_ALWAYS_EAGER = True
# CELERY_BROKER_URL = "memory://"
# CELERY_TASK_EAGER_PROPAGATES = True
# Celery worker configuration for production
CELERY_TASK_ALWAYS_EAGER = False
CELERY_BROKER_URL = "redis://localhost:6379"
CELERY_RESULT_BACKEND = CELERY_BROKER_URL

# Celery settings, it is not recommended to change these
CELERY_WORKER_MAX_MEMORY_PER_CHILD = 200000
CELERY_BEAT_SCHEDULE_FILENAME = os.path.join(DATA_DIR, "celery", "beat-schedule")
CELERY_TASK_ROUTES = {
    "weblate.trans.tasks.auto_translate*": {"queue": "translate"},
    "weblate.accounts.tasks.notify*": {"queue": "notify"},
    "weblate.accounts.tasks.send_mails": {"queue": "notify"},
    "weblate.utils.tasks.settings_backup": {"queue": "backup"},
    "weblate.utils.tasks.database_backup": {"queue": "backup"},
    "weblate.wladmin.tasks.backup": {"queue": "backup"},
    "weblate.wladmin.tasks.backup_service": {"queue": "backup"},
    "weblate.memory.tasks.*": {"queue": "memory"},
}

# Enable plain database backups
DATABASE_BACKUP = "plain"

# Enable auto updating
AUTO_UPDATE = False

# PGP commits signing
WEBLATE_GPG_IDENTITY = None

# Third party services integration
MATOMO_SITE_ID = None
MATOMO_URL = None

```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
GOOGLE_ANALYTICS_ID = None
SENTRY_DSN = None
SENTRY_ENVIRONMENT = SITE_DOMAIN
AKISMET_API_KEY = None
```

2.18 Management commands

Shënim: Running management commands under a different user than the one running your webserver can result in files getting wrong permissions, please check *Leje sistemi kartelash* for more details.

You will find basic management commands (available as `./manage.py` in the Django sources, or as an extended set in a script called **weblate** installable atop Weblate).

2.18.1 Invoking management commands

As mentioned before, invocation depends on how you installed Weblate.

If using virtualenv for Weblate, you can either specify the full path to **weblate**, or activate the virtualenv prior to invoking it:

```
# Direct invocation
~/weblate-env/bin/weblate

# Activating virtualenv adds it to search path
. ~/weblate-env/bin/activate
weblate
```

If you are using source code directly (either from a tarball or Git checkout), the management script is `./manage.py` available in the Weblate sources. To run it:

```
python ./manage.py list_versions
```

If you've installed Weblate using the pip or pip3 installer, or by using the `./setup.py` script, the **weblate** is installed to your path (or virtualenv path), from where you can use it to control Weblate:

```
weblate list_versions
```

For the Docker image, the script is installed like above, and you can run it using **docker exec**:

```
docker exec --user weblate <container> weblate list_versions
```

For **docker-compose** the process is similar, you just have to use **docker-compose exec**:

```
docker-compose exec --user weblate weblate weblate list_versions
```

In case you need to pass it a file, you can temporary add a volume:

```
docker-compose exec --user weblate /tmp:/tmp weblate weblate importusers /tmp/
↪users.json
```

Shihni edhe:

Installing using Docker, Installing on Debian and Ubuntu, Installing on SUSE and openSUSE, Installing on RedHat, Fedora and CentOS, Installing from sources

2.18.2 add_suggestions

weblate add_suggestions <project> <component> <language> <file>

Të reja në versionin 2.5.

Imports a translation from the file to use as a suggestion for the given translation. It skips duplicated translations; only different ones are added.

--author USER@EXAMPLE.COM

E-mail of author for the suggestions. This user has to exist prior to importing (you can create one in the admin interface if needed).

Shembull:

```
weblate --author michal@cihar.com add_suggestions weblate application cs /tmp/
↪ suggestions-cs.po
```

2.18.3 auto_translate

weblate auto_translate <project> <component> <language>

Të reja në versionin 2.5.

Ndryshuar në versionin 4.6: Added parameter for translation mode.

Performs automatic translation based on other component translations.

--source PROJECT/COMPONENT

Specifies the component to use as source available for translation. If not specified all components in the project are used.

--user USERNAME

Specify username listed as author of the translations. «Anonymous user» is used if not specified.

--overwrite

Whether to overwrite existing translations.

--inconsistent

Whether to overwrite existing translations that are inconsistent (see *Jo i njëtrajtshëm*).

--add

Automatically add language if a given translation does not exist.

--mt MT

Use machine translation instead of other components as machine translations.

--threshold THRESHOLD

Similarity threshold for machine translation, defaults to 80.

--mode MODE

Specify translation mode, default is `translate` but `fuzzy` or `suggest` can be used.

Shembull:

```
weblate auto_translate --user nijel --inconsistent --source weblate/application_
↪ weblate website cs
```

Shihni edhe:

Përkthim i automatizuar

2.18.4 celery_queues

weblate celery_queues

Të reja në versionin 3.7.

Displays length of Celery task queues.

2.18.5 checkgit

weblate checkgit <project|project/component>

Prints current state of the back-end Git repository.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

2.18.6 commitgit

weblate commitgit <project|project/component>

Commits any possible pending changes to the back-end Git repository.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

2.18.7 commit_pending

weblate commit_pending <project|project/component>

Commits pending changes older than a given age.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

--age HOURS

Age in hours for committing. If not specified the value configured in *Component configuration* is used.

Shënim: This is automatically performed in the background by Weblate, so there no real need to invoke this manually, besides forcing an earlier commit than specified by *Component configuration*.

Shihni edhe:

Xhirim aktesh mirëmbajtjeje, COMMIT_PENDING_HOURS

2.18.8 cleanuptrans

weblate cleanuptrans

Cleans up orphaned checks and translation suggestions. There is normally no need to run this manually, as the cleanups happen automatically in the background.

Shihni edhe:

Xhirim aktesh mirëmbajtjeje

2.18.9 createadmin

weblate createadmin

Creates an `admin` account with a random password, unless it is specified.

--password PASSWORD

Provides a password on the command-line, to not generate a random one.

--no-password

Do not set password, this can be useful with `--update`.

--username USERNAME

Use the given name instead of `admin`.

--email USER@EXAMPLE.COM

Specify the admin e-mail address.

--name

Specify the admin name (visible).

--update

Update the existing user (you can use this to change passwords).

Ndryshuar në versionin 2.9: Added parameters `--username`, `--email`, `--name` and `--update`.

2.18.10 dump_memory

weblate dump_memory

Të reja në versionin 2.20.

Export a JSON file containing Weblate Translation Memory content.

Shihni edhe:

Kujtesë Përkthimesh, Weblate Translation Memory Schema

2.18.11 dumpuserdata

weblate dumpuserdata <file.json>

Dumps userdata to a file for later use by *importuserdata*

Ndihmëz: This comes in handy when migrating or merging Weblate instances.

2.18.12 import_demo

weblate import_demo

Të reja në versionin 4.1.

Creates a demo project with components based on [<https://github.com/WeblateOrg/demo>](https://github.com/WeblateOrg/demo).

This can be useful when developing Weblate.

2.18.13 import_json

weblate import_json <json-file>

Të reja në versionin 2.7.

Batch import of components based on JSON data.

The imported JSON file structure pretty much corresponds to the component object (see `GET /api/components/(string:project)/(string:component)/`). You have to include the name and filemask fields.

--project PROJECT

Specifies where the components will be imported from.

--main-component COMPONENT

Use the given VCS repository from this component for all of them.

--ignore

Skip (already) imported components.

--update

Update (already) imported components.

Ndryshuar në versionin 2.9: The parameters `--ignore` and `--update` are there to deal with already imported components.

Example of JSON file:

```
[
  {
    "slug": "po",
    "name": "Gettext PO",
    "file_format": "po",
    "filemask": "po/*.po",
    "new_lang": "none"
  },
  {
    "name": "Android",
    "filemask": "android/values-*/strings.xml",
    "template": "android/values/strings.xml",
    "repo": "weblate://test/test",
    "file_format": "aresource"
  }
]
```

Shihni edhe:

`import_memory`

2.18.14 import_memory

weblate import_memory <file>

Të reja në versionin 2.20.

Imports a TMX or JSON file into the Weblate translation memory.

--language-map LANGMAP

Allows mapping languages in the TMX to the Weblate translation memory. The language codes are mapped after normalization usually done by Weblate.

`--language-map en_US:en` will for example import all `en_US` strings as `en` ones.

This can be useful in case your TMX file locales happen not to match what you use in Weblate.

Shihni edhe:

Kujtesë Përkthimesh, Weblate Translation Memory Schema

2.18.15 import_project

weblate import_project <project> <gitrepo> <branch> <filemask>

Ndryshuar në versionin 3.0: The import_project command is now based on the *Pikasje përbërësish* add-on, leading to some changes in behavior and what parameters are accepted.

Batch imports components into project based on filemask.

<project> names an existing project, into which the components are to be imported.

The <gitrepo> defines the Git repository URL to use, and <branch> signifies the Git branch. To import additional translation components from an existing Weblate component, use a *weblate://<project>/<component>* URL for the <gitrepo>.

The <filemask> defines file discovery for the repository. It can be either be made simple using wildcards, or it can use the full power of regular expressions.

The simple matching uses **** for component name and *** for language, for example: ***/*.po*

The regular expression has to contain groups named *component* and *language*. For example: *(?P<language>[^\s]*) / (?P<component>[^\s]*) \.po*

The import matches existing components based on files and adds the ones that do not exist. It does not change already existing ones.

--name-template TEMPLATE

Customize the name of a component using Django template syntax.

For example: *Documentation: {{ component }}*

--base-file-template TEMPLATE

Customize the base file for monolingual translations.

Për shembull: *{{ component }}/res/values/string.xml*

--new-base-template TEMPLATE

Customize the base file for addition of new translations.

Për shembull: *{{ component }}/ts/en.ts*

--file-format FORMAT

You can also specify the file format to use (see *Formate të mbuluar kartelash*), the default is auto-detection.

--language-regex REGEX

You can specify language filtering (see *Component configuration*) with this parameter. It has to be a valid regular expression.

--main-component

You can specify which component will be chosen as the main one—the one actually containing the VCS repository.

--license NAME

Specify the overall, project or component translation license.

--license-url URL

Specify the URL where the translation license is to be found.

--vcs NAME

In case you need to specify which version control system to use, you can do it here. The default version control is Git.

To give you some examples, let's try importing two projects.

First The Debian Handbook translations, where each language has separate a folder with the translations of each chapter:

```
weblate import_project \
  debian-handbook \
  git://anonscm.debian.org/debian-handbook/debian-handbook.git \
  squeeze/master \
  '*/**.po'
```

Then the Tanaguru tool, where the file format needs be specified, along with the base file template, and how all components and translations are located in single folder:

```
weblate import_project \
  --file-format=properties \
  --base-file-template=web-app/tgol-web-app/src/main/resources/i18n/%s-I18N.
↪properties \
  tanaguru \
  https://github.com/Tanaguru/Tanaguru \
  master \
  web-app/tgol-web-app/src/main/resources/i18n/**-I18N*.properties
```

More complex example of parsing of filenames to get the correct component and language out of a filename like `src/security/Numerous_security_holes_in_0.10.1.de.po`:

```
weblate import_project \
  tails \
  git://git.tails.boum.org/tails master \
  'wiki/src/security/(?P<component>.*).\.(?P<language>[^.]*)\.po$'
```

Filtering only translations in a chosen language:

```
./manage import_project \
  --language-regex '^(cs|sk)$' \
  weblate \
  https://github.com/WeblateOrg/weblate.git \
  'weblate/locale/*/LC_MESSAGES/**/*.po'
```

Importing Sphinx documentation split to multiple files:

```
$ weblate import_project --name-template 'Documentation: %s' \
  --file-format po \
  project https://github.com/project/docs.git master \
  'docs/locale/*/LC_MESSAGES/**/*.po'
```

Importing Sphinx documentation split to multiple files and directories:

```
$ weblate import_project --name-template 'Directory 1: %s' \
  --file-format po \
  project https://github.com/project/docs.git master \
  'docs/locale/*/LC_MESSAGES/dir1/**/*.po'
$ weblate import_project --name-template 'Directory 2: %s' \
  --file-format po \
  project https://github.com/project/docs.git master \
  'docs/locale/*/LC_MESSAGES/dir2/**/*.po'
```

Shihni edhe:

More detailed examples can be found in the starting chapter, alternatively you might want to use *import_json*.

2.18.16 importuserdata

weblate importuserdata <file.json>

Imports user data from a file created by *dumpuserdata*

2.18.17 importusers

weblate importusers --check <file.json>

Imports users from JSON dump of the Django auth_users database.

--check

With this option it will just check whether a given file can be imported and report possible conflicts arising from usernames or e-mails.

You can dump users from the existing Django installation using:

```
weblate dumpdata auth.User > users.json
```

2.18.18 install_addon

Të reja në versionin 3.2.

weblate install_addon --addon ADDON <project|project/component>

Installs an add-on to a set of components.

--addon ADDON

Name of the add-on to install. For example `weblate.gettext.customize`.

--configuration CONFIG

JSON encoded configuration of an add-on.

--update

Update the existing add-on configuration.

You can either define which project or component to install the add-on in (for example `weblate/application`), or use `--all` to include all existing components.

To install *Përshatni përfundimin e gettext-it* for all components:

```
weblate install_addon --addon weblate.gettext.customize --config '{"width": -1}' --  
↪update --all
```

Shihni edhe:

Shtesa

2.18.19 list_languages

weblate list_languages <locale>

Lists supported languages in MediaWiki markup - language codes, English names and localized names.

This is used to generate `<https://wiki.110n.cz/Slovn%C3%ADk_s_n%C3%A1zvy_jazyk%C5%AF>`.

2.18.20 list_translators

weblate list_translators <project|project/component>

Lists translators by contributed language for the given project:

```
[French]
Jean Dupont <jean.dupont@example.com>
[English]
John Doe <jd@example.com>
```

--language-code

List names by language code instead of language name.

You can either define which project or component to use (for example `weblate/application`), or use `--all` to list translators from all existing components.

2.18.21 list_versions

weblate list_versions

Lists all Weblate dependencies and their versions.

2.18.22 loadpo

weblate loadpo <project|project/component>

Reloads translations from disk (for example in case you have done some updates in the VCS repository).

--force

Force update, even if the files should be up-to-date.

--lang LANGUAGE

Limit processing to a single language.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

Shënim: You seldom need to invoke this, Weblate will automatically load changed files for every VCS update. This is needed in case you manually changed an underlying Weblate VCS repository or in some special cases following an upgrade.

2.18.23 lock_translation

weblate lock_translation <project|project/component>

Prevents further translation of a component.

Ndihmëz: Useful in case you want to do some maintenance on the underlying repository.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

Shihni edhe:

`unlock_translation`

2.18.24 move_language

weblate move_language source target

Të reja në versionin 3.0.

Allows you to merge language content. This is useful when updating to a new version which contains aliases for previously unknown languages that have been created with the *(generated)* suffix. It moves all content from the *source* language to the *target* one.

Shembull:

```
weblate move_language cze cs
```

After moving the content, you should check whether there is anything left (this is subject to race conditions when somebody updates the repository meanwhile) and remove the *(generated)* language.

2.18.25 pushgit

weblate pushgit <project|project/component>

Pushes committed changes to the upstream VCS repository.

--force-commit

Force commits any pending changes, prior to pushing.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

Shënim: Weblate pushes changes automatically if *Push on commit* in *Component configuration* is turned on, which is the default.

2.18.26 unlock_translation

weblate unlock_translation <project|project/component>

Unlocks a given component, making it available for translation.

Ndihmëz: Useful in case you want to do some maintenance on the underlying repository.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

Shihni edhe:

lock_translation

2.18.27 setupgroups

weblate setupgroups

Configures default groups and optionally assigns all users to that default group.

--no-privs-update

Turns off automatic updating of existing groups (only adds new ones).

--no-projects-update

Prevents automatic updates of groups for existing projects. This allows adding newly added groups to existing projects, see *Kontroll hyrjesh te projekti*.

Shihni edhe:

Listë privilegjesh

2.18.28 setuplang

weblate setuplang

Updates list of defined languages in Weblate.

--no-update

Turns off automatic updates of existing languages (only adds new ones).

2.18.29 updatechecks

weblate updatechecks <project|project/component>

Updates all checks for all strings.

Ndihmëz: Useful for upgrades which do major changes to checks.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

2.18.30 updategit

weblate updategit <project|project/component>

Fetches remote VCS repositories and updates the internal cache.

You can either define which project or component to update (for example `weblate/application`), or use `--all` to update all existing components.

Shënim: Usually it is better to configure hooks in the repository to trigger *Hook-e njoftimesh*, instead of regular polling by *updategit*.

2.19 Lajmërimi

Ndryshuar në versionin 4.0: In prior releases this feature was called whiteboard messages.

Provide info to your translators by posting announcements, site-wide, per project, component, or language.

Announce the purpose, deadlines, status, or specify targets for translation.

The users will receive notification on the announcements for watched projects (unless they opt out).

This can be useful for various things from announcing the purpose of the website to specifying targets for translations.

The announcements can be posted on each level in the *Manage* menu, using *Post announcement*:

Translations will be used only if they reach 60%.

Components Languages Info Search Insights Files Tools **Manage** Share Not watching

Post announcement

Message

You can use Markdown and mention users by @username.

Category

Info (light blue)

Category defines color used for the message.

Expiry date

mm/dd/yyyy

The message will be not shown after this date. Use it to announce string freeze and translation deadline for next release.

☒ **Notify users**

The message is shown for all translations within the project, until its given expiry, or permanently until it is deleted.

Add

Powered by Weblate 4.8 About Weblate Legal Contact Documentation Donate to Weblate

It can be also added using the admin interface:

Weblate administration
WELCOME, **WEBLATE TEST**. [RETURN TO WEBLATE](#) / [DOCUMENTATION](#) / [CHANGE PASSWORD](#) / [SIGN OUT](#)

Home · Weblate translations · Announcements · Add Announcement

Add Announcement

Required fields are marked in bold.

Message:

Translations will be used only if they reach 60%

You can use Markdown and mention users by @username.

Project: WeblateOrg

Component:

Language:

Category: Info (light blue)
Category defines color used for the message.

Expiry date: Today |

The message will be not shown after this date. Use it to announce string freeze and translation deadline for next release.

☒ Notify users

Save and add another
Save and continue editing
SAVE

The announcements are then shown based on their specified context:

S'është specifikuar kontekst

Shfaqur te pulti (faqja ardhjesh).

Project specified

Shown within the project, including all its components and translations.


Component specified

Shown for a given component and all its translations.

Language specified

Shown on the language overview and all translations in that language.

This is how it looks on the language overview page:



2.20 Lista Përbërësish

Specify multiple lists of components to appear as options on the user dashboard, from which users can pick one as their default view. See [Pult](#) to learn more.

Ndryshuar në versionin 2.20: A status will be presented for each component list presented on the dashboard.

The names and content of component lists can be specified in the admin interface, in *Component lists* section. Each component list must have a name that is displayed to the user, and a slug representing it in the URL.

Ndryshuar në versionin 2.13: Change dashboard settings for anonymous users from the admin interface, altering what dashboard is presented to unauthenticated users.

2.20.1 Automatic component lists

Të reja në versionin 2.13.

Add components to the list automatically based on their slug by creating *Automatic component list assignment* rules.

- Useful for maintaining component lists for large installations, or in case you want to have one component list with all components on your Weblate installation.

Ndihmëz: Make a component list containing all the components of your Weblate installation.

1. Define *Automatic component list assignment* with `^.*$` as regular expression in both the project and the component fields, as shown on this image:

Weblate administration

WELCOME, **WEBLATE TEST**. [RETURN TO WEBLATE](#) / [DOCUMENTATION](#) / [CHANGE PASSWORD](#) / [SIGN OUT](#)

[Home](#) > [Weblate translations](#) > [Component lists](#) > Add Component list

Add Component list

Required fields are marked in bold.

Component list name:
Display name

URL slug:
Name used in URLs and filenames.

☒ **Show on dashboard**
When enabled this component list will be shown as a tab on the dashboard

Components:

Available components ⓘ

WeblateOrg/Django
WeblateOrg/Language names
WeblateOrg/WeblateOrg

Chosen components ⓘ

[Choose all](#) ⓘ[Remove all](#)

Hold down "Control", or "Command" on a Mac, to select more than one.

AUTOMATIC COMPONENT LIST ASSIGNMENTS

PROJECT REGULAR EXPRESSION ⓘ	COMPONENT REGULAR EXPRESSION ⓘ	DELETE?
<input type="text" value="^.*\$"/>	<input type="text" value="^.*\$"/>	✕

[+ Add another Automatic component list assignment](#)

[Save and add another](#)

[Save and continue editing](#)

[SAVE](#)

2.21 Optional Weblate modules

Several optional modules are available for your setup.

2.21.1 Git exporter

Të reja në versionin 2.10.

Provides you read-only access to the underlying Git repository using HTTP(S).

Instalim

1. Add `weblate.gitexport` to installed apps in `settings.py`:

```
INSTALLED_APPS += ("weblate.gitexport",)
```

2. Export existing repositories by migrating your database after installation:

```
weblate migrate
```

Usage

The module automatically hooks into Weblate and sets the exported repository URL in the *Component configuration*. The repositories are accessible under the `/git/` part of the Weblate URL, for example `https://example.org/git/weblate/main/`.

Repositories for publicly available projects can be cloned without authentication:

```
git clone 'https://example.org/git/weblate/main/'
```

Access to browse the repositories with restricted access (with *Private access control* or when `REQUIRE_LOGIN` is enabled) requires an API token which can be obtained in your *user profile*:

```
git clone 'https://user:KEY@example.org/git/weblate/main/'
```

Ndihmëz: By default members or *Users* group and anonymous user have access to the repositories for public projects via *Access repository* and *Power user* roles.

2.21.2 Faturim

Të reja në versionin 2.4.

This is used on *Hosted Weblate* to define billing plans, track invoices and usage limits.

Instalim

1. Add `weblate.billing` to installed apps in `settings.py`:

```
INSTALLED_APPS += ("weblate.billing",)
```

2. Run the database migration to optionally install additional database structures for the module:

```
weblate migrate
```

Usage

After installation you can control billing in the admin interface. Users with billing enabled will get new *Billing* tab in their *Profil përdoruesi*.

The billing module additionally allows project admins to create new projects and components without being superusers (see *Adding translation projects and components*). This is possible when following conditions are met:

- The billing is in its configured limits (any overusage results in blocking of project/component creation) and paid (if its price is non zero)
- The user is admin of existing project with billing or user is owner of billing (the latter is necessary when creating new billing for users to be able to import new projects).

Upon project creation user is able to choose which billing should be charged for the project in case he has access to more of them.

2.21.3 Ligjore

Të reja në versionin 2.15.

This is used on *Hosted Weblate* to provide required legal documents. It comes provided with blank documents, and you are expected to fill out the following templates in the documents:

legal/documents/tos.html Terms of service document

legal/documents/privacy.html Privacy policy document

legal/documents/summary.html Short overview of the terms of service and privacy policy

Shënim: Legal documents for the Hosted Weblate service are available in this Git repository <<https://github.com/WeblateOrg/wllegal/tree/main/wllegal/templates/legal/documents>>.

Most likely these will not be directly usable to you, but might come in handy as a starting point if adjusted to meet your needs.

Instalim

1. Add `weblate.legal` to installed apps in `settings.py`:

```
INSTALLED_APPS += ("weblate.legal",)

# Optional:

# Social auth pipeline to confirm TOS upon registration/subsequent sign in
SOCIAL_AUTH_PIPELINE += ("weblate.legal.pipeline.tos_confirm",)

# Middleware to enforce TOS confirmation of signed in users
MIDDLEWARE += [
    "weblate.legal.middleware.RequireTOSMiddleware",
]
```

2. Run the database migration to optionally install additional database structures for the module:

```
weblate migrate
```

3. Edit the legal documents in the `weblate/legal/templates/legal/` folder to match your service.

Usage

After installation and editing, the legal documents are shown in the Weblate UI.

2.21.4 Avatars

Avatars are downloaded and cached server-side to reduce information leaks to the sites serving them by default. The built-in support for fetching avatars from e-mails addresses configured for it can be turned off using `ENABLE_AVATARS`.

Weblate currently supports:

- [Gravatar](#)
- [Libravatar](#)

Shihni edhe:

Avatar caching, `AVATAR_URL_PREFIX`, `ENABLE_AVATARS`

2.21.5 Spam protection

You can protect against spamming by users by using the [Akismet](#) service.

1. Install the *akismet* Python module (this is already included in the official Docker image).
2. Obtain the Akismet API key.
3. Store it as `AKISMET_API_KEY` or `WEBLATE_AKISMET_API_KEY` in Docker.

Following content is sent to Akismet for checking:

- Suggestions from unauthenticated users
- Project and component descriptions and links

Shënim: This (among other things) relies on IP address of the client, please see *[Running behind reverse proxy](#)* for properly configuring that.

Shihni edhe:

Running behind reverse proxy, `AKISMET_API_KEY`, `WEBLATE_AKISMET_API_KEY`

2.21.6 Signing Git commits with GnuPG


Të reja në versionin 3.1.

All commits can be signed by the GnuPG key of the Weblate instance.

1. Turn on `WEBLATE_GPG_IDENTITY`. (Weblate will generate a GnuPG key when needed and will use it to sign all translation commits.)

This feature needs GnuPG 2.1 or newer installed.

You can find the key in the `DATA_DIR` and the public key is shown on the «About» page:


[Dashboard](#)
[Projects](#)
[Languages](#)
[Checks](#)
[Register](#)
[Sign in](#)

[About Weblate](#) / [Weblate keys](#)

[About Weblate](#)
[Statistics](#)
[Keys](#)

SSH key

SSH key not available.

Commit signing

All commits made with Weblate are signed with the GPG key A60A50224147186AD3479B41E479AAE9BD71880A, for which the corresponding public key is found below.

```
-----BEGIN PGP PUBLIC KEY BLOCK-----

mQGNBGEgtI8BDACcMONIb+NocQVR5KkFFNs6G+88uRVKbnLUX1YaDnHNg63LZ/i
SOYrAfDd+fhX6hRUj32Zpn0wtdzhZBU7hBHPjmG4r9p05Guswf689VWQPoHrwY9X
q0TWCJDSIXz5+d5WkAebHqvtKQORIWFKlyTzWEajuHSXhuWgAiZC01JkNwVc10bW
AFqDCEIZ1fi8Iz+fHGHZ9AJNEtiURX5HyPPhF3ijyMlygzTfxEOkqiiHEJ9IIfRY
zGWYsJ0g6rqhWbVfGym68ti+2vPw0GORVHjQqzIFaK2WVgeu3hdZ+fbXirmWKcm
dZarsTFvclyn3vX7NG8eSIHn1rWZXCjgBL/2hMwphx3F3ycyQdAcvp2rJ8Q/ky
ZTmjTIfmq/hBmf0TJCsmHRBtfUquMjdXGQX7loXf9MaoosEtBj9BKIAJNspk3B7x
trbwvzZVUPq8oemmA9DvXWz0kISrDjlyl3b5qdKMBPcEPSjTjGeDO+PurlRF6mj
CIPhJ3Q3Qq69QEAEQEAAAbQdV2VibGF0ZSA8d2VibGF0ZUBleGFtcGxlMnVbT6J
Ac4EEwEKADgWlQSmCIAiQUcYatNHm0HkearpvXGICgUCYSC2XwlbAwULCQgHAgYV
CgkICwIEFgIDAQIeAQIXgAAKCRDkearpvXGICqJsDACMLe/VWw6wHE0hYq1fGikR
QbIRMeVn8UueOsoDsUwx/w3rYJku6V1Kmniozq2rjDBTfRRi1XfZbLQsrThCqUsp
pGRq3pIsIZ1brgLfRk7jROjJ6WGIjZdWKK3nKBkZRS2UMKAGQlw7Di0f0hT4JFwi
POdWbRnEmSvSOTIUR7mI00KMst1Ioc3cXz2HaOx1h/GTNI mYB+77WCORN/K6YDRoo
```

[Powered by Weblate 4.8](#)
[About Weblate](#)
[Legal](#)
[Contact](#)
[Documentation](#)
[Donate to Weblate](#)

2. Alternatively you can also import existing keys into Weblate, just set `HOME=$DATA_DIR/home` when invoking `gpg`.

Shihni edhe:

`WEBLATE_GPG_IDENTITY`

2.21.7 Rate limiting

Ndryshuar në versionin 3.2: The rate limiting now accepts more fine-grained configuration.

Ndryshuar në versionin 4.6: The rate limiting no longer applies to superusers.

Several operations in Weblate are rate limited. At most `RATELIMIT_ATTEMPTS` attempts are allowed within `RATELIMIT_WINDOW` seconds. The user is then blocked for `RATELIMIT_LOCKOUT`. There are also settings specific to scopes, for example `RATELIMIT_CONTACT_ATTEMPTS` or `RATELIMIT_TRANSLATE_ATTEMPTS`. The table below is a full list of available scopes.

The following operations are subject to rate limiting:

Emër	Fokus	Allowed attempts	Ratelimit window	Lockout period
Regjistrim	REGISTRATION	5	300	600
Sending message to admins	MESSAGE	5	300	600
Password authentication on sign in	LOGIN	5	300	600
Sitewide search	SEARCH	6	60	60
Translating	TRANSLATE	30	60	600
Adding to glossary	GLOSSARY	30	60	600
Starting translation into a new language	LANGUAGE	2	300	600
Creating new project	PROJECT	5	600	600

If a user fails to log in `AUTH_LOCK_ATTEMPTS` times, password authentication will be turned off on the account until having gone through the process of having its password reset.

The settings can be also applied in the Docker container by adding `WEBLATE_` prefix to the setting name, for example `RATELIMIT_ATTEMPTS` becomes `WEBLATE_RATELIMIT_ATTEMPTS`.

The API has separate rate limiting settings, see *API rate limiting*.

Shihni edhe:

Rate limiting, Running behind reverse proxy, API rate limiting

2.21.8 Fedora Messaging integration

Fedora Messaging is AMQP-based publisher for all changes happening in Weblate. You can hook additional services on changes happening in Weblate using this.

The Fedora Messaging integration is available as a separate Python module `weblate-fedora-messaging`. Please see https://github.com/WeblateOrg/fedora_messaging/ for setup instructions.

2.22 Përshtatje e Weblate-it

Extend and customize using Django and Python. Contribute your changes upstream so that everybody can benefit. This reduces your maintenance costs; code in Weblate is taken care of when changing internal interfaces or refactoring the code.

Sinjalizim: Neither internal interfaces nor templates are considered a stable API. Please review your own customizations for every upgrade, the interfaces or their semantics might change without notice.

Shihni edhe:

Dhënie ndihmese te Weblate

2.22.1 Krijim i një moduli Python

If you are not familiar with Python, you might want to look into [Python For Beginners](#), explaining the basics and pointing to further tutorials.

To write some custom Python code (called a module), a place to store it is needed, either in the system path (usually something like `/usr/lib/python3.7/site-packages/`) or in the Weblate directory, which is also added to the interpreter search path.

Better yet, turn your customization into a proper Python package:

1. Create a folder for your package (we will use `weblate_customization`).
2. Within it, create a `setup.py` file to describe the package:

```
from setuptools import setup

setup(
    name="weblate_customization",
    version="0.0.1",
    author="Your name",
    author_email="yourname@example.com",
    description="Sample Custom check for Weblate.",
    license="GPLv3+",
    keywords="Weblate check example",
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
packages=["weblate_customization"],
)
```

3. Create a folder for the Python module (also called `weblate_customization`) for the customization code.
4. Within it, create a `__init__.py` file to make sure Python can import the module.
5. This package can now be installed using **`pip install -e`**. More info to be found in “Editable” Installs.
6. Once installed, the module can be used in the Weblate configuration (for example `weblate_customization.checks.FooCheck`).

Your module structure should look like this:

```
weblate_customization
├── setup.py
└── weblate_customization
    ├── __init__.py
    ├── addons.py
    └── checks.py
```

You can find an example of customizing Weblate at <<https://github.com/WeblateOrg/customize-example>>, it covers all the topics described below.

2.22.2 Ndryshimi i stemës

1. Create a simple Django app containing the static files you want to overwrite (see *Krijim i një moduli Python*).

Branding appears in the following files:

icons/weblate.svg Stemë e shfaqur te shtylla e lëvizjeve.

logo-*.png Web icons depending on screen resolution and web-browser.

favicon.ico Web icon used by legacy browsers.

weblate-*.png Avatars for bots or anonymous users. Some web-browsers use these as shortcut icons.

email-logo.png E përdorur në email-e njoftimesh.

2. Add it to `INSTALLED_APPS`:

```
INSTALLED_APPS = (
    # Add your customization as first
    "weblate_customization",
    # Weblate apps are here...
)
```

3. Run `weblate collectstatic --noinput`, to collect static files served to clients.

Shihni edhe:

Managing static files (e.g. images, JavaScript, CSS), *Serving static files*

2.22.3 Custom quality checks, addons and auto-fixes

To install your code for *Custom automatic fixups*, *Si të shkruani kontrollet tuaja* or *Writing add-on* in Weblate:

1. Place the files into your Python module containing the Weblate customization (see *Krijim i një moduli Python*).
2. Add its fully-qualified path to the Python class in the dedicated settings (`WEBLATE_ADDONS`, `CHECK_LIST` or `AUTOFIX_LIST`):

```
# Checks
CHECK_LIST += ("weblate_customization.checks.FooCheck",)

# Autofixes
AUTOFIX_LIST += ("weblate_customization.autofix.FooFixer",)

# Add-ons
WEBLATE_ADDONS += ("weblate_customization.addons.ExamplePreAddon",)
```

Shihni edhe:

Custom automatic fixups, *Si të shkruani kontrollet tuaja*, *Writing add-on*, *Executing scripts from add-on*

2.23 Ndërfaqe administrimi

The management interface offer administration settings under the `/manage/` URL. It is available for users signed in with admin privileges, accessible by using the wrench icon top right:

The screenshot shows the Weblate management interface. At the top, there's a navigation bar with 'Weblate' logo, 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below this is a 'Manage' section with a wrench icon. The main content area has a sidebar with 'Weblate status' (selected), 'Backups', 'Translation memory', 'Performance report', 'SSH keys', 'Alerts', 'Repositories', 'Users', and 'Appearance'. The 'Weblate status' section displays the following information:

- Weblate support status** (with an info icon)
- Weblate version**: 4.8 — c05266dad2657545a900f6c74c66e26a3cb322ff
- Support status**: Community support
- Buttons: **Purchase support package** and **Donate to Weblate**

Below this, there's a section titled 'Activate support package' (with an info icon). It contains the text: 'The support packages include priority e-mail support, or cloud backups of your Weblate installation.' Underneath, there's a label 'Activation token' and an input field. A note says: 'Please enter the activation token obtained when making the subscription.' At the bottom of this section are buttons: **Activate** and **Purchase support package**.

At the very bottom of the page, there's a footer with the text: 'Powered by Weblate 4.8' followed by links: 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

It includes basic overview of your Weblate:

- Support status, see *Getting support for Weblate*
- Backups, see *Kopjeruajtje dhe zhvendosje e Weblate*
- Shared translation memory, see *Kujtesë Përkthimesh*
- Performance report to review Weblate health and length of Celery queues

- SSH keys management, see *Depo SSH*
- Alerts overview for all components, see alerts

2.23.1 Ndërfaqe përgjegjësi Django

Sinjalizim: Will be removed in the future, as its use is discouraged—most features can be managed directly in Weblate.

Here you can manage objects stored in the database, such as users, translations and other settings:

Weblate administration
WELCOME **WEBLATE TEST** / RETURN TO WEBLATE / DOCUMENTATION / CHANGE PASSWORD / SIGN OUT

Site administration

REPORTS

Weblate support status
Status of repositories
SSH keys
Performance report
Translation memory

ACCOUNTS

Audit log entries + Add Change
User profiles + Add Change
Verified e-mails + Add Change

AUTH TOKEN

Tokens + Add Change

AUTHENTICATION

Groups + Add Change
Roles + Add Change
Users + Add Change

BILLING

Billing plans + Add Change
Customer billings + Add Change
Invoices + Add Change

FONTS

Font groups + Add Change
Fonts + Add Change

LEGAL

TOS agreements + Add Change

PYTHON SOCIAL AUTH

Associations + Add Change
Nonces + Add Change
User social auths + Add Change

SCREENSHOTS

Screenshots + Add Change

TRANSLATION MEMORY

Translation memory entries + Add Change

WEBLATE CONFIGURATION

Settings + Add Change

WEBLATE LANGUAGES

Languages + Add Change

WEBLATE TRANSLATIONS

Announcements + Add Change
Component lists + Add Change
Components + Add Change
Contributor agreements + Add Change
Projects + Add Change

Recent actions

My actions
None available

In the *Reports* section, you can check the status of your site, tweak it for *Production setup*, or manage SSH keys used to access *Hyrje në depo*.

Manage database objects under any of the sections. The most interesting one is probably *Weblate translations*, where you can manage translatable projects, see *Project configuration* and *Component configuration*.

Weblate languages holds language definitions, explained further in *Language definitions*.

Shtimi i një projekti

Adding a project serves as container for all components. Usually you create one project for one piece of software, or book (See *Project configuration* for info on individual parameters):

Weblate administration
WELCOME, **WEBLATE TEST** · RETURN TO WEBLATE / DOCUMENTATION / CHANGE PASSWORD / SIGN OUT

Home · Weblate translations · Projects · Add Project

Add Project

Required fields are marked in bold.

Project name:

Display name

URL slug:

Name used in URLs and filenames.

Project website:

Main website of translated project.

Translation instructions:

You can use Markdown and mention users by @username.

☒ **Set "Language-Team" header**

Lets Weblate update the "Language-Team" file header of your project.

☒ **Use shared translation memory**

Uses the pool of shared translations between projects.

☒ **Contribute to shared translation memory**

Contributes to the pool of shared translations between projects.

Access control:

How to restrict access to this project is detailed in the documentation.

☐ **Enable reviews**

Requires dedicated reviewers to approve translations.

☐ **Enable source reviews**

Requires dedicated reviewers to approve source strings.

☒ **Enable hooks**

Whether to allow updating this repository by remote hooks.

Language aliases:

Comma-separated list of language code mappings, for example: en_GB,en_US,en

Shihni edhe:

Project configuration

Përbërës dygjuhësh

Once you have added a project, translation components can be added to it. (See *Component configuration* for info regarding individual parameters):

[illegible]

Shihni edhe:

Component configuration, Formate dygjuhësh dhe njëgjuhësh

Përbërës njëgjuhësh

For easier translation of these, provide a template file containing the mapping of message IDs to its respective source language (usually English). (See *Component configuration* for info regarding individual parameters):

[illegible]

Shihni edhe:

Component configuration, Formate dygjuhësh dhe njëgjuhësh

2.24 Getting support for Weblate

Weblate is copylefted libre software with community support. Subscribers receive priority support at no extra charge. Prepaid help packages are available for everyone. You can find more info about current support offerings at <https://weblate.org/support/>.

2.24.1 Integrating support

Të reja në versionin 3.8.

Purchased support packages can optionally be integrated into your Weblate [subscription management](#) interface, from where you will find a link to it. Basic instance details about your installation are also reported back to Weblate this way.

The screenshot shows the Weblate dashboard interface. At the top is a navigation bar with 'Weblate' logo, 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below this is a 'Manage' section with various links: 'Weblate status', 'Backups', 'Translation memory', 'Performance report', 'SSH keys', 'Alerts', 'Repositories', 'Users', and 'Appearance'. The 'Weblate status' link is highlighted. Below the navigation bar, there is a 'Weblate support status' section. It displays the 'Weblate version' as '4.8 — c05266dad2657545a900f6c74c66e26a3cb322ff' and the 'Support status' as 'Community support'. There are two buttons: 'Purchase support package' and 'Donate to Weblate'. Below this is an 'Activate support package' section. It contains a text box for an 'Activation token' and a message: 'The support packages include priority e-mail support, or cloud backups of your Weblate installation. Please enter the activation token obtained when making the subscription.' There are also two buttons: 'Activate' and 'Purchase support package'. At the bottom of the page, there is a footer with the text 'Powered by Weblate 4.8' and links to 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

2.24.2 Data submitted to the Weblate

- URL where your Weblate instance is configured
- Your site title
- The Weblate version you are running
- Tallies of some objects in your Weblate database (projects, components, languages, source strings and users)
- The public SSH key of your instance

Additionally, when *Zbuloni Weblate-in* is turned on:

- List of public projects (name, URL and website)

No other data is submitted.

2.24.3 Integration services

- See if your support package is still valid
- *Weblate provisioned backup storage*
- *Zbuloni Weblate-in*

Ndihmëz: Purchased support packages are already activated upon purchase, and can be used without integrating them.

2.24.4 Zbuloni Weblate-in

Të reja në versionin 4.5.2.

Shënim: Kjo veçori gjendet aktualisht në version të hershëm beta.

Discover Weblate is an opt-in service that makes it easier for users to find Weblate servers and communities. Users can browse registered services on <<https://weblate.org/discover/>>, and find there projects to contribute.

Getting listed

Ndihmëz: Participating in Discover Weblate makes Weblate submit some information about your server, please see *Data submitted to the Weblate*.

To list your server with an active support subscription (see *Integrating support*) in Discover Weblate all you need to do is turn this on in the management panel:

The screenshot displays the Weblate management dashboard. At the top, there's a navigation bar with 'Weblate' logo and links for 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below this is a 'Manage' section with tabs for 'Weblate status', 'Backups', 'Translation memory', 'Performance report', 'SSH keys', 'Alerts', 'Repositories', 'Users', and 'Appearance'. The 'Weblate status' tab is active, showing the 'Weblate support status' section. This section includes the 'Weblate version' (4.8), 'Support status' (Community support), and a 'Discover Weblate' section stating 'Your Weblate is not listed on weblate.org' with an 'Enable discovery' button. At the bottom of this section are buttons for 'Manage support package', 'Purchase support package', and 'Donate to Weblate'. Below this is the 'Activate support package' section, which includes a text box for an 'Activation token' and an 'Activate' button. The footer of the interface shows 'Powered by Weblate 4.8' and links for 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

Webblate support status

Webblate version 4.8 — c05266dad2657545a900f6c74c66e26a3cb322ff

Support status Community support

Discover Weblate Your Weblate is not listed on weblate.org [Browse discovery](#)

[Enable discovery](#)

[Manage support package](#) [Purchase support package](#) [Donate to Weblate](#)

Activate support package

The support packages include priority e-mail support, or cloud backups of your Weblate installation.

Activation token

Please enter the activation token obtained when making the subscription.

[Activate](#) [Purchase support package](#)

Powered by Weblate 4.8 [About Weblate](#) [Legal](#) [Contact](#) [Documentation](#) [Donate to Weblate](#)

Listing your server without a support subscription in Discover Weblate:

1. Register yourself at <https://weblate.org/user/>
2. Register your Weblate server in the discovery database at <https://weblate.org/subscription/discovery/>
3. Confirm the service activation in your Weblate and turn on the discovery listing in your Weblate management page using *Enable discovery* button:

The screenshot displays the Weblate dashboard interface. At the top, there's a navigation bar with 'Weblate' logo and links to 'Dashboard', 'Projects', 'Languages', and 'Checks'. Below this is a 'Manage' section with tabs for 'Weblate status', 'Backups', 'Translation memory', 'Performance report', 'SSH keys', 'Alerts', 'Repositories', 'Users', and 'Appearance'. The 'Weblate status' tab is active, showing the following information:

- Weblate version:** 4.8 — c05266dad2657545a900f6c74c66e26a3cb322ff
- Support status:** Community support
- Discover Weblate:** Your Weblate is not listed on weblate.org. A button 'Enable discovery' is present, along with a link 'Browse discovery'.

At the bottom of the status section are three buttons: 'Manage support package', 'Purchase support package', and 'Donate to Weblate'. Below this is the 'Activate support package' section, which includes a text box for an 'Activation token' and a note: 'Please enter the activation token obtained when making the subscription.' At the bottom of this section are buttons for 'Activate' and 'Purchase support package'.

At the very bottom of the dashboard, there's a footer with links: 'Powered by Weblate 4.8', 'About Weblate', 'Legal', 'Contact', 'Documentation', and 'Donate to Weblate'.

Customizing listing

You can customize the listing by providing a text and image (570 x 260 pixels) at <https://weblate.org/user/>.

2.25 Dokumente ligjore

Shënim: Herein you will find various legal information you might need to operate Weblate in certain legal jurisdictions. It is provided as a means of guidance, without any warranty of accuracy or correctness. It is ultimately your responsibility to ensure that your use of Weblate complies with all applicable laws and regulations.

2.25.1 ITAR dhe kontrolle të tjera eksporti

Weblate can be run within your own datacenter or virtual private cloud. As such, it can be used to store ITAR or other export-controlled information, however, end users are responsible for ensuring such compliance.

The Hosted Weblate service has not been audited for compliance with ITAR or other export controls, and does not currently offer the ability to restrict translations access by country.

2.25.2 Kontrolle fshehtëzimi të ShBA-ee

Weblate does not contain any cryptographic code, but might be subject export controls as it uses third party components utilizing cryptography for authentication, data-integrity and -confidentiality.

Most likely Weblate would be classified as ECCN 5D002 or 5D992 and, as publicly available libre software, it should not be subject to EAR (see [Encryption items NOT Subject to the EAR](#)).

Software components used by Weblate (listing only components related to cryptographic function):

Python See https://wiki.python.org/moin/PythonSoftwareFoundationLicenseFaq#Is_Python_subject_to_export_laws.3F

GnuPG Optionally used by Weblate

Git Optionally used by Weblate

curl Përdorur nga Git

OpenSSL Përdorur nga Python dhe cURL

The strength of encryption keys depends on the configuration of Weblate and the third party components it interacts with, but in any decent setup it will include all export restricted cryptographic functions:

- In excess of 56 bits for a symmetric algorithm
- Factorisation of integers in excess of 512 bits for an asymmetric algorithm
- Computation of discrete logarithms in a multiplicative group of a finite field of size greater than 512 bits for an asymmetric algorithm
- Discrete logarithms in a group different than above in excess of 112 bits for an asymmetric algorithm

Weblate doesn't have any cryptographic activation feature, but it can be configured in a way where no cryptography code would be involved. The cryptographic features include:

- Accessing remote servers using secure protocols (HTTPS)
- Generating signatures for code commits (PGP)

Shihni edhe:

[Export Controls \(EAR\) on Open Source Software](#)

3.1 Dhënie ndihmese te Weblate

There are dozens of ways to improve Weblate. You can choose the one you feel comfortable with, be it coding, graphics design, documentation, sponsorship, or an idea:

- *Njoftim problemesh në Weblate*
- *Starting contributing code to Weblate*
- *Përkthim i Weblate-it*
- *Contribute to Weblate documentation*
- *Weblate discussions*
- *Financim i zhvillimit të Weblate-it*

3.1.1 Përkthim i Weblate-it

Weblate is continually being [translated](#) using Weblate itself. Feel free to take your part in the effort of making Weblate available in as many human languages as possible. It brings Weblate closer to its users!

If you find a possible mistake in the source string, you can mark it with a comment in the Weblate editor. This way, it can be discussed and corrected. If you're certain, you can also click on the link in the *Source string location* section and submit a PR with your correction.

3.1.2 Contribute to Weblate documentation

You are welcome to improve the documentation page of your choice. Do it easily by clicking the *Edit on GitHub* button in the top-right corner of the page.

Please respect these guidelines while writing:

1. Don't remove part of the documentation if it's valid.
2. Use clear and easily-understandable language. You are writing tech docs, not a poem. Not all docs readers are native speakers, be thoughtful.

3. Don't be afraid to ask if you are not certain. If you have to ask about some feature while editing, don't change its docs before you have the answer. This means: You change or ask. Don't do both at the same time.
4. Verify your changes by performing described actions while following the docs.
5. Send PR with changes in small chunks to make it easier and quicker to review and merge.
6. If you want to rewrite and change the structure of a big article, do it in two steps:
 1. Rewrite
 2. Once the rewrite is reviewed, polished, and merged, change the structure of the paragraphs in another PR.

Ndihmëz: You can [translate the docs](#).

3.1.3 Extending built-in language definitions

The language definitions are in the [weblate-language-data repository](#).

You are welcome to add missing language definitions to `languages.csv`, other files are generated from that file.

3.1.4 Weblate discussions

If you have an idea and not sure if it's suitable for an issue, don't worry. You can join the community in [GitHub discussions](#).

3.1.5 Financim i zhvillimit të Weblate-it

You can boost Weblate's development on the [donate page](#). Funds collected there are used to enable gratis hosting for libre software projects and further development of Weblate. Please check the [donate page](#) for options, such as funding goals and the rewards you get as a proud funder.

Backers who have funded Weblate

Listë e Përkrahësve të Weblate-it:

- Yashiro Ccs
- Cheng-Chia Tseng
- Timon Reinhard
- [Cassidy James](#)
- Loic Dachary
- Marozed
- <https://freedombox.org/>
- GNU Solidario (GNU Health)
- BallotReady
- Richard Nespithal
- MyExpenses.Mobi

Do you want to be in the list? Please see options on the [Donate to Weblate](#).

3.2 Starting contributing code to Weblate

Understand the Weblate source code by going through *Kod burim i Weblate-it*, *Pjesa e dukshme e Weblate-it* and *Gjërat e brendshme të Weblate-it*.

3.2.1 Starting with the codebase

Familiarize yourself with the Weblate codebase, by having a go at the bugs labelled *good first issue*.

3.2.2 Xhirim lokalisht i Weblate-it

The most comfortable approach to get started with Weblate development is to follow *Installing from sources*. It will get you a virtualenv with editable Weblate sources.

1. Clone the Weblate source code:

```
git clone https://github.com/WeblateOrg/weblate.git
cd weblate
```

2. Create a virtualenv:

```
virtualenv .venv
.venv/bin/activate
```

3. Install Weblate (for this you need some system dependencies, see *Installing from sources*):

```
pip install -e .
```

3. Install all dependencies useful for development:

```
pip install -r requirements-dev.txt
```

4. Start a development server:

```
weblate runserver
```

5. Depending on your configuration, you might also want to start Celery workers:

```
./weblate/examples/celery start
```

6. To run a test (see *Testim vendor* for more details):

```
. scripts/test-database
./manage.py test
```

Shihni edhe:

Installing from sources

3.2.3 Running Weblate locally in Docker

If you have Docker and docker-compose installed, you can spin up the development environment by simply running:

```
./rundev.sh
```

It will create a development Docker image and start it. Weblate is running on <http://127.0.0.1:8080/> and you can sign in as the user `admin` using `admin` as the password. The new installation is empty, so you might want to continue with *Adding translation projects and components*.

The `Dockerfile` and `docker-compose.yml` for this are located in the `dev-docker` directory.

The script also accepts some parameters, to execute tests, run it with the `test` parameter and then specify any `test` parameters, for example running only tests in the `weblate.machine` module:

```
./rundev.sh test --failfast weblate.machine
```

Shënim: Be careful that your Docker containers are up and running before running the tests. You can check that by running the `docker ps` command.

To display the logs:

```
./rundev.sh logs
```

To stop the background containers, run:

```
./rundev.sh stop
```


Running the script without arguments will re-create the Docker container and restart it.

Shënim: This is not a suitable setup for production, as it includes several hacks which are insecure, but they make development easier.


3.2.4 Coding Weblate with PyCharm

PyCharm is a known IDE for Python, here are some guidelines to help you set up your Weblate project in it.

Considering you have just cloned the GitHub repository to a folder, just open it with PyCharm. Once the IDE is open, the first step is to specify the interpreter you want to use:




You can either choose to let PyCharm create the virtualenv for you, or select an already existing one:




Don't forget to install the dependencies once the interpreter is set: Either through the console (the console from the IDE will directly use your virtualenv by default), or through the interface when you get a warning about missing dependencies.


The second step is to set the right info to use Django natively inside PyCharm: The idea is to be able to immediately trigger the unit tests in the IDE. For that you need to specify the root path of the Django project and the path to its settings:



Be careful, the *Django project root* is the actual root of the repository, not the Weblate sub-directory. About the settings, you could use the `weblate/settings_test.py` from the repository, but you could create your own setting and set it there.

The last step is to run the server and to put breakpoints in the code to be able to debug it. This is done by creating a new *Django Server* configuration:





Ndihmëz: Be careful with the property called *No reload*: It prevents the server from being reloaded live if you modify files. This allows the existing debugger breakpoints to persist, when they normally would be discarded upon reloading the server.

3.2.5 Bootstrapping your devel instance

You might want to use `import_demo` to create demo translations and `createadmin` to make an admin user.

3.3 Kod burim i Weblate-it

Weblate is developed on [GitHub](#). You are welcome to fork the code and open pull requests. Patches in any other form are welcome too.

Shihni edhe:

Check out [Gjërat e brendshme të Weblate-it](#) to see how Weblate looks from inside.

3.3.1 Security by Design Principles

Any code for Weblate should be written with [Security by Design Principles](#) in mind.

3.3.2 Standarde kodimi

The code should follow PEP-8 coding guidelines and should be formatted using **black** code formatter.

To check the code quality, you can use **flake8**, the recommended plugins are listed in `.pre-commit-config.yaml` and its configuration is placed in `setup.cfg`.

The easiest approach to enforce all this is to install [pre-commit](#). Weblate repository contains configuration for it to verify the committed files are sane. After installing it (it is already included in the `requirements-lint.txt`) turn it on by running `pre-commit install` in Weblate checkout. This way all your changes will be automatically checked.

You can also trigger check manually, to check all files run:

```
pre-commit run --all
```

3.4 Diagnostikim Weblate-i

Bugs can behave as application crashes or as misbehavior. You are welcome to collect info on any such issue and submit it to the [issue tracker](#).

3.4.1 Mënyra diagnostikim

Turning on debug mode will make the exceptions show in the browser. This is useful to debug issues in the web interface, but not suitable for production environment as it has performance consequences and might leak private data.

Shihni edhe:

[Disable debug mode](#)

3.4.2 Regjistra Weblate-i

Weblate can produce detailed logs of what is going in the background. In the default configuration it uses syslog and that makes the log appear either in `/var/log/messages` or `/var/log/syslog` (depending on your syslog daemon configuration).

The Celery process (see [Background tasks using Celery](#)) usually produces own logs as well. The example system-wide setups log to several files under `/var/log/celery/`.

Docker containers log to their output (as usual in the Docker world), so you can look at the logs using `docker-compose logs`.

Shihni edhe:

[Sample configuration](#) contains `LOGGING` configuration.

3.4.3 Not processing background tasks

Lot of things happen in background Celery workers. In case things like sending out e-mails or component removal does not work, there might be some issue with it.

Things to check in that case:

- Check Celery process is running, see *Background tasks using Celery*
- Check Celery queue status either in *Ndërfaqe administrimi* or using `celery_queues`
- Look into Celery logs for errors (see *Regjistra Weblate-i*)

3.4.4 Not receiving e-mails from Weblate

You can verify whether outgoing e-mail is working correctly by using the `sendtestemail` management command (see *Invoking management commands* for instructions on how to invoke it in different environments) or using *Ndërfaqe administrimi* under the *Tools* tab.

These send e-mail directly, so this verifies that your SMTP configuration is correct (see *Formësim i email-eve që dërgohen*). Most of the e-mails from Weblate are however sent in the background and there might be some issues with Celery involved as well, please see *Not processing background tasks* for debugging that.

3.4.5 Analyzing application crashes

In case the application crashes, it is useful to collect as much info about the crash as possible. The easiest way to achieve this is by using third-party services which can collect such info automatically. You can find info on how to set this up in *Collecting error reports*.

3.4.6 Silent failures

Lots of tasks are offloaded to Celery for background processing. Failures are not shown in the user interface, but appear in the Celery logs. Configuring *Collecting error reports* helps you to notice such failures easier.

3.4.7 Probleme funksionimi

In case Weblate performs badly in some situation, please collect the relevant logs showing the issue, and anything that might help figuring out where the code might be improved.

In case some requests take too long without any indication, you might want to install `dogslow` along with *Collecting error reports* and get pinpointed and detailed tracebacks in the error collection tool.

3.5 Gjërat e brendshme të Weblate-it

Shënim: This chapter will give you basic overview of Weblate internals.

Weblate derives most of its code structure from, and is based on `Django`.

3.5.1 Strukturë drejtorish

Quick overview of directory structure of Weblate main repository:

dokumentime Source code for this documentation, which can be built using [Sphinx](#).

dev-docker Docker code to run development server, see [Running Weblate locally in Docker](#).

weblate Source code of Weblate as a [Django](#) application, see [Gjërat e brendshme të Weblate-it](#).

weblate/static Client files (CSS, Javascript and images), see [Pjesa e dukshme e Weblate-it](#).

3.5.2 Module

Weblate consists of several Django applications (some optional, see [Optional Weblate modules](#)):

`llogari`

Llogari, profile dhe njoftime përdoruesi.

`shtesa`

Add-ons to tweak Weblate behavior, see [Shtesa](#).

`api`

API based on [Django REST framework](#).

`auth`

Mirëfilltësim dhe Leje.

`faturim`

The optional [Faturim](#) module.

`kontrolle`

Translation string [Kontrolle cilësie](#) module.

`shkronja`

Font rendering checks module.

`formate`

File format abstraction layer based on [translate-toolkit](#).

`gitexport`

The optional [Git exporter](#) module.

`gjuhë`

Module defining language and plural models.

`ligjore`

The optional [Ligjore](#) module.

`makineri`

Integrim shërbimesh përkthimi nga makina.

`kujtesë`

Built-in translation memory, see [Kujtesë Përkthimesh](#).

`foto ekrani`

Screenshots management and OCR module.

`trans`

Main module handling translations.

`utils`

Various helper utilities.

`vcs`

Version control system abstraction.

`wladmin`

Përshtatje ndërfaqeje përgjegjësi Django.

3.6 Developing addons

Shitesa are way to customize localization workflow in Weblate.

```
class weblate.addons.base.BaseAddon (storage=None)
```

```
classmethod can_install (component, user)
```

Check whether add-on is compatible with given component.

```
configure (settings)
```

Save configuration.

```
daily (component)
```

Hook triggered daily.

```
classmethod get_add_form (user, component, **kwargs)
```

Return configuration form for adding new add-on.

```
get_settings_form (user, **kwargs)
```

Return configuration form for this add-on.

```
post_add (translation)
```

Hook triggered after new translation is added.

```
post_commit (component)
```

Hook triggered after changes are committed to the repository.

```
post_push (component)
```

Hook triggered after repository is pushed upstream.

```
post_update (component, previous_head: str, skip_push: bool)
```

Hook triggered after repository is updated from upstream.

Parametra

- **previous_head** (*str*) – HEAD of the repository prior to update, can be blank on initial clone.
- **skip_push** (*bool*) – Whether the add-on operation should skip pushing changes upstream. Usually you can pass this to underlying methods as `commit_and_push` or `commit_pending`.

```
pre_commit (translation, author)
```

Hook triggered before changes are committed to the repository.

```
pre_push (component)
```

Hook triggered before repository is pushed upstream.

```
pre_update (component)
```

Hook triggered before repository is updated from upstream.

```
save_state ()
```

Save add-on state information.

stay_on_create = False

Base class for Weblate add-ons.

store_post_load (*translation, store*)

Hook triggered after a file is parsed.

It receives an instance of a file format class as a argument.

This is useful to modify file format class parameters, for example adjust how the file will be saved.

unit_pre_create (*unit*)

Hook triggered before new unit is created.

Ja një shembull shtese:

```
#
# Copyright © 2012 - 2021 Michal Čihař <michal@cihar.com>
#
# This file is part of Weblate <https://weblate.org/>
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <https://www.gnu.org/licenses/>.
#

from django.utils.translation import gettext_lazy as _

from weblate.addons.base import BaseAddon
from weblate.addons.events import EVENT_PRE_COMMIT

class ExampleAddon(BaseAddon):
    # Filter for compatible components, every key is
    # matched against property of component
    compat = {"file_format": {"po", "po-mono"}}
    # List of events add-on should receive
    events = (EVENT_PRE_COMMIT,)
    # Add-on unique identifier
    name = "weblate.example.example"
    # Verbose name shown in the user interface
    verbose = _("Example add-on")
    # Detailed add-on description
    description = _("This add-on does nothing it is just an example.")

    # Callback to implement custom behavior
    def pre_commit(self, translation, author):
        return
```

3.7 Pjesa e dukshme e Weblate-it

The frontend is currently built using Bootstrap, jQuery and few third party libraries.

3.7.1 Supported browsers

Weblate supports the latest, stable releases of all major browsers and platforms.

Alternative browsers which use the latest version of WebKit, Blink, or Gecko, whether directly or via the platform's web view API, are not explicitly supported. However, Weblate should (in most cases) display and function correctly in these browsers as well.

Older browsers might work, but some features might be limited.

3.7.2 Administrim varësish

The yarn package manager is used to update third party libraries. The configuration lives in `scripts/yarn` and there is a wrapper script `scripts/yarn-update` to upgrade the libraries, build them and copy to correct locations in `weblate/static/vendor`, where all third partly frontend code is located.

Adding new third-party library typically consists of:

```
# Add a yarn package
yarn --cwd scripts/yarn add PACKAGE
# Edit the script to copy package to the static folder
edit scripts/yarn-update
# Run the update script
./scripts/yarn-update
# Add files to git
git add .
```

3.7.3 Stil kodimi

Weblate relies on [Prettier](#) for the code formatting for both JavaScript and CSS files.

We also use [ESLint](#) to check the JavaScript code.

3.7.4 Përkthim

Should you need any user visible text in the frontend code, it should be localizable. In most cases all you need is to wrap your text inside `gettext` function, but there are more complex features available:

```
document.write(gettext('this is to be translated'));

var object_count = 1 // or 0, or 2, or 3, ...
s = gettext('literal for the singular case',
            'literal for the plural case', object_count);

fmts = gettext('There is %s object. Remaining: %s',
               'There are %s objects. Remaining: %s', 11);
s = interpolate(fmts, [11, 20]);
// s is 'There are 11 objects. Remaining: 20'
```

Shihni edhe:

[Translation topic in the Django documentation](#)

3.7.5 Ikona

Weblate currently uses material design icons. In case you are looking for new symbol, check [Material Design Icons](#) or [Material Design Resources](#).

Additionally, there is `scripts/optimize-svg` to reduce size of the SVG as most of the icons are embedded inside the HTML to allow styling of the paths.

3.8 Njoftim problemesh në Weblate

Weblate [issue tracker](#) is hosted at GitHub.

Feel welcome to report any issues you have, or suggest improvement for Weblate there. There are various templates prepared to comfortably guide you through the issue report.

If what you have found is a security issue in Weblate, please consult the [Probleme sigurie](#) section below.

If you are not sure about your bug report or feature request, you can try [Weblate discussions](#).

3.8.1 Probleme sigurie

In order to give the community time to respond and upgrade, you are strongly urged to report all security issues privately. HackerOne is used to handle security issues, and can be reported directly at [HackerOne](#). Once you submit it there, community has limited but enough time to solve the incident.

Alternatively, report to security@weblate.org, which ends up on HackerOne as well.

If you don't want to use HackerOne, for whatever reason, you can send the report by e-mail to michal@cihar.com. You can choose to encrypt it using this PGP key `3CB 1DF1 EF12 CF2A C0EE 5A32 9C27 B313 42B7 511D`. You can also get the PGP key from [Keybase](#).

Shënim: Weblate depends on third-party components for many things. In case you find a vulnerability affecting one of those components in general, please report it directly to the respective project.

Disa nga këto janë:

- [Django](#)
 - [Django REST framework](#)
 - [Python Social Auth](#)
-

3.9 Weblate testsuite and continuous integration

Testsuites exist for most of the current code, increase coverage by adding testcases for any new functionality, and verify that it works.

3.9.1 Continuous integration

Current test results can be found on [GitHub Actions](#) and coverage is reported on [Codecov](#).

There are several jobs to verify different aspects:

- Unit tests
- Documentation build and external links
- Migration testing from all supported releases
- Code linting
- Setup verification (ensures that generated dist files do not miss anything and can be tested)

The configuration for the CI is in `.github/workflows` directory. It heavily uses helper scripts stored in `ci` directory. The scripts can be also executed manually, but they require several environment variables, mostly defining Django settings file to use and database connection. The example definition of that is in `scripts/test-database`:

```
# Simple way to configure test database from environment

# Database backend to use postgresql / mysql / mariadb
export CI_DATABASE=${1:-postgresql}

# Database server configuration
export CI_DB_USER=weblate
export CI_DB_PASSWORD=weblate
export CI_DB_HOST=127.0.0.1

# Django settings module to use
export DJANGO_SETTINGS_MODULE=weblate.settings_test
```

The simple execution can look like:

```
. scripts/test-database
./ci/run-migrate
./ci/run-test
./ci/run-docs
```

3.9.2 Testim vendor

To run a testsuite locally, use:

```
DJANGO_SETTINGS_MODULE=weblate.settings_test ./manage.py test
```

Ndihmëz: You will need a database (PostgreSQL) server to be used for tests. By default Django creates separate database to run tests with `test_` prefix, so in case your settings is configured to use `weblate`, the tests will use `test_weblate` database. See [Ujdisje baze të dhënash për Weblate](#) for setup instructions.

The `weblate/settings_test.py` is used in CI environment as well (see [Continuous integration](#)) and can be tuned using environment variables:

```
# Simple way to configure test database from environment

# Database backend to use postgresql / mysql / mariadb
export CI_DATABASE=${1:-postgresql}

# Database server configuration
export CI_DB_USER=weblate
```

(vazhdon në faqen pasuese)

(vazhduar nga faqja e mëparshme)

```
export CI_DB_PASSWORD=weblate
export CI_DB_HOST=127.0.0.1

# Django settings module to use
export DJANGO_SETTINGS_MODULE=weblate.settings_test
```

Prior to running tests you should collect static files as some tests rely on them being present:

```
DJANGO_SETTINGS_MODULE=weblate.settings_test ./manage.py collectstatic
```

You can also specify individual tests to run:

```
DJANGO_SETTINGS_MODULE=weblate.settings_test ./manage.py test weblate.gitexport
```

Ndihmëz: The tests can also be executed inside developer docker container, see [Running Weblate locally in Docker](#).

Shihni edhe:

See [Testing in Django](#) for more info on running and writing tests for Django.

3.10 Skema të dhënash

Weblate uses [JSON Schema](#) to define layout of external JSON files.

3.10.1 Weblate Translation Memory Schema

https://weblate.org/schemas/weblate-memory.schema.json	
lloj	array
objekte	<i>The Translation Memory Item</i>
lloj	objekt
veti	
• kategori	<i>The String Category</i>
	1 is global, 2 is shared, 10000000+ are project specific, 20000000+ are user specific
lloj	integer
shembuj	1
minimum	0
parazgjedhje	1
• origjinë	<i>The String Origin</i>
	Emër kartele ose emër përbërësi
lloj	varg
shembuj	test.tmx
	project/component
parazgjedhje	
• burim	<i>The Source String</i>
lloj	varg
shembuj	Tungjatjeta
minLength	1
parazgjedhje	
• source_language	<i>The Source Language</i>
	ISO 639-1 / ISO 639-2 / IETF BCP 47
lloj	varg
shembuj	en

vazhdon në faqen pasuese

Tabela 1 – vazhduar nga faqja e mëparshme

		rregullsi	^[^]+\$
		parazgjedhje	
	• target	The Target String	
		lloj	varg
		shembuj	Ahoj
		minLength	1
		parazgjedhje	
	• target_language	The Target Language	
		ISO 639-1 / ISO 639-2 / IETF BCP 47	
		lloj	varg
		shembuj	cs
		rregullsi	^[^]+\$
		parazgjedhje	
	additionalProperties		False
përkufizime			

Shihni edhe:

Kujtesë Përkthimesh, dump_memory, import_memory

3.10.2 Eksportim të dhënash përdoruesi në Weblate

https://weblate.org/schemas/weblate-userdata.schema.json			
lloj	<i>objekt</i>		
veti			
• basic	<i>Basic</i>		
	lloj	<i>objekt</i>	
	veti		
	• emër përdoruesi	<i>Emër përdoruesi</i>	
		lloj	<i>varg</i>
		shembuj	përgjegjës
		parazgjedhje	
	• full_name	<i>Emër i plotë</i>	
		lloj	<i>varg</i>
		shembuj	Përgjegjës Weblate
		parazgjedhje	
	• email	<i>Email</i>	
		lloj	<i>varg</i>
		shembuj	noreply@example.com
		parazgjedhje	
	• date_joined	<i>Date joined</i>	
		lloj	<i>varg</i>
		shembuj	2019-11-18T18:53:54.862Z
		parazgjedhje	
• profil	<i>Profil</i>		
	lloj	<i>objekt</i>	
	veti		
	• gjuhë	<i>Gjuhë</i>	
		lloj	<i>varg</i>
		shembuj	cs
		rregullsi	^.*\$
		parazgjedhje	
	• suggested	<i>Numër vargësh të sugjeruar</i>	
		lloj	<i>integer</i>
		shembuj	1

vazhdon në faqen pasuese

Tabela 2 – vazhduar nga faqja e mëparshme

	• translated	parazgjedhje		0		
		Numër vargjesh të përkthyer				
		lloj		integer		
		shembuj		24		
	• uploaded	parazgjedhje		0		
		Numër fotosh ekrani të ngarkuara				
		lloj		integer		
		shembuj		1		
	• hide_completed	parazgjedhje		0		
		Hide completed translations on the dashboard				
		lloj		boolean		
		shembuj		False		
	• secondary_in_zen	parazgjedhje		True		
		Show secondary translations in the Zen mode				
		lloj		boolean		
		shembuj		True		
	• hide_source_secondary	parazgjedhje		True		
		Fshihe burimin nëse ekziston një përkthim dytësor				
		lloj		boolean		
		shembuj		False		
	• editor_link	parazgjedhje		True		
		Lidhje përpunuesi				
		lloj		varg		
		shembuj				
		rregullsi		^.*\$		
	• translate_model	parazgjedhje				
		Mënyrë përpunuesi përkthimesh				
		lloj		integer		
		shembuj		0		
	• zen_mode	parazgjedhje		0		
		Mënyra përpunues Zen				
		lloj		integer		
		shembuj		0		
	• special_chars	parazgjedhje		0		
		Shenja speciale				
		lloj		varg		
		shembuj				
	• dashboard_view	rregullsi		^.*\$		
		parazgjedhje				
		Pamje parazgjedhje e pultit				
lloj		integer				
• dashboard_components	shembuj		1			
	parazgjedhje		0			
	Listë përbërësish parazgjedhje					
	component		null			
• gjuhë	anyOf		lloj		null	
			lloj		integer	
	Gjuhë të përkthyer					
	lloj		array			
	parazgjedhje					
	objekte		Kod gjuhe			
			lloj		varg	
			shembuj		cs	
• secondary_languages			rregullsi		^.*\$	
	parazgjedhje					
	Gjuhë dytësore					
	vazhdon në faqen pasues					

vazhdon në faqen pasuese

Tabela 2 – vazhduar nga faqja e mëparshme

		lloj	array		
		parazgjedhje			
		objekte	Kod gjuhe		
			lloj	varg	
			shembuj	sk	
			rregullsi	^.*\$	
			parazgjedhje		
		• watched	Projekte të mbikëqyrur		
			lloj	array	
			parazgjedhje		
	objekte		Identifikues projekti		
			lloj	varg	
			shembuj	weblate	
			rregullsi	^.*\$	
		parazgjedhje			
• auditlog	Audit log				
	lloj	array			
	parazgjedhje				
	objekte	Items			
		lloj	objekt		
		veti			
		• adresë	IP address		
			lloj	varg	
			shembuj	127.0.0.1	
			rregullsi	^.*\$	
			parazgjedhje		
		• user_agent	Agjent përdoruesi		
			lloj	varg	
			shembuj	PC / Linux / Firefox 70.0	
			rregullsi	^.*\$	
			parazgjedhje		
		• vulë kohore	Vulë kohore		
			lloj	varg	
			shembuj	2019-11-18T18:58:30.845Z	
			rregullsi	^.*\$	
			parazgjedhje		
• veprimtari		Veprimtari			
		lloj	varg		
	shembuj	login			
	rregullsi	^.*\$			
	parazgjedhje				
përkufizime					

Shihni edhe:*Profil përdoruesi, dumpuserdata*

3.11 Releasing Weblate

3.11.1 Releasing schedule

Weblate has two month release cycle for releases (x.y). These are usually followed by a bunch of bugfix releases to fix issues which slip into them (x.y.z).

The change in the major version indicates that the upgrade process can not skip this version - you always have to upgrade to x.0 before upgrading to higher x.y releases.

Shihni edhe:

Upgrading Weblate

3.11.2 Release planning

The features for upcoming releases are collected using GitHub milestones, you can see our roadmap at <https://github.com/WeblateOrg/weblate/milestones>.

3.11.3 Release process

Things to check prior to release:

1. Check newly translated languages by `./scripts/list-translated-languages`.
2. Set final version by `./scripts/prepare-release`.
3. Make sure screenshots are up to date `make -C docs update-screenshots`.
4. Merge any possibly pending translations `wlc push; git remote update; git merge origin/weblate`

Perform the release:

5. Create a release `./scripts/create-release --tag` (see below for requirements).

Post release manual steps:

6. Update Docker image.
7. Close GitHub milestone.
8. Once the Docker image is tested, add a tag and push it.
9. Update Helm chart to new version.
10. Include new version in `.github/workflows/migrations.yml` to cover it in migration testing.
11. Increase version in the website download links.
12. Increase version in the repository by `./scripts/set-version`.

To create tags using the `./scripts/create-release` script you will need following:

- GnuPG with private key used to sign the release
- Push access to Weblate git repositories (it pushes tags)
- Configured **hub** tool and access to create releases on the Weblate repo
- SSH access to Weblate download server (the Website downloads are copied there)

3.12 Security and privacy

Ndihmëz: Te Weblate, siguria mban një mjedis që vlerëson privatësinë e përdoruesve tanë.

Development of Weblate adheres to the [Best Practices of the Linux Foundation's Core Infrastructure Initiative](#).

Shihni edhe:

Probleme sigurie

3.12.1 Tracking dependencies for vulnerabilities

Security issues in our dependencies are monitored using [Dependabot](#). This covers the Python and JavaScript libraries, and the latest stable release has its dependencies updated to avoid vulnerabilities.

Ndihmëz: There might be vulnerabilities in third-party libraries which do not affect Weblate, so those are not addressed by releasing bugfix versions of Weblate.

3.12.2 Docker container security

The Docker containers are scanned using [Anchore](#) and [Trivy](#).

This allows us to detect vulnerabilities early and release improvements quickly.

You can get the results of these scans at GitHub — they are stored as artifacts on our CI in the SARIF format (Static Analysis Results Interchange Format).

Shihni edhe:

Continuous integration

3.13 Rreth Weblate-it

3.13.1 Objektiva projekti

Web-based continuous localization tool with tight *Integrim kontrolli versioni* supporting a wide range of *Formate të mbuluar kartelash*, making it easy for translators to contribute.

3.13.2 Emër projekti

«Weblate» is a portmanteau of the words «web» and «translate».

3.13.3 Sajt projekti

The landing page is <https://weblate.org> and there is a cloud-hosted service at <https://hosted.weblate.org>. The documentation can be read at <https://docs.weblate.org>.

3.13.4 Stema projekti

The project logos and other graphics are available in <https://github.com/WeblateOrg/graphics>.

3.13.5 Drejtues

This project is maintained by Michal Čihař, who can be reached at michal@cihar.com.

3.13.6 Autorë

Weblate was started by Michal Čihař. Since its inception in 2012, thousands of people have contributed.

3.14 Licencë

Copyright (C) 2012 - 2021 Michal Čihař <michal@cihar.com>

Ky program është software i lirë; mund ta rishpërndani dhe/ose ndryshoni sipas kushteve të licencës GNU General Public License, siç botohet nga Free Software Foundation; ose versioni 3 i Licencës, ose (në dëshirën tuaj) çfarëdo versioni të mëvonshëm.

Ky program shpërndahet me shpresën se do të jetë i dobishëm, por PA ASNJË GARANCI; madje pa as edhe garancinë e nënkuptuar të TREGTUESHMËRISË ose PËRSHTATSHMËRISË PËR NJË QËLLIM TË VEÇANTË. Për më tepër hollësi, shihni licencën GNU General Public License.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.

4.1 Weblate 4.8

Released on August 21th 2021.

- Added support for Apple stringsdict format.
- The exact search operator is now case-sensitive on PostgreSQL.
- Fixed saving glossary explanations in some cases.
- Documentation improvements.
- Përmirësime funksionimi.
- Improved squash add-on compatibility with Gerrit.
- Fixed adding strings to a monolingual glossary components.
- Improved performance in handling variants.
- Fixed squash add-on sometimes skipping parsing upstream changes.
- Preserve file extension on download.
- Added support for the Fluent format.
- Add support for using tabs to indent JSON formats.

[All changes in detail.](#)

4.2 Weblate 4.7.2

Released on July 15th 2021.

- Support more language aliases to be configured on a project.
- Fixed search string validation in API.
- Fixed Git exporter URLs after a domain change.
- Fixed cleanup addon for Windows RC files.
- Fixed possible crash on Xliff updating.

[All changes in detail.](#)

4.3 Weblate 4.7.1

Released on June 30th 2021.

- Improved popup for adding terms to glossary.
- Added support for LibreTranslate machine translation service.
- Added rate limiting on creating new projects.
- Improved performance of file updates.

[All changes in detail.](#)

4.4 Weblate 4.7

Released on June 17th 2021.

- Improved configuration health check.
- Added support for `object-pascal-format` used in gettext PO, see *Object Pascal format*.
- Renamed *Nearby keys* to *Similar keys* to better describe the purpose.
- Added support for *mi18n lang files*.
- Improved SAML authentication integration.
- Fixed *Gerrit* integration to better handle corner cases.
- Weblate now requires Django 3.2.
- Fixed inviting users when e-mail authentication is disabled.
- Improved language definitions.
- Added support for blocking users from contributing to a project.
- Fixed automatic creation of glossary languages.
- Extended documentation about add-ons.
- Performance improvements for components with linked repositories.
- Added support for free DeepL API.
- The user management no longer needs Django admin interface.

[All changes in detail.](#)

4.5 Weblate 4.6.2

Released on May 8th 2021.

- Fixed crash after moving shared component between projects.
- Fixed adding new strings to empty properties files.
- Fixed copy icon alignment in RTL languages.
- Extended string statistics on the Info tab.
- Fixed handling of translation files ignored in Git.

- Improved metrics performance.
- Fixed possible bug in saving glossaries.
- Fixed consistency check behavior on languages with different plural rules.

[All changes in detail.](#)

4.6 Weblate 4.6.1

Released on May 2nd 2021.

- Remove obsolete spam protection code.
- Improve source plural check accuracy.
- Update list of user interface languages in Docker.
- Improved error messages when creating pull requests.
- Fixed creating pull requests on Pagure.
- Fixed triggering automatically installed add-ons.
- Fixed possible caching issues on upgrade.
- Fixed adding new units to monolingual translations using upload.

[All changes in detail.](#)

4.7 Weblate 4.6

Released on April 19th 2021.

- The `auto_translate` management command has now a parameter for specifying translation mode.
- Added support for *Kartela tekst*.
- Added trends and metrics for all objects.
- Added support for direct copying text from secondary languages.
- Added date filtering when browsing changes.
- Improved activity charts.
- Sender for contact form e-mails can now be configured.
- Improved parameters validation in component creation API.
- The rate limiting no longer applies to superusers.
- Improved automatic translation add-on performance and reliability.
- The rate limiting now can be customized in the Docker container.
- API for creating components now automatically uses *URL të brendshme Weblate*.
- Simplified state indication while listing strings.
- Password hashing now uses Argon2 by default.
- Simplified progress bars indicating translation status.
- Renamed *Add missing languages* to clarify the purpose.
- Fixed saving string state to XLIFF.
- Added language-wide search.

- Initial support for *Scaling horizontally* the Docker deployment.

[All changes in detail.](#)

4.8 Weblate 4.5.3

Released on April 1st 2021.

- Fixed metrics collection.
- Fixed possible crash when adding strings.
- Improved search query examples.
- Fixed possible loss of newly added strings on replace upload.

4.9 Weblate 4.5.2

Released on March 26th 2021.

- Configurable schedule for automatic translation.
- Added Lua format check.
- Ignore format strings in the *Fjalë të njëpasnjëshme të përsëdytura* check.
- Allow uploading screenshot from a translate page.
- Added forced file synchronization to the repository maintenance.
- Fixed automatic suggestions for languages with a longer code.
- Improved performance when adding new strings.
- Several bug fixes in quality checks.
- Several performance improvements.
- Added integration with *Zbuloni Weblate-in*.
- Fixed checks behavior with read-only strings.

[All changes in detail.](#)

4.10 Weblate 4.5.1

Released on March 5th 2021.

- Fixed editing of glossary flags in some corner cases.
- Extend metrics usage to improve performance of several pages.
- Store correct source language in TMX files.
- Better handling for uploads of monolingual PO using API.
- Improved alerts behavior glossaries.
- Improved Markdown link checks.
- Indicate glossary and source language in breadcrumbs.
- Paginated component listing of huge projects.
- Improved performance of translation, component or project removal.

- Improved bulk edit performance.
- Fixed preserving «Needs editing» and «Approved» states for ODF files.
- Improved interface for customizing translation-file downloads

[All changes in detail.](#)

4.11 Weblate 4.5

Released on February 19th 2021.

- Added support for `lua-format` used in gettext PO.
- Added support for sharing a component between projects.
- Fixed multiple unnamed variables check behavior with multiple format flags.
- Dropped mailing list field on the project in favor of generic instructions for translators.
- Added pseudolocale generation add-on.
- Added support for TermBase eXchange files.
- Added support for manually defining string variants using a flag.
- Improved performance of consistency checks.
- Improved performance of translation memory for long strings.
- Added support for searching in explanations.
- Strings can now be added and removed in bilingual formats as well.
- Extend list of supported languages in Amazon Translate machine translation.
- Automatically enable Java MessageFormat checks for Java Properties.
- Added a new upload method to add new strings to a translation.
- Added a simple interface to browse translation.
- Glossaries are now stored as regular components.
- Dropped specific API for glossaries as component API is used now.
- Added simplified interface to toggle some of the flags.
- Added support for non-translatable or forbidden terms in the glossary.
- Added support for defining terminology in a glossary.
- Moved text direction toggle to get more space for the visual keyboard.
- Added option to automatically watch projects user-contributed to.
- Added check whether translation matches the glossary.
- Added support for customizing navigation text color.

[All changes in detail.](#)

4.12 Weblate 4.4.2

Released on January 14th 2021.

- Fixed corruption of one distributed MO file.

4.13 Weblate 4.4.1

Released on January 13th 2021.

- Fixed reverting plural changes.
- Fixed displaying help for project settings.
- Improved administration of users.
- Improved handling of context in monolingual PO files.
- Fixed cleanup add-on behavior with HTML, ODF, IDML and Windows RC formats.
- Fixed parsing of location from CSV files.
- Use content compression for file downloads.
- Improved user experience on importing from ZIP file.
- Improved detection of file format for uploads.
- Avoid duplicate pull requests on Pagine.
- Improved performance when displaying ghost translations.
- Reimplemented translation editor to use native browser textarea.
- Fixed cleanup add-on breaking adding new strings.
- Added API for add-ons.

[All changes in detail.](#)

4.14 Weblate 4.4

Released on December 15th 2020.

- Improved validation when creating a component.
- Weblate now requires Django 3.1.
- Added support for appearance customization in the management interface.
- Fixed read-only state handling in bulk edit.
- Improved CodeMirror integration.
- Added add-on to remove blank strings from translation files.
- The CodeMirror editor is now used for translations.
- Syntax highlighting in translation editor for XML, HTML, Markdown and reStructuredText.
- Highlight placeables in translation editor.
- Improved support for non-standard language codes.
- Added alert when using ambiguous language codes.
- The user is now presented with a filtered list of languages when adding a new translation.

- Extended search capabilities for changes in history.
- Improved billing detail pages and libre hosting workflow.
- Extended translation statistics API.
- Improved «other translations» tab while translating.
- Added tasks API.
- Improved performance of file upload.
- Improved display of user defined special characters.
- Improved performance of auto-translation.
- Several minor improvements in the user interface.
- Improved naming of ZIP downloads.
- Added option for getting notifications on unwatched projects.

[All changes in detail.](#)

4.15 Weblate 4.3.2

Released on November 4th 2020.

- Fixed crash on certain component filemasks.
- Improved accuracy of the consecutive duplicated words check.
- Added support for Pagure pull requests.
- Improved error messages for failed registrations.
- Reverted rendering developer comments as Markdown.
- Simplified setup of Git repositories with different default branch than «master».
- Newly created internal repositories now use main as the default branch.
- Reduced false positives rate of unchanged translation while translating reStructuredText.
- Fixed CodeMirror display issues in some situations.
- Renamed Template group to «Sources» to clarify its meaning.
- Fixed GitLab pull requests on repositories with longer paths.

[All changes in detail.](#)

4.16 Weblate 4.3.1

Hedhur në qarkullim m 21 tetor, 2020.

- Improved auto-translation performance.
- Fixed session expiry for authenticated users.
- Shtim mbulimi për fshehje të dhënash versioni.
- Improve hooks compatibility with Bitbucket Server.
- Improved performance of translation memory updates.
- Reduced memory usage.
- Improved performance of Matrix view.

- Added confirmation before removing a user from a project.

[All changes in detail.](#)

4.17 Weblate 4.3

Released on October 15th 2020.

- Include user stats in the API.
- Fixed component ordering on paginated pages.
- Define source language for a glossary.
- Rewritten support for GitHub and GitLab pull requests.
- Fixed stats counts after removing suggestion.
- Extended public user profile.
- Fixed configuration of enforced checks.
- Improve documentation about built-in backups.
- Moved source language attribute from project to a component.
- Add Vue I18n formatting check.
- Generic placeholders check now supports regular expressions.
- Improved look of Matrix mode.
- Machinery is now called automatic suggestions.
- Added support for interacting with multiple GitLab or GitHub instances.
- Extended API to cover project updates, unit updates and removals and glossaries.
- Unit API now properly handles plural strings.
- Component creation can now handle ZIP file or document upload.
- Consolidated API response status codes.
- Support Markdown in contributor agreement.
- Improved source strings tracking.
- Improved JSON, YAML and CSV formats compatibility.
- Added support for removing strings.
- Improved performance of file downloads.
- Improved repository management view.
- Automatically enable java-format for Android.
- Added support for localized screenshots.
- Added support for Python 3.9.
- Fixed translating HTML files under certain conditions.

[All changes in detail.](#)

4.18 Weblate 4.2.2

Released on September 2nd 2020.

- Fixed matching of source strings for JSON formats.
- Fixed login redirect for some authentication configurations.
- Fixed LDAP authentication with group sync.
- Fixed crash in reporting automatic translation progress.
- Fixed Git commit squashing with trailers enabled.
- Fixed creating local VCS components using API.

4.19 Weblate 4.2.1

Released on August 21st 2020.

- Fixed saving plurals for some locales in Android resources.
- Fixed crash in the cleanup add-on for some XLIFF files.
- Allow setting up localization CDN in Docker image.

4.20 Weblate 4.2

Released on August 18th 2020.

- Improved user pages and added listing of users.
- Dropped support for migrating from 3.x releases, migrate through 4.1 or 4.0.
- Added exports into several monolingual formats.
- Improved activity charts.
- Number of displayed nearby strings can be configured.
- Added support for locking components experiencing repository errors.
- Simplified main navigation (replaced buttons with icons).
- Improved language code handling in Google Translate integration.
- The Git squash add-on can generate `Co-authored-by:` trailers.
- Improved query search parser.
- Improved user feedback from format strings checks.
- Improved performance of bulk state changes.
- Added compatibility redirects after project or component renaming.
- Added notifications for strings approval, component locking and license change.
- Added support for ModernMT.
- Allow to avoid overwriting approved translations on file upload.
- Dropped support for some compatibility URL redirects.
- Added check for ECMAScript template literals.
- Added option to watch a component.

- Removed leading dot from JSON unit keys.
- Removed separate Celery queue for translation memory.
- Allow translating all components a language at once.
- Allow to configure Content-Security-Policy HTTP headers.
- Added support for aliasing languages at project level.
- New add-on to help with HTML or JavaScript localization, see *CDN përthimesh JavaScript*.
- The Weblate domain is now configured in the settings, see *SITE_DOMAIN*.
- Add support for searching by component and project.

4.21 Weblate 4.1.1

Released on June 19th 2020.

- Fixed changing autofix or add-ons configuration in Docker.
- Fixed possible crash in «About» page.
- Improved installation of byte-compiled locale files.
- Fixed adding words to glossary.
- Fixed keyboard shortcuts for machinery.
- Removed debugging output causing discarding log events in some setups.
- Fixed lock indication on project listing.
- Fixed listing GPG keys in some setups.
- Added option for which DeepL API version to use.
- Added support for acting as SAML Service Provider, see *Mirëfilltësim SAML*.

4.22 Weblate 4.1

Released on June 15th 2020.

- Added support for creating new translations with included country code.
- Added support for searching source strings with screenshot.
- Extended info available in the stats insights.
- Improved search editing on «Translate» pages.
- Improve handling of concurrent repository updates.
- Include source language in project creation form.
- Include changes count in credits.
- Fixed UI language selection in some cases.
- Allow to whitelist registration methods with registrations closed.
- Improved lookup of related terms in glossary.
- Improved translation memory matches.
- Group same machinery results.
- Add direct link to edit screenshot from translate page.

- Improved removal confirmation dialog.
- Include templates in ZIP download.
- Add support for Markdown and notification configuration in announcements.
- Extended details in check listings.
- Added support for new file formats: *Vargje PHP Lavarel*, *Kartela HTML*, *Format OpenDocument*, *Format IDML*, *Kartela Windows RC*, *Përkthime INI*, *Inno Setup INI translations*, *Veti GWT*, *go-i18n JSON files*, *Kartelë ARB*.
- Consistently use dismissed as state of dismissed checks.
- Add support for configuring default add-ons to enable.
- Fixed editor keyboard shortcut to dismiss checks.
- Improved machine translation of strings with placeholders.
- Show ghost translation for user languages to ease starting them.
- Improved language code parsing.
- Show translations in user language first in the list.
- Renamed shapings to more generic name variants.
- Added new quality checks: *Ndryshore të shumta të paemërtuara*, *I papërkthyer prej kohësh*, *Fjalë të njëpasnjëshme të përsëdytura*.
- Reintroduced support for wiping translation memory.
- Fixed option to ignore source checks.
- Added support for configuring different branch for pushing changes.
- API now reports rate limiting status in the HTTP headers.
- Added support for Google Translate V3 API (Advanced).
- Added ability to restrict access on component level.
- Added support for whitespace and other special chars in translation flags, see *Customizing behavior using flags*.
- Always show rendered text check if enabled.
- API now supports filtering of changes.
- Added support for sharing glossaries between projects.

4.23 Weblate 4.0.4

Released on May 7th 2020.

- Fixed testsuite execution on some Python 3.8 environments.
- Typo fixes in the documentation.
- Fixed creating components using API in some cases.
- Fixed JavaScript errors breaking mobile navigation.
- Fixed crash on displaying some checks.
- Fixed screenshots listing.
- Fixed monthly digest notifications.
- Fixed intermediate translation behavior with units non existing in translation.

4.24 Weblate 4.0.3

Released on May 2nd 2020.

- Fixed possible crash in reports.
- User mentions in comments are now case insensitive.
- Fixed PostgreSQL migration for non superusers.
- Fixed changing the repository URL while creating component.
- Fixed crash when upstream repository is gone.

4.25 Weblate 4.0.2

Released on April 27th 2020.

- Improved performance of translation stats.
- Improved performance of changing labels.
- Improved bulk edit performance.
- Improved translation memory performance.
- Fixed possible crash on component deletion.
- Fixed displaying of translation changes in some corner cases.
- Improved warning about too long celery queue.
- Fixed possible false positives in the consistency check.
- Fixed deadlock when changing linked component repository.
- Included edit distance in changes listing and CSV and reports.
- Avoid false positives of punctuation spacing check for Canadian French.
- Fixed XLIFF export with placeholders.
- Fixed false positive with zero width check.
- Improved reporting of configuration errors.
- Fixed bilingual source upload.
- Automatically detect supported languages for DeepL machine translation.
- Fixed progress bar display in some corner cases.
- Fixed some checks triggering on non translated strings.

4.26 Weblate 4.0.1

Released on April 16th 2020.

- Fixed package installation from PyPI.

4.27 Weblate 4.0

Released on April 16th 2020.

- Weblate now requires Python 3.6 or newer.
- Added management overview of component alerts.
- Added component alert for broken repository browser URLs.
- Improved sign in and registration pages.
- Project access control and workflow configuration integrated to project settings.
- Added check and highlighter for i18next interpolation and nesting.
- Added check and highlighter for percent placeholders.
- Display suggestions failing checks.
- Record source string changes in history.
- Upgraded Microsoft Translator to version 3 API.
- Reimplemented translation memory backend.
- Added support for several `is:` lookups in *Kërkim*.
- Allow to make *Përkthim i pandryshuar* avoid internal blacklist.
- Improved comments extraction from monolingual po files.
- Renamed whiteboard messages to announcements.
- Fixed occasional problems with registration mails.
- Improved LINGUAS update add-on to handle more syntax variants.
- Fixed editing monolingual XLIFF source file.
- Added support for exact matching in *Kërkim*.
- Extended API to cover screenshots, users, groups, componentlists and extended creating projects.
- Add support for source upload on bilingual translations.
- Added support for intermediate language from developers.
- Added support for source strings review.
- Extended download options for platform wide translation memory.

4.28 Weblate 3.x series

4.28.1 Weblate 3.11.3

Released on March 11th 2020.

- Fixed searching for fields with certain priority.
- Fixed predefined query for recently added strings.
- Fixed searching returning duplicate matches.
- Fixed notifications rendering in Gmail.
- Fixed reverting changes from the history.
- Added links to events in digest notifications.
- Fixed email for account removal confirmation.

- Added support for Slack authentication in Docker container.
- Avoid sending notifications for not subscribed languages.
- Include Celery queues in performance overview.
- Fixed documentation links for add-ons.
- Reduced false negatives for unchanged translation check.
- Raised bleach dependency to address CVE-2020-6802.
- Fixed listing project level changes in history.
- Fixed stats invalidation in some corner cases.
- Fixed searching for certain string states.
- Improved format string checks behavior on missing percent.
- Fixed authentication using some third party providers.

4.28.2 Weblate 3.11.2

Released on February 22nd 2020.

- Fixed rendering of suggestions.
- Fixed some strings wrongly reported as having no words.

4.28.3 Weblate 3.11.1

Released on February 20th 2020.

- Documented Celery setup changes.
- Improved filename validation on component creation.
- Fixed minimal versions of some dependencies.
- Fixed adding groups with certain Django versions.
- Fixed manual pushing to upstream repository.
- Improved glossary matching.

4.28.4 Weblate 3.11

Released on February 17th 2020.

- Allow using VCS push URL during component creation via API.
- Rendered width check now shows image with the render.
- Fixed links in notifications e-mails.
- Improved look of plaintext e-mails.
- Display ignored checks and allow to make them active again.
- Display nearby keys on monolingual translations.
- Added support for grouping string shapings.
- Recommend upgrade to new Weblate versions in the system checks.
- Provide more detailed analysis for duplicate language alert.
- Include more detailed license info on the project pages.

- Automatically unshallow local copies if needed.
- Fixed download of strings needing action.
- New alert to warn about using the same filemask twice.
- Improve XML placeables extraction.
- The *SINGLE_PROJECT* can now enforce redirection to chosen project.
- Added option to resolve comments.
- Added bulk editing of flags.
- Added support for labels.
- Added bulk edit add-on.
- Added option for *Enforcing checks*.
- Increased default validity of confirmation links.
- Improved Matomo integration.
- Fixed *Është përkthyer* to correctly handle source string change.
- Extended automatic updates configuration by *AUTO_UPDATE*.
- LINGUAS add-ons now do full sync of translations in Weblate.

4.28.5 Weblate 3.10.3

Released on January 18th 2020.

- Support for translate-toolkit 2.5.0.

4.28.6 Weblate 3.10.2

Released on January 18th 2020.

- Add lock indication to projects.
- Fixed CSS bug causing flickering in some web browsers.
- Fixed searching on systems with non-English locales.
- Improved repository matching for GitHub and Bitbucket hooks.
- Fixed data migration on some Python 2.7 installations.
- Allow configuration of Git shallow cloning.
- Improved background notification processing.
- Fixed broken form submission when navigating back in web browser.
- New add-on to configure YAML formatting.
- Fixed same plurals check to not fire on single plural form languages.
- Fixed regex search on some fields.

4.28.7 Weblate 3.10.1

Released on January 9th 2020.

- Extended API with translation creation.
- Fixed several corner cases in data migrations.
- Compatibility with Django 3.0.
- Improved data clean-up performance.
- Added support for customizable security.txt.
- Improved breadcrumbs in changelog.
- Improved translations listing on dashboard.
- Improved HTTP responses for webhooks.
- Added support for GitLab merge requests in Docker container.

4.28.8 Weblate 3.10

Released on December 20th 2019.

- Improved application user interface.
- Added doublespace check.
- Fixed creating new languages.
- Avoid sending auditlog notifications to deleted e-mails.
- Added support for read only strings.
- Added support for Markdown in comments.
- Allow placing translation instruction text in project info.
- Add copy to clipboard for secondary languages.
- Improved support for Mercurial.
- Improved Git repository fetching performance.
- Add search lookup for age of string.
- Show source language for all translations.
- Show context for nearby strings.
- Added support for notifications on repository operations.
- Improved translation listings.
- Extended search capabilities.
- Added support for automatic translation strings marked for editing.
- Avoid sending duplicate notifications for linked component alerts.
- Improve default merge request message.
- Better indicate string state in Zen mode.
- Added support for more languages in Yandex Translate.
- Improved look of notification e-mails.
- Provide choice for translation license.

4.28.9 Weblate 3.9.1

Released on October 28th 2019.

- Remove some unneeded files from backups.
- Fixed potential crash in reports.
- Fixed cross database migration failure.
- Added support for force pushing Git repositories.
- Reduced risk of registration token invalidation.
- Fixed account removal hitting rate limiter.
- Added search based on priority.
- Fixed possible crash on adding strings to JSON file.
- Safe HTML check and fixup now honor source string markup.
- Avoid sending notifications to invited and deleted users.
- Fix SSL connection to redis in Celery in Docker container.

4.28.10 Weblate 3.9

Released on October 15th 2019.

- Include Weblate metadata in downloaded files.
- Improved UI for failing checks.
- Indicate missing strings in format checks.
- Separate check for French punctuation spacing.
- Add support for fixing some of quality checks errors.
- Add separate permission to create new projects.
- Extend stats for char counts.
- Improve support for Java style language codes.
- Added new generic check for placeholders.
- Added support for WebExtension JSON placeholders.
- Added support for flat XML format.
- Extended API with project, component and translation removal and creation.
- Added support for Gitea and Gitee webhooks.
- Added new custom regex based check.
- Allow to configure contributing to shared translation memory.
- Added ZIP download for more translation files.
- Make XLIFF standard compliant parsing of maxwidth and font.
- Added new check and fixer for safe HTML markup for translating web applications.
- Add component alert on unsupported configuration.
- Added automatic translation add-on to bootstrap translations.
- Extend automatic translation to add suggestions.
- Display add-on parameters on overview.

- Sentry is now supported through modern Sentry SDK instead of Raven.
- Changed example settings to be better fit for production environment.
- Added automated backups using BorgBackup.
- Split cleanup add-on for RESX to avoid unwanted file updates.
- Added advanced search capabilities.
- Allow users to download their own reports.
- Added localization guide to help configuring components.
- Added support for GitLab merge requests.
- Improved display of repository status.
- Perform automated translation in the background.

4.28.11 Weblate 3.8

Released on August 15th 2019.

- Added support for simplified creating of similar components.
- Added support for parsing translation flags from the XML based file formats.
- Log exceptions into Celery log.
- Improve performance of repository scoped add-ons.
- Improved look of notification e-mails.
- Fixed password reset behavior.
- Improved performance on most of translation pages.
- Fixed listing of languages not known to Weblate.
- Add support for cloning add-ons to discovered components.
- Add support for replacing file content with uploaded.
- Add support for translating non VCS based content.
- Added OpenGraph widget image to use on social networks.
- Added support for animated screenshots.
- Improved handling of monolingual XLIFF files.
- Avoid sending multiple notifications for single event.
- Add support for filtering changes.
- Extended predefined periods for reporting.
- Added webhook support for Azure Repos.
- New opt-in notifications on pending suggestions or untranslated strings.
- Add one click unsubscribe link to notification e-mails.
- Fixed false positives with Has been translated check.
- New management interface for admins.
- String priority can now be specified using flags.
- Added language management views.
- Add checks for Qt library and Ruby format strings.
- Added configuration to better fit single project installations.

- Notify about new string on source string change on monolingual translations.
- Added separate view for translation memory with search capability.

4.28.12 Weblate 3.7.1

Released on June 28th 2019.

- Documentation updates.
- Fixed some requirements constraints.
- Updated language database.
- Localization updates.
- Various user interface tweaks.
- Improved handling of unsupported but discovered translation files.
- More verbosely report missing file format requirements.

4.28.13 Weblate 3.7

Released on June 21st 2019.

- Added separate Celery queue for notifications.
- Use consistent look with application for API browsing.
- Include approved stats in the reports.
- Report progress when updating translation component.
- Allow to abort running background component update.
- Extend template language for filename manipulations.
- Use templates for editor link and repository browser URL.
- Indicate max length and current characters count when editing translation.
- Improved handling of abbreviations in unchanged translation check.
- Refreshed landing page for new contributors.
- Add support for configuring msgmerge add-on.
- Delay opening SMTP connection when sending notifications.
- Improved error logging.
- Allow custom location in MO generating add-on.
- Added add-ons to cleanup old suggestions or comments.
- Added option to enable horizontal mode in the Zen editor.
- Improved import performance with many linked components.
- Fixed examples installation in some cases.
- Improved rendering of alerts in changes.
- Added new horizontal stats widget.
- Improved format strings check on plurals.
- Added font management tool.
- New check for rendered text dimensions.

- Added support for subtitle formats.
- Include overall completion stats for languages.
- Added reporting at project and global scope.
- Improved user interface when showing translation status.
- New Weblate logo and color scheme.
- New look of bitmap badges.

4.28.14 Weblate 3.6.1

Released on April 26th 2019.

- Improved handling of monolingual XLIFF files.
- Fixed digest notifications in some corner cases.
- Fixed add-on script error alert.
- Fixed generating MO file for monolingual PO files.
- Fixed display of uninstalled checks.
- Indicate administered projects on project listing.
- Allow update to recover from missing VCS repository.

4.28.15 Weblate 3.6

Released on April 20th 2019.

- Add support for downloading user data.
- Add-ons are now automatically triggered upon installation.
- Improved instructions for resolving merge conflicts.
- Cleanup add-on is now compatible with app store metadata translations.
- Configurable language code syntax when adding new translations.
- Warn about using Python 2 with planned termination of support in April 2020.
- Extract special characters from the source string for visual keyboard.
- Extended contributor stats to reflect both source and target counts.
- Admins and consistency add-ons can now add translations even if disabled for users.
- Fixed description of toggle disabling Language-Team header manipulation.
- Notify users mentioned in comments.
- Removed file format autodetection from component setup.
- Fixed generating MO file for monolingual PO files.
- Added digest notifications.
- Added support for muting component notifications.
- Added notifications for new alerts, whiteboard messages or components.
- Notifications for administered projects can now be configured.
- Improved handling of three letter language codes.

4.28.16 Weblate 3.5.1

Released on March 10th 2019.

- Fixed Celery systemd unit example.
- Fixed notifications from HTTP repositories with login.
- Fixed race condition in editing source string for monolingual translations.
- Include output of failed add-on execution in the logs.
- Improved validation of choices for adding new language.
- Allow to edit file format in component settings.
- Update installation instructions to prefer Python 3.
- Performance and consistency improvements for loading translations.
- Make Microsoft Terminology service compatible with current Zeep releases.
- Localization updates.

4.28.17 Weblate 3.5

Released on March 3rd 2019.

- Improved performance of built-in translation memory.
- Added interface to manage global translation memory.
- Improved alerting on bad component state.
- Added user interface to manage whiteboard messages.
- Add-on commit message now can be configured.
- Reduce number of commits when updating upstream repository.
- Fixed possible metadata loss when moving component between projects.
- Improved navigation in the Zen mode.
- Added several new quality checks (Markdown related and URL).
- Added support for app store metadata files.
- Added support for toggling GitHub or Gerrit integration.
- Added check for Kashida letters.
- Added option to squash commits based on authors.
- Improved support for XLSX file format.
- Compatibility with Tesseract 4.0.
- Billing add-on now removes projects for unpaid billings after 45 days.

4.28.18 Weblate 3.4

Released on January 22nd 2019.

- Added support for XLIFF placeholders.
- Celery can now utilize multiple task queues.
- Added support for renaming and moving projects and components.
- Include characters counts in reports.
- Added guided adding of translation components with automatic detection of translation files.
- Customizable merge commit messages for Git.
- Added visual indication of component alerts in navigation.
- Improved performance of loading translation files.
- New add-on to squash commits prior to push.
- Improved displaying of translation changes.
- Changed default merge style to rebase and made that configurable.
- Better handle private use subtags in language code.
- Improved performance of fulltext index updates.
- Extended file upload API to support more parameters.

4.28.19 Weblate 3.3

Released on November 30th 2018.

- Added support for component and project removal.
- Improved performance for some monolingual translations.
- Added translation component alerts to highlight problems with a translation.
- Expose XLIFF string resname as context when available.
- Added support for XLIFF states.
- Added check for non writable files in DATA_DIR.
- Improved CSV export for changes.

4.28.20 Weblate 3.2.2

Released on October 20th 2018.

- Remove no longer needed Babel dependency.
- Updated language definitions.
- Improve documentation for add-ons, LDAP and Celery.
- Fixed enabling new dos-eol and auto-java-messageformat flags.
- Fixed running setup.py test from PyPI package.
- Improved plurals handling.
- Fixed translation upload API failure in some corner cases.
- Fixed updating Git configuration in case it was changed manually.

4.28.21 Weblate 3.2.1

Released on October 10th 2018.

- Document dependency on backports.csv on Python 2.7.
- Fix running tests under root.
- Improved error handling in gitexport module.
- Fixed progress reporting for newly added languages.
- Correctly report Celery worker errors to Sentry.
- Fixed creating new translations with Qt Linguist.
- Fixed occasional fulltext index update failures.
- Improved validation when creating new components.
- Added support for cleanup of old suggestions.

4.28.22 Weblate 3.2

Released on October 6th 2018.

- Add install_addon management command for automated add-on installation.
- Allow more fine grained ratelimit settings.
- Added support for export and import of Excel files.
- Improve component cleanup in case of multiple component discovery add-ons.
- Rewritten Microsoft Terminology machine translation backend.
- Weblate now uses Celery to offload some processing.
- Improved search capabilities and added regular expression search.
- Added support for Youdao Zhiyun API machine translation.
- Added support for Baidu API machine translation.
- Integrated maintenance and cleanup tasks using Celery.
- Improved performance of loading translations by almost 25%.
- Removed support for merging headers on upload.
- Removed support for custom commit messages.
- Configurable editing mode (zen/full).
- Added support for error reporting to Sentry.
- Added support for automated daily update of repositories.
- Added support for creating projects and components by users.
- Built-in translation memory now automatically stores translations done.
- Users and projects can import their existing translation memories.
- Better management of related strings for screenshots.
- Added support for checking Java MessageFormat.

See [3.2 milestone on GitHub](#) for detailed list of addressed issues.

4.28.23 Weblate 3.1.1

Released on July 27th 2018.

- Fix testsuite failure on some setups.

4.28.24 Weblate 3.1

Released on July 27th 2018.

- Upgrades from older version than 3.0.1 are not supported.
- Allow to override default commit messages from settings.
- Improve webhooks compatibility with self hosted environments.
- Added support for Amazon Translate.
- Compatibility with Django 2.1.
- Django system checks are now used to diagnose problems with installation.
- Removed support for soon shutdown libavatar service.
- New add-on to mark unchanged translations as needing edit.
- Add support for jumping to specific location while translating.
- Downloaded translations can now be customized.
- Improved calculation of string similarity in translation memory matches.
- Added support by signing Git commits by GnuPG.

4.28.25 Weblate 3.0.1

Released on June 10th 2018.

- Fixed possible migration issue from 2.20.
- Localization updates.
- Removed obsolete hook examples.
- Improved caching documentation.
- Fixed displaying of admin documentation.
- Improved handling of long language names.

4.28.26 Weblate 3.0

Released on June 1st 2018.

- Rewritten access control.
- Several code cleanups that lead to moved and renamed modules.
- New add-on for automatic component discovery.
- The `import_project` management command has now slightly different parameters.
- Added basic support for Windows RC files.
- New add-on to store contributor names in PO file headers.
- The per component hook scripts are removed, use add-ons instead.
- Add support for collecting contributor agreements.

- Access control changes are now tracked in history.
- New add-on to ensure all components in a project have same translations.
- Support for more variables in commit message templates.
- Add support for providing additional textual context.

4.29 Weblate 2.x series

4.29.1 Weblate 2.20

Released on April 4th 2018.

- Improved speed of cloning subversion repositories.
- Changed repository locking to use third party library.
- Added support for downloading only strings needing action.
- Added support for searching in several languages at once.
- New add-on to configure gettext output wrapping.
- New add-on to configure JSON formatting.
- Added support for authentication in API using RFC 6750 compatible Bearer authentication.
- Added support for automatic translation using machine translation services.
- Added support for HTML markup in whiteboard messages.
- Added support for mass changing state of strings.
- Translate-toolkit at least 2.3.0 is now required, older versions are no longer supported.
- Added built-in translation memory.
- Added componentlists overview to dashboard and per component list overview pages.
- Added support for DeepL machine translation service.
- Machine translation results are now cached inside Weblate.
- Added support for reordering committed changes.

4.29.2 Weblate 2.19.1

Released on February 20th 2018.

- Fixed migration issue on upgrade from 2.18.
- Improved file upload API validation.

4.29.3 Weblate 2.19

Released on February 15th 2018.

- Fixed imports across some file formats.
- Display human friendly browser information in audit log.
- Added TMX exporter for files.
- Various performance improvements for loading translation files.
- Added option to disable access management in Weblate in favor of Django one.

- Improved glossary lookup speed for large strings.
- Compatibility with django_auth_ldap 1.3.0.
- Configuration errors are now stored and reported persistently.
- Honor ignore flags in whitespace autofixer.
- Improved compatibility with some Subversion setups.
- Improved built-in machine translation service.
- Added support for SAP Translation Hub service.
- Added support for Microsoft Terminology service.
- Removed support for advertisement in notification e-mails.
- Improved translation progress reporting at language level.
- Improved support for different plural formulas.
- Added support for Subversion repositories not using stdlayout.
- Added add-ons to customize translation workflows.

4.29.4 Weblate 2.18

Released on December 15th 2017.

- Extended contributor stats.
- Improved configuration of special characters virtual keyboard.
- Added support for DTD file format.
- Changed keyboard shortcuts to less likely collide with browser/system ones.
- Improved support for approved flag in XLIFF files.
- Added support for not wrapping long strings in gettext PO files.
- Added button to copy permalink for current translation.
- Dropped support for Django 1.10 and added support for Django 2.0.
- Removed locking of translations while translating.
- Added support for adding new strings to monolingual translations.
- Added support for translation workflows with dedicated reviewers.

4.29.5 Weblate 2.17.1

Released on October 13th 2017.

- Fixed running testsuite in some specific situations.
- Locales updates.

4.29.6 Weblate 2.17

Released on October 13th 2017.

- Weblate by default does shallow Git clones now.
- Improved performance when updating large translation files.
- Added support for blocking certain e-mails from registration.
- Users can now delete their own comments.
- Added preview step to search and replace feature.
- Client side persistence of settings in search and upload forms.
- Extended search capabilities.
- More fine grained per project ACL configuration.
- Default value of BASE_DIR has been changed.
- Added two step account removal to prevent accidental removal.
- Project access control settings is now editable.
- Added optional spam protection for suggestions using Akismet.

4.29.7 Weblate 2.16

Released on August 11th 2017.

- Various performance improvements.
- Added support for nested JSON format.
- Added support for WebExtension JSON format.
- Fixed git exporter authentication.
- Improved CSV import in certain situations.
- Improved look of Other translations widget.
- The max-length checks is now enforcing length of text in form.
- Make the commit_pending age configurable per component.
- Various user interface cleanups.
- Fixed component/project/site wide search for translations.

4.29.8 Weblate 2.15

Released on June 30th 2017.

- Show more related translations in other translations.
- Add option to see translations of current string to other languages.
- Use 4 plural forms for Lithuanian by default.
- Fixed upload for monolingual files of different format.
- Improved error messages on failed authentication.
- Keep page state when removing word from glossary.
- Added direct link to edit secondary language translation.
- Added Perl format quality check.

- Added support for rejecting reused passwords.
- Extended toolbar for editing RTL languages.

4.29.9 Weblate 2.14.1

Released on May 24th 2017.

- Fixed possible error when paginating search results.
- Fixed migrations from older versions in some corner cases.
- Fixed possible CSRF on project watch and unwatch.
- The password reset no longer authenticates user.
- Fixed possible CAPTCHA bypass on forgotten password.

4.29.10 Weblate 2.14

Released on May 17th 2017.

- Add glossary entries using AJAX.
- The logout now uses POST to avoid CSRF.
- The API key token reset now uses POST to avoid CSRF.
- Weblate sets Content-Security-Policy by default.
- The local editor URL is validated to avoid self-XSS.
- The password is now validated against common flaws by default.
- Notify users about important activity with their account such as password change.
- The CSV exports now escape potential formulas.
- Various minor improvements in security.
- The authentication attempts are now rate limited.
- Suggestion content is stored in the history.
- Store important account activity in audit log.
- Ask for password confirmation when removing account or adding new associations.
- Show time when suggestion has been made.
- There is new quality check for trailing semicolon.
- Ensure that search links can be shared.
- Included source string information and screenshots in the API.
- Allow to overwrite translations through API upload.

4.29.11 Weblate 2.13.1

Released on Apr 12th 2017.

- Fixed listing of managed projects in profile.
- Fixed migration issue where some permissions were missing.
- Fixed listing of current file format in translation download.
- Return HTTP 404 when trying to access project where user lacks privileges.

4.29.12 Weblate 2.13

Released on Apr 12th 2017.

- Fixed quality checks on translation templates.
- Added quality check to trigger on losing translation.
- Add option to view pending suggestions from user.
- Add option to automatically build component lists.
- Default dashboard for unauthenticated users can be configured.
- Add option to browse 25 random strings for review.
- History now indicates string change.
- Better error reporting when adding new translation.
- Added per language search within project.
- Group ACLs can now be limited to certain permissions.
- The per project ACLs are now implemented using Group ACL.
- Added more fine grained privileges control.
- Various minor UI improvements.

4.29.13 Weblate 2.12

Released on Mar 3rd 2017.

- Improved admin interface for groups.
- Added support for Yandex Translate API.
- Improved speed of site wide search.
- Added project and component wide search.
- Added project and component wide search and replace.
- Improved rendering of inconsistent translations.
- Added support for opening source files in local editor.
- Added support for configuring visual keyboard with special characters.
- Improved screenshot management with OCR support for matching source strings.
- Default commit message now includes translation information and URL.
- Added support for Joomla translation format.
- Improved reliability of import across file formats.

4.29.14 Weblate 2.11

Released on Jan 31st 2017.

- Include language detailed information on language page.
- Mercurial backend improvements.
- Added option to specify translation component priority.
- More consistent usage of Group ACL even with less used permissions.
- Added WL_BRANCH variable to hook scripts.
- Improved developer documentation.
- Better compatibility with various Git versions in Git exporter add-on.
- Included per project and component stats.
- Added language code mapping for better support of Microsoft Translate API.
- Moved fulltext cleanup to background job to make translation removal faster.
- Fixed displaying of plural source for languages with single plural form.
- Improved error handling in import_project.
- Various performance improvements.

4.29.15 Weblate 2.10.1

Released on Jan 20th 2017.

- Do not leak account existence on password reset form (CVE-2017-5537).

4.29.16 Weblate 2.10

Released on Dec 15th 2016.

- Added quality check to check whether plurals are translated differently.
- Fixed GitHub hooks for repositories with authentication.
- Added optional Git exporter module.
- Support for Microsoft Cognitive Services Translator API.
- Simplified project and component user interface.
- Added automatic fix to remove control characters.
- Added per language overview to project.
- Added support for CSV export.
- Added CSV download for stats.
- Added matrix view for quick overview of all translations.
- Added basic API for changes and strings.
- Added support for Apertium APy server for machine translations.

4.29.17 Weblate 2.9

Released on Nov 4th 2016.

- Extended parameters for createadmin management command.
- Extended import_json to be able to handle with existing components.
- Added support for YAML files.
- Project owners can now configure translation component and project details.
- Use «Watched» instead of «Subscribed» projects.
- Projects can be watched directly from project page.
- Added multi language status widget.
- Highlight secondary language if not showing source.
- Record suggestion deletion in history.
- Improved UX of languages selection in profile.
- Fixed showing whiteboard messages for component.
- Keep preferences tab selected after saving.
- Show source string comment more prominently.
- Automatically install Gettext PO merge driver for Git repositories.
- Added search and replace feature.
- Added support for uploading visual context (screenshots) for translations.

4.29.18 Weblate 2.8

Hedhur në qarkullim më 31 gusht, 2016.

- Documentation improvements.
- Translations.
- Updated bundled javascript libraries.
- Added list_translators management command.
- Django 1.8 is no longer supported.
- Fixed compatibility with Django 1.10.
- Added Subversion support.
- Separated XML validity check from XML mismatched tags.
- Fixed API to honor HIDE_REPO_CREDENTIALS settings.
- Show source change in Zen mode.
- Alt+PageUp/PageDown/Home/End now works in Zen mode as well.
- Add tooltip showing exact time of changes.
- Add option to select filters and search from translation page.
- Added UI for translation removal.
- Improved behavior when inserting placeables.
- Fixed auto locking issues in Zen mode.

4.29.19 Weblate 2.7

Released on Jul 10th 2016.

- Removed Google web translate machine translation.
- Improved commit message when adding translation.
- Fixed Google Translate API for Hebrew language.
- Compatibility with Mercurial 3.8.
- Added import_json management command.
- Correct ordering of listed translations.
- Show full suggestion text, not only a diff.
- Extend API (detailed repository status, statistics, ...).
- Testsuite no longer requires network access to test repositories.

4.29.20 Weblate 2.6

Hedhur në qarkullim më 28 prill, 2016.

- Fixed validation of components with language filter.
- Improved support for XLIFF files.
- Fixed machine translation for non English sources.
- Added REST API.
- Django 1.10 compatibility.
- Added categories to whiteboard messages.

4.29.21 Weblate 2.5

Hedhur në qarkullim më 10 mars, 2016.

- Fixed automatic translation for project owners.
- Improved performance of commit and push operations.
- New management command to add suggestions from command line.
- Added support for merging comments on file upload.
- Added support for some GNU extensions to C printf format.
- Documentation improvements.
- Added support for generating translator credits.
- Added support for generating contributor stats.
- Site wide search can search only in one language.
- Improve quality checks for Armenian.
- Support for starting translation components without existing translations.
- Support for adding new translations in Qt TS.
- Improved support for translating PHP files.
- Performance improvements for quality checks.
- Fixed site wide search for failing checks.

- Added option to specify source language.
- Improved support for XLIFF files.
- Extended list of options for import_project.
- Improved targeting for whiteboard messages.
- Support for automatic translation across projects.
- Optimized fulltext search index.
- Added management command for auto translation.
- Added placeables highlighting.
- Added keyboard shortcuts for placeables, checks and machine translations.
- Improved translation locking.
- Added quality check for AngularJS interpolation.
- Added extensive group based ACLs.
- Clarified terminology on strings needing edit (formerly fuzzy).
- Clarified terminology on strings needing action and not translated strings.
- Mbulim për Python 3.
- Dropped support for Django 1.7.
- Dropped dependency on msginit for creating new gettext PO files.
- Added configurable dashboard views.
- Improved notifications on parse errors.
- Added option to import components with duplicate name to import_project.
- Improved support for translating PHP files.
- Added XLIFF export for dictionary.
- Added XLIFF and gettext PO export for all translations.
- Documentation improvements.
- Added support for configurable automatic group assignments.
- Improved adding of new translations.

4.29.22 Weblate 2.4

Released on Sep 20th 2015.

- Improved support for PHP files.
- Ability to add ACL to anonymous user.
- Improved configurability of import_project command.
- Added CSV dump of history.
- Avoid copy/paste errors with whitespace characters.
- Added support for Bitbucket webhooks.
- Tighter control on fuzzy strings on translation upload.
- Several URLs have changed, you might have to update your bookmarks.
- Hook scripts are executed with VCS root as current directory.
- Hook scripts are executed with environment variables describing current component.

- Add management command to optimize fulltext index.
- Added support for error reporting to Rollbar.
- Projects now can have multiple owners.
- Project owners can manage themselves.
- Added support for `javascript-format` used in gettext PO.
- Support for adding new translations in XLIFF.
- Improved file format autodetection.
- Extended keyboard shortcuts.
- Improved dictionary matching for several languages.
- Improved layout of most of pages.
- Support for adding words to dictionary while translating.
- Added support for filtering languages to be managed by Weblate.
- Added support for translating and importing CSV files.
- Rewritten handling of static files.
- Direct login/registration links to third-party service if that's the only one.
- Commit pending changes on account removal.
- Add management command to change site name.
- Add option to configure default committer.
- Add hook after adding new translation.
- Add option to specify multiple files to add to commit.

4.29.23 Weblate 2.3

Hedhur në qarkullim më 22 maj, 2015.

- Dropped support for Django 1.6 and South migrations.
- Support for adding new translations when using Java Property files.
- Allow to accept suggestion without editing.
- Improved support for Google OAuth 2.0.
- Added support for Microsoft .resx files.
- Tuned default robots.txt to disallow big crawling of translations.
- Simplified workflow for accepting suggestions.
- Added project owners who always receive important notifications.
- Allow to disable editing of monolingual template.
- More detailed repository status view.
- Direct link for editing template when changing translation.
- Allow to add more permissions to project owners.
- Allow to show secondary language in Zen mode.
- Support for hiding source string in favor of secondary language.

4.29.24 Weblate 2.2

Hedhur në qarkullim më 19 shkurt, 2015.

- Përmirësime funksionimi.
- Fulltext search on location and comments fields.
- New SVG/javascript based activity charts.
- Mbulim për Django 1.8.
- Mbulim për fshirje komentesh.
- Added own SVG badge.
- U shtua mbulim për Google Analytics.
- U përmirësua trajtimi i emrave të kartelave të përkthimit.
- Added support for monolingual JSON translations.
- Record component locking in a history.
- Support for editing source (template) language for monolingual translations.
- U shtua mbulim i thjeshtë për Gerrit.

4.29.25 Weblate 2.1

Released on Dec 5th 2014.

- U shtua mbulim për depo Mercurial.
- U zëvendësuan shkronjat Glyphicon me ato Awesome.
- U shtuan ikona për shërbime mirëfilltësi përmes rrjetesh shoqërore.
- Better consistency of button colors and icons.
- Documentation improvements.
- Ndreqje të metash të ndryshme.
- Automatic hiding of columns in translation listing for small screens.
- U ndryshua formësimi për shtigje sistemi kartelash.
- Improved SSH keys handling and storage.
- U përmirësua kyçje deposh.
- Customizable quality checks per source string.
- Allow to hide completed translations from dashboard.

4.29.26 Weblate 2.0

Released on Nov 6th 2014.

- New responsive UI using Bootstrap.
- Rewritten VCS backend.
- Documentation improvements.
- Added whiteboard for site wide messages.
- Configurable strings priority.
- U shtua mbulim për format JSON kartelash.

- Fixed generating mo files in certain cases.
- U shtua mbulim për njoftime GitLab.
- U shtua mbulim për çaktivizim sugjerimesh përkthimi.
- Mbulim për Django 1.7.
- ACL projects now have user management.
- U zgjeruan mundësitë e kërkimit.
- Give more hints to translators about plurals.
- U ndreq kyçje depush Git.
- Përputhshmëri me versione të vjetër Git-i.
- U përmirësua mbulimi për ACL.
- Added buttons for per language quotes and other special characters.
- Mbulim për eksportim statistikash si JSONP.

4.30 Seritë Weblate 1.x

4.30.1 Weblate 1.9

Hedhur në qarkullim më 6 maj, 2014.

- Përputhshmëri me Django 1.6.
- No longer maintained compatibility with Django 1.4.
- Management commands for locking/unlocking translations.
- Improved support for Qt TS files.
- Përdoruesit tani mund të fshijnë llogarinë e tyre.
- Avatarët mund të çaktivizohen.
- Merged first and last name attributes.
- Avatars are now fetched and cached server side.
- U shtua mbulim për stemë shields.io.

4.30.2 Weblate 1.8

Hedhur në qarkullim më 7 nëntor, 2013.

- Ju lutemi, shihni doracakun për udhëzime përmirësimi.
- Nicer listing of project summary.
- Better visible options for sharing.
- More control over anonymous users privileges.
- Supports login using third party services, check manual for more details.
- Users can login by e-mail instead of username.
- Documentation improvements.
- U përmirësua shqyrtim vargësh burim.
- Kërkim nëpër krejt vargjet.

- Ndjekje më e mirë e vargjeve burim.
- Mbrojtje CAPTCHA për regjistrimet.

4.30.3 Weblate 1.7

Hedhur në qarkullim më 7 tetor, 2013.

- Ju lutemi, shihni doracakun për udhëzime përmirësimi.
- Mbulim për kontroll vargu formati kllapash Python.
- Per component customization of quality checks.
- Detailed per translation stats.
- Changed way of linking suggestions, checks and comments to strings.
- Users can now add text to commit message.
- Support for subscribing on new language requests.
- Mbulim për shtim përkthimesh të reja.
- Widgets and charts are now rendered using Pillow instead of Pango + Cairo.
- Add status badge widget.
- Dropped invalid text direction check.
- Changes in dictionary are now logged in history.
- Përmirësime funksionimi të pamjes përkthim.

4.30.4 Weblate 1.6

Hedhur në qarkullim më 25 korrik, 2013.

- Nicer error handling on registration.
- Shfletim ndryshimesh.
- U ndreq renditja e sugjerimeve të përkthimit nga makina.
- Improved support for MyMemory machine translation.
- U shtua mbulim për përkthimi Amagama nga makina.
- Various optimizations on frequently used pages.
- Highlights searched phrase in search results.
- Support for automatic fixups while saving the message.
- Tracking of translation history and option to revert it.
- U shtua mbulim për API Google Translate.
- Added support for managing SSH host keys.
- Përmirësime të ndryshme vlerësimi formularësh.
- Përmirësime të ndryshme kontrollesh cilësie.
- Përmirësime funksionimi për importimet.
- U shtua mbulim për votim sugjerimesh.
- Pastrim i ndërfaqes së përdoruesit.

4.30.5 Weblate 1.5

Hedhur në qarkullim më 6 prill, 2013.

- Ju lutemi, shihni doracakun për udhëzime përmirësimi.
- U shtuan faqe publike përdoruesi.
- Emërtim më i mirë i formave të shumës.
- Added support for TBX export of glossary.
- U shtua mbulim për njoftime Bitbucket.
- Activity charts are now available for each translation, language or user.
- Extended options of import_project admin command.
- I përputhshëm me Django 1.5.
- Avatars are now shown using libavatar.
- Added possibility to pretty print JSON export.
- Various performance improvements.
- Indicate failing checks or fuzzy strings in progress bars for projects or languages as well.
- Added support for custom pre-commit hooks and committing additional files.
- Rewritten search for better performance and user experience.
- Ndërfaqe e re për përkthime nga makina.
- Added support for monolingual po files.
- Extend amount of cached metadata to improve speed of various searches.
- Now shows word counts as well.

4.30.6 Weblate 1.4

Hedhur në qarkullim më 23 janar, 2013.

- Fixed deleting of checks/comments on string deletion.
- Added option to disable automatic propagation of translations.
- Added option to subscribe for merge failures.
- Correctly import on projects which needs custom ttkit loader.
- Added sitemaps to allow easier access by crawlers.
- Provide direct links to string in notification e-mails or feeds.
- Përmirësime të ndryshme të ndërfaqes së përgjegjësit.
- Provide hints for production setup in admin interface.
- Added per language widgets and engage page.
- U përmirësua trajtimi i kyçjes së përkthimeve.
- Show code snippets for widgets in more variants.
- Indicate failing checks or fuzzy strings in progress bars.
- More options for formatting commit message.
- Fixed error handling with machine translation services.
- Improved automatic translation locking behaviour.

- Support for showing changes from previous source string.
- Added support for substring search.
- Përmirësime të ndryshme kontrollesh cilësie.
- Support for per project ACL.
- Basic code coverage by unit tests.

4.30.7 Weblate 1.3

Released on November 16th 2012.

- Compatibility with PostgreSQL database backend.
- Removes languages removed in upstream git repository.
- U përmirësua kryerja e kontrolleve të cilësisë.
- Added new checks (BB code, XML markup and newlines).
- Support for optional rebasing instead of merge.
- Possibility to relocate Weblate (for example to run it under /weblate path).
- Support for manually choosing file type in case autodetection fails.
- Mbulim më i mirë për burime Android.
- Support for generating SSH key from web interface.
- More visible data exports.
- New buttons to enter some special characters.
- Mbulim për eksportim fjalori.
- Support for locking down whole Weblate installation.
- Checks for source strings and support for source strings review.
- Support for user comments for both translations and source strings.
- Better changes log tracking.
- Changes can now be monitored using RSS.
- U përmirësua mbulimi për gjuhë DNM.

4.30.8 Weblate 1.2

Released on August 14th 2012.

- Weblate now uses South for database migration, please check upgrade instructions if you are upgrading.
- Fixed minor issues with linked git repos.
- New introduction page for engaging people with translating using Weblate.
- Added widgets which can be used for promoting translation projects.
- Added option to reset repository to origin (for privileged users).
- Project or component can now be locked for translations.
- Mundësi për çaktivizim të disa përkthimeve.
- Mundësi të formësueshme për shtim përkthimesh të reja.
- Configuration of git commits per project.

- Mbrojtje e thjeshtë antispam.
- Better layout of main page.
- Support for automatically pushing changes on every commit.
- Support for e-mail notifications of translators.
- List only used languages in preferences.
- Improved handling of not known languages when importing project.
- Support for locking translation by translator.
- Optionally maintain `Language-Team` header in po file.
- Include some statistics in about page.
- Supports (and requires) django-registration 0.8.
- Caching counts of strings with failing checks.
- Checking of requirements during setup.
- Documentation improvements.

4.30.9 Weblate 1.1

Released on July 4th 2012.

- U përmirësuan disa përkthime.
- Better validation while creating component.
- Added support for shared git repositories across components.
- Do not necessary commit on every attempt to pull remote repo.
- Added support for offloading indexing.

4.30.10 Weblate 1.0

Hedhur në qarkullim më 10 maj, 2012.

- Improved validation while adding/saving component.
- Experimental support for Android component files (needs patched ttkit).
- Updates from hooks are run in background.
- U përmirësuan udhëzime instalimi.
- U përmirësua lëvizja në fjalor.

4.31 Weblate 0.x series

4.31.1 Weblate 0.9

Released on April 18th 2012.

- U ndreq importimi i gjuhëve të panjohura.
- Improved listing of nearby messages.
- U përmirësuan disa kontrolle.
- Documentation updates.

- Added definition for several more languages.
- Pastrime të ndryshme kodi.
- Documentation improvements.
- Changed file layout.
- Update helper scripts to Django 1.4.
- Improved navigation while translating.
- Better handling of po file renames.
- Better validation while creating component.
- Integrated full setup into syncdb.
- Added list of recent changes to all translation pages.
- Check for not translated strings ignores format string only messages.

4.31.2 Weblate 0.8

Hedhur në qarkullim më 3 prill, 2012.

- Replaced own full text search with Whoosh.
- Ndreqje dhe përmirësime të ndryshme te kontrollet.
- New command updatechecks.
- Plot përditësime përkthimesh.
- Added dictionary for storing most frequently used terms.
- Added /admin/report/ for overview of repositories status.
- Machine translation services no longer block page loading.
- Management interface now contains also useful actions to update data.
- Records log of changes made by users.
- Ability to postpone commit to Git to generate less commits from single user.
- Possibility to browse failing checks.
- Automatic translation using already translated strings.
- New about page showing used versions.
- Përputhshmëri me Django 1.4.
- Ability to push changes to remote repo from web interface.
- Added review of translations done by others.

4.31.3 Weblate 0.7

Released on February 16th 2012.

- Mbulim i drejtpërdrejtë për njoftime GitHub-u.
- Added support for cleaning up orphaned checks and translations.
- Displays nearby strings while translating.
- Displays similar strings while translating.
- U përmirësua kërkimi për varg.

4.31.4 Weblate 0.6

Released on February 14th 2012.

- U shtuan kontrole të ndryshme për mesazhe të përkthyer.
- Tunable access control.
- Improved handling of translations with new lines.
- Added client side sorting of tables.
- Please check upgrading instructions in case you are upgrading.

4.31.5 Weblate 0.5

Released on February 12th 2012.

- **Support for machine translation using following online services:**
 - Apertium
 - Microsoft Translator
 - MyMemory
- Disa përkthime të reja.
- Improved merging of upstream changes.
- Better handle concurrent git pull and translation.
- Propagating works for fuzzy changes as well.
- Propagating works also for file upload.
- Fixed file downloads while using FastCGI (and possibly others).

4.31.6 Weblate 0.4

Released on February 8th 2012.

- U shtua udhëzues përdorimi të dokumentimi.
- Fixed API hooks not to require CSRF protection.

4.31.7 Weblate 0.3

Released on February 8th 2012.

- Better display of source for plural translations.
- Dokumentim i ri, në formatin Sphinx.
- Displays secondary languages while translating.
- Improved error page to give list of existing projects.
- New per language stats.

4.31.8 Weblate 0.2

Hedhur në qarkullim më 7 shkurt, 2012.

- U përmirësua vlerësimi për disa formularë.
- Sinjalizojë përdoruesve përmirësim profili.
- Remember URL for login.
- Naming of text areas while entering plural forms.
- Automatic expanding of translation area.

4.31.9 Weblate 0.1

Released on February 6th 2012.

- Hedhja fillestare në qarkullim.

W

wlc, [138](#)

wlc.config, [139](#)

wlc.main, [139](#)

HTTP Routing Table

/	GET /api/components/(string:project)/(string:component)/(string:language)/, 112
ANY /, 90	GET /api/components/(string:project)/(string:component)/(string:language)/, 114
/api	GET /api/components/(string:project)/(string:component)/(string:language)/, 114
GET /api/, 92	GET /api/components/(string:project)/(string:component)/(string:language)/, 113
/api/addons	GET /api/components/(string:project)/(string:component)/(string:language)/, 112
GET /api/addons/, 127	GET /api/components/(string:project)/(string:component)/(string:language)/, 116
GET /api/addons/(int:id)/, 127	GET /api/components/(string:project)/(string:component)/(string:language)/, 114
PUT /api/addons/(int:id)/, 128	POST /api/components/(string:project)/(string:component)/(string:language)/, 127
DELETE /api/addons/(int:id)/, 128	POST /api/components/(string:project)/(string:component)/(string:language)/, 116
PATCH /api/addons/(int:id)/, 127	POST /api/components/(string:project)/(string:component)/(string:language)/, 112
/api/changes	POST /api/components/(string:project)/(string:component)/(string:language)/, 113
GET /api/changes/, 124	POST /api/components/(string:project)/(string:component)/(string:language)/, 114
GET /api/changes/(int:id)/, 124	PUT /api/components/(string:project)/(string:component)/(string:language)/, 111
/api/component-lists	DELETE /api/components/(string:project)/(string:component)/(string:language)/, 111
GET /api/component-lists/, 128	DELETE /api/components/(string:project)/(string:component)/(string:language)/, 116
GET /api/component-lists/(str:slug)/, 128	POST /api/components/(string:project)/(string:component)/(string:language)/, 110
POST /api/component-lists/(str:slug)/components/, 129	/api/groups
PUT /api/component-lists/(str:slug)/, 128	GET /api/groups/, 96
DELETE /api/component-lists/(str:slug)/, 129	GET /api/groups/(int:id)/, 96
DELETE /api/component-lists/(str:slug)/components/(string:project)/(string:component)/(string:language)/, 129	POST /api/groups/, 96
PATCH /api/component-lists/(str:slug)/, 128	POST /api/groups/(int:id)/componentlists/, 98
/api/components	POST /api/groups/(int:id)/changes/, 98
GET /api/components/, 108	POST /api/groups/(int:id)/links/, 98
GET /api/components/(string:project)/(string:component)/(string:language)/, 108	POST /api/groups/(int:id)/languages/, 98
GET /api/components/(string:project)/(string:component)/(string:language)/, 112	
GET /api/components/(string:project)/(string:component)/(string:language)/, 116	

POST /api/groups/(int:id)/projects/, **/api/roles**
 98
 POST /api/groups/(int:id)/roles/, 97
 PUT /api/groups/(int:id)/, 97
 DELETE /api/groups/(int:id)/, 97
 DELETE /api/groups/(int:id)/componentlists/(int:component_list_id), 100
 98
 DELETE /api/groups/(int:id)/components/(int:component_id),
 98
 DELETE /api/groups/(int:id)/languages/(string:language_code),
 98
 DELETE /api/groups/(int:id)/projects/(int:project_id),
 98
 PATCH /api/groups/(int:id)/, 97

/api/languages

GET /api/languages/, 100
 GET /api/languages/(string:language)/,
 100
 GET /api/languages/(string:language)/statistics/,
 101
 POST /api/languages/, 100
 PUT /api/languages/(string:language)/,
 101
 DELETE /api/languages/(string:language)/,
 101
 PATCH /api/languages/(string:language)/,
 101

/api/metrics

GET /api/metrics/, 130

/api/projects

GET /api/projects/, 102
 GET /api/projects/(string:project)/,
 102
 GET /api/projects/(string:project)/changes/,
 103
 GET /api/projects/(string:project)/components/,
 104
 GET /api/projects/(string:project)/languages/,
 107
 GET /api/projects/(string:project)/repository/,
 103
 GET /api/projects/(string:project)/statistics/,
 107
 POST /api/projects/, 102
 POST /api/projects/(string:project)/components/,
 104
 POST /api/projects/(string:project)/repository/,
 104
 PUT /api/projects/(string:project)/,
 103
 DELETE /api/projects/(string:project)/,
 103
 PATCH /api/projects/(string:project)/,
 103

GET /api/roles/, 99
 GET /api/roles/(int:id)/, 99
 POST /api/roles/, 99
 PUT /api/roles/(int:id)/, 99
 DELETE /api/roles/(int:id)/, 99
 PATCH /api/roles/(int:id)/, 99
/api/screenshots
 GET /api/screenshots/, 125
 GET /api/screenshots/(int:id)/, 125
 GET /api/screenshots/(int:id)/file/,
 125
 POST /api/screenshots/, 126
 POST /api/screenshots/(int:id)/file/,
 125
 POST /api/screenshots/(int:id)/units/,
 125
 PUT /api/screenshots/(int:id)/, 126
 DELETE /api/screenshots/(int:id)/, 127
 DELETE /api/screenshots/(int:id)/units/(int:unit_id)/,
 126
 PATCH /api/screenshots/(int:id)/, 126

/api/tasks

GET /api/tasks/, 129
 GET /api/tasks/(str:uuid)/, 129

/api/translations

GET /api/translations/, 117
 GET /api/translations/(string:project)/(string:component)/,
 117
 GET /api/translations/(string:project)/(string:component)/,
 119
 GET /api/translations/(string:project)/(string:component)/,
 120
 GET /api/translations/(string:project)/(string:component)/,
 121
 GET /api/translations/(string:project)/(string:component)/,
 121
 GET /api/translations/(string:project)/(string:component)/,
 119
 POST /api/translations/(string:project)/(string:component)/,
 120
 POST /api/translations/(string:project)/(string:component)/,
 120
 POST /api/translations/(string:project)/(string:component)/,
 121
 POST /api/translations/(string:project)/(string:component)/,
 119
 DELETE /api/translations/(string:project)/(string:component)/,
 119

/api/units

GET /api/units/, 122
 GET /api/units/(int:id)/, 122
 PUT /api/units/(int:id)/, 123

DELETE /api/units/(int:id)/, 124
 PATCH /api/units/(int:id)/, 123

/api/users

GET /api/users/, 93
 GET /api/users/(str:username)/, 93
 GET /api/users/(str:username)/notifications/,
 95
 GET /api/users/(str:username)/notifications/(int:subscription_id)/,
 95
 GET /api/users/(str:username)/statistics/,
 95
 POST /api/users/, 93
 POST /api/users/(str:username)/groups/,
 94
 POST /api/users/(str:username)/notifications/,
 95
 PUT /api/users/(str:username)/, 94
 PUT /api/users/(str:username)/notifications/(int:subscription_id)/,
 95
 DELETE /api/users/(str:username)/, 94
 DELETE /api/users/(str:username)/notifications/(int:subscription_id)/,
 96
 PATCH /api/users/(str:username)/, 94
 PATCH /api/users/(str:username)/notifications/(int:subscription_id)/,
 95

/exports

GET /exports/rss/, 133
 GET /exports/rss/(string:project)/, 133
 GET /exports/rss/(string:project)/(string:component)/,
 133
 GET /exports/rss/(string:project)/(string:component)/(string:language)/,
 133
 GET /exports/rss/language/(string:language)/,
 133
 GET /exports/stats/(string:project)/(string:component)/,
 132

/hooks

GET /hooks/update/(string:project)/,
 130
 GET /hooks/update/(string:project)/(string:component)/,
 130
 POST /hooks/azure/, 131
 POST /hooks/bitbucket/, 131
 POST /hooks/gitea/, 131
 POST /hooks/gitee/, 131
 POST /hooks/github/, 130
 POST /hooks/gitlab/, 131
 POST /hooks/pagure/, 131

Simbole

.XML resource file			Mundësi për rresht urdhrash wlc, 135
file format, 76			
--add			--ignore
Mundësi për rresht urdhrash			Mundësi për rresht urdhrash
auto_translate, 348			import_json, 351
--addon ADDON			--inconsistent
Mundësi për rresht urdhrash			Mundësi për rresht urdhrash
install_addon, 354			auto_translate, 348
--age HOURS			--input
Mundësi për rresht urdhrash			Mundësi për rresht urdhrash wlc, 136
commit_pending, 349			--key KEY
--author USER@EXAMPLE.COM			Mundësi për rresht urdhrash wlc, 135
Mundësi për rresht urdhrash			--lang LANGUAGE
add_suggestions, 348			Mundësi për rresht urdhrash loadpo,
--base-file-template TEMPLATE			355
Mundësi për rresht urdhrash			--language-code
import_project, 352			Mundësi për rresht urdhrash
--check			list_translators, 355
Mundësi për rresht urdhrash			--language-map LANGMAP
importusers, 354			Mundësi për rresht urdhrash
--config PATH			import_memory, 351
Mundësi për rresht urdhrash wlc, 135			--language-regex REGEX
--config-section SECTION			Mundësi për rresht urdhrash
Mundësi për rresht urdhrash wlc, 135			import_project, 352
--configuration CONFIG			--license NAME
Mundësi për rresht urdhrash			Mundësi për rresht urdhrash
install_addon, 354			import_project, 352
--convert			--license-url URL
Mundësi për rresht urdhrash wlc, 136			Mundësi për rresht urdhrash
--email USER@EXAMPLE.COM			import_project, 352
Mundësi për rresht urdhrash			--main-component
createadmin, 350			Mundësi për rresht urdhrash
--file-format FORMAT			import_project, 352
Mundësi për rresht urdhrash			--main-component COMPONENT
import_project, 352			Mundësi për rresht urdhrash
--force			import_json, 351
Mundësi për rresht urdhrash loadpo,			--mode MODE
355			Mundësi për rresht urdhrash
--force-commit			auto_translate, 348
Mundësi për rresht urdhrash			--mt MT
pushgit, 356			Mundësi për rresht urdhrash
--format {csv,json,text,html}			auto_translate, 348
			--name
			Mundësi për rresht urdhrash
			createadmin, 350

--name-template TEMPLATE		ADMINs
Mundësi për rresht	urdhrash	setting, 183
import_project, 352		AKISMET_API_KEY
--new-base-template TEMPLATE		setting, 302
Mundësi për rresht	urdhrash	ALLOWED_HOSTS
import_project, 352		setting, 183
--no-password		Android
Mundësi për rresht	urdhrash	file format, 71
createadmin, 350		ANONYMOUS_USER_NAME
--no-privs-update		setting, 302
Mundësi për rresht	urdhrash	API, 90, 133, 138
setupgroups, 357		Apple strings
--no-projects-update		file format, 72
Mundësi për rresht	urdhrash	ARB
setupgroups, 357		file format, 75
--no-update		AUDITLOG_EXPIRY
Mundësi për rresht	urdhrash	setting, 303
setuplang, 357		AUTH_LOCK_ATTEMPTS
--output		setting, 303
Mundësi për rresht	urdhrash	AUTH_TOKEN_VALID
wlc, 136		setting, 304
--overwrite		auto_translate
Mundësi për rresht	urdhrash	weblate admin command, 348
auto_translate, 348		AUTO_UPDATE
Mundësi për rresht	urdhrash	setting, 303
wlc, 136		AUTOFIX_LIST
--password PASSWORD		setting, 304
Mundësi për rresht	urdhrash	AVATAR_URL_PREFIX
createadmin, 350		setting, 303
--project PROJECT		
Mundësi për rresht	urdhrash	
import_json, 351		
--source PROJECT/COMPONENT		B
Mundësi për rresht	urdhrash	BACKGROUND_TASKS
auto_translate, 348		setting, 305
--threshold THRESHOLD		BASE_DIR
Mundësi për rresht	urdhrash	setting, 305
auto_translate, 348		BaseAddon (<i>klasë te weblate.addons.base</i>), 391
--update		BASIC_LANGUAGES
Mundësi për rresht	urdhrash	setting, 305
createadmin, 350		bilingual
Mundësi për rresht	urdhrash	translation, 63
import_json, 351		
Mundësi për rresht	urdhrash	C
install_addon, 354		can_install() (<i>metodë</i> <i>klase</i>
--url URL		<i>weblate.addons.base.BaseAddon</i>), 391
Mundësi për rresht	urdhrash	CELERY_BACKUP_OPTIONS, 145, 159
wlc, 135		CELERY_BEAT_OPTIONS, 145, 159
--user USERNAME		CELERY_MAIN_OPTIONS, 145, 159
Mundësi për rresht	urdhrash	CELERY_MEMORY_OPTIONS, 145, 159
auto_translate, 348		CELERY_NOTIFY_OPTIONS, 145, 159
--username USERNAME		celery_queues
Mundësi për rresht	urdhrash	weblate admin command, 349
createadmin, 350		CELERY_TRANSLATE_OPTIONS, 145, 159
--vcs NAME		changes
Mundësi për rresht	urdhrash	Mundësi për rresht urdhrash wlc, 136
import_project, 352		CHECK_LIST
		setting, 306
		checkgit
		weblate admin command, 349
A		
add_suggestions		
weblate admin command, 348		

cleanup
 Mundësi për rresht urdhrash wlc, 136

cleanuptrans
 weblate admin command, 349

Comma separated values
 file format, 76

Command (*klasë te wlc.main*), 140

COMMENT_CLEANUP_DAYS
 setting, 306

commit
 Mundësi për rresht urdhrash wlc, 135

commit_pending
 weblate admin command, 349

COMMIT_PENDING_HOURS
 setting, 307

commitgit
 weblate admin command, 349

configure() (*metodë weblate.addons.base.BaseAddon*), 391

CONTACT_FORM
 setting, 307

createadmin
 weblate admin command, 350

CSP_CONNECT_SRC
 setting, 305

CSP_FONT_SRC
 setting, 305

CSP_IMG_SRC
 setting, 305

CSP_SCRIPT_SRC
 setting, 305

CSP_STYLE_SRC
 setting, 305

CSV
 file format, 76

D

daily() (*metodë weblate.addons.base.BaseAddon*), 391

DATA_DIR
 setting, 307

DATABASE_BACKUP
 setting, 308

DATABASES
 setting, 183

DEBUG
 setting, 183

DEFAULT_ACCESS_CONTROL
 setting, 308

DEFAULT_ADD_MESSAGE
 setting, 308

DEFAULT_ADDON_MESSAGE
 setting, 308

DEFAULT_ADDONS
 setting, 309

DEFAULT_AUTO_WATCH
 setting, 308

DEFAULT_COMMIT_MESSAGE
 setting, 308

DEFAULT_COMMITER_EMAIL
 setting, 309

DEFAULT_COMMITER_NAME
 setting, 309

DEFAULT_DELETE_MESSAGE
 setting, 308

DEFAULT_FROM_EMAIL
 setting, 183

DEFAULT_LANGUAGE
 setting, 309

DEFAULT_MERGE_MESSAGE
 setting, 308

DEFAULT_MERGE_STYLE
 setting, 310

DEFAULT_PAGE_LIMIT
 setting, 323

DEFAULT_PULL_MESSAGE
 setting, 310

DEFAULT_RESTRICTED_COMPONENT
 setting, 308

DEFAULT_SHARED_TM
 setting, 310

DEFAULT_TRANSLATION_PROPAGATION
 setting, 310

download
 Mundësi për rresht urdhrash wlc, 136

DTD
 file format, 78

dump_memory
 weblate admin command, 350

dumpuserdata
 weblate admin command, 350

E

ENABLE_AVATARS
 setting, 310

ENABLE_HOOKS
 setting, 310

ENABLE_HTTPS
 setting, 311

ENABLE_SHARING
 setting, 311

F

file format
 .XML resource file, 76

Android, 71

Apple strings, 72

ARB, 75

Comma separated values, 76

CSV, 76

DTD, 78

gettext, 65

go-i18n, 74

GWT properties, 69

i18next, 74

INI translations, 69, 70

- Java properties, 68
- Joomla translations, 70
- JSON, 73
- mi18n lang, 69
- PHP strings, 72
- PO, 65
- Qt, 70
- RC, 79
- RESX, 76
- Ruby YAML, 77
- Ruby YAML Ain't Markup Language, 77
- string resources, 71
- TS, 70
- XLIFF, 66
- XML, 78
- YAML, 77
- YAML Ain't Markup Language, 77

G

- `get()` (*metodë wlc. Weblate*), 138
- `get_add_form()` (*metodë klase weblate.addons.base.BaseAddon*), 391
- `GET_HELP_URL`
 - setting, 311
- `get_settings_form()` (*metodë weblate.addons.base.BaseAddon*), 391
- `gettext`
 - file format, 65
- `GITHUB_CREDENTIALS`
 - setting, 312
- `GITHUB_TOKEN`
 - setting, 312
- `GITHUB_USERNAME`
 - setting, 312
- `GITLAB_CREDENTIALS`
 - setting, 311
- `GITLAB_TOKEN`
 - setting, 312
- `GITLAB_USERNAME`
 - setting, 311
- `go-i18n`
 - file format, 74
- `GOOGLE_ANALYTICS_ID`
 - setting, 312
- GWT properties
 - file format, 69

H

- `HIDE_REPO_CREDENTIALS`
 - setting, 313
- `HIDE_VERSION`
 - setting, 313

I

- `i18next`
 - file format, 74
- `import_demo`
 - weblate admin command, 350

- `import_json`
 - weblate admin command, 351
- `import_memory`
 - weblate admin command, 351
- `import_project`
 - weblate admin command, 352
- `importuserdata`
 - weblate admin command, 354
- `importusers`
 - weblate admin command, 354
- INI translations
 - file format, 69, 70
- `install_addon`
 - weblate admin command, 354
- `IP_BEHIND_REVERSE_PROXY`
 - setting, 313
- `IP_PROXY_HEADER`
 - setting, 313
- `IP_PROXY_OFFSET`
 - setting, 314
- iPad
 - translation, 72
- iPhone
 - translation, 72

J

- Java properties
 - file format, 68
- Joomla translations
 - file format, 70
- JSON
 - file format, 73

L

- `LEGAL_URL`
 - setting, 314
- `LICENSE_EXTRA`
 - setting, 314
- `LICENSE_FILTER`
 - setting, 315
- `LICENSE_REQUIRED`
 - setting, 315
- `LIMIT_TRANSLATION_LENGTH_BY_SOURCE_LENGTH`
 - setting, 315
- `list_languages`
 - weblate admin command, 354
- `list_translators`
 - weblate admin command, 355
- `list_versions`
 - weblate admin command, 355
- list-components
 - Mundësi për rresht urdhrash wlc, 135
- list-languages
 - Mundësi për rresht urdhrash wlc, 135
- list-projects
 - Mundësi për rresht urdhrash wlc, 135
- list-translations
 - Mundësi për rresht urdhrash wlc, 135

`load()` (*metodë wlc.config.WeblateConfig*), 139
`loadpo`
 weblate admin command, 355
`LOCALIZE_CDN_PATH`
 setting, 315
`LOCALIZE_CDN_URL`
 setting, 315
`lock`
 Mundësi për rresht urdhrash wlc, 136
`lock_translation`
 weblate admin command, 355
`lock-status`
 Mundësi për rresht urdhrash wlc, 136
`LOGIN_REQUIRED_URLS`
 setting, 316
`LOGIN_REQUIRED_URLS_EXCEPTIONS`
 setting, 316
`ls`
 Mundësi për rresht urdhrash wlc, 135

M

`MACHINE_TRANSLATION_SERVICES`
 setting, 317
`main()` (*te moduli wlc.main*), 139
`MATOMO_SITE_ID`
 setting, 316
`MATOMO_URL`
 setting, 317
`mi18n lang`
 file format, 69
`modul`
 wlc, 138
 wlc.config, 139
 wlc.main, 139
`monolingual`
 translation, 63
`move_language`
 weblate admin command, 356
`MT_APERTIUM_APY`
 setting, 318
`MT_AWS_ACCESS_KEY_ID`
 setting, 318
`MT_AWS_REGION`
 setting, 318
`MT_AWS_SECRET_ACCESS_KEY`
 setting, 318
`MT_BAIDU_ID`
 setting, 318
`MT_BAIDU_SECRET`
 setting, 318
`MT_DEEPL_API_URL`
 setting, 319
`MT_DEEPL_KEY`
 setting, 319
`MT_GOOGLE_CREDENTIALS`
 setting, 320
`MT_GOOGLE_KEY`
 setting, 320

`MT_GOOGLE_LOCATION`
 setting, 320
`MT_GOOGLE_PROJECT`
 setting, 320
`MT_LIBRETRANSLATE_API_URL`
 setting, 319
`MT_LIBRETRANSLATE_KEY`
 setting, 319
`MT_MICROSOFT_BASE_URL`
 setting, 320
`MT_MICROSOFT_COGNITIVE_KEY`
 setting, 320
`MT_MICROSOFT_ENDPOINT_URL`
 setting, 321
`MT_MICROSOFT_REGION`
 setting, 321
`MT_MODERNMT_KEY`
 setting, 321
`MT_MODERNMT_URL`
 setting, 321
`MT_MYMEMORY_EMAIL`
 setting, 321
`MT_MYMEMORY_KEY`
 setting, 321
`MT_MYMEMORY_USER`
 setting, 321
`MT_NETEASE_KEY`
 setting, 322
`MT_NETEASE_SECRET`
 setting, 322
`MT_SAP_BASE_URL`
 setting, 322
`MT_SAP_PASSWORD`
 setting, 323
`MT_SAP_SANDBOX_APIKEY`
 setting, 323
`MT_SAP_USE_MT`
 setting, 323
`MT_SAP_USERNAME`
 setting, 323
`MT_SERVICES`
 setting, 317
`MT_TMSERVER`
 setting, 322
`MT_YANDEX_KEY`
 setting, 322
`MT_YOUDAO_ID`
 setting, 322
`MT_YOUDAO_SECRET`
 setting, 322
Mundësi për rresht urdhrash
 add_suggestions
 --author USER@EXAMPLE.COM, 348
Mundësi për rresht urdhrash
 auto_translate
 --add, 348
 --inconsistent, 348
 --mode MODE, 348

```

--mt MT, 348
--overwrite, 348
--source PROJECT/COMPONENT, 348
--threshold THRESHOLD, 348
--user USERNAME, 348
Mundësi për rresht urdhrash
    commit_pending
--age HOURS, 349
Mundësi për rresht urdhrash
    createadmin
--email USER@EXAMPLE.COM, 350
--name, 350
--no-password, 350
--password PASSWORD, 350
--update, 350
--username USERNAME, 350
Mundësi për rresht urdhrash
    import_json
--ignore, 351
--main-component COMPONENT, 351
--project PROJECT, 351
--update, 351
Mundësi për rresht urdhrash
    import_memory
--language-map LANGMAP, 351
Mundësi për rresht urdhrash
    import_project
--base-file-template TEMPLATE, 352
--file-format FORMAT, 352
--language-regex REGEX, 352
--license NAME, 352
--license-url URL, 352
--main-component, 352
--name-template TEMPLATE, 352
--new-base-template TEMPLATE, 352
--vcs NAME, 352
Mundësi për rresht urdhrash
    importusers
--check, 354
Mundësi për rresht urdhrash
    install_addon
--addon ADDON, 354
--configuration CONFIG, 354
--update, 354
Mundësi për rresht urdhrash
    list_translators
--language-code, 355
Mundësi për rresht urdhrash loadpo
--force, 355
--lang LANGUAGE, 355
Mundësi për rresht urdhrash pushgit
--force-commit, 356
Mundësi për rresht urdhrash
    setupgroups
--no-privs-update, 357
--no-projects-update, 357
Mundësi për rresht urdhrash setuplang
--no-update, 357

```

```

Mundësi për rresht urdhrash wlc
--config PATH, 135
--config-section SECTION, 135
--convert, 136
--format {csv,json,text,html}, 135
--input, 136
--key KEY, 135
--output, 136
--overwrite, 136
--url URL, 135
changes, 136
cleanup, 136
commit, 135
download, 136
list-components, 135
list-languages, 135
list-projects, 135
list-translations, 135
lock, 136
lock-status, 136
ls, 135
pull, 135
push, 136
repo, 136
reset, 136
show, 135
statistics, 136
unlock, 136
upload, 136
version, 135

```

N

```

ndryshore mjedisi
    CELERY_BACKUP_OPTIONS, 145, 159
    CELERY_BEAT_OPTIONS, 145, 159
    CELERY_MAIN_OPTIONS, 145, 159
    CELERY_MEMORY_OPTIONS, 145, 159
    CELERY_NOTIFY_OPTIONS, 145, 159
    CELERY_TRANSLATE_OPTIONS, 145, 159
    POSTGRES_ALTER_ROLE, 156
    POSTGRES_DATABASE, 155
    POSTGRES_HOST, 155
    POSTGRES_PASSWORD, 155
    POSTGRES_PASSWORD_FILE, 155
    POSTGRES_PORT, 155
    POSTGRES_SSL_MODE, 155
    POSTGRES_USER, 155
    REDIS_DB, 156
    REDIS_HOST, 156
    REDIS_PASSWORD, 156
    REDIS_PORT, 156
    REDIS_TLS, 156
    REDIS_VERIFY_SSL, 156
    ROLLBAR_ENVIRONMENT, 158
    ROLLBAR_KEY, 158
    SENTRY_DSN, 158
    SENTRY_ENVIRONMENT, 158
    SOCIAL_AUTH_SLACK_SECRET, 155

```

UWSGI_WORKERS, 145, 159, 160
 WEBLATE_ADD_ADDONS, 159
 WEBLATE_ADD_APPS, 159
 WEBLATE_ADD_AUTOFIX, 159
 WEBLATE_ADD_CHECK, 159
 WEBLATE_ADD_LOGIN_REQUIRED_URLS_EXCEPT_DOMAINS, 149
 WEBLATE_ADMIN_EMAIL, 145--147, 151
 WEBLATE_ADMIN_NAME, 145--147
 WEBLATE_ADMIN_PASSWORD, 142, 145--147
 WEBLATE_ADMIN_PASSWORD_FILE, 147
 WEBLATE_AKISMET_API_KEY, 150, 364
 WEBLATE_ALLOWED_HOSTS, 147, 183, 187, 188, 327
 WEBLATE_AUTH_LDAP_BIND_DN, 152
 WEBLATE_AUTH_LDAP_BIND_PASSWORD, 152
 WEBLATE_AUTH_LDAP_CONNECTION_OPTION_REFERRALS, 152
 WEBLATE_AUTH_LDAP_SERVER_URI, 152
 WEBLATE_AUTH_LDAP_USER_ATTR_MAP, 152
 WEBLATE_AUTH_LDAP_USER_DN_TEMPLATE, 152
 WEBLATE_AUTH_LDAP_USER_SEARCH, 152
 WEBLATE_AUTH_LDAP_USER_SEARCH_FILTER, 152
 WEBLATE_AUTH_LDAP_USER_SEARCH_UNION, 152
 WEBLATE_AUTH_LDAP_USER_SEARCH_UNION_DELETE, 152
 WEBLATE_BASIC_LANGUAGES, 150
 WEBLATE_CONTACT_FORM, 147
 WEBLATE_CSP_CONNECT_SRC, 150
 WEBLATE_CSP_FONT_SRC, 150
 WEBLATE_CSP_IMG_SRC, 150
 WEBLATE_CSP_SCRIPT_SRC, 150
 WEBLATE_CSP_STYLE_SRC, 150
 WEBLATE_DATABASE_BACKUP, 156
 WEBLATE_DEBUG, 146
 WEBLATE_DEFAULT_ACCESS_CONTROL, 149
 WEBLATE_DEFAULT_AUTO_WATCH, 150
 WEBLATE_DEFAULT_COMMITTER_EMAIL, 149
 WEBLATE_DEFAULT_COMMITTER_NAME, 149
 WEBLATE_DEFAULT_FROM_EMAIL, 147
 WEBLATE_DEFAULT_RESTRICTED_COMPONENT, 149
 WEBLATE_DEFAULT_SHARED_TM, 150
 WEBLATE_DEFAULT_TRANSLATION_PROPAGATION, 149
 WEBLATE_EMAIL_BACKEND, 157
 WEBLATE_EMAIL_HOST, 157
 WEBLATE_EMAIL_HOST_PASSWORD, 157
 WEBLATE_EMAIL_HOST_PASSWORD_FILE, 157
 WEBLATE_EMAIL_HOST_USER, 157
 WEBLATE_EMAIL_PORT, 157
 WEBLATE_EMAIL_USE_SSL, 157
 WEBLATE_EMAIL_USE_TLS, 157
 WEBLATE_ENABLE_AVATARS, 151
 WEBLATE_ENABLE_HTTPS, 147, 215
 WEBLATE_GET_HELP_URL, 158
 WEBLATE_GITHUB_TOKEN, 149
 WEBLATE_GITHUB_USERNAME, 149
 WEBLATE_GITLAB_TOKEN, 149
 WEBLATE_GITLAB_USERNAME, 149
 WEBLATE_GOOGLE_ANALYTICS_ID, 149
 WEBLATE_GPG_IDENTITY, 150
 WEBLATE_HIDE_VERSION, 150
 WEBLATE_IP_PROXY_HEADER, 148
 WEBLATE_LEGAL_URL, 158
 WEBLATE_LICENSE_FILTER, 150
 WEBLATE_LICENSE_REQUIRED, 150
 WEBLATE_LOCALIZE_CDN_PATH, 158
 WEBLATE_LOCALIZE_CDN_URL, 158
 WEBLATE_LOGIN_REQUIRED_URLS_EXCEPTIONS, 148
 WEBLATE_LOGLEVEL, 146
 WEBLATE_MT_APERTIUM_API_KEY, 151
 WEBLATE_MT_AWS_ACCESS_KEY_ID, 151
 WEBLATE_MT_AWS_REGION, 151
 WEBLATE_MT_AWS_SECRET_ACCESS_KEY, 151
 WEBLATE_MT_DEEPL_API_URL, 151
 WEBLATE_MT_DEEPL_KEY, 151
 WEBLATE_MT_GLOSBE_ENABLED, 152
 WEBLATE_MT_GOOGLE_KEY, 151
 WEBLATE_MT_LIBRETRANSLATE_API_URL, 151
 WEBLATE_MT_LIBRETRANSLATE_KEY, 151
 WEBLATE_MT_MICROSOFT_BASE_URL, 151
 WEBLATE_MT_MICROSOFT_COGNITIVE_KEY, 151
 WEBLATE_MT_MICROSOFT_ENDPOINT_URL, 151
 WEBLATE_MT_MICROSOFT_REGION, 151
 WEBLATE_MT_MICROSOFT_TERMINOLOGY_ENABLED, 152
 WEBLATE_MT_MODERNMT_KEY, 151
 WEBLATE_MT_MYMOMORY_ENABLED, 151
 WEBLATE_MT_SAP_BASE_URL, 152
 WEBLATE_MT_SAP_PASSWORD, 152
 WEBLATE_MT_SAP_SANDBOX_APIKEY, 152
 WEBLATE_MT_SAP_USE_MT, 152
 WEBLATE_MT_SAP_USERNAME, 152
 WEBLATE_NO_EMAIL_AUTH, 155
 WEBLATE_PAGURE_TOKEN, 149
 WEBLATE_PAGURE_USERNAME, 149
 WEBLATE_RATELIMIT_ATTEMPTS, 150, 366
 WEBLATE_RATELIMIT_LOCKOUT, 150
 WEBLATE_RATELIMIT_WINDOW, 150
 WEBLATE_REGISTRATION_ALLOW_BACKENDS, 147
 WEBLATE_REGISTRATION_OPEN, 147
 WEBLATE_REMOVE_ADDONS, 159
 WEBLATE_REMOVE_APPS, 159

P

pre_commit() (metodë
weblate.addons.base.BaseAddon), 391

pre_push() (metodë
weblate.addons.base.BaseAddon), 391

pre_update() (metodë
weblate.addons.base.BaseAddon), 391

pull
Mundësi për rresht urdhrash wlc, 135

push
Mundësi për rresht urdhrash wlc, 136

pushgit
weblate admin command, 356

Python, 138

Q

Qt
file format, 70

R

RATELIMIT_ATTEMPTS
setting, 324

RATELIMIT_LOCKOUT
setting, 325

RATELIMIT_WINDOW
setting, 324

RC
file format, 79

register_command() (te moduli wlc.main), 139

REGISTRATION_ALLOW_BACKENDS
setting, 325

REGISTRATION_CAPTCHA
setting, 325

REGISTRATION_EMAIL_MATCH
setting, 325

REGISTRATION_OPEN
setting, 326

repo
Mundësi për rresht urdhrash wlc, 136

REPOSITORY_ALERT_THRESHOLD
setting, 326

REQUIRE_LOGIN
setting, 326

reset
Mundësi për rresht urdhrash wlc, 136

REST, 90

RESX
file format, 76

RFC
RFC 5646, 62

Ruby YAML
file format, 77

Ruby YAML Ain't Markup Language
file format, 77

S

save_state() (metodë
weblate.addons.base.BaseAddon), 391

SECRET_KEY

setting, 183

SENTRY_DSN
setting, 326

SERVER_EMAIL
setting, 184

SESSION_COOKIE_AGE_AUTHENTICATED
setting, 327

SESSION_ENGINE
setting, 183

setting
ADMINS, 183
AKISMET_API_KEY, 302
ALLOWED_HOSTS, 183
ANONYMOUS_USER_NAME, 302
AUDITLOG_EXPIRY, 303
AUTH_LOCK_ATTEMPTS, 303
AUTH_TOKEN_VALID, 304
AUTO_UPDATE, 303
AUTOFIX_LIST, 304
AVATAR_URL_PREFIX, 303
BACKGROUND_TASKS, 305
BASE_DIR, 305
BASIC_LANGUAGES, 305
CHECK_LIST, 306
COMMENT_CLEANUP_DAYS, 306
COMMIT_PENDING_HOURS, 307
CONTACT_FORM, 307
CSP_CONNECT_SRC, 305
CSP_FONT_SRC, 305
CSP_IMG_SRC, 305
CSP_SCRIPT_SRC, 305
CSP_STYLE_SRC, 305
DATA_DIR, 307
DATABASE_BACKUP, 308
DATABASES, 183
DEBUG, 183
DEFAULT_ACCESS_CONTROL, 308
DEFAULT_ADD_MESSAGE, 308
DEFAULT_ADDON_MESSAGE, 308
DEFAULT_ADDONS, 309
DEFAULT_AUTO_WATCH, 308
DEFAULT_COMMIT_MESSAGE, 308
DEFAULT_COMMITTER_EMAIL, 309
DEFAULT_COMMITTER_NAME, 309
DEFAULT_DELETE_MESSAGE, 308
DEFAULT_FROM_EMAIL, 183
DEFAULT_LANGUAGE, 309
DEFAULT_MERGE_MESSAGE, 308
DEFAULT_MERGE_STYLE, 310
DEFAULT_PAGE_LIMIT, 323
DEFAULT_PULL_MESSAGE, 310
DEFAULT_RESTRICTED_COMPONENT, 308
DEFAULT_SHARED_TM, 310
DEFAULT_TRANSLATION_PROPAGATION, 310
ENABLE_AVATARS, 310
ENABLE_HOOKS, 310
ENABLE_HTTPS, 311

- ENABLE_SHARING, 311
- GET_HELP_URL, 311
- GITHUB_CREDENTIALS, 312
- GITHUB_TOKEN, 312
- GITHUB_USERNAME, 312
- GITLAB_CREDENTIALS, 311
- GITLAB_TOKEN, 312
- GITLAB_USERNAME, 311
- GOOGLE_ANALYTICS_ID, 312
- HIDE_REPO_CREDENTIALS, 313
- HIDE_VERSION, 313
- IP_BEHIND_REVERSE_PROXY, 313
- IP_PROXY_HEADER, 313
- IP_PROXY_OFFSET, 314
- LEGAL_URL, 314
- LICENSE_EXTRA, 314
- LICENSE_FILTER, 315
- LICENSE_REQUIRED, 315
- LIMIT_TRANSLATION_LENGTH_BY_SOURCE_LENGTH, 315
- LOCALIZE_CDN_PATH, 315
- LOCALIZE_CDN_URL, 315
- LOGIN_REQUIRED_URLS, 316
- LOGIN_REQUIRED_URLS_EXCEPTIONS, 316
- MACHINE_TRANSLATION_SERVICES, 317
- MATOMO_SITE_ID, 316
- MATOMO_URL, 317
- MT_APERTIUM_API, 318
- MT_AWS_ACCESS_KEY_ID, 318
- MT_AWS_REGION, 318
- MT_AWS_SECRET_ACCESS_KEY, 318
- MT_BAIDU_ID, 318
- MT_BAIDU_SECRET, 318
- MT_DEEPL_API_URL, 319
- MT_DEEPL_KEY, 319
- MT_GOOGLE_CREDENTIALS, 320
- MT_GOOGLE_KEY, 320
- MT_GOOGLE_LOCATION, 320
- MT_GOOGLE_PROJECT, 320
- MT_LIBRETRANSLATE_API_URL, 319
- MT_LIBRETRANSLATE_KEY, 319
- MT_MICROSOFT_BASE_URL, 320
- MT_MICROSOFT_COGNITIVE_KEY, 320
- MT_MICROSOFT_ENDPOINT_URL, 321
- MT_MICROSOFT_REGION, 321
- MT_MODERNMT_KEY, 321
- MT_MODERNMT_URL, 321
- MT_MYMOMETRY_EMAIL, 321
- MT_MYMOMETRY_KEY, 321
- MT_MYMOMETRY_USER, 321
- MT_NETEASE_KEY, 322
- MT_NETEASE_SECRET, 322
- MT_SAP_BASE_URL, 322
- MT_SAP_PASSWORD, 323
- MT_SAP_SANDBOX_APIKEY, 323
- MT_SAP_USE_MT, 323
- MT_SAP_USERNAME, 323
- MT_SERVICES, 317
- MT_TMSERVER, 322
- MT_YANDEX_KEY, 322
- MT_YOUDAO_ID, 322
- MT_YOUDAO_SECRET, 322
- NEARBY_MESSAGES, 323
- PAGURE_CREDENTIALS, 323
- PAGURE_TOKEN, 324
- PAGURE_USERNAME, 324
- PIWIK_SITE_ID, 316
- PIWIK_URL, 317
- RATELIMIT_ATTEMPTS, 324
- RATELIMIT_LOCKOUT, 325
- RATELIMIT_WINDOW, 324
- REGISTRATION_ALLOW_BACKENDS, 325
- REGISTRATION_CAPTCHA, 325
- REGISTRATION_EMAIL_MATCH, 325
- REGISTRATION_OPEN, 326
- REPOSITORY_ALERT_THRESHOLD, 326
- REQUIRE_LOGIN, 326
- SECRET_KEY, 183
- SENTRY_DSN, 326
- SERVER_EMAIL, 184
- SESSION_COOKIE_AGE_AUTHENTICATED, 327
- SESSION_ENGINE, 183
- SIMPLIFY_LANGUAGES, 327
- SINGLE_PROJECT, 328
- SITE_DOMAIN, 327
- SITE_TITLE, 327
- SPECIAL_CHARS, 328
- STATUS_URL, 328
- SUGGESTION_CLEANUP_DAYS, 328
- UPDATE_LANGUAGES, 328
- URL_PREFIX, 328
- VCS_BACKENDS, 329
- VCS_CLONE_DEPTH, 329
- WEBLATE_ADDONS, 329
- WEBLATE_EXPORTERS, 330
- WEBLATE_FORMATS, 330
- WEBLATE_GPG_IDENTITY, 331
- WEBSITE_REQUIRED, 331
- setupgroups
 - weblate admin command, 357
- setuplang
 - weblate admin command, 357
- show
 - Mundësi për rresht urdhrash wlc, 135
- SIMPLIFY_LANGUAGES
 - setting, 327
- SINGLE_PROJECT
 - setting, 328
- SITE_DOMAIN
 - setting, 327
- SITE_TITLE
 - setting, 327
- SPECIAL_CHARS
 - setting, 328
- statistics

Mundësi për rresht urdhrash wlc, 136
STATUS_URL
 setting, 328
stay_on_create (atribut
 weblate.addons.base.BaseAddon), 391
store_post_load() (metodë
 weblate.addons.base.BaseAddon), 392
string resources
 file format, 71
SUGGESTION_CLEANUP_DAYS
 setting, 328

T

translation
 bilingual, 63
 iPad, 72
 iPhone, 72
 monolingual, 63
TS
 file format, 70

U

unit_pre_create() (metodë
 weblate.addons.base.BaseAddon), 392
unlock
 Mundësi për rresht urdhrash wlc, 136
unlock_translation
 weblate admin command, 356
UPDATE_LANGUAGES
 setting, 328
updatechecks
 weblate admin command, 357
updategit
 weblate admin command, 357
upload
 Mundësi për rresht urdhrash wlc, 136
URL_PREFIX
 setting, 328
UWSGI_WORKERS, 145, 159

V

VCS_BACKENDS
 setting, 329
VCS_CLONE_DEPTH
 setting, 329
version
 Mundësi për rresht urdhrash wlc, 135

W

Weblate (klasë te wlc), 138
weblate admin command
 add_suggestions, 348
 auto_translate, 348
 celery_queues, 349
 checkgit, 349
 cleanuptrans, 349
 commit_pending, 349
 commitgit, 349

createadmin, 350
dump_memory, 350
dumpuserdata, 350
import_demo, 350
import_json, 351
import_memory, 351
import_project, 352
importuserdata, 354
importusers, 354
install_addon, 354
list_languages, 354
list_translators, 355
list_versions, 355
loadpo, 355
lock_translation, 355
move_language, 356
pushgit, 356
setupgroups, 357
setuplang, 357
unlock_translation, 356
updatechecks, 357
updategit, 357
WEBLATE_ADDONS
 setting, 329
WEBLATE_ADMIN_EMAIL, 145--147, 151
WEBLATE_ADMIN_NAME, 145--147
WEBLATE_ADMIN_PASSWORD, 142, 145--147
WEBLATE_ADMIN_PASSWORD_FILE, 147
WEBLATE_AKISMET_API_KEY, 364
WEBLATE_ALLOWED_HOSTS, 183, 187, 188, 327
WEBLATE_EMAIL_HOST_PASSWORD, 157
WEBLATE_EMAIL_PORT, 157
WEBLATE_EMAIL_USE_SSL, 157
WEBLATE_EMAIL_USE_TLS, 157
WEBLATE_ENABLE_HTTPS, 215
WEBLATE_EXPORTERS
 setting, 330
WEBLATE_FORMATS
 setting, 330
WEBLATE_GPG_IDENTITY
 setting, 331
WEBLATE_LOCALIZE_CDN_PATH, 158
WEBLATE_RATELIMIT_ATTEMPTS, 366
WEBLATE_REQUIRE_LOGIN, 326
WEBLATE_SECURE_PROXY_SSL_HEADER, 148
WEBLATE_SERVICE, 145
WEBLATE_SILENCED_SYSTEM_CHECKS, 212
WEBLATE_SITE_DOMAIN, 185, 203, 327
WEBLATE_WORKERS, 145, 159, 160
WeblateConfig (klasë te wlc.config), 139
WeblateException, 138
WEBSITE_REQUIRED
 setting, 331
wlc, 133
 modul, 138
wlc.config
 modul, 139
wlc.main

modul, [139](#)

X

XLIFF

file format, [66](#)

XML

file format, [78](#)

Y

YAML

file format, [77](#)

YAML Ain't Markup Language

file format, [77](#)